

General Catalog for Compressed Air, Gas and Vacuum Solutions



Download a QR Reader and scan
the code to read this catalog
on your tablet.



Sustainable Productivity

Atlas Copco

FOR 140 YEARS, WE HAVE INCREASED OUR CUSTOMER'S PRODUCTIVITY

Atlas Copco is an industrial group with world-leading position in products and services that deliver sustainable productivity. The company was founded in Sweden in 1873, celebrating 140 years of successful business in 2013.

Today, we have sale and service operations in more than 170 countries. The voices of our customers around the world are very important to us. By listening to customers we learn about what we do well and what we need to improve.

Each year, we open new customer centers in emerging markets, always with a long-term commitment to local customers and partners.

Atlas Copco Compressor Technique provides air and gas compressors, expanders, air and gas treatment equipment as well as air management systems and service for industrial applications.

In this catalogue you will find our comprehensive offering of energy efficient compressed air, gas and vacuum solutions to help improve customers' sustainable productivity.

Drivers of innovation - from idea to customer benefit



We want to put our customers ahead of their competition. For Atlas Copco, energy efficiency is always a top priority and a strong incentive to seek new and better solutions.

Our continuous drive to further reduce the carbon footprint, to find new and better ways of utilizing materials and to minimize waste has resulted in numerous innovations.

A lot of new opportunities relate to the development of intelligent controls and monitoring systems. Further development of oil-free and low pressure technology will open up opportunities to reach new heights in air efficiency.

For the oil-injected technology, continuous innovations and new solutions make this technology a strong contributor to customer efficiency and energy savings for the future.

An industry benchmark

Our achievements are also recognized externally and we are perceived as an industry benchmark in many areas.

For example, we are listed in the Dow Jones Sustainability index as one of the world's most innovative companies. And at the World Economic Forum in Davos in Switzerland we were listed as the 10th most sustainable company in the world. We have been on that list six times.

Sustainable development

Atlas Copco has set very high environmental targets for our operations as well as for our equipment.

By making our equipment as energy efficient as possible, we help our customers to reduce their impact on the environment. This can help them to promote their products as sustainable solutions in the marketplace.

For our operations, we are continuously reducing the environmental impact in key areas such as energy consumption, water consumption, CO₂ emissions, and waste.

A large majority of our employees already work in companies that are triple certified (ISO 9001, ISO 14001 and OHSAS 18001). By the end of 2013 Compressor Technique is committed to having triple certifications for all of our operations.



ISO 9001
We have the quality leading role in the Industry.
We trust the customer introduced.



ISO 14001
The Environmental Management System is an integrated part of any business process at Atlas Copco Airpower.



OHSAS 18001:1999
International Labour and Health and Safety Management system

Energy efficiency is our benchmark



Compressed air is simply indispensable in many processes today, so it is all the more astonishing that many businesses have long since disregarded the most significant cost factor in compressed air supply - the cost of energy. Approximately 80% of the total life-cycle cost is apportionable to energy! For this reason, Atlas Copco has been striving for greater energy efficiency for many years, with the aim of boosting our customers' productivity in the long term.

"Committed to sustainable productivity" is the standard we bear. Nevertheless, we are always seeking to develop new, more efficient drive systems and to better tailor individual components to overall designs.

Today, operators are able to run their systems consistently at the optimum operating point and to ensure that all machines are used to full capacity. The result in both cases is a lower electricity bill. When scrutinizing the lifecycle costs of compressed air systems, investments in energy efficient systems always pay off.

This is particularly true when it comes to heat recovery: Compressors generate heat energy which can be harnessed for other purposes in the operating environment. We have the experience and technical means at our disposal to implement appropriate solutions. Electrical energy that has been expended once, for instance, can be reused in the form of thermal energy: to support hall heating, heat warm water or warm up processes. Heat recovery quickly pays for itself. We offer compressors already equipped with these systems, but there are also retrofitting options available for existing systems.



Variable Speed Drive (VSD): reducing energy consumption


In the company's relentless quest to cut costs and develop innovative products, Atlas Copco unveiled the pioneering variable speed drive (VSD) technology in 1994. Early 2013, Atlas Copco surprised the market with a new, very compact oil-injected rotary screw compressor from 7 to 37 kW: the 7-37 GA VSD+. Besides a small footprint, it offers a leap forward in Free Air Delivery and a breakthrough energy efficiency, requiring on average 50% less energy than a comparable idling compressor. Read more on page 27

Fluctuating compressed air demand in 92% of all systems

In almost every production environment, air demand fluctuates based on a number of factors (time of day, week or even month). Extensive measurements and studies of compressed air demand profiles show that compressed air demand varies considerably in 92% of all compressor and fan systems. Compressed air demand is found to be relatively stable in just 8% of all systems. Tests have indicated that VSD compressors and fans save energy in these situations too.




Profile 1



- 64% of all systems
- Factory in 24-hour operation: low demand at night, high demand during the day

Profile 2




- 28% of all systems
- Factory in two-shift operation, inoperative at weekends: irregular air demand

Profile 3



- 8% of all systems
- Factory in two-shift operation, inoperative at weekends: typical area of operation at "constant" speed



Cost over entire service life of compressor and fan - 50% energy savings on average (VSD+)

VSD+ technology from Atlas Copco adjusts the motor speed to the air demand automatically, achieving substantial energy savings of 50% on average. Over the entire service life of a compressor or

fan, costs can be reduced on average by 22%. What's more, thanks to lower system pressure, VSD dramatically reduces the energy requirements in the overall production process.



The leader in oil-free compressed air technology



Oil-free air is used in all kinds of industries where air quality is paramount for the production process and end product. These applications include food and beverage processing, the pharmaceutical industry (manufacturing and packaging), wastewater treatment, chemical and petrochemical processing, semiconductor and electronics manufacturing, the medical sector, automotive paint spraying, textile manufacturing and many more. Contamination by even the smallest quantities of oil can result in costly production downtime and product spoilage, making **Class 0** an industry standard.

First in oil-free air technology

Over the past sixty years Atlas Copco has pioneered the development of oil-free air technology, resulting in a range of air compressors and blowers that provide 100% pure, clean air. Through continuous research and development, Atlas Copco achieved a new milestone, setting the standard for air purity as the first manufacturer to be awarded ISO 8573-1 CLASS 0 certification.



Eliminating any risk

As the industry leader committed to meeting the needs of the most demanding customers, Atlas Copco requested the renowned TÜV institute to type-test its range of oil-free compressors and blowers. Using the most rigorous testing methodologies available, all possible oil forms were measured across a range of temperatures and pressures. The TÜV found no traces of oil at all in the output air stream. Thus Atlas Copco is not only the first compressor and blower manufacturer to receive CLASS 0 certification, but also exceeds ISO 8573-1 CLASS 0 specifications.



Download a QR Reader and scan the code for more information about www.classzero.com.

CLASS 0 means:

- ✓ Zero risk of contamination.
- ✓ Zero risk of damaged or unsafe products.
- ✓ Zero risk of losses from operational downtime.
- ✓ Zero risk of damaging your company's hard-won professional reputation.

| CLASS | Concentration total oil (aerosol, liquid, vapor) mg/m ³ |
|----------|--|
| 0 | As specified by the equipment user or supplier and more stringent than class 1 |
| 1 | < 0.01 |
| 2 | < 0.1 |
| 3 | < 1 |
| 4 | < 5 |

Current ISO 8573-1 (2010) classes (the five main classes and the associated maximum concentration in total oil content).

Service and optimization for your compressed air system



Sustainable economic performance, reduced energy costs and improved profitability: Our services get you there faster. Operators' unique requirements for servicing and maintenance are just as varied as the range of compressed air systems available. These requirements range from original replacement parts and premium maintenance agreements to system optimization and remote monitoring. With our perfectly tailored and extendable aftermarket products, we have the ideal solutions for worry-free compressed air systems and high availability.

Our range of services and our experienced, qualified service team are at your disposal regardless of whether you have purchased a compressor or dryer from us: Let us optimize your energy consumption, boost your availability and safeguard the reliability and efficient operation of your compressed air system for many years, or even decades, to come. We can perform regular inspections of your systems, enable you to take advantage of the technical progress made and help you to steadily boost your efficiency. If required, we can also remotely monitor your compressed air system centrally via the Internet, 24 hours a day, 365 days a year, allowing you to depend on the productivity and availability of your system at all times.



Atlas Copco Rental



Your trusted partner for temporary Air, Power, Steam and Nitrogen Solutions

At Atlas Copco Rental we can do from the more simple projects in all industries to the large and complex ones in challenging conditions or in the most harsh environments, and this for over 50 years in a successful way.

We provide the most reliable solutions to our customers, thanks to our highly competent and committed sales and service staff.

Safety first

All our equipment is factory-tested prior to dispatch in accordance with our internationally accredited quality system. Designed and built to perform dependably and safely anywhere, anytime, our products come with the most advanced additional safety features.

As an approved quality supplier of temporary air, nitrogen, steam and power systems, Atlas Copco Rental meets and exceeds the strictest environmental rules and legislation.

24/7 Availability and Customer Service

Atlas Copco Rental has a global network of rental depots and service centers, devoted to bringing you customized solutions for your applications. We know you need a fast and reliable service – that's why we're never more than a phone call away. Whatever you need for your Oil and Gas process, you can contact us around the clock. Our highly trained service technicians speak your language and are readily accessible 24/7.

Tough Standards

Atlas Copco Rental has been granted triple certification to ISO 9001:2000, ISO 14001:2004 and OHSAS 18001 for Quality,

Environmental and Occupational Health and Safety Management by Lloyd's Register Quality Assurance (LRQA).

This triple certification demonstrates our commitment to the quality of our services, our care for the environmental impact of our operations and the health of our employees and customers.

A global player with local presence

With over 130 offices and depots around the globe we ensure equipment is always close to customers.



iACCESS

The Intelligent Atlas Copco Equipment Satellite System (iACCESS) is a satellite-based application that remotely monitors fleet performance to improve machine uptime, security and safety.

When we know where your fleet is, what condition it's in and how it's performing, we can help you increase productivity, improve response times and lower your cost per project.

Learn more at: www.atlascopcorental.com



Atlas Copco
Adem çadır

Atlas Copco
Rental

Table of Content

| CONTENT | PAGE |
|--|-----------|
| INTRODUCTION | 2 |
| Drivers of innovation - from idea to customer benefit | 3 |
| Energy efficiency is our benchmark 12 to 13 | 4 |
| Variable Speed Drive (VSD): Reducing energy costs | 5 |
| The leader in oil-free compressed air technology | 6 |
| Service and optimization for your compressed air system | 7 |
| Atlas Copco Rental | 8 |
| OIL-INJECTED COMPRESSORS | 13 |
| Oil-lubricated aluminium piston compressors, 1.5-7.5 kW / 2-10 hp: Automan | 16 |
| Industrial oil-lubricated aluminium piston compressors: LE/LT | 19 |
| Oil-injected rotary screw compressors, 2-11 kW / 3-15 hp: GX 2-11 | 22 |
| Oil-injected rotary screw compressors, 5.5-11 kW / 7.5-15 hp: GA 5-11/GA 5-15 VSD | 24 |
| Oil-injected rotary screw compressors, with variable speed drive+, 7-15 kW / 10-20 hp: GA 7-15 VSD+ | 27 |
| Oil-injected rotary screw compressors, 15-22 kW / 20-30 hp: GA 15-22 | 29 |
| Oil-injected rotary screw compressors, 11-30 kW / 15-40 hp: GA 11+30/GA 15-30 VSD | 31 |
| Oil-injected rotary screw compressors, 30-90 kW / 40-125 hp: GA 30+90 / GA 37-90 VSD | 35 |
| Oil-injected rotary screw compressors, 90-160 kW / 125-200 hp: GA 90+160+ / GA 110-160 VSD | 39 |
| Oil-injected rotary screw compressors: GA 200-500 (VSD) | 42 |
| Oil-injected rotary screw compressors, 110-200 kW / 150-270 hp: GR 110-200 | 45 |
| Oil-lubricated high-pressure reciprocating compressors, up to 450 bar (a) (6500 psia), 37-150 kW: B&D | 47 |
| Oil-lubricated high pressure trunk-piston compressors, up to 351 bar(a) 5090 psia, 22-200 kW: CU/CT/CN | 48 |
| Oil-lubricated gas screw compressors, 17 bar(a) (247 psia): GG | 49 |
| Car and bus refueling stations: S100/S750 | 50 |
| OIL-FREE COMPRESSORS | 51 |
| Compact oil-free piston compressors, 0.5-1.5 kW / 0.7-2 hp: LFX 0.7 - 2.0 series | 55 |
| Industrial oil-free aluminum piston compressors, 1.5-7.5 kW / 2-10 hp: LF | 57 |
| Oil-free scroll compressors, 1.5-22 kW / 2-30 hp: SF 1-22 | 59 |
| Water-injected screw compressors, 15-55 kW / 20-75 hp: AQ 30-55 / 15-55 VSD | 62 |
| Oil-free rotary tooth compressors, 15-55 kW / 20-75 hp: ZT 15-22, ZR/ZT 30-45, ZR/ZT 22-37-55 VSD | 65 |
| Oil-free air- and water-cooled rotary screw compressors, 55-935 kW / 75-1253 hp: Z 55-900 (VSD) | 67 |
| Oil-free centrifugal compressors, 355-2750 kW, 475-3500 hp: ZH / ZH+ | 78 |
| Oil-free high-speed drive centrifugal compressors, 350 kW, 470 hp: ZH 350+ | 81 |
| Energy recovery control unit for water-cooled oil-free air compressors from 90 to 900 kW. ER 90-900 | 82 |
| OIL-FREE COMPRESSORS FOR LOW & HIGH PRESSURE APPLICATIONS | 84 |
| Oil-free rotary screw compressors, 22-500 kW / 40-700 hp: ZE/ZA (VSD) | 87 |
| Oil-free positive displacement screw blowers, 7-132 kW, 10-180 hp: ZS | 88 |

| CONTENT | PAGE |
|---|------------|
| Oil-free Variable Speed Drive positive displacement screw blowers, 18-160 kW, 25-215 hp: ZS ⁺ VSD | 89 |
| Oil-free Variable Speed Drive centrifugal air compressors, 100-160 kW, 135-215 hp: ZB 100-160 VSD | 90 |
| Oil-free multistage centrifugal pressure and vacuum blowers 1 to 2,600 kW / 1 to 3,600 hp: ZM 31-246 | 91 |
| Oil-less reciprocating trunk-piston compressors, up to 351 bar (a) (5090 psia), 30 kW: DM | 92 |
| Oil-free reciprocating piston compressors, up to 45 bar (652 psig) 30-315 kW /40-422 hp: DX/DN | 93 |
| Oil-free reciprocating compressors: HX HN | 94 |
| Oil-free reciprocating piston compressors, up to 40 bar (580 psig), 37-275 kW /50-368 hp: P | 95 |
| Oil-free screw and reciprocating piston compressors, up to 40 bar (580 psig), 136-770 kW / 182-1032 hp: ZD | 97 |
| MEDICAL EQUIPMENT AND CUSTOM SOLUTIONS | 100 |
| Medical air purifiers: MED / MED ⁺ | 102 |
| Screw compressors for medical applications: GA MED | 104 |
| Medical Air Plant: uAIR | 106 |
| Medical vacuum systems: mVAC | 109 |
| Medical oxygen plant: Oxyplant | 112 |
| Oil-free scroll compressors for medical applications: SF MED | 114 |
| Oil-free piston compressors for medical applications: LFX MED | 115 |
| Custom solutions for railway, marine and ski slope applications | 116 |
| AIR AND GAS TREATMENT | 118 |
| Refrigerant air dryers, 7-1236 l/s, 14-2516 cfm: FX | 122 |
| Refrigerant air dryers, 6-4000 l/s, 13-8480 cfm: FD | 124 |
| Heatless desiccant air dryers, 32-1600 l/s, 68-3392 cfm: CD | 129 |
| Heatless desiccant air dryers, 1-1400 l/s, 2-2968 cfm: CD ⁺ | 130 |
| Blower purge desiccant air dryers, 360-1600 l/s, 763-3392 cfm: BD | 132 |
| Blower purge desiccant air dryers, 100-3000 l/s, 212-6360 cfm: BD ⁺ | 134 |
| Heat of compression rotary drum dryers, 88-2500 l/s, 185-5297 cfm: MD | 136 |
| Heat of compression rotary drum dryers, 1800-2500 l/s, 3816-5297 cfm:ND | 138 |
| Heat-of-compression desiccant air dryers, 550-3600 l/s, 1165-7628 cfm: XD ⁺ | 140 |
| Membrane dryers: SD | 142 |
| Purification units for breathable air: BAP / BAP ⁺ | 144 |
| Compressed air purification: Something else you should consider | 146 |
| PSA nitrogen generators, capacity 1-300 l/s, flow 4-1100 Nm ³ /h purity 95-99.999%: NGP series | 147 |
| Membrane nitrogen generators, capacity 1.4-140 l/s, flow 5-500 Nm ³ /h, purity 95-99%: NGM 1-7 | 149 |
| PSA oxygen generators, capacity 0.6-56 l/s, flow 2-200 Nm ³ /h, purity 90-95%: OGP series | 151 |
| Compressed air filters: DD ⁺ , DDp ⁺ , PD ⁺ , PDp ⁺ , QD ⁺ filters | 153 |
| Water separators and drains: WSD 25-750 / WD 80 / EWD 50-1500 | 156 |
| Activated carbon tower, 20-310 l/s, 42-657 cfm: QDT | 158 |
| Oil/water separator systems for the condensate treatment: OSC and OSD | 160 |

Table of Content

| CONTENT | PAGE |
|--|------------|
| VACUUM PUMPS | 162 |
| Oil-sealed rotary vane vacuum pumps, 20-365 m³/h, 12-215 cfm: GV 20-300 | 164 |
| Oil-sealed rotary screw vacuum pumps, 557-5734 m³/h, 328-3377 cfm: GV 630-4800 | 166 |
| CENTRIFUGAL COMPRESSORS, EXPANDERS AND PUMPS | 168 |
| Integrally geared centrifugal compressors for gas and air applications, up to 200 bar discharge pressure, driver power up to 40 MW: Compressor GT Series | 171 |
| Centrifugal compressors for air and nitrogen, discharge pressures up to 30 bar: H Series | 172 |
| Direct-driven Centrifugal turbocompressors polyethylene and polypropylene: T Series | 173 |
| Centrifugal compressors for air and gas applications, up to 70 bar: SC Series | 174 |
| Integrally geared centrifugal compressor for gas and air, up to 70 bar: TP Series | 175 |
| Features of Turbocompressor Products | 176 |
| Integrally-geared turbo expanders for air applications, up to 4,000 kW / 70 bar: ETB, ETG, ETF Series | 177 |
| Radial inflow expansion turbines (turboexpanders): EC, ECM, ECMi | 178 |
| Integrally geared expander generators for industrial applications or energy recovery: EG, EGi | 179 |
| Low Pressure Vertical Turbine Pump: Type TA & TX | 180 |
| Process Radial Diffuser Pump – RD: Versatile Pump Handling Multiple Applications | 181 |
| High Pressure Continuous Crossover: Type CC | 182 |
| TOTAL CUSTOMER CARE | 183 |
| Save energy | 185 |
| Monitor your products | 188 |
| Customer support plans | 191 |
| Upgrade your product | 195 |
| Genuine parts | 196 |
| AIRnet | 206 |

OIL-INJECTED COMPRESSORS

Atlas Copco offers a wide range of oil-injected compressors: from pistons over oil-injected screw compressors, from fixed speed compressors to superior variable speed drive technology...

We offer compressed air solutions for virtually every application and can deliver them, tailored to your exact needs. Our oil-injected compressors are the best choice for all industrial applications requiring high performance, best energy efficiency and premium reliability.

In 1994, Atlas Copco pioneered with variable speed drive technology to offer the market compressed air when they needed it. This technology offers energy savings of 35% on average when compared to fixed speed compressors.

In 2013, Atlas Copco sets a new standard. The GA VSD⁺ technology is the next step in Variable Speed Drive with energy savings of 50% on average!

Oil-injected compressors

We offer durable piston compressors (such as the LE/LT series) and premium screw compressors with high volume flows and efficiencies (GA series, from up to 14 to up to 13 bar and GG gas screw up to 16 bar). If somewhat higher pressures are required, our two-stage GR screw compressors are also available (13 to 20 bar). For pressures up to 350 bar, our C series compressors are available for air and gas applications.

VSD - Direct power savings of 35% on average

- Minimal unloading losses
- Volume flow adjusts to current compressed air requirement
- No wasteful idling
- The precise pressure control in the VSD compressors enables a narrow pressure band and a low working pressure, which results in a lower power requirement

GA VSD+ - Direct power savings of 50% on average

- With the new released GA VSD+ updated VSD technology, 50% energy savings on average can be achieved

Indirect power savings

- The lower working pressure through VSD leads to additional savings of up to 10%
- Lower power requirement for existing base load machines
- Lower leakage losses; e.g., at 6 bar, the air losses are 13% lower than at 7 bar
- Most compressed air applications consume less air at a lower pressure

Whether you cast large diesel engines or vibration dampers for the automotive industry, clean metal parts with sanding machines, or manufacture construction machinery, bicycles, bridge components or household china, we can supply you with the compressed air and gas system you need.

The compressor, the refrigerant dryer, all the filters and condensate drains, the control system, the piping, and even the connections. (Almost) all of them can be integrated into one machine according to your needs – Always reliable and robust, made up of thousands of proven components and extremely efficient.

Wherever a compressed air supply is needed, we have the right equipment. Whether it is shipping companies looking for a compressed air supply for ships, or rolling stock manufacturers, suppliers of coke oven machinery, or providers of welding beads for pipeline construction in the desert. Our compressors supply the right air for every purpose and are extremely reliable, even in the harshest conditions.

Whether our customers are medium-sized businesses or global companies with specific requirements, we can adapt our organization to meet these specific requirements.

We have separate engineering teams for marine and railway settings, and have developed specific products for these industries. In the railway industry, for example, our screw compressors supply working air for braking or to control the valves. Our piston compressors support the main engines on ships when they start up; our equipment can provide the nitrogen required on cargo ships - to extend the shelf life of food being transported by sea, or for cleaning oil pipeline systems. And our spare parts are available worldwide.





Oil-lubricated aluminium piston compressors, 1.5-7.5 kW / 2-10 hp Automan

High performance, easy operation

AUTOMAN compressors are built to provide maximum safety for the user. They require minimal space, are easy to maneuver, and are supplied as a complete ready-to-use system.

- AH 10 - 20E | Page 16
- AF 20 - 30E | Page 17
- AC 20 - 100E | Page 17



Oil-injected rotary screw compressors GA VSD Series

Power savings of 35% on average

Adapting to the fluctuating compressed air requirement. Precise pressure control, flexible operation, and flexible pressure selection result in considerable power savings.

- GA 5-15 VSD | Page 24
- GA 7-15 VSD* | Page 27
- GA 15-30 VSD | Page 31
- GA 37-90 VSD | Page 35
- GA 110-160 VSD | Page 39



Industrial oil-lubricated aluminium piston compressors LE/LT

Powerful, durable and reliable

Ideal for trade and industry. Can be individually combined. For smaller air volumes and high performance, with low energy costs and low environmental impact.

- LE/LT 2-20 | Page 20



Oil-injected rotary screw compressors GA VSD+ Series

On average 50% energy savings

This range provides superior energy savings, with uptimes assured even in the harshest operational conditions. The new vertical set-up also provides a small footprint while silent operation is guaranteed.

- GA VSD+ 7-15 | Page 27



Oil-injected rotary screw compressors, 2-11 kW / 3-15 hp GX 2-11

Proven industrial technology for your workshop

The proven Atlas Copco screw technology is characterized by optimum performance, high reliability, long service life, and low maintenance requirements.

- GX 2-11 | Page 23



Oil-lubricated high pressure compressors High Pressure range

A complete offering up to 500 bar.

- GR 110-200 | Page 45
- B&D | Page 47
- CU/CT/CN | Page 48
- GG | Page 49
- S100/S750 | Page 50



Oil-injected rotary screw compressors GA Series

Robust work horses

This series offers the perfect combination of innovative screw technology, environmentally-friendly design, and outstanding quality with minimal operation and installation costs. Numerous variants and options offer the ideal compressor for any use.

- GA 5-11 | Page 25
- GA 11-30 | Page 31
- GA 30-90 | Page 35
- GA 90-160* | Page 39
- GA 200 - 500 (VSD) | Page 42

Oil-lubricated aluminium piston compressors, 1.5-7.5 kW / 2-10 hp

Automan

Automan oil-lubricated aluminium piston compressors are solid, robust and reliable. They are designed for professional applications where they offer trouble-free performance even under demanding circumstances.

CUSTOMER BENEFITS

• **Solid reliability** - The Automan tank is powder coated, giving it the best protection against damage and corrosion. Its block is slow running, which extends its lifetime.

• **Durable components** - The heavy-duty air intake filter is built to work reliably in dusty conditions and offers long service intervals. The TEFC motor is weather resistant thanks to Class F insulation and IP54 protection. All models are equipped with a pressure reducing valve with quick coupling and D.O.L with a built in pressure differential switch making the compressor complete, ready to operate.

• **Minimum maintenance** - All Automan models are built for easy maintenance. The Automan oil, approved by Atlas Copco, is the guarantee for extended compressor lifetime.



AH 15 E 24



AH 20 E 6



AH 10 E 6



AH 15 E 6

AH series oil-free 230 Volt 1 phase - 8 bar(e)/115 psig

Direct drive - portable or mobile - 6 or 24 l horizontal receiver

| Type | Installed power | | Piston displacement | | rpm | Cylinders | Stages | Mass | |
|-------------------------------|-----------------|------|---------------------|-----|------|-----------|--------|------|-----|
| | hp | kW | l/s | cfm | | | | kg | lbs |
| AH 10 E 6 silent, portable | 1 | 0.75 | 1.4 | 2.9 | 1450 | 1 | 1 | 15 | 33 |
| AH 15 E 6 portable | 1.5 | 1.1 | 2.6 | 5.6 | 3400 | 1 | 1 | 10 | 22 |
| AH 15 E 24 mobile | 1.5 | 1.1 | 2.6 | 5.6 | 3400 | 1 | 1 | 18 | 40 |
| AH 20 E 6 roll cage, portable | 2 | 1.5 | 3.2 | 6.8 | 2850 | 1 | 1 | 22 | 48 |



AF 20 E 6



AF 20 E 10



AF 30 E 22



AF 20 E 24



AF 30 E 24

AF series 230 Volt 1 phase - 8 bar(e)/115 psig for AF 20 E or 10 bar(e)/145 psig for AF 30 E

Direct drive - stationary or mobile – 2 x 11, 6, 10, 24, 50 or 90 l receiver

| Type | Installed power | | Piston displacement | | Free air delivery | | rpm | Cylinders | Stages |
|---------|-----------------|-----|---------------------|-----|-------------------|-----|------|-----------|--------|
| | hp | kW | l/s | cfm | l/s | cfm | | | |
| AF 20 E | 2 | 1.5 | 3.2 | 6.8 | 1.7 | 3.6 | 2850 | 1 | 1 |
| AF 30 E | 3 | 2.2 | 5.2 | 11 | 3.1 | 6.6 | 1450 | 2 | 1 |



AC 75 E 300 V



AC 21 E 90 H



AC 55 E 270 H

AC series 230 Volt 1 phase - 10 bar(e)/145 psig

Belt drive - stationary or mobile – 27, 50, 90 or 200 l horizontal alternatively 150 l vertical receiver

| Type | Installed power | | Piston displacement | | Free air delivery | | rpm | Cylinders | Stages |
|---------|-----------------|-----|---------------------|------|-------------------|-----|-----|-----------|--------|
| | hp | kW | l/s | cfm | l/s | cfm | | | |
| AC 21 E | 2 | 1.5 | 3.1 | 6.6 | 1.8 | 3.8 | 777 | 2 | 1 |
| AC 31 E | 3 | 2.2 | 5.8 | 12.3 | 4.2 | 8.9 | 950 | 2 | 1 |

AC series 230 or 400 V 3 phase - 10 bar(e)/145 psig for AC 20-30 E, 11 bar(e)/160 psig for AC 40-100 E

Belt drive - stationary or mobile – 50, 90, 200, 270 or 500 l horizontal alternatively 270 l vertical receiver - Star Delta starter from 5.5 hp

| Type | Installed power | | Piston displacement | | Free air delivery | | rpm | Cylinders | Stages |
|----------|-----------------|-----|---------------------|------|-------------------|------|------|-----------|--------|
| | hp | kW | l/s | cfm | l/s | cfm | | | |
| AC 21 E | 2 | 1.5 | 3.8 | 8.1 | 2.2 | 4.7 | 950 | 2 | 1 |
| AC 31 E | 3 | 2.2 | 5.8 | 12.3 | 4.2 | 8.9 | 950 | 2 | 1 |
| AC 40 E | 4 | 3 | 7.7 | 16.3 | 5.7 | 12.1 | 1303 | 2 | 2 |
| AC 55 E | 5.5 | 4 | 10.6 | 22.4 | 6.9 | 14.6 | 975 | 2 | 2 |
| AC 75 E | 7.5 | 5.5 | 13.9 | 29.5 | 10.7 | 23.3 | 663 | 2 | 2 |
| AC 100 E | 10 | 7.5 | 16.7 | 35.4 | 12.9 | 27.5 | 795 | 2 | 2 |

AC series 230 or 400 V 3 phase - 14 bar(e)/203 psig

Belt drive - stationary - 300 or 500 l horizontal alternatively 270 l vertical receiver – Star Delta starter from 5.5 hp

| Type | Installed power | | Piston displacement | | Free air delivery | | rpm | Cylinders | Stages |
|----------|-----------------|-----|---------------------|------|-------------------|------|-----|-----------|--------|
| | hp | kW | l/s | cfm | l/s | cfm | | | |
| AC 40 T | 4 | 3 | 5.3 | 11.2 | 3.9 | 8.3 | 896 | 2 | 2 |
| AC 55 T | 5.5 | 4 | 8.1 | 17.2 | 5.3 | 11.2 | 750 | 2 | 2 |
| AC 75 T | 7.5 | 5.5 | 11.2 | 23.6 | 8.6 | 18.2 | 530 | 2 | 2 |
| AC 100 T | 10 | 7.5 | 13.9 | 29.5 | 10.7 | 22.7 | 663 | 2 | 2 |



Petrol & diesel series 10-14 bar/145-203 psi

| Type | Model | Motor | | | Vessel | Pressure | | FAD @ 7 bar | | Weight |
|-------------------------------|------------|-------|-----|--------|--------|----------|-----|-------------|------|--------|
| | | hp | kW | Fuel | | bar | psi | l/m | cfm | |
| AC40E100 Petrol | Mobile | 3.5 | 2.6 | Petrol | 100 | 10 | 145 | 188 | 6.7 | 71 |
| AC55E50 Petrol | Mobile | 4.8 | 3.6 | Petrol | 50 | 10 | 145 | 251 | 8.9 | 73 |
| AC55E100 Petrol | Mobile | 4.8 | 3.6 | Petrol | 100 | 10 | 145 | 251 | 8.9 | 94 |
| AC55E200 Petrol | Mobile | 4.8 | 3.6 | Petrol | 200 | 10 | 145 | 251 | 8.9 | 120 |
| AC55E11*11 Petrol | Mobile | 4.8 | 3.6 | Petrol | 11+11 | 10 | 145 | 251 | 8.9 | 70 |
| AC55E11*11R Petrol | Rollbar | 4.8 | 3.6 | Petrol | 11+11 | 10 | 145 | 254 | 9.0 | 70 |
| AC71E25*25R Petrol | Rollbar | 7.1 | 5.3 | Petrol | 25+25 | 10 | 145 | 416 | 14.7 | 143 |
| AC71T270 Petrol | Stationary | 7.1 | 5.3 | Petrol | 270 | 14 | 203 | 347 | 12.3 | 223 |
| AC100T270 Petrol | Stationary | 10.7 | 8.2 | Petrol | 270 | 14 | 203 | 571 | 20.2 | 235 |
| AC71T270 Diesel | Stationary | 7.5 | 5.5 | Diesel | 270 | 14 | 203 | 485 | 17.1 | 239 |
| AC110T270 Diesel | Stationary | 10.9 | 8.2 | Diesel | 270 | 14 | 203 | 762 | 26.9 | 258 |
| AC75T270 Diesel 2KvA | Stationary | 7.5 | 5.5 | Diesel | 270 | 14 | 203 | 302 | 10.7 | 265 |
| AC110T270 Diesel 2KvA | Stationary | 10.9 | 8.2 | Diesel | 270 | 14 | 203 | 439 | 15.5 | 270 |
| Silencer extension kit Petrol | Option | - | - | Petrol | - | - | - | - | - | - |
| Silencer extension kit Diesel | Option | - | - | Diesel | - | - | - | - | - | - |

Industrial oil-lubricated aluminium piston compressors

LE/LT

Looking for a durable, high-performance compressed air solution for your specific industrial application? Designed with the highest attention to quality, Atlas Copco's LE/LT oil-lubricated aluminium piston compressors stand for exceptional reliability and low operating costs. LE is your compressor for 10 bar and the LT for 15, 20 or 30 bar applications. Incorporating state-of-the-art technology, LE/LT compressors deliver the lowest operating temperatures in the industry, while offering quality air with very low oil carryover. Proven design and high-quality materials ensure performance and extra long life. The LE/LT range is suitable for stand-alone use or easy integration in your OEM product. Atlas Copco also offers an oil-free piston compressor: the LF.



LE/LT Compressor

CUSTOMER BENEFITS

- **Solid reliability** – Thanks to a unique, robust design and the optimal combination of quality materials, LE/LT compressors offer improved performance and extended product life. The fan is designed for an optimal cooling air flow.
- **Low running costs** – Operational costs are limited and due to the use of highly durable components the compressors have a long lifetime. Easy maintenance – All components and service points are easily accessible.
- **Saving floor space** – The compressor block which is directly coupled to the motor is manufactured using lightweight materials. This provides excellent cooling characteristics: ideal for integration with limited space requirements.

FEATURES



- Oil-lubricated or 100% oil-free (see LF compressors)
- Direct drive
- Working pressure up to 30 bar
- IP-55 electric motors with ISO Class F

Valve assembly

The patented stainless "Flexi-Disc Valve Assembly" provides a consistent air flow. The system also has a special construction designed for very long operating times

Aluminum construction

The aluminum casing with cooling fins, supported by a large fan, ensures optimum heat dissipation.

Piston – cylinder assembly

The ideal combination of cylinders and pistons has an aluminum-silicon alloy and a graphite insert. This guarantees excellent, smooth operating characteristics, even with too little oil.



LE/LT 2–20
oil-lubricated piston compressors

| Type | Maximum working pressure | Volume flow ¹⁾ | | Motor rated power | Sound pressure level ²⁾ | | Container volume ³⁾ | Approx. Weight | Dimensions L × W × H |
|----------------------------|--------------------------------|---------------------------|--------|-------------------------|------------------------------------|----|-----------------------------------|-------------------|-------------------------|
| | bar | l/s | m³/min | kW | db(A) | | L | kg | mm |
| LE/LT – Piston compressors | | | | | | | | | |
| LE 2–10/90 | 10 | 3.40 | 0.20 | 1.5 | 80 | 65 | 90 | 85 | 1118 × 510 × 1017 |
| LE 3–10/90 | 10 | 4.40 | 0.26 | 2.2 | 81 | 66 | 90 | 89 | 1118 × 510 × 1017 |
| LE 5–10/250 | 10 | 8.40 | 0.50 | 4.0 | 81 | 66 | 250 | 150 | 1852 × 510 × 1082 |
| LE 7–10/250 | 10 | 11.70 | 0.70 | 5.5 | 82 | 70 | 250 | 191 | 1852 × 592 × 1162 |
| LE 10–10/250 | 10 | 15.70 | 0.94 | 7.5 | 83 | 70 | 250 | 203 | 1852 × 592 × 1162 |
| LE 15–10/250 | 10 | 18.60 | 1.12 | 11.0 | 86 | - | 250 | 330 | 1852 × 790 × 1200 |
| LE 20–10/250 | 10 | 23.90 | 1.43 | 15.0 | 86 | - | 250 | 360 | 1852 × 790 × 1200 |
| LT 2–15/90 | 15 | 3.10 | 0.19 | 1.5 | 80 | 65 | 90 | 100 | 1118 × 533 × 1017 |
| LT 3–15/90 | 15 | 4.00 | 0.24 | 2.2 | 81 | 66 | 90 | 104 | 1118 × 533 × 1017 |
| LT 5–15/250 | 15 | 6.70 | 0.40 | 4.0 | 81 | 66 | 250 | 170 | 1852 × 533 × 1082 |
| LT 7–15/250 | 15 | 9.20 | 0.55 | 5.5 | 82 | 70 | 250 | 211 | 1852 × 606 × 1162 |
| LT 10–15/250 | 15 | 11.70 | 0.70 | 7.5 | 83 | 70 | 250 | 223 | 1852 × 606 × 1162 |
| LT 2–20/90 | 20 | 2.10 | 0.13 | 1.5 | 80 | 65 | 90 | 100 | 1118 × 533 × 1017 |
| LT 3–20/90 | 20 | 2.90 | 0.17 | 2.2 | 81 | 66 | 90 | 104 | 1118 × 533 × 1017 |
| LT 5–20/250 | 20 | 5.00 | 0.30 | 4.0 | 81 | 66 | 250 | 170 | 1852 × 533 × 1082 |
| LT 7–20/250 | 20 | 6.70 | 0.40 | 5.5 | 82 | 70 | 250 | 211 | 1852 × 606 × 1162 |
| LT 10–20/250 | 20 | 9.10 | 0.55 | 7.5 | 83 | 70 | 250 | 223 | 1852 × 606 × 1162 |
| LT 15–20/250 | 20 | 15.10 | 0.91 | 11.0 | 86 | 73 | 250 | 333 | 1852 × 830 × 1980 |
| LT 20–20/250 | 20 | 18.00 | 1.08 | 15.0 | 86 | 73 | 250 | 361 | 1852 × 830 × 1980 |
| LT 3–30 | 30 | 2.50 | 0.15 | 2.2 | 81 | - | - | 49 | 686 × 533 × 497 |
| LT 5–30 | 30 | 4.40 | 0.26 | 4.0 | 81 | - | - | 51 | 686 × 533 × 497 |
| LT 7–30 | 30 | 6.40 | 0.38 | 5.5 | 82 | - | - | 90 | 860 × 606 × 600 |
| LT 10–30 | 30 | 8.50 | 0.51 | 7.5 | 83 | - | - | 102 | 932 × 606 × 600 |
| LT 15–30 | 30 | 9.30 | 0.56 | 11.0 | 83 | - | - | 166 | 1024 × 682 × 675 |
| LT 20–30 | 30 | 17.00 | 1.02 | 15.0 | 89 | - | - | 194 | 1103 × 713 × 675 |

¹⁾ Volume flow measured in accordance with ISO 1217, Ed. 4, Appendix C-2009, reference conditions: dry intake air, intake pressure 1 bar, coolant temperature 20°C. Details for: 10-bar versions at 7 bar, 15-bar versions at 12 bar, 20-bar versions at 20 bar, 30-bar versions at 30 bar. Volume flow reduction through regeneration air requirement on versions with cd dryers.

²⁾ Sound pressure level measured in accordance with ISO 2151, Edition 2004 with a tolerance of 3 dB(A); right column in table LE/LT for versions with canopy. Voltage 400 V/50 Hz. Other voltages available on request.

³⁾ Other container sizes available on request



We can help you to choose the best option

As well as the product quality and product range, we have focused on a combined product portfolio. This includes compressors with a drive performance of 1.5–15 kW, and volume flows of 3.4–24 l/s, as well as a variety of other options.

We will help you find a compressor that suits your demands and requirements at all times.

Special design / options- the LE / LT series



LE / LT unit



LE / LT with acoustic enclosure
(Pack)



LE-/LT-Trolley mobile version available with electric
or petrol engine



LE / LT (15 bar) on standing vessel



LE / LT (15 bar), special version.
Complete compressed air station with FX refrigerant
dryer and DD + PD filters, on vessel



LE / LT-special version
Quality compressed air system with CD adsorption kit on
container (volume reduction due to purge air requirement)

Oil-injected rotary screw compressors, 2-11 kW / 3-15 hp GX 2-11

Atlas Copco's oil-injected rotary screw GX compressors are the powerful and reliable industrial screw compressors for small and medium sized industries. The GX compressors are available in various versions (floor mounted, tank mounted, with or without integrated dryer) to provide flexibility. Built from high-quality components and materials, they provide a reliable source of high-quality air in temperatures up to 46°C/115°F.



CUSTOMER BENEFITS

- **Reliability** – The GX series is designed, manufactured and tested in accordance with ISO 9001, ISO 14001 and ISO 1217. The screw compressor technology allows 100% continuous duty cycle and the reinforced frame eliminates resonance. GX compressors are built for a long lifetime of reliable operation.
- **Reduced energy costs** – Our GX compressors offer the low energy consumption and high efficiency of a rotary screw compressor. Compared to piston compressors that suffer from increased energy consumption over time, these screw compressors always provide high efficiency.
- **Plug and play installation** – In addition to boasting a minimum footprint, the GX series discharges cooling air from the top, allowing placement against the wall or in a corner. The tank mounted GX with built-in dryer reduces space requirements even further, making it ideal if you have limited space at your facility.
- **Silent operation** – Atlas Copco supplies GX compressors with full sound enclosures which reduce the sound levels to as low as 61 dB(A). The rotary screw technology minimizes vibration, while optimized cooling air flow enhances quiet operation.
- **Integrated air treatment** – The GX 2-11 FF is available with an advanced built-in refrigerant air dryer. By cooling the compressed air and removing water before it can enter your compressed air network, it prevents rust in your compressed air piping and avoids damage to your air tools.

GX 2-11 SERIES

Easy maintenance at low costs

- Fewer wear parts
- Longer service intervals
- Easy service access with front door and removable side parts
- Guaranteed long service life for components



| Type | Max. working pressure | | Capacity fad | | | Installed motor power* | | Noise level** | Weight (kg/lbs)* | |
|---------------|-----------------------|-----|--------------|-------|------|------------------------|-----|---------------|------------------|-----------------|
| | bar(e) | psi | l/s | m³/h | cfm | kW | hp | dB(A) | Pack | Full feature*** |
| 50 Hz VERSION | | | | | | | | | | |
| GX 2 EP | 10 | 145 | 4.0 | 14.4 | 8.5 | 2.2 | 3 | 61 | 165/364 | 200/441 |
| GX 3 EP | 10 | 145 | 5.3 | 19.1 | 11.2 | 3 | 4 | 61 | 165/364 | 200/441 |
| GX 4 EP | 10 | 145 | 7.8 | 28.1 | 16.5 | 4 | 5 | 62 | 165/364 | 200/441 |
| GX 5 EP | 10 | 145 | 10.0 | 36.0 | 21.2 | 5.5 | 7.5 | 64 | 165/364 | 200/441 |
| GX 7 EP | 10 | 145 | 14.0 | 50.4 | 29.7 | 7.5 | 10 | 66 | 214/472 | 264/582 |
| GX 7 EL | 7.5 | 109 | 19.6 | 70.6 | 41.5 | 7.5 | 10 | 65 | 245/540 | 314/692 |
| | 10 | 145 | 16.1 | 58.0 | 34.1 | 7.5 | 10 | 65 | 245/540 | 314/692 |
| | 13 | 189 | 12.9 | 46.4 | 27.3 | 7.5 | 10 | 65 | 245/540 | 314/692 |
| GX 11 EL | 7.5 | 109 | 27.0 | 97.2 | 57.2 | 11 | 15 | 67 | 257/567 | 326/719 |
| | 10 | 145 | 23.3 | 83.9 | 49.4 | 11 | 15 | 67 | 257/567 | 326/719 |
| | 13 | 189 | 19.0 | 68.4 | 40.3 | 11 | 15 | 67 | 257/567 | 326/719 |
| 60 Hz VERSION | | | | | | | | | | |
| GX 2 EP | 10.3 | 150 | 4.0 | 14.4 | 8.5 | 2.2 | 3 | 61 | 165/364 | 200/441 |
| GX 4 EP | 10.3 | 150 | 7.8 | 28.1 | 16.5 | 4 | 5 | 62 | 165/364 | 200/441 |
| GX 5 EP | 10.3 | 150 | 10.0 | 36.0 | 21.2 | 5.5 | 7.5 | 64 | 165/364 | 200/441 |
| GX 7 EP | 10.3 | 150 | 13.8 | 49.6 | 29.2 | 7.5 | 10 | 66 | 214/472 | 264/582 |
| GX 7 EL | 7.4 | 107 | 19.5 | 70.2 | 41.3 | 7.5 | 10 | 67 | 245/540 | 314/692 |
| | 9.1 | 132 | 17.3 | 62.3 | 36.7 | 7.5 | 10 | 67 | 245/540 | 314/692 |
| | 10.8 | 157 | 14.9 | 53.6 | 31.6 | 7.5 | 10 | 67 | 245/540 | 314/692 |
| | 12.5 | 181 | 12.3 | 44.3 | 26.1 | 7.5 | 10 | 67 | 245/540 | 314/692 |
| GX 11 EL | 7.4 | 107 | 27.8 | 100.1 | 58.9 | 11 | 15 | 68 | 257/567 | 326/719 |
| | 9.1 | 132 | 24.7 | 88.9 | 52.3 | 11 | 15 | 68 | 257/567 | 326/719 |
| | 10.8 | 157 | 22.5 | 81.0 | 47.7 | 11 | 15 | 68 | 257/567 | 326/719 |
| | 12.5 | 181 | 20.0 | 72.0 | 42.4 | 11 | 15 | 68 | 257/567 | 326/719 |

EP: Electropneumatic; EL: Elektronikon.

Standard air receiver size, GX 2-7 EP: 200 l/60 gal, GX 7-11 EL: 270 l/80 gal.

*Unit performance measured according to ISO 1217, latest edition.

**Mean noise level (pack variant) measured according to Pneurop/Cagi PN8NTC2 test code; tolerance 3 dB(A).

*** Tank mounted variant.

| Available options | GX 2-7 EP | GX 2-7 EP FF | GX 7-11 EL | GX 7-11 EL FF |
|--|-----------|--------------|------------|---------------|
| Integrated aftercooler | - | - | ○ | ● |
| Water separator (shipped loose) | - | ● | ○ | ● |
| Timer water drain on water separator (shipped loose) | - | - | ○ | - |
| Timer drain on air receiver (tank mounted only) | ○ | ○ | ○ | ○ |
| Electronic no loss water drain on water separator (shipped loose) | - | ● | ○ | ● |
| Electronic no loss water drain on air receiver (500 l/120 gal tank mounted only) | ○ | ○ | ○ | ○ |
| Integrated DDx filter kit | - | - | - | ○ |
| Integrated high performance PDx filter kit | - | ○ | - | ○ |
| 500 l/120 gal air receiver (tank mounted only) | - | - | ○ | ○ |
| Tropical thermostat | - | - | ○ | ○ |

- : Not available


● : Standard

○ : Optional


| | L (mm) | W (mm) | H (mm) |
|----------------------------|------------|----------|--------|
| PACK FLOOR MOUNTED | | | |
| GX 2-7 EP | 620 | 575/605* | 975 |
| GX 7-11 EL | 810/840* | 590 | 1085 |
| FULL FEATURE FLOOR MOUNTED | | | |
| GX 2-7 EP | - | - | - |
| GX 7-11 EL | 1205/1235* | 590 | 1085 |
| PACK TANK MOUNTED | | | |
| GX 2-7 EP | 1420 | 575 | 1280 |
| GX 7-11 EL** | 1533 | 590 | 1332 |
| FULL FEATURE TANK MOUNTED | | | |
| GX 2-7 EP | 1420 | 575 | 1280 |
| GX 7-11 EL** | 1533 | 590 | 1332 |

* Length with inlet grating.

** Dimensions of GX 7-11 EL tank mounted are 1935 x 590 x 1463 mm (L x W x H) with a 500 l vessel and 1880 x 590 x 1463 mm (L x W x H) with a 120 gal vessel.



GX 2-7 EP
(floor mounted)



GX 7-11 EL FF
(tank mounted)

Oil-injected rotary screw compressors, 5.5-11 KW / 7.5-15 hp

GA 5-11/GA 5-15 VSD

Atlas Copco's oil-injected rotary screw compressors are leader in the market thanks to outstanding performance and flexible operation. This results in the highest productivity while minimizing the total cost of ownership. GA compressors are available in two series: GA 5-11 and GA 5-15 VSD. The GA 5-11 is the best workshop solution, built to perform even in the harshest conditions. The GA 5-15 VSD range is the ideal solution for productions with a fluctuating air demand, optimizing your energy consumption. Both ranges supply the high-quality air you need to keep your air network clean and your production up and running.

CUSTOMER BENEFITS

- **Highest reliability** – The GA series is designed, manufactured and tested in accordance with ISO 9001, ISO 14001 and ISO 1217. Ensuring a long and trouble-free life at the lowest operating cost. The compressor contains the latest generation of Atlas Copco's innovative oil-injected screw element.

- **Reduced energy costs** – Our GA compressors can reduce your energy costs and overall compressor lifecycle costs thanks to the use of our highly efficient element. Furthermore, the GA Variable Speed Drive (VSD) reduces energy costs by a further 35% by automatically adjusting the air supply to your air demand with a large turndown operating range.

- **Air system integration** – The GA Work Place Air System can be installed where you need compressed air. Its low noise operation and integrated air treatment equipment eliminates the need for a separate compressor room. All GA compressors are tested and delivered ready for use. The integrated options will reduce installation costs and pressure drops significantly, thus saving additional energy cost.

- **Advanced control and monitoring** – To maximize efficiency and reliability, the Elektronikon® controls the main drive motor and regulates system pressure within a predefined and narrow pressure band. The Elektronikon® controller can be adapted to your specific needs with extra sensors, digital contacts, fieldbus, Internet and SMS communication functions. In combination with the ES multiple compressor controller, the operation of your complete compressor room is optimized.

- **Integrated air treatment** – All GA compressors can be installed with integrated dryers, filters and oil-water separators to protect your compressed air network. This quality air expands the life of equipment, increasing efficiency and ensuring quality in your final product.



| Type | | Working pressure workplace | | Capacity FAD* min-max | | | Installed motor power | | Noise level** | Weight (kg) | | | |
|---------------|-----|-------------------------------|------|--------------------------|-------|------|--------------------------|-----|------------------|-------------|---------------|------------------------|-------------------|
| | | | | | | | | | | Workplace | | Workplace Full feature | |
| | | bar(e) | psig | l/s | m³/h | cfm | kW | hp | | dB(A) | Floor-mounted | Tank-mounted | Floor- mounted |
| 50 Hz VERSION | | | | | | | | | | | | | |
| GA 5 | 7.5 | 7.5 | 109 | 15.0 | 54.0 | 31.7 | 5.5 | 7.5 | 60 | 257 | 317 | 300 | 360 |
| | 8.5 | 8.5 | 123 | 13.2 | 47.5 | 27.9 | 5.5 | 7.5 | 60 | 257 | 317 | 300 | 360 |
| | 10 | 10 | 145 | 11.7 | 42.1 | 24.7 | 5.5 | 7.5 | 60 | 257 | 317 | 300 | 360 |
| | 13 | 13 | 189 | 8.4 | 30.2 | 17.7 | 5.5 | 7.5 | 60 | 257 | 317 | 300 | 360 |
| GA 7 | 7.5 | 7.5 | 109 | 21.0 | 75.6 | 44.3 | 7.5 | 10 | 61 | 270 | 330 | 315 | 375 |
| | 8.5 | 8.5 | 123 | 21.8 | 78.5 | 46.0 | 7.5 | 10 | 61 | 270 | 330 | 315 | 375 |
| | 10 | 10 | 145 | 17.2 | 70.6 | 36.3 | 7.5 | 10 | 61 | 270 | 330 | 315 | 375 |
| | 13 | 13 | 189 | 14.2 | 51.1 | 30.0 | 7.5 | 10 | 61 | 270 | 330 | 315 | 375 |
| GA 11 | 7.5 | 7.5 | 109 | 30.7 | 110.5 | 64.8 | 11 | 15 | 62 | 293 | 353 | 343 | 403 |
| | 8.5 | 8.5 | 123 | 28.3 | 101.9 | 59.7 | 11 | 15 | 62 | 293 | 353 | 343 | 403 |
| | 10 | 10 | 145 | 26.0 | 93.6 | 54.9 | 11 | 15 | 62 | 293 | 353 | 343 | 403 |
| | 13 | 13 | 189 | 22.0 | 79.2 | 46.5 | 11 | 15 | 62 | 293 | 353 | 343 | 403 |

| Type | | Max. working pressure workplace | | Capacity FAD* min-max | | | Installed motor power | | Noise level** | Weight (kg/lbs) | | | |
|---------------|-----|---------------------------------|------|-----------------------|-------|------|-----------------------|-----|---------------|-----------------|---------------|------------------------|---------------|
| | | | | | | | | | | Workplace | | Workplace Full feature | |
| | | bar(e) | psig | l/s | m³/h | cfm | kW | hp | | dB(A) | Floor-mounted | Tank-mounted | Floor-mounted |
| 60 Hz VERSION | | | | | | | | | | | | | |
| GA 5 | 100 | 7.4 | 107 | 15.0 | 54.0 | 31.7 | 5.5 | 7.5 | 60 | 257 | 317 | 300 | 360 |
| | 125 | 9.1 | 132 | 13.2 | 47.5 | 27.9 | 5.5 | 7.5 | 60 | 257 | 317 | 300 | 360 |
| | 150 | 10.8 | 157 | 11.7 | 42.1 | 24.7 | 5.5 | 7.5 | 60 | 257 | 317 | 300 | 360 |
| | 175 | 12.5 | 181 | 8.4 | 30.2 | 17.7 | 5.5 | 7.5 | 60 | 257 | 317 | 300 | 360 |
| GA 7 | 100 | 7.4 | 107 | 21.0 | 75.6 | 44.3 | 7.5 | 10 | 61 | 270 | 330 | 315 | 375 |
| | 125 | 9.1 | 132 | 21.8 | 78.5 | 46.0 | 7.5 | 10 | 61 | 270 | 330 | 315 | 375 |
| | 150 | 10.8 | 157 | 17.2 | 70.6 | 36.3 | 7.5 | 10 | 61 | 270 | 330 | 315 | 375 |
| | 175 | 12.5 | 181 | 14.2 | 51.1 | 30.0 | 7.5 | 10 | 61 | 270 | 330 | 315 | 375 |
| GA 11 | 100 | 7.4 | 107 | 30.4 | 109.4 | 64.1 | 11 | 15 | 62 | 293 | 353 | 343 | 403 |
| | 125 | 9.1 | 132 | 27.0 | 97.2 | 57.0 | 11 | 15 | 62 | 293 | 353 | 343 | 403 |
| | 150 | 10.8 | 157 | 24.9 | 89.6 | 52.5 | 11 | 15 | 62 | 293 | 353 | 343 | 403 |
| | 175 | 12.5 | 181 | 22.0 | 79.2 | 46.4 | 11 | 15 | 62 | 293 | 353 | 343 | 403 |

* Unit performance measured according to ISO 1217, Ed. 3, Annex E-1996.

** Mean noise level measured at a distance of 1 m according to ISO 2151; tolerance 3 dB(A).

Reference conditions:

- Absolute inlet pressure 1 bar (14.5 psi).
- Intake air temperature 20°C, 68°F.

FAD is measured at the following working pressures:

- 7.5 bar versions at 7 bar(e).
- 8.5 bar versions at 8 bar(e).
- 10 bar versions at 9.5 bar(e).
- 13 bar versions at 12.5 bar(e).

Maximum working pressure for VSD machines:

- 13 bar(e) (188 psig)



GA 5-7-11 pack & GA 5-7-11-15 VSD pack
(floor-mounted)



GA 5-7-11 pack & GA 5-7-11-15 VSD pack
(tank-mounted)

| Type | Max. working pressure workplace | | Capacity FAD* min-max | | | Installed motor power | | Noise level** | Weight (kg/lbs) | | | |
|--------------------|---------------------------------|------|-----------------------|------------|-----------|-----------------------|-----|---------------|-----------------|--------------|------------------------|--------------|
| | bar(e) | psig | l/s | m³/h | cfm | kW | hp | | Workplace | | Workplace FULL FEATURE | |
| | | | | | | | | | Floor-mounted | Tank-mounted | Floor-mounted | Tank-mounted |
| 50 / 60 Hz VERSION | | | | | | | | | | | | |
| GA 5 VSD | 5.5 | 80 | 6.1-15.2 | 22.0-54.7 | 13.4-33.4 | 5.5 | 7.5 | 62 | 275 | 335 | 318 | 378 |
| | 7.5 | 109 | 6.0-15.0 | 21.6-54.0 | 13.2-33.0 | 5.5 | 7.5 | 62 | 275 | 335 | 318 | 378 |
| | 10 | 145 | 6.8-11.7 | 24.5-42.1 | 15.0-25.7 | 5.5 | 7.5 | 62 | 275 | 335 | 318 | 378 |
| | 13 | 188 | 8.3-10 | 29.9-36.0 | 18.3-22.0 | 5.5 | 7.5 | 62 | 275 | 335 | 318 | 378 |
| GA 7 VSD | 5.5 | 80 | 5.1-20.5 | 18.4-73.8 | 11.2-45.1 | 7.5 | 10 | 64 | 280 | 340 | 325 | 385 |
| | 7.5 | 109 | 5.1-20.3 | 18.4-73.1 | 11.2-44.7 | 7.5 | 10 | 64 | 280 | 340 | 325 | 385 |
| | 10 | 145 | 6.5-16.8 | 23.4-60.5 | 14.3-37.0 | 7.5 | 10 | 64 | 280 | 340 | 325 | 385 |
| | 13 | 188 | 7.9-13.8 | 28.4-49.7 | 17.4-30.4 | 7.5 | 10 | 64 | 280 | 340 | 325 | 385 |
| GA 11 VSD | 5.5 | 80 | 8.2-31 | 29.5-111.6 | 18.0-68.2 | 11 | 15 | 66 | 293 | 353 | 343 | 403 |
| | 7.5 | 109 | 8.1-30.7 | 29.2-110.5 | 17.8-67.5 | 11 | 15 | 66 | 293 | 353 | 343 | 403 |
| | 10 | 145 | 8.7-24.1 | 31.3-86.8 | 19.1-53.0 | 11 | 15 | 66 | 293 | 353 | 343 | 403 |
| | 13 | 188 | 10.2-20.7 | 36.7-74.5 | 22.4-45.5 | 11 | 15 | 66 | 293 | 353 | 343 | 403 |
| GA 15 VSD | 5.5 | 80 | 9.0-37.5 | 32.4-135.0 | 19.8-82.5 | 15 | 20 | 69 | 300 | 360 | 352 | 412 |
| | 7.5 | 109 | 9.1-37.1 | 32.8-133.6 | 20.0-81.6 | 15 | 20 | 69 | 300 | 360 | 352 | 412 |
| | 10 | 145 | 8.8-30.9 | 31.7-111.2 | 19.4-68.0 | 15 | 20 | 69 | 300 | 360 | 352 | 412 |
| | 13 | 188 | 8.5-24.8 | 30.6-89.3 | 18.7-54.6 | 15 | 20 | 69 | 300 | 360 | 352 | 412 |

* Unit performance measured according to ISO 1217, Ed. 3, Annex E-1996.

** Mean noise level measured at a distance of 1 m according to ISO 2151; tolerance 3 dB(A).

Reference conditions:

- Absolute inlet pressure 1 bar (14.5 psi).

- Intake air temperature 20°C, 68°F.

FAD is measured at the following working pressures:

- 7.5 bar versions at 7 bar(e).

- 8.5 bar versions at 8 bar(e).

- 10 bar versions at 9.5 bar(e).

- 13 bar versions at 12.5 bar(e).

Maximum working pressure for VSD machines:

- 13 bar(e) (188 psig)



GA 5-7-11 FF & GA 5-7-11-15 VSD FF
(floor-mounted)



GA 5-7-11 FF & GA 5-7-11-15 VSD FF
(tank-mounted)

Oil-injected rotary screw compressors, with variable speed drive⁺, 7-15 kW / 10-20 hp

GA 7-15 VSD⁺

Atlas Copco's GA VSD⁺ range brings a game-changing innovation to the general industry. The GA 7-15 VSD⁺ variable speed drive compressor reduces your energy consumption by a staggering 50% on average, compared to idling compressors. At the same time it offers improved performance, silent operation (down to 62 dB(A)) and a compact footprint, thanks to its vertical drive train design. The heart of the GA VSD⁺ is an interior permanent magnet motor, directly coupled to Atlas Copco's best-in-class screw element: all of which have been in-house designed and have patents pending. All these benefits make the GA VSD⁺ the compressor of the future, setting a new standard in the industry for years to come.



CUSTOMER BENEFITS

• **Highest reliability** – The GA VSD⁺ has proven its reliability during extensive field-testing. The drive train is a completely closed, oil-cooled unit that is both quiet and reliable (IP 66), even in the harshest conditions.

• **Exceptional energy savings** – Atlas Copco's GA Variable Speed Drive⁺ (VSD⁺) technology closely follows the air demand by automatically adjusting the motor speed to match the compressed air supply to the air demand. Combined with the innovative design of the iPM (Permanent Magnet) motor (efficiency corresponding to IE4 efficiency), this results in average energy savings of 50% and an average cut of 37% in the lifecycle cost of a compressor. A new, more efficient fan motor achieves another saving on specific energy requirements of up to 7% of the compressor power.

On top of the energy savings, the GA VSD⁺ realizes a Free Air Delivery (FAD) increase of up to 12%. The design of the motor and the drive train are protected by pending patents.

• **Air system integration** – The GA VSD⁺ is compact, with a footprint that is less than half of the current GA VSD. Thanks to the silent motor and fully-enclosed drive train, this compressor runs as quietly as 62 dB(A). Thanks to its smart design, all maintenance parts are easy accessible and the compressor allows for installation close to a wall or even in corners.

• **Advanced control and monitoring** – To maximize efficiency and reliability, the Elektronikon[®] controls the main drive motor and regulates system pressure within a predefined and narrow pressure band. The Elektronikon[®] controller can be adapted to your specific needs with extra sensors, digital contacts, fieldbus, Internet and SMS communication functions. In combination with the ES multiple compressor controller, the operation of your complete compressor room is optimized.

• **Integrated air treatment** – The GA VSD⁺ is available in a Full Feature version that includes an energy-friendly integrated refrigerant dryer of the newest generation.

| Technical specifications | Metric | Imperial |
|--------------------------|--------------------------------|-----------------|
| Capacity FAD | 6.7 - 41.2 l/s | 6.7 - 41.2 l/s |
| Capacity FAD | 21.1 - 148.3 m ³ /h | 14.2 - 87.3 cfm |
| Working pressure | 4 - 13 bar(e) | 58 - 188 psig |
| Installed motor power | 7 - 15 kW | 10 - 20 hp |

| Type | Maximum working pressure workplace | | Capacity FAD* min-max | | | Installed motor power | | Noise level** | Weight workplace | Weight Workplace Full feature |
|------------|------------------------------------|------|-----------------------|------------|-----------|-----------------------|----|---------------|------------------|-------------------------------|
| | bar(e) | psig | l/s | m³/h | cfm | kW | hp | | | |
| GA 7 VSD+ | 5.5 | 80 | 7.1-21.8 | 25.5-78.5 | 15.0-46.2 | 7.5 | 10 | 62 | 193 | 277 |
| | 7 | 102 | 7.0-21.6 | 25.2-77.8 | 14.8-45.7 | 7.5 | 10 | 62 | 193 | 277 |
| | 9.5 | 138 | 6.7-17.9 | 24.1-64.4 | 14.2-37.9 | 7.5 | 10 | 62 | 193 | 277 |
| | 12.5 | 181 | 7.2-14.1 | 25.9-50.7 | 15.2-29.8 | 7.5 | 10 | 62 | 193 | 277 |
| GA 11 VSD+ | 5.5 | 80 | 7.2-32.4 | 25.9-116.6 | 15.2-68.6 | 11 | 15 | 63 | 196 | 280 |
| | 7 | 102 | 7.1-32.0 | 25.5-115.2 | 15.0-67.8 | 11 | 15 | 63 | 196 | 280 |
| | 9.5 | 138 | 6.9-26.8 | 24.8-96.5 | 14.6-56.8 | 11 | 15 | 63 | 196 | 280 |
| | 12.5 | 181 | 7.5-23.1 | 27.0-115.6 | 15.9-48.9 | 11 | 15 | 63 | 196 | 280 |
| GA 15 VSD+ | 5.5 | 80 | 7.1-41.2 | 25.5-148.3 | 15.0-87.3 | 15 | 20 | 64 | 199 | 288 |
| | 7 | 102 | 7.0-40.8 | 25.2-146.9 | 14.8-86.4 | 15 | 20 | 64 | 199 | 288 |
| | 9.5 | 138 | 6.7-34.6 | 24.1-124.5 | 14.2-73.3 | 15 | 20 | 64 | 199 | 288 |
| | 12.5 | 181 | 7.1-27.2 | 25.5-97.9 | 15.0-57.6 | 15 | 20 | 64 | 199 | 288 |

* Unit performance measured according ISO 1217 ed. 4 2009, annex E, latest edition.

** Mean noise level measured at a distance of 1 m according to ISO 2151: 2004 using ISO 9614/2 (sound intensity method); tolerance 3 dB(A).

Reference conditions:


- Absolute inlet pressure 1 bar (14.5 psi).
- Intake air temperature 20°C, 68°F.

FAD is measured at the following effective working pressures:


- 5.5 bar(e)
- 7 bar(e)
- 9.5 bar(e)
- 12.5 bar(e)

Maximum working pressure:

- 13 bar(e) (188 psig)



FLOW CHART GA VSD+ FF



- 1 Inlet filter
- 2 Sentinel valve
- 3 Screw element
- 4 iPM
- 5 Air/oil vessel
- 6 Thermostatic bypass valve
- 7 Oil filter
- 8 Safety valve
- 9 Oil separator
- 10 Minimum pressure valve
- 11 Solenoid valve
- 12 After cooler
- 13 Fan
- 14 Oil cooler
- 15 Electronic drain (* mounted on after cooler on models without dryer)
- 16 Dryer

- Intake air
- Air/oil mixture
- Oil
- Wet compressed air
- Condensate
- Dry compressed air

Oil-injected rotary screw compressors, 15-22 kW / 20-30 hp

GA 15-22

Atlas Copco's oil-injected rotary screw compressors are leader in the market thanks to outstanding performance and flexible operation. This results in the highest productivity while minimizing the total cost of ownership. GA compressors are built to perform even in the harshest environments; these products will keep your production running smoothly.

CUSTOMER BENEFITS

- **Highest reliability** – The GA series is designed, manufactured and tested in accordance with ISO 9001, ISO 14001 and ISO 1217. Ensuring a long and trouble-free life at the lowest operating cost. GA compressors are equipped with the latest generation of Atlas Copco's innovative oil-injected screw element.

- **Reduced energy costs** – Our GA compressors can reduce your energy costs and overall compressor lifecycle costs thanks to the use of our highly efficient element and motors, and minimal internal losses.

- **Air system integration** – The GA WorkPlace Air System can be installed where you need compressed air. Its low noise operation and integrated air treatment equipment eliminates the need for a separate compressor room. All GA compressors are tested and delivered ready for use. The integrated options will reduce installation costs and pressure drops significantly, thus saving additional energy cost.

- **Advanced control and monitoring** – To maximize efficiency and reliability, the Elektronikon® controls the main drive motor and regulates system pressure within a predefined and narrow pressure band. The Elektronikon® controller can be adapted to your specific needs with extra sensors, digital contacts, fieldbus, Internet and SMS communication functions. In combination with the ES multiple compressor controller, the operation of your complete compressor room is optimized.

- **Integrated air treatment** – All GA compressors have integrated dryer and filters available to protect your compressed air network. This quality air expands the life of equipment, increasing efficiency and ensuring quality in your final product.



GA 15-22

| Type | Max. working pressure | | Capacity FAD* | Installed motor power | Noise Level** | Weight |
|---------------|----------------------------|---------|------------------|--------------------------|---------------|----------------------------|
| | Workplace/ workplace FF | | | | | Workplace/ workplace FF |
| | bar(e) | | m³/h | kW | dB(A) | kg |
| 50 Hz VERSION | | | | | | |
| GA 15 | 7.5 | 7.5/7.3 | 154.8 | 15 | 72 | 375/440 |
| | 8.5 | 8.5/8.3 | 141.8 | 15 | 72 | 375/440 |
| | 10 | 10/9.8 | 130.7 | 15 | 72 | 375/440 |
| | 13 | 13/12.8 | 108.4 | 15 | 72 | 375/440 |
| GA 18 | 7.5 | 7.5/7.3 | 189 | 18.5 | 73 | 395/470 |
| | 8.5 | 8.5/8.3 | 180.7 | 18.5 | 73 | 395/470 |
| | 10 | 10/9.8 | 156.6 | 18.5 | 73 | 395/470 |
| | 13 | 13/12.8 | 133.9 | 18.5 | 73 | 395/470 |
| GA 22 | 7.5 | 7.5/7.3 | 216.7 | 22 | 74 | 410/485 |
| | 8.5 | 8.5/8.3 | 209.9 | 22 | 74 | 410/485 |
| | 10 | 10/9.8 | 186.1 | 22 | 74 | 410/485 |
| | 13 | 13/12.8 | 162 | 22 | 74 | 410/485 |
| 50 Hz VERSION | | | | | | |
| | psig | | cfm | hp | dB(A) | lbs |
| GA 15 | 100 | 107/104 | 90.1 | 20 | 72 | 827/970 |
| | 125 | 132/128 | 83.9 | 20 | 72 | 827/970 |
| | 150 | 157/149 | 75.9 | 20 | 72 | 827/970 |
| | 175 | 181/178 | 62.1 | 20 | 72 | 827/970 |
| GA 18 | 100 | 107/104 | 108.7 | 25 | 73 | 871/1036 |
| | 125 | 132/128 | 101.1 | 25 | 73 | 871/1036 |
| | 150 | 157/149 | 91.7 | 25 | 73 | 871/1036 |
| | 175 | 181/178 | 80.1 | 25 | 73 | 871/1036 |
| GA 22 | 100 | 107/104 | 128.4 | 30 | 74 | 904/1069 |
| | 125 | 132/128 | 118.7 | 30 | 74 | 904/1069 |
| | 150 | 157/149 | 107.4 | 30 | 74 | 904/1069 |
| | 175 | 181/178 | 98.5 | 30 | 74 | 904/1069 |

* Unit performance measured according to ISO 1217, Ed. 3, Annex C-1996.

** Mean noise level measured according to ISO 2151/Pneuro/Cagi PN8NTC2 test code ; tolerance 2 dB(A)

Reference conditions:

- Absolute inlet pressure 1 bar (14.5 psi)
- Intake air temperature 20°C, 68°F

FAD is measured at the following working pressures:

- 7.5 bar versions at 7 bar
- 8.5 bar versions at 8 bar
- 10 bar versions at 9.5 bar
- 13 bar versions at 12.5 bar

Pressure dew point of integrated refrigerant dryer
of GA 15 - GA 18 - GA 22 at reference conditions 5°C, 41°F.

Air receiver size : 500 l.

Added weight: 125 kg.

GA 15 - GA 18 - GA 22
Full feature

H: 1558 mm, 61"
L: 1853 mm, 73"
W: 680 mm, 27"



GA 15 - GA 18 - GA 22
Pack

H1: 1558 mm, 61"
H2: 932 mm, 37"
L1: 1853 mm, 73"
L2: 1285 mm, 51"
W: 680 mm, 27"



Oil-injected rotary screw compressors, 11-30 kW / 15-40 hp

GA 11⁺-30/GA 15-30 VSD

Atlas Copco's oil-injected rotary screw compressors are leader in the market thanks to outstanding performance and flexible operation. This results in the highest productivity while minimizing the total cost of ownership. GA compressors are available in two series, GA⁺ 11-30 and GA 15-30 VSD, enabling you to perfectly match your requirements for compressed air solutions. Built to perform even in the harshest environments, these products will keep your production running efficiently.

CUSTOMER BENEFITS

- **Highest reliability** – The GA series is designed, manufactured and tested in accordance with ISO 9001, ISO 14001 and ISO 1217. Ensuring a long and trouble-free life at the lowest operating cost. GA compressors are equipped with the latest generation of Atlas Copco's innovative oil-injected screw element integrated with a closed gear drive eliminating the need for a coupling suitable for the harshest environment.

- **Reduced energy costs** – GA compressors can reduce your energy costs and overall compressor lifecycle costs thanks to the use of our highly efficient element and motors. The GA Variable Speed Drive (VSD) also reduces energy costs by a further 35% by automatically adjusting the air supply to your air demand with a large turndown operating range.

- **Air system integration** – The GA WorkPlace Air System can be installed where you need compressed air. Its low noise operation and integrated air treatment equipment eliminates the need for a separate compressor room. All GA compressors are tested and delivered ready for use. The integrated options will reduce installation costs and pressure drops significantly, thus saving additional energy cost.

- **Advanced control and monitoring** – To maximize efficiency and reliability, the Elektronikon® controls the main drive motor and regulates system pressure within a predefined and narrow pressure band. The Elektronikon® controller can be adapted to your specific needs with extra sensors, digital contacts, fieldbus, Internet and SMS communication functions. In combination with the ES multiple compressor controller, the operation of your complete compressor room is optimized.

- **Integrated air treatment** – All GA compressors have integrated dryer, filters and oil-water separator available to protect your compressed air network. This quality air expands the life of equipment, increasing efficiency and ensuring quality in your final product.



A PLUS FOR PERFORMANCE



GA⁺ series: Your advantage for more power and efficiency

With the new GA⁺ series, Atlas Copco is offering premium oil-injected screw compressors with excellent volume flow and high efficiency.

The improved performance is a direct result of the multitude of innovations that have been integrated into the compressor unit.

- Higher volume flow
- Lower specific power input
- Improved efficiency

GA 11⁺-30 (50 Hz version)

| Type | | Max. working pressure | | | | Capacity FAD* | | | Installed motor power | | Noise level** | Weight (kg) | | Length (mm) | Width (mm) | Height (mm) |
|--------------------|-----|-----------------------|------|------------------------|------|---------------|-------|-------|-----------------------|----|---------------|-------------|------------------------|-------------|------------|-------------|
| | | Workplace | | Workplace Full feature | | | | | | | | WorkPlace | Workplace Full feature | | | |
| | | bar(e) | psig | bar(e) | psig | l/s | m³/h | cfm | kW | hp | dB(A) | | | | | |
| 50 Hz VERSION | | | | | | | | | | | | | | | | |
| GA 11 ⁺ | 7.5 | 7.5 | 109 | 7.3 | 105 | 35.8 | 128.9 | 75.9 | 11 | 15 | 63 | 410 | 455 | 1255 | 692 | 1475 |
| | 8.5 | 8.5 | 116 | 8.3 | 120 | 33.8 | 121.7 | 71.7 | 11 | 15 | 63 | 410 | 455 | 1255 | 692 | 1475 |
| | 10 | 10 | 145 | 9.8 | 141 | 30.3 | 109.1 | 64.2 | 11 | 15 | 63 | 410 | 455 | 1255 | 692 | 1475 |
| | 13 | 13 | 189 | 12.8 | 185 | 25.2 | 90.7 | 53.4 | 11 | 15 | 63 | 410 | 455 | 1255 | 692 | 1475 |
| GA 15 ⁺ | 7.5 | 7.5 | 109 | 7.3 | 105 | 46.9 | 168.8 | 99.4 | 15 | 20 | 64 | 420 | 470 | 1255 | 692 | 1475 |
| | 8.5 | 8.5 | 116 | 8.3 | 120 | 43.8 | 157.7 | 92.9 | 15 | 20 | 64 | 420 | 470 | 1255 | 692 | 1475 |
| | 10 | 10 | 145 | 9.8 | 141 | 39.8 | 143.3 | 84.4 | 15 | 20 | 64 | 420 | 470 | 1255 | 692 | 1475 |
| | 13 | 13 | 189 | 12.8 | 185 | 32.8 | 118.1 | 69.5 | 15 | 20 | 64 | 420 | 470 | 1255 | 692 | 1475 |
| GA 18 ⁺ | 7.5 | 7.5 | 109 | 7.3 | 105 | 58.1 | 209.2 | 123.2 | 18.5 | 25 | 65 | 440 | 500 | 1255 | 692 | 1475 |
| | 8.5 | 8.5 | 116 | 8.3 | 120 | 54.3 | 195.5 | 115.1 | 18.5 | 25 | 65 | 440 | 500 | 1255 | 692 | 1475 |
| | 10 | 10 | 145 | 9.8 | 141 | 48.7 | 175.3 | 103.2 | 18.5 | 25 | 65 | 440 | 500 | 1255 | 692 | 1475 |
| | 13 | 13 | 189 | 12.8 | 185 | 41.1 | 148.0 | 87.1 | 18.5 | 25 | 65 | 440 | 500 | 1255 | 692 | 1475 |
| GA 22 ⁺ | 7.5 | 7.5 | 109 | 7.3 | 105 | 68.2 | 245.5 | 144.6 | 22 | 30 | 66 | 455 | 515 | 1255 | 692 | 1475 |
| | 8.5 | 8.5 | 116 | 8.3 | 120 | 64.5 | 232.2 | 136.7 | 22 | 30 | 66 | 455 | 515 | 1255 | 692 | 1475 |
| | 10 | 10 | 145 | 9.8 | 141 | 58.1 | 209.2 | 123.2 | 22 | 30 | 66 | 455 | 515 | 1255 | 692 | 1475 |
| | 13 | 13 | 189 | 12.8 | 185 | 50.7 | 182.5 | 107.5 | 22 | 30 | 66 | 455 | 515 | 1255 | 692 | 1475 |
| GA 26 ⁺ | 7.5 | 7.5 | 109 | 7.3 | 105 | 79.8 | 287.3 | 169.2 | 26 | 35 | 67 | 525 | 595 | 1255 | 865 | 1475 |
| | 8.5 | 8.5 | 116 | 8.3 | 120 | 76.2 | 274.3 | 161.5 | 26 | 35 | 67 | 525 | 595 | 1255 | 865 | 1475 |
| | 10 | 10 | 145 | 9.8 | 141 | 69.3 | 249.5 | 146.9 | 26 | 35 | 67 | 525 | 595 | 1255 | 865 | 1475 |
| | 13 | 13 | 189 | 12.8 | 185 | 60.1 | 216.4 | 127.4 | 26 | 35 | 67 | 525 | 595 | 1255 | 865 | 1475 |
| GA 30 | 7.5 | 7.5 | 109 | 7.3 | 105 | 90.0 | 324.0 | 190.8 | 30 | 40 | 68 | 540 | 610 | 1255 | 865 | 1475 |
| | 8.5 | 8.5 | 116 | 8.3 | 120 | 86.4 | 311.0 | 183.2 | 30 | 40 | 68 | 540 | 610 | 1255 | 865 | 1475 |
| | 10 | 10 | 145 | 9.8 | 141 | 79.8 | 287.3 | 169.2 | 30 | 40 | 68 | 540 | 610 | 1255 | 865 | 1475 |
| | 13 | 13 | 189 | 12.8 | 185 | 68.7 | 247.3 | 145.6 | 30 | 40 | 68 | 540 | 610 | 1255 | 865 | 1475 |

* Unit performance measured according to ISO 1217, Annex C, latest edition.

Reference conditions:

- Absolute inlet pressure 1 bar (14.5 psi)
- Intake air temperature 20°C, 68°F

FAD is measured at the following working pressures:

- 7.5 bar versions at 7 bar
- 8 bar versions at 7.5 bar
- 10 bar versions at 9.5 bar
- 13 bar versions at 12.5 bar

** Mean noise level measured according to ISO 2151/Pneuro/Cagi PN8NTC2 test code; tolerance 2 dB(A).

Pressure dew point of integrated refrigerant dryer of GA 11⁺ - GA 15⁺ - GA 18⁺ - GA 22⁺ - GA 26⁺ - GA 30 at reference conditions 2°C to 3°C, 36°F to 37°F.

GA 11⁺ - GA 15⁺ - GA 18⁺ - GA 22⁺

H: 1475 mm, 58"
L: 1255 mm, 49"
W: 692 mm, 27"



GA 11⁺-30 (60 Hz version)

| Type | | Max. working pressure | | | | Capacity FAD* | | | Installed motor power | | Noise level** | Weight (kg) | | Length (mm) | Width (mm) | Height (mm) |
|--------------------|-----|-----------------------|------|------------------------|------|---------------|-------|-------|-----------------------|----|---------------|-------------|------------------------|-------------|------------|-------------|
| | | Workplace | | Workplace Full feature | | | | | | | | Work-place | Workplace Full feature | | | |
| | | bar(e) | psig | bar(e) | psig | l/s | m³/h | cfm | kW | hp | dB(A) | | | | | |
| 60 Hz VERSION | | | | | | | | | | | | | | | | |
| GA 11 ⁺ | 100 | 7.4 | 107 | 7.2 | 104 | 37.0 | 133.2 | 78.4 | 11 | 15 | 63 | 410 | 455 | 1255 | 692 | 1475 |
| | 125 | 9.1 | 132 | 8.9 | 128 | 32.0 | 115.2 | 67.8 | 11 | 15 | 63 | 410 | 455 | 1255 | 692 | 1475 |
| | 150 | 10.8 | 157 | 10.3 | 149 | 29.3 | 105.5 | 62.1 | 11 | 15 | 63 | 410 | 455 | 1255 | 692 | 1475 |
| | 175 | 12.5 | 181 | 12.3 | 178 | 25.3 | 91.1 | 53.6 | 11 | 15 | 63 | 410 | 455 | 1255 | 692 | 1475 |
| GA 15 ⁺ | 100 | 7.4 | 107 | 7.2 | 104 | 48.3 | 173.9 | 102.4 | 15 | 20 | 64 | 420 | 470 | 1255 | 692 | 1475 |
| | 125 | 9.1 | 132 | 8.9 | 128 | 42.9 | 154.4 | 90.9 | 15 | 20 | 64 | 420 | 470 | 1255 | 692 | 1475 |
| | 150 | 10.8 | 157 | 10.3 | 149 | 39.4 | 141.8 | 83.5 | 15 | 20 | 64 | 420 | 470 | 1255 | 692 | 1475 |
| | 175 | 12.5 | 181 | 12.3 | 178 | 33.9 | 122.0 | 71.9 | 15 | 20 | 64 | 420 | 470 | 1255 | 692 | 1475 |
| GA 18 ⁺ | 100 | 7.4 | 107 | 7.2 | 104 | 59.6 | 214.6 | 126.4 | 18.5 | 25 | 66 | 440 | 500 | 1255 | 692 | 1475 |
| | 125 | 9.1 | 132 | 8.9 | 128 | 53.3 | 191.9 | 113.0 | 18.5 | 25 | 66 | 440 | 500 | 1255 | 692 | 1475 |
| | 150 | 10.8 | 157 | 10.3 | 149 | 47.8 | 172.1 | 101.3 | 18.5 | 25 | 66 | 440 | 500 | 1255 | 692 | 1475 |
| | 175 | 12.5 | 181 | 12.3 | 178 | 42.5 | 153.0 | 90.1 | 18.5 | 25 | 66 | 440 | 500 | 1255 | 692 | 1475 |
| GA 22 ⁺ | 100 | 7.4 | 107 | 7.2 | 104 | 70.3 | 253.1 | 149.0 | 22 | 30 | 67 | 455 | 515 | 1255 | 692 | 1475 |
| | 125 | 9.1 | 132 | 8.9 | 128 | 62.9 | 226.4 | 133.3 | 22 | 30 | 67 | 455 | 515 | 1255 | 692 | 1475 |
| | 150 | 10.8 | 157 | 10.3 | 149 | 56.9 | 204.8 | 120.6 | 22 | 30 | 67 | 455 | 515 | 1255 | 692 | 1475 |
| | 175 | 12.5 | 181 | 12.3 | 178 | 52.3 | 188.3 | 110.9 | 22 | 30 | 67 | 455 | 515 | 1255 | 692 | 1475 |
| GA 26 ⁺ | 100 | 7.4 | 107 | 7.2 | 104 | 81.2 | 292.3 | 172.1 | 26 | 35 | 67 | 525 | 595 | 1255 | 865 | 1475 |
| | 125 | 9.1 | 132 | 8.9 | 128 | 74.1 | 266.8 | 157.1 | 26 | 35 | 67 | 525 | 595 | 1255 | 865 | 1475 |
| | 150 | 10.8 | 157 | 10.3 | 149 | 67.4 | 242.6 | 142.9 | 26 | 35 | 67 | 525 | 595 | 1255 | 865 | 1475 |
| | 175 | 12.5 | 181 | 12.3 | 178 | 60.7 | 218.5 | 128.7 | 26 | 35 | 67 | 525 | 595 | 1255 | 865 | 1475 |
| GA 30 | 100 | 7.4 | 107 | 7.2 | 104 | 90.1 | 324.4 | 191.0 | 30 | 40 | 68 | 540 | 610 | 1255 | 865 | 1475 |
| | 125 | 9.1 | 132 | 8.9 | 128 | 84.1 | 302.8 | 178.3 | 30 | 40 | 68 | 540 | 610 | 1255 | 865 | 1475 |
| | 150 | 10.8 | 157 | 10.3 | 149 | 77.1 | 277.6 | 163.5 | 30 | 40 | 68 | 540 | 610 | 1255 | 865 | 1475 |
| | 175 | 12.5 | 181 | 12.3 | 178 | 70.1 | 252.4 | 148.6 | 30 | 40 | 68 | 540 | 610 | 1255 | 865 | 1475 |

* Unit performance measured according to ISO 1217, Annex C, latest edition.

** Mean noise level measured according to ISO 2151/Pneuro/Cagi PN8NTC2 test code; tolerance 2 dB(A).

Reference conditions:

- Absolute inlet pressure 1 bar (14.5 psi)
- Intake air temperature 20°C, 68°F

Pressure dew point of integrated refrigerant dryer of GA 11⁺ - GA 15⁺ - GA 18⁺ - GA 22⁺ - GA 26⁺ - GA 30 at reference conditions 2°C to 3°C, 35°F to 37°F.

FAD is measured at the following working pressures:

- 7.5 bar versions at 7 bar
- 8 bar versions at 7.5 bar
- 10 bar versions at 9.5 bar
- 13 bar versions at 12.5 bar

GA 26⁺ - GA 30

H: 1475 mm, 58"
L: 1255 mm, 49"
W: 865 mm, 34"



GA 15-30 VSD

| Type | Max. working pressure | | Capacity FAD min.-max. | | | | | | Installed motor power | | Noise level 50/60 Hz | Weight (kg) | | Length (mm) | Width (mm) | Height (mm) |
|-----------|-----------------------|------|------------------------|------|------|-------|------|-------|-----------------------|----|-------------------------|-------------|------------------------|-------------|------------|-------------|
| | Workplace | | l/s | | m³/h | | cfm | | | | | Work-Place | Workplace Full feature | | | |
| | bar(e) | psig | Min. | Max. | Min. | Max. | Min. | Max. | kW | hp | dB(A) | | | | | |
| GA 15 VSD | 4 | 58 | 16.0 | 48.7 | 57.6 | 175.3 | 33.9 | 103.2 | 15 | 20 | 66 | 480 | 530 | 1255 | 865 | 1475 |
| | 7 | 102 | 15.9 | 48.5 | 57.2 | 174.6 | 33.7 | 102.8 | 15 | 20 | 66 | 480 | 530 | 1255 | 865 | 1475 |
| | 10 | 145 | 18.0 | 41.6 | 64.8 | 149.8 | 38.2 | 88.2 | 15 | 20 | 66 | 480 | 530 | 1255 | 865 | 1475 |
| | 13 | 188 | 20.4 | 32.8 | 73.4 | 118.1 | 43.2 | 69.5 | 15 | 20 | 65 | 480 | 530 | 1255 | 865 | 1475 |
| GA 18 VSD | 4 | 58 | 16.0 | 60.1 | 57.6 | 216.4 | 33.9 | 127.4 | 18 | 25 | 67 | 490 | 550 | 1255 | 865 | 1475 |
| | 7 | 102 | 15.9 | 60.0 | 57.2 | 216.0 | 33.7 | 127.2 | 18 | 25 | 67 | 490 | 550 | 1255 | 865 | 1475 |
| | 10 | 145 | 18.0 | 52.0 | 64.8 | 187.2 | 38.2 | 110.2 | 18 | 25 | 67 | 490 | 550 | 1255 | 865 | 1475 |
| | 13 | 188 | 20.4 | 42.0 | 73.4 | 151.2 | 43.2 | 89.0 | 18 | 25 | 66 | 490 | 550 | 1255 | 865 | 1475 |
| GA 22 VSD | 4 | 58 | 16.0 | 70.5 | 57.6 | 253.8 | 33.9 | 149.5 | 22 | 30 | 68 | 500 | 560 | 1255 | 865 | 1475 |
| | 7 | 102 | 15.9 | 70.3 | 57.2 | 253.1 | 33.7 | 149.5 | 22 | 30 | 68 | 500 | 560 | 1255 | 865 | 1475 |
| | 10 | 145 | 18.0 | 61.4 | 64.8 | 221.0 | 38.2 | 130.2 | 22 | 30 | 68 | 500 | 560 | 1255 | 865 | 1475 |
| | 13 | 188 | 20.4 | 50.2 | 73.4 | 180.7 | 43.2 | 106.4 | 22 | 30 | 67 | 500 | 560 | 1255 | 865 | 1475 |
| GA 26 VSD | 4 | 58 | 16.0 | 81.5 | 57.6 | 293.4 | 33.9 | 172.8 | 26 | 35 | 70 | 520 | 590 | 1255 | 865 | 1475 |
| | 7 | 102 | 15.9 | 81.2 | 57.2 | 292.3 | 33.7 | 172.1 | 26 | 35 | 70 | 520 | 590 | 1255 | 865 | 1475 |
| | 10 | 145 | 18.0 | 72.4 | 64.8 | 260.6 | 38.2 | 153.5 | 26 | 35 | 70 | 520 | 590 | 1255 | 865 | 1475 |
| | 13 | 188 | 20.4 | 59.7 | 73.4 | 214.9 | 43.2 | 126.6 | 26 | 35 | 69 | 520 | 590 | 1255 | 865 | 1475 |
| GA 30 VSD | 4 | 58 | 16.0 | 93.3 | 57.6 | 335.9 | 33.9 | 197.8 | 30 | 35 | 70 | 530 | 600 | 1255 | 865 | 1475 |
| | 7 | 102 | 15.9 | 93.0 | 57.2 | 334.8 | 33.7 | 197.2 | 30 | 35 | 70 | 530 | 600 | 1255 | 865 | 1475 |
| | 10 | 145 | 18.0 | 82.7 | 64.8 | 297.7 | 38.2 | 175.3 | 30 | 35 | 70 | 530 | 600 | 1255 | 865 | 1475 |
| | 13 | 188 | 20.4 | 70.8 | 73.4 | 254.9 | 43.2 | 150.1 | 30 | 35 | 69 | 530 | 600 | 1255 | 865 | 1475 |

* Unit performance measured according to ISO 1217, Annex C, latest edition.

Reference conditions:

- Absolute inlet pressure 1 bar (14.5 psi)
- Intake air temperature 20°C, 68°F

** Mean noise level measured according to ISO 2151/Pneuro/Cagi PN8NTC2 test code; tolerance 2 dB(A).

Pressure dew point of integrated refrigerant dryer at reference conditions: 2°C to 3°C, 35°F to 37°F.

Maximum working pressure for VSD machines: 13 bar(e) (188 psig)

GA 15 VSD - GA 18 VSD -
GA 22 VSD - GA 30 VSD

H: 1475 mm
L: 1255 mm
W: 862 mm



Oil-injected rotary screw compressors, 30-90 kW / 40-125 hp

GA 30⁺-90 / GA 37-90 VSD

Atlas Copco's oil-injected rotary screw GA compressors are leaders in the market, with outstanding reliable performance. Their flexible operation results in the highest productivity, while minimizing the total cost of ownership. GA compressors are available in three series – GA, GA⁺ and GA VSD – enabling you to perfectly match your requirements for compressed air solutions. Built to perform even in the harshest environments, these products will keep your production running efficiently.

CUSTOMER BENEFITS

• **Highest reliability** – The GA series is designed, manufactured and tested in accordance with ISO 9001, ISO 14001 and ISO 1217. The latest generation of Atlas Copco's innovative oil-injected screw element ensures a long and trouble-free life, at the lowest operating costs. The integrated closed gear drive eliminates the need for a coupling thus reducing maintenance requirements while increasing GA reliability suitable for the harshest environments.

• **Reduced energy costs** – Our GA / GA⁺ compressors can reduce your energy costs and overall compressor lifecycle costs thanks to the use of our highly efficient element and motors. Furthermore, the GA Variable Speed Drive (VSD) reduces energy costs by a further 35% by automatically adjusting the air supply to your air demand with a large turndown operating range.

• **Air system integration** – The GA WorkPlace Air System can be placed where you need it. Its low noise operation and integrated air treatment equipment eliminate the need for a separate compressor room. All GA compressors are delivered ready for use, significantly reducing installation costs, pressure drops and thus saving additional energy cost.

• **Advanced control and monitoring** – To maximize efficiency and reliability, the Elektronikon® controls the main drive motor and regulates system pressure within a predefined and narrow pressure band. The Elektronikon® controller can be adapted to your specific needs with extra sensors, digital contacts, fieldbus, Internet and SMS communication functions. In combination with the ES multiple compressor controller, the operation of your complete compressor room is optimized.

• **Integrated air treatment** – All GA compressors are available with an integrated dryer that efficiently removes moisture, aerosols and dirt particles to protect your investment. This quality air expands the life of equipment, increasing efficiency and ensuring quality in your final product.



iOS app

Download a QR Reader and scan the code for our interactive leaflet.



Android app



GA 30⁺-90 (50 Hz versions)

| Type | Pressure variant | Max. working pressure workPlace | | Capacity FAD* | | | Installed motor power | | Noise level** | Weight workplace | | Weight workplace Full feature | |
|--------------------|------------------|---------------------------------|------|---------------|--------|-----|-----------------------|-----|---------------|------------------|------|-------------------------------|------|
| | | bar(e) | psig | l/s | m³/min | cfm | kW | hp | | kg | lbs | kg | lbs |
| GA 30 ⁺ | 7.5 | 7.5 | 109 | 99 | 5.9 | 209 | 30 | 40 | 65 | 817 | 1801 | 898 | 1980 |
| | 8.5 | 8.5 | 123 | 90 | 5.4 | 191 | 30 | 40 | 65 | 817 | 1801 | 898 | 1980 |
| | 10 | 10 | 145 | 82 | 4.9 | 175 | 30 | 40 | 65 | 817 | 1801 | 898 | 1980 |
| | 13 | 13 | 189 | 71 | 4.3 | 151 | 30 | 40 | 65 | 817 | 1801 | 898 | 1980 |
| GA 37 | 7.5 | 7.5 | 109 | 115 | 6.9 | 243 | 37 | 50 | 69 | 905 | 1994 | 820 | 1807 |
| | 8.5 | 8.5 | 123 | 106 | 6.4 | 225 | 37 | 50 | 69 | 905 | 1995 | 820 | 1808 |
| | 10 | 10 | 145 | 100 | 6.0 | 213 | 37 | 50 | 69 | 905 | 1995 | 820 | 1808 |
| | 13 | 13 | 189 | 81 | 4.9 | 172 | 37 | 50 | 69 | 905 | 1995 | 820 | 1808 |
| GA 37 ⁺ | 7.5 | 7.5 | 109 | 122 | 7.3 | 258 | 37 | 50 | 65 | 902 | 1989 | 987 | 2176 |
| | 8.5 | 8.5 | 123 | 118 | 7.1 | 250 | 37 | 50 | 65 | 902 | 1989 | 987 | 2176 |
| | 10 | 10 | 145 | 102 | 6.1 | 216 | 37 | 50 | 65 | 902 | 1989 | 987 | 2176 |
| | 13 | 13 | 189 | 85 | 5.1 | 180 | 37 | 50 | 65 | 902 | 1989 | 987 | 2176 |
| GA 45 | 7.5 | 7.5 | 109 | 137 | 8.2 | 291 | 45 | 60 | 72 | 894 | 1971 | 979 | 2158 |
| | 8.5 | 8.5 | 123 | 127 | 7.6 | 268 | 45 | 60 | 72 | 894 | 1971 | 979 | 2158 |
| | 10 | 10 | 145 | 117 | 7.0 | 248 | 45 | 60 | 72 | 894 | 1971 | 979 | 2158 |
| | 13 | 13 | 189 | 102 | 6.1 | 217 | 45 | 60 | 72 | 894 | 1971 | 979 | 2158 |
| GA 45 ⁺ | 7.5 | 7.5 | 109 | 149 | 8.9 | 315 | 45 | 60 | 66 | 970 | 2138 | 1060 | 2337 |
| | 8.5 | 8.5 | 123 | 139 | 8.3 | 295 | 45 | 60 | 66 | 970 | 2138 | 1060 | 2337 |
| | 10 | 10 | 145 | 128 | 7.7 | 270 | 45 | 60 | 66 | 970 | 2138 | 1060 | 2337 |
| | 13 | 13 | 189 | 106 | 6.4 | 225 | 45 | 60 | 66 | 970 | 2138 | 1060 | 2337 |
| GA 55 | 7.5 | 7.5 | 109 | 169 | 10.2 | 359 | 55 | 75 | 69 | 1229 | 2709 | 1329 | 2930 |
| | 8.5 | 8.5 | 123 | 159 | 9.5 | 336 | 55 | 75 | 69 | 1229 | 2709 | 1329 | 2930 |
| | 10 | 10 | 145 | 148 | 8.9 | 313 | 55 | 75 | 69 | 1229 | 2709 | 1329 | 2930 |
| | 13 | 13 | 189 | 126 | 7.6 | 267 | 55 | 75 | 69 | 1229 | 2709 | 1329 | 2930 |
| GA 55 ⁺ | 7.5 | 7.5 | 109 | 184 | 11.1 | 390 | 55 | 75 | 66 | 1358 | 2994 | 1458 | 3214 |
| | 8.5 | 8.5 | 123 | 174 | 10.4 | 369 | 55 | 75 | 66 | 1358 | 2994 | 1458 | 3214 |
| | 10 | 10 | 145 | 156 | 9.5 | 331 | 55 | 75 | 66 | 1358 | 2994 | 1458 | 3214 |
| GA 75 | 7.5 | 7.5 | 109 | 226 | 13.5 | 478 | 75 | 100 | 73 | 1259 | 2776 | 1379 | 3040 |
| | 8.5 | 8.5 | 123 | 209 | 12.6 | 444 | 75 | 100 | 73 | 1259 | 2776 | 1379 | 3040 |
| | 10 | 10 | 145 | 189 | 11.4 | 401 | 75 | 100 | 73 | 1259 | 2776 | 1379 | 3040 |
| | 13 | 13 | 189 | 162 | 9.7 | 344 | 75 | 100 | 73 | 1259 | 2776 | 1379 | 3040 |
| GA 75 ⁺ | 7.5 | 7.5 | 109 | 248 | 14.9 | 526 | 75 | 100 | 68 | 1413 | 3115 | 1533 | 3380 |
| | 8.5 | 8.5 | 123 | 235 | 14.1 | 497 | 75 | 100 | 68 | 1413 | 3115 | 1533 | 3380 |
| | 10 | 10 | 145 | 210 | 12.6 | 445 | 75 | 100 | 68 | 1413 | 3115 | 1533 | 3380 |
| | 13 | 13 | 189 | 177 | 10.6 | 375 | 75 | 100 | 68 | 1413 | 3115 | 1533 | 3380 |
| GA 90 | 7.5 | 7.5 | 109 | 281 | 16.9 | 596 | 90 | 125 | 73 | 1425 | 3142 | 1545 | 3406 |
| | 8.5 | 8.5 | 123 | 275 | 16.5 | 582 | 90 | 125 | 73 | 1425 | 3142 | 1545 | 3406 |
| | 10 | 10 | 145 | 250 | 15.0 | 529 | 90 | 125 | 73 | 1425 | 3142 | 1545 | 3406 |
| | 13 | 13 | 189 | 216 | 13.0 | 458 | 90 | 125 | 73 | 1425 | 3142 | 1545 | 3406 |

* Unit performance measured according to ISO 1217, Annex C, Edition 4

Reference conditions:

Absolute inlet pressure 1 bar (14.5 psi)

Intake air temperature 20°C, 68°F

FAD is measured at the following working pressures:

7.5 bar versions at 7 bar

8.5 bar versions at 8 bar

10 bar versions at 9.5 bar

13 bar versions at 12.5 bar

** A-weighted emission sound pressure level at the work station, Lp WSA (re 20 µPa) dB (with uncertainty 3 dB).

Values determined according to noise level test code ISO 2151 and noise measurement standard ISO 9614.

Pressure dew point of integrated refrigerant dryer at reference conditions: 2°C to 3°C, 36°F to 37°F.

GA 30⁺-90 (60 Hz version)

| Type | Pressure variant | Max. working pressure workplace | | Capacity FAD* | | | Installed motor power | | Noise level** | Weight workplace | | Weight workplace Full feature | |
|--------------------|------------------|---------------------------------|------|---------------|---------------------|-----|-----------------------|-----|---------------|------------------|------|-------------------------------|------|
| | | bar(e) | psig | l/s | m ³ /min | cfm | kW | hp | | kg | lbs | kg | lbs |
| GA 30 ⁺ | 100 | 7.4 | 107 | 100 | 6.0 | 212 | 30 | 40 | 65 | 817 | 1801 | 898 | 1980 |
| | 125 | 9.1 | 132 | 91 | 5.4 | 192 | 30 | 40 | 65 | 817 | 1801 | 898 | 1980 |
| | 150 | 10.8 | 157 | 82 | 4.9 | 174 | 30 | 40 | 65 | 817 | 1801 | 898 | 1980 |
| | 175 | 12.5 | 181 | 75 | 4.5 | 158 | 30 | 40 | 65 | 817 | 1801 | 898 | 1980 |
| GA 37 | 100 | 7.4 | 107 | 116 | 7.0 | 246 | 37 | 50 | 69 | 905 | 1995 | 820 | 1808 |
| | 125 | 9.1 | 132 | 108 | 6.5 | 229 | 37 | 50 | 69 | 905 | 1995 | 820 | 1808 |
| | 150 | 10.8 | 157 | 96 | 5.8 | 204 | 37 | 50 | 69 | 905 | 1995 | 820 | 1808 |
| | 175 | 12.5 | 181 | 87 | 5.2 | 185 | 37 | 50 | 69 | 905 | 1995 | 820 | 1808 |
| GA 37 ⁺ | 100 | 7.4 | 107 | 120 | 7.2 | 255 | 37 | 50 | 65 | 905 | 1995 | 987 | 2176 |
| | 125 | 9.1 | 132 | 111 | 6.6 | 234 | 37 | 50 | 65 | 905 | 1995 | 987 | 2176 |
| | 150 | 10.8 | 157 | 100 | 6.0 | 212 | 37 | 50 | 65 | 905 | 1995 | 987 | 2176 |
| | 175 | 12.5 | 181 | 91 | 5.4 | 192 | 37 | 50 | 65 | 905 | 1995 | 987 | 2176 |
| GA 45 | 100 | 7.4 | 107 | 139 | 8.3 | 294 | 45 | 60 | 72 | 894 | 1971 | 979 | 2158 |
| | 125 | 9.1 | 132 | 128 | 7.7 | 271 | 45 | 60 | 72 | 894 | 1971 | 979 | 2158 |
| | 150 | 10.8 | 157 | 118 | 7.1 | 250 | 45 | 60 | 72 | 894 | 1971 | 979 | 2158 |
| | 175 | 12.5 | 181 | 105 | 6.3 | 222 | 45 | 60 | 72 | 894 | 1971 | 979 | 2158 |
| GA 45 ⁺ | 100 | 7.4 | 107 | 146 | 8.8 | 310 | 45 | 60 | 66 | 970 | 2138 | 1060 | 2337 |
| | 125 | 9.1 | 132 | 134 | 8.0 | 284 | 45 | 60 | 66 | 970 | 2138 | 1060 | 2337 |
| | 150 | 10.8 | 157 | 126 | 7.5 | 266 | 45 | 60 | 66 | 970 | 2138 | 1060 | 2337 |
| | 175 | 12.5 | 181 | 111 | 6.7 | 236 | 45 | 60 | 66 | 970 | 2138 | 1060 | 2337 |
| GA 55 | 100 | 7.4 | 107 | 174 | 10.5 | 369 | 55 | 75 | 69 | 1229 | 2709 | 1329 | 2930 |
| | 125 | 9.1 | 132 | 154 | 9.3 | 327 | 55 | 75 | 69 | 1229 | 2709 | 1329 | 2930 |
| | 150 | 10.8 | 157 | 142 | 8.5 | 300 | 55 | 75 | 69 | 1229 | 2709 | 1329 | 2930 |
| | 175 | 12.5 | 181 | 128 | 7.7 | 272 | 55 | 75 | 69 | 1229 | 2709 | 1329 | 2930 |
| GA 55 ⁺ | 100 | 7.4 | 107 | 184 | 11.0 | 390 | 55 | 75 | 67 | 1358 | 2994 | 1458 | 3214 |
| | 125 | 9.1 | 132 | 166 | 10.0 | 352 | 55 | 75 | 67 | 1358 | 2994 | 1458 | 3214 |
| | 150 | 10.8 | 157 | 141 | 8.5 | 299 | 55 | 75 | 67 | 1358 | 2994 | 1458 | 3214 |
| GA 75 | 100 | 7.4 | 107 | 229 | 13.7 | 485 | 75 | 100 | 73 | 1259 | 2776 | 1359 | 2996 |
| | 125 | 9.1 | 132 | 200 | 12.0 | 424 | 75 | 100 | 73 | 1259 | 2776 | 1359 | 2996 |
| | 150 | 10.8 | 157 | 189 | 11.4 | 401 | 75 | 100 | 73 | 1259 | 2776 | 1359 | 2996 |
| | 175 | 12.5 | 181 | 169 | 10.1 | 358 | 75 | 100 | 73 | 1259 | 2776 | 1359 | 2996 |
| GA 75 ⁺ | 100 | 7.4 | 107 | 248 | 14.9 | 525 | 75 | 100 | 69 | 1413 | 3115 | 1533 | 3380 |
| | 125 | 9.1 | 132 | 227 | 13.6 | 481 | 75 | 100 | 69 | 1413 | 3115 | 1533 | 3380 |
| | 150 | 10.8 | 157 | 204 | 12.3 | 433 | 75 | 100 | 69 | 1413 | 3115 | 1533 | 3380 |
| | 175 | 12.5 | 181 | 182 | 10.9 | 385 | 75 | 100 | 69 | 1413 | 3115 | 1533 | 3380 |
| GA 90 | 100 | 7.4 | 107 | 289 | 17.4 | 613 | 90 | 125 | 74 | 1425 | 3142 | 1545 | 3406 |
| | 125 | 9.1 | 132 | 267 | 16.0 | 565 | 90 | 125 | 74 | 1425 | 3142 | 1545 | 3406 |
| | 150 | 10.8 | 157 | 250 | 15.0 | 530 | 90 | 125 | 74 | 1425 | 3142 | 1545 | 3406 |
| | 175 | 12.5 | 181 | 228 | 13.7 | 484 | 90 | 125 | 74 | 1425 | 3142 | 1545 | 3406 |

Please refer to the footnotes, reference conditions and FAD details of the 50 Hz versions.

GA 37-90 VSD (50/60 Hz versions)

| Type | Working pressure | | Capacity FAD* | | | | | | Installed motor power | | Noise level** | Weight workplace | | Weight workplace Full feature | |
|-----------|------------------|------|---------------|-----|--------|------|-----|-----|-----------------------|-----|---------------|------------------|------|-------------------------------|------|
| | | | l/s | | m³/min | | cfm | | | | | | | | |
| | bar(e) | psig | min | max | min | max | min | max | kW | hp | | dB(A) | kg | lbs | kg |
| GA 37 VSD | 4 | 58 | 26.0 | 124 | 1.6 | 7.4 | 55 | 263 | 37 | 50 | 66/67 | 1042 | 2297 | 1127 | 2485 |
| | 7 | 102 | 26.0 | 123 | 1.6 | 7.4 | 55 | 260 | 37 | 50 | 66/67 | 1042 | 2297 | 1127 | 2485 |
| | 10 | 145 | 25.8 | 107 | 1.5 | 6.4 | 55 | 226 | 37 | 50 | 66/67 | 1042 | 2297 | 1127 | 2485 |
| | 13 | 189 | 40.3 | 87 | 2.4 | 5.2 | 85 | 185 | 37 | 50 | 66/67 | 1042 | 2297 | 1127 | 2485 |
| GA 45 VSD | 4 | 58 | 26.0 | 146 | 1.6 | 8.8 | 55 | 310 | 45 | 60 | 69/72 | 1100 | 2425 | 1190 | 2624 |
| | 7 | 102 | 26.0 | 145 | 1.6 | 8.7 | 55 | 307 | 45 | 60 | 69/72 | 1100 | 2425 | 1190 | 2624 |
| | 10 | 145 | 25.8 | 128 | 1.5 | 7.7 | 55 | 271 | 45 | 60 | 69/72 | 1100 | 2425 | 1190 | 2624 |
| | 13 | 189 | 40.3 | 107 | 2.4 | 6.4 | 85 | 226 | 45 | 60 | 69/72 | 1100 | 2425 | 1190 | 2624 |
| GA 55 VSD | 4 | 58 | 32.4 | 197 | 1.9 | 11.8 | 69 | 418 | 55 | 75 | 69/72 | 1380 | 3042 | 1480 | 3263 |
| | 7 | 102 | 26.0 | 175 | 1.6 | 10.5 | 55 | 371 | 55 | 75 | 69/72 | 1380 | 3042 | 1480 | 3263 |
| | 10 | 145 | 25.4 | 155 | 1.5 | 9.3 | 54 | 328 | 55 | 75 | 69/72 | 1380 | 3042 | 1480 | 3263 |
| | 13 | 189 | 37.0 | 129 | 2.2 | 7.7 | 78 | 273 | 55 | 75 | 69/72 | 1380 | 3042 | 1480 | 3263 |
| GA 75 VSD | 4 | 58 | 37.8 | 250 | 2.3 | 15.0 | 80 | 529 | 75 | 100 | 69/70 | 1534 | 3382 | 1654 | 3646 |
| | 7 | 102 | 37.4 | 250 | 2.2 | 15.0 | 79 | 530 | 75 | 100 | 69/70 | 1534 | 3382 | 1654 | 3646 |
| | 10 | 145 | 48.1 | 219 | 2.9 | 13.2 | 102 | 465 | 75 | 100 | 69/70 | 1534 | 3382 | 1654 | 3646 |
| | 13 | 189 | 58.3 | 182 | 3.5 | 10.9 | 124 | 386 | 75 | 100 | 69/70 | 1534 | 3382 | 1654 | 3646 |
| GA 90 VSD | 4 | 58 | 37.0 | 293 | 2.2 | 17.6 | 78 | 621 | 90 | 125 | 73/74 | 1534 | 3382 | 1654 | 3646 |
| | 7 | 102 | 39.4 | 292 | 2.4 | 17.5 | 84 | 619 | 90 | 125 | 73/74 | 1534 | 3382 | 1654 | 3646 |
| | 10 | 145 | 48.3 | 257 | 2.9 | 15.4 | 102 | 545 | 90 | 125 | 73/74 | 1534 | 3382 | 1654 | 3646 |
| | 13 | 189 | 59.4 | 214 | 3.6 | 12.9 | 126 | 454 | 90 | 125 | 73/74 | 1534 | 3382 | 1654 | 3646 |

*Unit performance measured according to ISO 1217, Annex E, Edition 4

Maximum working pressure for VSD machines: 13 bar(e) (188 psig)

Oil-injected rotary screw compressors, 90-160 kW / 125-200 hp

GA 90⁺-160⁺ / GA 110-160 VSD

Efficient, reliable and built to last, the GA 90⁺-160⁺ / GA 110-160 VSD compressors are designed to provide high-quality compressed air even under harsh conditions. Every GA is designed, manufactured and tested to comply with ISO 9001, ISO 14001 and ISO 1217. They use the latest generation of Atlas Copco's oil-injected screw element, ensuring a long and trouble-free life at the lowest possible operating cost. Engineered for reliable service, even in ambient temperatures up to 55°C/131°F and very harsh environmental circumstances, the GA takes reliability to a new level. Features such as Variable Speed Drive and energy recovery lead to significant reductions in energy use and cost

continuously in the toughest conditions and at ambient temperatures up to 55°C/131°F. Together they ensure long and trouble-free life of your compressor at the lowest operating cost.

• **Maximum energy savings** – The innovative design of our GA compressors (including screw element, motor, VSD-controlled cooling fans etc.) enables you to achieve substantial savings in your energy costs and overall compressor lifecycle costs. The GA Variable Speed Drive (VSD) reduces energy costs by a further 35% on average by automatically adjusting the air supply to your air demand. And to reduce your costs even further, install the optional energy recovery system.

• **Integrated air treatment** – The GA Full Feature with highly energy efficient integrated refrigerant dryer and air filter ensures the continuous supply of clean and dry air to extend the life of equipment, enhance system reliability and avoid costly downtime and production delays.

• **Advanced control and monitoring** – To maximize efficiency and reliability, the Elektronikon® controls the main drive motor and regulates system pressure within a predefined and narrow pressure band. The Elektronikon® controller can be adapted to your specific needs with extra sensors, digital contacts, fieldbus, Internet and SMS communication functions. In combination with the ES multiple compressor controller, the operation of your complete compressor room is optimized.

• **Easy installation** – The integrated design includes internal piping, coolers, motor, lubrication and control system: all supplied as a ready-to-use package. Installation is fault-free and commissioning time is low. Simply plug and run.

CUSTOMER BENEFITS

• **Highest reliability** – GA compressors incorporate the latest generation of Atlas Copco's state-of-the-art compression elements based on innovative asymmetric rotor profiles, a high-quality drive system and heavy-duty air inlet filters. All these components are selected to operate



| Type | Dimensions | | | | | | | | | | | | | | | | | |
|--------------------------------------|-----------------|------|------|------|------|------|-------------------------|------|------|------|------|------|----------------------------------|------|------|------|------|------|
| | Air-cooled pack | | | | | | Air-cooled full feature | | | | | | Water-cooled pack & Full feature | | | | | |
| | L | | W | | H | | L | | W | | H | | L | | W | | H | |
| | mm | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm | inch |
| GA 90 ⁺ -160 ⁺ | 2600 | 102 | 2000 | 79 | 2000 | 79 | 3200 | 126 | 2000 | 79 | 2000 | 79 | 2600 | 102 | 1630 | 64 | 2000 | 79 |
| GA 110-160 | 2600 | 102 | 2000 | 79 | 2000 | 79 | 3200 | 126 | 2000 | 79 | 2000 | 79 | 2600 | 102 | 1632 | 64 | 2000 | 79 |
| GA 110-160 VSD | 3200 | 132 | 2000 | 79 | 2000 | 79 | 3800 | 150 | 2002 | 79 | 2347 | 92 | 3200 | 156 | 1630 | 64 | 2347 | 92 |

GA 90+ -160+/GA 110-160/GA 110-160 VSD – 50 Hz

| Type | Maximum working pressure | | | | Capacity FAD ⁽¹⁾ | | | | | | Installed motor power | | Noise level ⁽²⁾ | Weight | | | |
|---------------|--------------------------|------|-----------------------------|------|-----------------------------|--------|------|--------------|--------|------|-----------------------|-----|----------------------------|--------|------|--------------|------|
| | Pack | | Full Feature ⁽³⁾ | | Pack | | | Full Feature | | | | | | Pack | | Full Feature | |
| | bar(e) | psig | bar(e) | psig | l/s | m³/min | cfm | l/s | m³/min | cfm | kW | HP | dB(A) | kg | lb | kg | lb |
| GA 50 Hz | | | | | | | | | | | | | | | | | |
| GA 90+ - 5.5 | 5.5 | 80 | 5.3 | 77 | 330 | 19.8 | 699 | 333 | 20.0 | 706 | 90 | 125 | 68 | 2917 | 6417 | 3310 | 7282 |
| GA 90+ - 7.5 | 7.5 | 109 | 7.3 | 106 | 292 | 17.5 | 619 | 293 | 17.6 | 621 | 90 | 125 | 68 | 2917 | 6417 | 3310 | 7282 |
| GA 90+ - 8.5 | 8.5 | 123 | 8.3 | 120 | 274 | 16.4 | 581 | 275 | 16.5 | 583 | 90 | 125 | 68 | 2897 | 6373 | 3290 | 7238 |
| GA 90+ - 10 | 10 | 145 | 9.8 | 142 | 244 | 14.6 | 517 | 244 | 14.6 | 517 | 90 | 125 | 68 | 2709 | 5960 | 3102 | 6824 |
| GA 90+ - 14 | 14 | 203 | 13.8 | 200 | 196 | 11.8 | 415 | 204 | 12.2 | 432 | 90 | 125 | 68 | 2709 | 5960 | 3102 | 6824 |
| GA 110 - 7.5 | 7.5 | 109 | 7.3 | 106 | 342 | 20.5 | 725 | 343 | 20.6 | 727 | 110 | 150 | 69 | 2779 | 6114 | 3172 | 6978 |
| GA 110 - 8.5 | 8.5 | 123 | 8.3 | 120 | 324 | 19.4 | 687 | 326 | 19.6 | 691 | 110 | 150 | 69 | 2779 | 6114 | 3172 | 6978 |
| GA 110 - 10 | 10 | 145 | 9.8 | 142 | 297 | 17.8 | 629 | 297 | 21.4 | 754 | 110 | 150 | 69 | 2759 | 6070 | 3152 | 6934 |
| GA 110+ - 5.5 | 5.5 | 80 | 5.3 | 77 | 401 | 24.1 | 850 | 404 | 24.2 | 856 | 110 | 150 | 69 | 2967 | 6527 | 3360 | 7392 |
| GA 110+ - 7.5 | 7.5 | 109 | 7.3 | 106 | 356 | 21.4 | 754 | 357 | 21.4 | 756 | 110 | 150 | 69 | 2967 | 6527 | 3360 | 7392 |
| GA 110+ - 8.5 | 8.5 | 123 | 8.3 | 120 | 337 | 20.2 | 714 | 338 | 20.3 | 716 | 110 | 150 | 69 | 2967 | 6527 | 3360 | 7392 |
| GA 110+ - 10 | 10 | 145 | 9.8 | 142 | 306 | 23.8 | 839 | 306 | 18.4 | 648 | 110 | 150 | 69 | 2947 | 6483 | 3340 | 7348 |
| GA 110+ - 14 | 14 | 203 | 13.8 | 200 | 245 | 14.7 | 519 | 252 | 15.1 | 534 | 110 | 150 | 69 | 2759 | 6070 | 3152 | 6934 |
| GA 132 - 7.5 | 7.5 | 109 | 7.3 | 106 | 405 | 24.3 | 858 | 406 | 24.4 | 860 | 132 | 175 | 70 | 3134 | 6895 | 3527 | 7759 |
| GA 132 - 8.5 | 8.5 | 123 | 8.3 | 120 | 385 | 23.1 | 816 | 386 | 23.2 | 818 | 132 | 175 | 70 | 3134 | 6895 | 3527 | 7759 |
| GA 132 - 10 | 10 | 145 | 9.8 | 142 | 356 | 21.4 | 754 | 356 | 21.4 | 754 | 132 | 175 | 70 | 3114 | 6851 | 3507 | 7715 |
| GA 132+ - 5.5 | 5.5 | 80 | 5.3 | 77 | 471 | 28.3 | 998 | 475 | 28.5 | 1006 | 132 | 175 | 70 | 3271 | 7196 | 3644 | 8017 |
| GA 132+ - 7.5 | 7.5 | 109 | 7.3 | 106 | 424 | 25.4 | 898 | 425 | 25.5 | 901 | 132 | 175 | 70 | 3251 | 7152 | 3644 | 8017 |
| GA 132+ - 8.5 | 8.5 | 123 | 8.3 | 120 | 401 | 24.1 | 850 | 402 | 24.1 | 852 | 132 | 175 | 70 | 3251 | 7152 | 3644 | 8017 |
| GA 132+ - 10 | 10 | 145 | 9.8 | 142 | 368 | 22.1 | 780 | 368 | 22.1 | 780 | 132 | 175 | 70 | 3237 | 7121 | 3630 | 7986 |
| GA 132+ - 14 | 14 | 203 | 13.8 | 200 | 295 | 17.7 | 625 | 301 | 18.1 | 638 | 132 | 175 | 70 | 3049 | 6708 | 3442 | 7572 |
| GA 160 - 7.5 | 7.5 | 109 | 7.3 | 106 | 505 | 30.3 | 1070 | 506 | 30.4 | 1072 | 160 | 215 | 71 | 3361 | 7394 | 3754 | 8259 |
| GA 160 - 8.5 | 8.5 | 123 | 8.3 | 120 | 480 | 28.8 | 1017 | 481 | 28.9 | 1019 | 160 | 215 | 71 | 3341 | 7350 | 3734 | 8215 |
| GA 160 - 10 | 10 | 145 | 9.8 | 142 | 443 | 26.6 | 939 | 443 | 26.6 | 939 | 160 | 215 | 71 | 3341 | 7350 | 3734 | 8215 |
| GA 160+ - 10 | 10 | 145 | 9.8 | 142 | 443 | 26.6 | 939 | 443 | 26.6 | 939 | 160 | 215 | 71 | 3341 | 7350 | 3734 | 8215 |
| GA 160+ - 14 | 14 | 203 | 13.8 | 200 | 362 | 21.7 | 767 | 369 | 22.1 | 782 | 160 | 215 | 71 | 3327 | 7319 | 3720 | 8184 |

| Type | Maximum working pressure ⁽⁴⁾ | | | | Capacity FAD ¹ | | | Installed motor power | | Noise level ⁽²⁾ | Weight | | | |
|------------------|---|------|-----------------------------|------|---------------------------|------------|------------|-----------------------|-----|----------------------------|--------|------|--------------|------|
| | Pack | | Full Feature ⁽³⁾ | | Pack / Full Feature | | | | | | Pack | | Full Feature | |
| | bar(e) | psig | bar(e) | psig | l/s | m³/min | cfm | kW | HP | dB(A) | kg | lb | kg | lb |
| GA VSD 50 Hz | | | | | | | | | | | | | | |
| GA 110 VSD - 8.5 | 3.5 | 72.5 | 5 | 72.5 | 96 - 412 | 5.8 - 24.7 | 203 - 873 | 110 | 150 | 71 | 3894 | 8585 | 4154 | 9158 |
| | 7 | 102 | 7 | 102 | 93 - 369 | 5.6 - 22.1 | 198 - 782 | 110 | 150 | 71 | 3894 | 8585 | 4154 | 9158 |
| | 8 | 116 | 8 | 116 | 92 - 348 | 5.5 - 20.9 | 194 - 737 | 110 | 150 | 71 | 3894 | 8585 | 4154 | 9158 |
| GA 110 VSD - 10 | 6 | 87 | 6 | 87 | 95 - 389 | 5.7 - 23.3 | 201 - 824 | 110 | 150 | 71 | 3894 | 8585 | 4154 | 9158 |
| | 8 | 116 | 8 | 116 | 92 - 348 | 5.5 - 20.9 | 194 - 813 | 110 | 150 | 71 | 3894 | 8585 | 4154 | 9158 |
| | 9.5 | 138 | 9.5 | 138 | 88 - 322 | 5.3 - 19.3 | 187 - 682 | 110 | 150 | 71 | 3894 | 8585 | 4154 | 9158 |
| GA 110 VSD - 14 | 9 | 131 | 9 | 131 | 90 - 330 | 5.4 - 19.8 | 190 - 699 | 110 | 150 | 71 | 3894 | 8585 | 4154 | 9158 |
| | 10 | 145 | 10 | 145 | 87 - 314 | 5.2 - 18.8 | 184 - 665 | 110 | 150 | 71 | 3894 | 8585 | 4154 | 9158 |
| | 13.5 | 196 | 13.5 | 196 | 74 - 256 | 4.5 - 15.4 | 157 - 542 | 110 | 150 | 71 | 3894 | 8585 | 4154 | 9158 |
| GA 132 VSD - 8.5 | 3.5 | 51 | 3.5 | 51 | 97 - 539 | 5.8 - 32.3 | 206 - 1142 | 132 | 175 | 68 | 3930 | 8646 | 4248 | 9346 |
| | 7 | 102 | 7 | 102 | 93 - 457 | 5.6 - 27.4 | 197 - 968 | 132 | 175 | 68 | 3930 | 8646 | 4248 | 9346 |
| | 8 | 116 | 8 | 116 | 91 - 435 | 5.5 - 26.1 | 193 - 922 | 132 | 175 | 68 | 3930 | 8646 | 4248 | 9346 |
| GA 132 VSD - 10 | 6 | 87 | 6 | 87 | 94 - 481 | 5.6 - 28.9 | 199 - 1019 | 132 | 175 | 68 | 3930 | 8646 | 4248 | 9346 |
| | 8 | 116 | 8 | 116 | 91 - 435 | 5.5 - 26.1 | 193 - 922 | 132 | 175 | 68 | 3930 | 8646 | 4248 | 9346 |
| | 9.5 | 138 | 9.5 | 138 | 89 - 403 | 5.3 - 24.2 | 189 - 854 | 132 | 175 | 68 | 3930 | 8646 | 4248 | 9346 |
| GA 132 VSD - 14 | 9 | 131 | 9 | 131 | 90 - 412 | 5.4 - 24.7 | 191 - 873 | 132 | 175 | 68 | 3930 | 8646 | 4248 | 9346 |
| | 10 | 145 | 10 | 145 | 88 - 393 | 5.3 - 23.5 | 186 - 828 | 132 | 175 | 68 | 3930 | 8646 | 4248 | 9346 |
| | 13.5 | 196 | 13.5 | 196 | 81 - 325 | 4.9 - 19.5 | 172 - 689 | 132 | 175 | 68 | 3930 | 8646 | 4248 | 9346 |
| GA 160 VSD - 8.5 | 3.5 | 51 | 3.5 | 51 | 97 - 572 | 5.8 - 34.3 | 206 - 1212 | 160 | 215 | 69 | 3930 | 8646 | 4248 | 9346 |
| | 7 | 102 | 7 | 102 | 93 - 540 | 5.6 - 32.4 | 197 - 1144 | 160 | 215 | 69 | 3930 | 8646 | 4248 | 9346 |
| | 8 | 116 | 8 | 116 | 91 - 515 | 5.5 - 30.9 | 193 - 1091 | 160 | 215 | 69 | 3930 | 8646 | 4248 | 9346 |
| GA 160 VSD - 10 | 6 | 87 | 6 | 87 | 94 - 566 | 5.5 - 34.0 | 199 - 1199 | 160 | 215 | 69 | 3930 | 8646 | 4248 | 9346 |
| | 8 | 116 | 8 | 116 | 91 - 515 | 5.5 - 30.9 | 193 - 1091 | 160 | 215 | 69 | 3930 | 8646 | 4248 | 9346 |
| | 9.5 | 138 | 9.5 | 138 | 89 - 480 | 5.3 - 28.8 | 189 - 1017 | 160 | 215 | 69 | 3930 | 8646 | 4248 | 9346 |
| GA 160 VSD - 14 | 9 | 131 | 9 | 131 | 90 - 492 | 5.4 - 29.5 | 191 - 1042 | 160 | 215 | 69 | 3930 | 8646 | 4248 | 9346 |
| | 10 | 145 | 10 | 145 | 88 - 469 | 5.3 - 28.1 | 186 - 994 | 160 | 215 | 69 | 3930 | 8646 | 4248 | 9346 |
| | 13.5 | 196 | 13.5 | 196 | 82 - 394 | 4.9 - 23.6 | 174 - 835 | 160 | 215 | 69 | 3930 | 8646 | 4248 | 9346 |

(1) Unit Performance Measured according to ISO 1217, Ed. 3, Annex C - 1996

Reference conditions:

- Absolute inlet pressure 1 bar (14.5 psi)
- Intake air temperature 20°C (68°F)
- Cooling medium temperature 20°C (68°F)

(2) Noise level:

Measured according to ISO 2151: 2004 using ISO 9614/2

(3) Maximum working pressure is reduced by 0.2 bar when integrated DD filter option is selected

(4) Maximum working pressure for GA VSD - 8.5; 10; 14 bar (e)/ GA VSD FF - 8.3; 9.8; 13.8 bar(e)

Integrated dryer: Compressed air pressure dewpoint at dryer reference conditions 3°C

Integrated DD filter: Particle removal down to 1 micron and maximum remaining aerosol 0.1 mg/m³

FAD is measured at the following working pressures:

- 5.5 bar variants at 5 bar
- 7.5 bar variants at 7 bar
- 8.5 bar variants at 8 bar
- 10 bar variants at 9.5 bar
- 14 bar variants at 13.5 bar

GA 90+ -160+/GA 110-160/GA 110-160 VSD – 60 Hz

| Type | Maximum working pressure | | | | Capacity FAD ⁽¹⁾ | | | | | | Installed motor power | | Noise level ⁽²⁾ | Weight | | | |
|---------------|--------------------------|------|-----------------------------|------|-----------------------------|--------|------|--------------|--------|------|-----------------------|-----|----------------------------|--------|------|--------------|------|
| | Pack | | Full feature ⁽³⁾ | | Pack | | | Full feature | | | | | | Pack | | Full feature | |
| | bar(e) | psig | bar(e) | psig | l/s | m³/min | cfm | l/s | m³/min | cfm | kW | HP | dB(A) | kg | lb | kg | lb |
| GA 60 Hz | | | | | | | | | | | | | | | | | |
| GA 90+ - 75 | 5.5 | 80 | 5.3 | 77 | 343 | 20.6 | 727 | 346 | 20.8 | 733 | 90 | 125 | 68 | 2917 | 6417 | 3310 | 7282 |
| GA 90+ - 100 | 7.4 | 107 | 7.2 | 104 | 302 | 18.1 | 640 | 303 | 18.2 | 642 | 90 | 125 | 68 | 2917 | 6417 | 3310 | 7282 |
| GA 90+ - 125 | 9.1 | 132 | 8.9 | 129 | 274 | 16.4 | 581 | 275 | 16.5 | 583 | 90 | 125 | 68 | 2897 | 6373 | 3290 | 7238 |
| GA 90+ - 150 | 10.9 | 158 | 10.7 | 155 | 239 | 14.3 | 506 | 239 | 14.3 | 506 | 90 | 125 | 68 | 2709 | 5960 | 3102 | 6824 |
| GA 90+ - 200 | 14 | 203 | 13.5 | 196 | 205 | 12.3 | 434 | 213 | 12.8 | 451 | 90 | 125 | 68 | 2709 | 5960 | 3102 | 6824 |
| GA 110 - 100 | 7.4 | 107 | 7.2 | 104 | 350 | 21.0 | 742 | 352 | 21.1 | 746 | 110 | 150 | 69 | 2779 | 6114 | 3172 | 6978 |
| GA 110 - 125 | 9.1 | 132 | 8.9 | 129 | 320 | 19.2 | 678 | 322 | 19.3 | 682 | 110 | 150 | 69 | 2779 | 6114 | 3172 | 6978 |
| GA 110 - 150 | 10.9 | 158 | 10.7 | 155 | 286 | 17.2 | 606 | 286 | 17.2 | 606 | 110 | 150 | 69 | 2759 | 6070 | 3152 | 6934 |
| GA 110+ - 75 | 5.5 | 80 | 5.3 | 77 | 406 | 24.4 | 860 | 409 | 24.5 | 867 | 110 | 150 | 69 | 2967 | 6527 | 3360 | 7392 |
| GA 110+ - 100 | 7.4 | 107 | 7.2 | 104 | 363 | 21.8 | 769 | 364 | 21.8 | 771 | 110 | 150 | 69 | 2967 | 6527 | 3360 | 7392 |
| GA 110+ - 125 | 9.1 | 132 | 8.9 | 129 | 331 | 19.9 | 701 | 332 | 19.9 | 703 | 110 | 150 | 69 | 2967 | 6527 | 3360 | 7392 |
| GA 110+ - 150 | 10.9 | 158 | 10.7 | 155 | 295 | 17.7 | 625 | 295 | 17.7 | 625 | 110 | 150 | 69 | 2947 | 6483 | 3340 | 7348 |
| GA 110+ - 200 | 14 | 203 | 13.5 | 196 | 248 | 14.9 | 525 | 255 | 15.3 | 540 | 110 | 150 | 69 | 2759 | 6070 | 3152 | 6934 |
| GA 132 - 100 | 7.4 | 107 | 7.2 | 104 | 403 | 24.2 | 854 | 405 | 24.3 | 858 | 132 | 175 | 70 | 3134 | 6895 | 3527 | 7759 |
| GA 132 - 125 | 9.1 | 132 | 8.9 | 129 | 370 | 22.2 | 784 | 371 | 22.3 | 786 | 132 | 175 | 70 | 3134 | 6895 | 3527 | 7759 |
| GA 132 - 150 | 10.9 | 158 | 10.7 | 155 | 336 | 20.2 | 712 | 336 | 20.2 | 712 | 132 | 175 | 70 | 3114 | 6851 | 3507 | 7715 |
| GA 132+ - 75 | 5.5 | 80 | 5.3 | 77 | 467 | 28.0 | 990 | 471 | 28.3 | 998 | 132 | 175 | 70 | 3271 | 7196 | 3644 | 8017 |
| GA 132+ - 100 | 7.4 | 107 | 7.2 | 104 | 421 | 25.3 | 892 | 422 | 25.3 | 894 | 132 | 175 | 70 | 3251 | 7152 | 3644 | 8017 |
| GA 132+ - 125 | 9.1 | 132 | 8.9 | 129 | 385 | 23.1 | 816 | 386 | 23.2 | 818 | 132 | 175 | 70 | 3251 | 7152 | 3644 | 8017 |
| GA 132+ - 150 | 10.9 | 158 | 10.7 | 155 | 346 | 20.8 | 733 | 346 | 20.8 | 733 | 132 | 175 | 70 | 3237 | 7121 | 3630 | 7986 |
| GA 132+ - 200 | 14 | 203 | 13.5 | 196 | 290 | 17.4 | 614 | 296 | 17.8 | 627 | 132 | 175 | 70 | 3049 | 6708 | 3442 | 7572 |
| GA 160 - 100 | 7.4 | 107 | 7.2 | 104 | 475 | 28.5 | 1006 | 477 | 28.6 | 1011 | 150 | 200 | 71 | 3361 | 7394 | 3754 | 8259 |
| GA 160 - 125 | 9.1 | 132 | 8.9 | 129 | 437 | 26.2 | 926 | 438 | 26.3 | 928 | 150 | 200 | 71 | 3341 | 7350 | 3734 | 8215 |
| GA 160 - 150 | 10.9 | 158 | 10.7 | 155 | 397 | 23.8 | 841 | 397 | 23.8 | 841 | 150 | 200 | 71 | 3341 | 7350 | 3734 | 8215 |
| GA 160+ - 150 | 10.9 | 158 | 10.7 | 155 | 397 | 23.8 | 841 | 397 | 23.8 | 841 | 150 | 200 | 71 | 3341 | 7350 | 3734 | 8215 |
| GA 160+ - 200 | 14 | 203 | 13.5 | 196 | 337 | 20.2 | 714 | 345 | 20.7 | 731 | 150 | 200 | 71 | 3327 | 7319 | 3720 | 8184 |

| Type | Maximum working pressure ⁽⁴⁾ | | | | Capacity FAD ⁽¹⁾ | | | Installed motor power | | Noise level ⁽²⁾ | Weight | | | |
|------------------|---|------|-----------------------------|------|-----------------------------|------------|------------|-----------------------|-----|----------------------------|--------|------|--------------|------|
| | Pack | | Full feature ⁽³⁾ | | Pack / Full feature | | | | | | Pack | | Full feature | |
| | bar(e) | psig | bar(e) | psig | l/s | m³/min | cfm | kW | HP | dB(A) | kg | lb | kg | lb |
| GA VSD 60 Hz | | | | | | | | | | | | | | |
| GA 110 VSD - 125 | 3.5 | 72.5 | 5 | 72.5 | 96 - 412 | 5.7 - 24.5 | 203 - 867 | 110 | 148 | 71 | 3894 | 8585 | 4154 | 9158 |
| | 7 | 102 | 7 | 102 | 93 - 371 | 5.6 - 22.2 | 198 - 786 | 110 | 148 | 71 | 3894 | 8585 | 4154 | 9158 |
| GA 110 VSD - 150 | 8 | 116 | 8 | 116 | 90 - 336 | 5.4 - 20.0 | 191 - 711 | 110 | 148 | 71 | 3894 | 8585 | 4154 | 9158 |
| | 6 | 87 | 6 | 87 | 95 - 389 | 5.7 - 23.3 | 201 - 824 | 110 | 148 | 71 | 3894 | 8585 | 4154 | 9158 |
| GA 110 VSD - 200 | 8 | 116 | 8 | 116 | 90 - 336 | 5.4 - 20.0 | 192 - 712 | 110 | 148 | 71 | 3894 | 8585 | 4154 | 9158 |
| | 9.5 | 138 | 9.5 | 138 | 86 - 307 | 5.1 - 18.4 | 182 - 651 | 110 | 148 | 71 | 3894 | 8585 | 4154 | 9158 |
| | 9 | 131 | 9 | 131 | 90 - 330 | 5.3 - 19.8 | 190 - 699 | 110 | 148 | 71 | 3894 | 8585 | 4154 | 9158 |
| GA 132 VSD - 125 | 10 | 145 | 10 | 145 | 86 - 307 | 5.2 - 18.4 | 182 - 650 | 110 | 148 | 71 | 3894 | 8585 | 4154 | 9158 |
| | 13.5 | 196 | 13.5 | 196 | 74 - 256 | 4.4 - 15.3 | 157 - 543 | 110 | 148 | 71 | 3894 | 8585 | 4154 | 9158 |
| | 3.5 | 51 | 3.5 | 51 | 97 - 539 | 5.8 - 32.3 | 206 - 1142 | 132 | 175 | 68 | 3930 | 8646 | 4248 | 9346 |
| GA 132 VSD - 150 | 6.9 | 100 | 6.9 | 100 | 93 - 459 | 5.6 - 27.5 | 197 - 973 | 132 | 175 | 68 | 3930 | 8646 | 4248 | 9346 |
| | 8.6 | 125 | 8.6 | 125 | 90 - 422 | 5.4 - 25.2 | 191 - 890 | 132 | 175 | 68 | 3930 | 8646 | 4248 | 9346 |
| | 6 | 87 | 6 | 87 | 94 - 481 | 5.4 - 25.2 | 191 - 890 | 132 | 175 | 68 | 3930 | 8646 | 4248 | 9346 |
| GA 132 VSD - 200 | 8.6 | 125 | 8.6 | 125 | 90 - 422 | 5.4 - 25.2 | 191 - 890 | 132 | 175 | 68 | 3930 | 8646 | 4248 | 9346 |
| | 10.4 | 151 | 10.4 | 151 | 87 - 386 | 5.2 - 23.0 | 184 - 812 | 132 | 175 | 68 | 3930 | 8646 | 4248 | 9346 |
| | 9 | 131 | 9 | 131 | 90 - 414 | 5.4 - 24.7 | 191 - 873 | 132 | 175 | 68 | 3930 | 8646 | 4248 | 9346 |
| GA 160 VSD - 125 | 10.4 | 151 | 10.4 | 151 | 87 - 386 | 5.2 - 23.0 | 184 - 812 | 132 | 175 | 68 | 3930 | 8646 | 4248 | 9346 |
| | 13.5 | 196 | 13.5 | 196 | 81 - 325 | 4.9 - 19.5 | 172 - 689 | 132 | 175 | 68 | 3930 | 8646 | 4248 | 9346 |
| | 3.5 | 51 | 3.5 | 51 | 97 - 579 | 5.8 - 34.3 | 206 - 1212 | 160 | 215 | 69 | 3930 | 8646 | 4248 | 9346 |
| GA 160 VSD - 150 | 6.9 | 100 | 6.9 | 100 | 93 - 543 | 5.6 - 32.6 | 197 - 1151 | 160 | 215 | 69 | 3930 | 8646 | 4248 | 9346 |
| | 8.6 | 125 | 8.6 | 125 | 90 - 501 | 5.4 - 30.1 | 191 - 1062 | 160 | 215 | 69 | 3930 | 8646 | 4248 | 9346 |
| | 6 | 87 | 6 | 87 | 94 - 566 | 5.6 - 34.0 | 199 - 1199 | 160 | 215 | 69 | 3930 | 8646 | 4248 | 9346 |
| GA 160 VSD - 200 | 8.6 | 125 | 8.6 | 125 | 90 - 501 | 5.4 - 30.1 | 191 - 1062 | 160 | 215 | 69 | 3930 | 8646 | 4248 | 9346 |
| | 10.4 | 151 | 10.4 | 151 | 87 - 461 | 5.2 - 27.7 | 184 - 977 | 160 | 215 | 69 | 3930 | 8646 | 4248 | 9346 |
| | 9 | 131 | 9 | 131 | 90 - 492 | 5.4 - 29.5 | 191 - 1042 | 160 | 215 | 69 | 3930 | 8646 | 4248 | 9346 |
| | 10.4 | 151 | 10.4 | 151 | 87 - 461 | 5.2 - 27.7 | 184 - 977 | 160 | 215 | 69 | 3930 | 8646 | 4248 | 9346 |
| | 13.5 | 196 | 13.5 | 196 | 82 - 394 | 4.9 - 23.6 | 174 - 835 | 160 | 215 | 69 | 3930 | 8646 | 4248 | 9346 |

(1) Unit Performance Measured according to ISO 1217, Ed. 3, Annex C - 1996

Reference conditions:

- Absolute inlet pressure 1 bar (14.5 psi)
- Intake air temperature 20°C (68°F)
- Cooling medium temperature 20°C (68°F)

(2) Noise level:

Measured according to ISO 2151: 2004 using ISO 9614/2

(3) Maximum working pressure is reduced by 0.2 bar when integrated DD filter option is selected

(4) Maximum working pressure for GA VSD - 8.5; 10; 14 bar (e)/GA VSD FF - 8.3; 9.8; 13.8 bar(e)

Integrated dryer: Compressed air pressure dewpoint at dryer reference conditions 3°C

Integrated DD filter: Particle removal down to 1 micron and maximum remaining aerosol 0.1 mg/m³
FAD is measured at the following working pressures:

- 75 psi variants at 73 psi
- 100 psi variants at 100 psi
- 125 psi variants at 125 psi
- 150 psi variants at 150 psi
- 200 psi variants at 200 psi

Oil-injected rotary screw compressors

GA 200-500 (VSD)

Atlas Copco's GA 200-500 (VSD) oil-injected rotary screw compressors are designed and built to provide the maximum free air delivery at the lowest energy costs. The robust design ensures your process will function continuously even in the harshest conditions such as temperatures up to 46°C/115°F.

CUSTOMER BENEFITS

- **Highest reliability** – Our GA 200-500 (VSD) compressors incorporate a superior oil-injected screw element based on innovative asymmetric rotor profiles and a high-quality drive system. All components are selected to ensure a long and trouble-free life of your compressor at the lowest operating cost. ,

- **Reduced energy costs** – The GA Series' superior screw elements are designed to give the optimum combination of maximum free air delivery for low energy consumption. The state-of-the-art compressor

element is powered by Efficiency 1 class/NEMA EPAct electric motors, contributing to maximum compressor package efficiency. Beside this, the GA 315 VSD can offer additional energy savings of on average 35% by automatically adjusting the motor speed to the air demand. ,

- **Integrated air treatment** – The GA Full Feature with highly energy-efficient integrated refrigerant dryer and air filter ensures the continuous supply of clean and dry air to extend the life of equipment, enhance system reliability and avoid costly downtime and production delays. ,

- **Advanced control monitoring** – To maximize efficiency and reliability, the Elektronikon® controls the main drive motor and regulates system pressure within a predefined and narrow pressure band. The Elektronikon® controller can be adapted to your specific needs with extra sensors, digital contacts, fieldbus, Internet and SMS communication functions. In combination with the ES multiple compressor controller, the operation of your complete compressor room is optimized.

- **Easy installation** – The integrated design includes internal piping, coolers, motor, lubrication and control system: all supplied as a ready-to-use package. Installation is fault-free and commissioning time is low. Simply plug and run.



GA compressor range - 50 Hz: air and water-cooled variants

| Type | Maximum working pressure | | | | Capacity FAD ⁽¹⁾ | | | Installed motor power | | Noise level ⁽²⁾ | Weight | | | |
|-----------------|--------------------------|------|--------------|------|-----------------------------|---------|------|-----------------------|-----|----------------------------|--------|-------|--------------|-------|
| | Pack | | Full feature | | Pack / Full feature | | | | | | Pack | | Full feature | |
| | bar(e) | psig | bar(e) | psig | l/s | m³/ min | cfm | kW | hp | dB(A) | kg | lb | kg | lb |
| GA 200-500 Twin | | | | | | | | | | | | | | |
| GA 200 | 7.5 | 109 | 7.25 | 105 | 603 | 36.1 | 1278 | 200 | 270 | 75 | 4727 | 10421 | 5127 | 11303 |
| | 8.5 | 123 | 8.25 | 120 | 568 | 34.0 | 1204 | 200 | 270 | 75 | 4727 | 10421 | 5127 | 11303 |
| | 10 | 145 | 9.75 | 141 | 513 | 30.7 | 1087 | 200 | 270 | 75 | 4727 | 10421 | 5127 | 11303 |
| | 13 | 189 | 12.75 | 185 | 436 | 26.1 | 924 | 200 | 270 | 75 | 4727 | 10421 | 5127 | 11303 |
| GA 250 | 7.5 | 109 | 7.25 | 105 | 730 | 43.7 | 1548 | 250 | 335 | 75 | 5017 | 11060 | 5417 | 11942 |
| | 8.5 | 123 | 8.25 | 120 | 697 | 41.7 | 1477 | 250 | 335 | 75 | 5017 | 11060 | 5417 | 11942 |
| | 10 | 145 | 9.75 | 141 | 631 | 37.8 | 1338 | 250 | 335 | 75 | 5017 | 11060 | 5417 | 11942 |
| | 13 | 189 | 12.75 | 185 | 530 | 31.7 | 1124 | 250 | 335 | 75 | 5017 | 11060 | 5417 | 11942 |
| GA 315 | 7.5 | 109 | - | - | 928 | 55.8 | 1966 | 315 | 420 | 72 | 7510 | 16559 | - | - |
| | 8.5 | 123 | - | - | 864 | 51.9 | 1831 | 315 | 420 | 72 | 7510 | 16559 | - | - |
| | 10 | 145 | - | - | 784 | 47.1 | 1661 | 315 | 420 | 72 | 7510 | 16559 | - | - |
| GA 355 | 7.5 | 109 | - | - | 1050 | 63.1 | 2225 | 355 | 475 | 73 | 7760 | 17110 | - | - |
| | 8.5 | 123 | - | - | 969 | 58.2 | 2053 | 355 | 475 | 73 | 7760 | 17110 | - | - |
| | 10 | 145 | - | - | 890 | 53.5 | 1886 | 355 | 475 | 73 | 7760 | 17110 | - | - |
| | 13 | 189 | - | - | 731 | 43.9 | 1549 | 355 | 475 | 73 | 7760 | 17110 | - | - |
| GA 400 | 7.5 | 109 | - | - | 1175 | 70.6 | 2490 | 400 | 535 | 74 | 8360 | 18433 | - | - |
| | 8.5 | 123 | - | - | 1109 | 66.6 | 2350 | 400 | 535 | 74 | 8360 | 18433 | - | - |
| | 10 | 145 | - | - | 1011 | 60.8 | 2142 | 400 | 535 | 74 | 8360 | 18433 | - | - |
| | 13 | 189 | - | - | 844 | 50.7 | 1788 | 400 | 535 | 74 | 8360 | 18433 | - | - |
| GA 450 | 7.5 | 109 | - | - | 1298 | 78.0 | 2750 | 450 | 600 | 75 | 8360 | 18433 | - | - |
| | 8.5 | 123 | - | - | 1240 | 74.5 | 2628 | 450 | 600 | 75 | 8360 | 18433 | - | - |
| | 10 | 145 | - | - | 1144 | 68.8 | 2424 | 450 | 600 | 75 | 8360 | 18433 | - | - |
| | 13 | 189 | - | - | 960 | 57.7 | 2034 | 450 | 600 | 75 | 8360 | 18433 | - | - |
| GA 500 | 7.5 | 109 | - | - | 1410 | 84.7 | 2988 | 500 | 670 | 76 | 7960 | 17551 | - | - |
| | 8.5 | 123 | - | - | 1347 | 80.9 | 2854 | 500 | 670 | 76 | 7960 | 17551 | - | - |
| | 10 | 145 | - | - | 1257 | 75.5 | 2664 | 500 | 670 | 76 | 7960 | 17551 | - | - |
| | 13 | 189 | - | - | 1068 | 64.2 | 2263 | 500 | 670 | 76 | 7960 | 17551 | - | - |

GA 500 figures are for medium voltage IP 23 motor

GA compressor range - 60 Hz: air and water-cooled variants

| Type | Maximum working pressure | | | | Capacity FAD ⁽¹⁾ | | | Installed motor power | | Noise level ⁽²⁾ | Weight | | | |
|-----------------|--------------------------|------|--------------|------|-----------------------------|---------|------|-----------------------|-----|----------------------------|-----------|-------------|--------------|-------|
| | Pack | | Full feature | | Pack / Full feature | | | | | | Pack | | Full feature | |
| | bar(e) | psig | bar(e) | psig | l/s | m³/ min | cfm | kW | hp | dB(A) | kg | lb | kg | lb |
| GA 200-315 Twin | | | | | | | | | | | | | | |
| GA 200-100 | 7.4 | 107 | 7.15 | 104 | 586 | 35.1 | 1242 | 185 | 250 | 76 | 4957 | 10928 | 5357 | 11810 |
| GA 200-125 | 9.1 | 132 | 8.85 | 128 | 532 | 32.0 | 1128 | 185 | 250 | 76 | 4957 | 10928 | 5357 | 11810 |
| GA 200-150 | 10.8 | 157 | 10.55 | 153 | 483 | 29.0 | 1024 | 185 | 250 | 76 | 4957 | 10928 | 5357 | 11810 |
| GA 250-100 | 7.4 | 107 | 7.15 | 104 | 683 | 41.0 | 1448 | 225 | 300 | 76 | 5057 | 11149 | 5457 | 12030 |
| GA 250-125 | 9.1 | 132 | 8.85 | 128 | 620 | 37.1 | 1314 | 225 | 300 | 76 | 5057 | 11149 | 5457 | 12030 |
| GA 250-150 | 10.8 | 157 | 10.55 | 153 | 569 | 34.1 | 1206 | 225 | 300 | 76 | 5057 | 11149 | 5457 | 12030 |
| GA 250-200 | 13.8 | 200 | 13.55 | 196 | 477 | 28.6 | 1011 | 225 | 300 | 76 | 5057 | 11149 | 5457 | 12030 |
| GA 315-100 | 7.4 | 107 | 7.15 | 104 | 777 | 46.5 | 1647 | 260 | 350 | 76 | 5257 | 11590 | 5657 | 12470 |
| GA 315-125 | 9.1 | 132 | 8.85 | 128 | 707 | 42.3 | 1499 | 260 | 350 | 76 | 5257 | 11590 | 5657 | 12470 |
| GA 315-150 | 10.8 | 157 | 10.55 | 153 | 660 | 39.5 | 1399 | 260 | 350 | 76 | 5257 | 11590 | 5657 | 12470 |
| GA 315-200 | 13.8 | 200 | 13.55 | 196 | 555 | 33.2 | 1177 | 260 | 350 | 76 | 5257 | 11590 | 5657 | 12470 |
| GA 355-100 | 7.4 | 107 | - | - | 1032 | 62.1 | 2191 | 335 | 450 | 73 | 7760/7860 | 17110/17331 | - | - |
| GA 355-125 | 9.1 | 132 | - | - | 940 | 56.5 | 1992 | 335 | 450 | 73 | 7760/7860 | 17110/17331 | - | - |
| GA 355-150 | 10.8 | 157 | - | - | 831 | 49.9 | 1761 | 335 | 450 | 73 | 7760/7860 | 17110/17331 | - | - |
| GA 355-200 | 13.8 | 200 | - | - | 692 | 41.6 | 1466 | 335 | 450 | 73 | 7760/7860 | 17110/17331 | - | - |
| GA 400-100 | 7.4 | 107 | - | - | 1128 | 67.9 | 2394 | 372 | 500 | 74 | 8360/7960 | 18433/17551 | - | - |
| GA 400-125 | 9.1 | 132 | - | - | 1042 | 62.6 | 2208 | 372 | 500 | 74 | 8360/7960 | 18433/17551 | - | - |
| GA 400-150 | 10.8 | 157 | - | - | 935 | 56.2 | 1981 | 372 | 500 | 74 | 8360/7960 | 18433/17551 | - | - |
| GA 400-200 | 13.8 | 200 | - | - | 784 | 47.1 | 1661 | 372 | 500 | 74 | 8360/7960 | 18433/17551 | - | - |
| GA 450-100 | 7.4 | 107 | - | - | 1334 | 80.4 | 2835 | 447 | 600 | 75 | 8360/8620 | 18433/19007 | - | - |
| GA 450-125 | 9.1 | 132 | - | - | 1222 | 73.4 | 2589 | 447 | 600 | 75 | 8360/8620 | 18433/19007 | - | - |
| GA 450-150 | 10.8 | 157 | - | - | 1126 | 67.7 | 2386 | 447 | 600 | 75 | 8360/8620 | 18433/19007 | - | - |
| GA 450-200 | 13.8 | 200 | - | - | 943 | 56.7 | 1998 | 447 | 600 | 75 | 8360/8620 | 18433/19007 | - | - |
| GA 500-100 | 7.4 | 107 | - | - | 1518 | 91.2 | 3217 | 522 | 700 | 76 | 7960 | 17551 | - | - |
| GA 500-125 | 9.1 | 132 | - | - | 1404 | 84.4 | 2975 | 522 | 700 | 76 | 7960 | 17551 | - | - |
| GA 500-150 | 10.8 | 157 | - | - | 1296 | 77.9 | 2746 | 522 | 700 | 76 | 7960 | 17551 | - | - |
| GA 500-200 | 13.8 | 200 | - | - | 1114 | 66.9 | 2361 | 522 | 700 | 76 | 7960 | 17551 | - | - |

GA 500W figures are for medium voltage IP 23 motor. GA 355W - GA 400W - GA 450W: two different motor types used for IEC/CSA-UL at 60Hz low voltage

(1) Unit performance measured according to ISO 1217 (1996)

Reference conditions:

- absolute inlet pressure 1 bar (14.5 psi)
- intake air temperature 20°C (68°F)

FAD is measured at the following working pressures:

- 7.5 bar variants at 7 bar
- 8.5 bar variants at 8 bar
- 10 bar variants at 9.5 bar
- 13 bar variants at 12.5 bar
- 20 bar variants at 19 bar
- 100 psi variants at 100 psi
- 125 psi variants at 125 psi
- 150 psi variants at 150 psi
- 200 psi variants at 193 psi
- 290 psi variants at 276 psi

(2) Noise level:

measured according to Pneurop / Cagi PN8NTC2.2 test code; tolerance ±3 dB(A)

Integrated dryer:

pressure dewpoint of integrated refrigerant dryer at reference conditions: 3 to 4°C

Integrated filter:

particle removal down to 1 micron and maximum remaining oil aerosol of 0.1 mg/m³

Oil-injected rotary screw compressors, 110-200 kW / 150-270 hp

GR 110-200

Atlas Copco's GR 110-200 oil-injected rotary screw compressors are ideal for high-pressure applications requiring a reliable air supply of 13 and 20 bar. The installation, operation and maintenance of these robust and reliable machines is kept simple. Their two-stage design ensures the most efficient operation at higher pressure. Our GR 110-200 compressors will cut your costs and enable smooth, continuous operation right across your production processes. You can choose from air- or water-cooled versions.

CUSTOMER BENEFITS

- **High reliability** – The two-stage compression element features an asymmetric rotor profile you can rely on. Thanks to the extremely reduced load on bearings, rotors and gears, the element lifetime is long, ensuring low wear and tear and reliability at the lowest operating cost.
- **Advanced control monitoring** – To maximize efficiency and reliability, the Elektronikon® controls the main drive motor and regulates system pressure within a predefined and narrow pressure band. The Elektronikon® controller can be adapted to your specific needs with extra sensors, digital contacts, fieldbus, Internet and SMS communication functions. In combination with the ES multiple compressor controller, the operation of your complete compressor room is optimized.
- **Easy installation** – The GR 110-200 is truly plug-and-play. Simply put the machine on a flat floor, connect the power line and the compressed air outlet, and push the start button.
- **Minimal maintenance** – GR 110-200 compressors are designed for trouble-free maintenance, with easily accessible oil and air filters and simple cooler cleaning procedures.

GA VSD/ GR compressor range 50Hz

| Type | Max. working pressure | | | | Capacity FAD* | | | Installed motor power | | Noise level** | Weight | | | |
|-------------------------------|-----------------------|------|--------------|------|--------------------|--------|------|-----------------------|-----|---------------|--------|-------|--------------|-------|
| | Pack | | Full feature | | Pack/ Full feature | | | | | | Pack | | Full feature | |
| | bar(e) | psig | bar(e) | psig | l/s | m³/min | cfm | kW | hp | dB(A) | kg | lb | kg | lb |
| GA 315 VSD | | | | | | | | | | | | | | |
| GA 315 VSD | 4 | 58 | 4 | 58 | 854 | 51.2 | 1810 | 290 | 390 | 75 | 6165 | 13563 | 6615 | 14553 |
| | 7 | 109 | 7 | 109 | 847 | 50.8 | 1795 | 290 | 390 | 75 | 6165 | 13563 | 6615 | 14553 |
| | 10 | 145 | 9.9 | 143 | 710 | 42.6 | 1505 | 290 | 390 | 75 | 6165 | 13563 | 6615 | 14553 |
| GR 110 - 200 Two stage 13 bar | | | | | | | | | | | | | | |
| GR 110 | 13 | 189 | 12.75 | 185 | 255 | 15.3 | 541 | 110 | 150 | 72 | 3140 | 6908 | 3470 | 7634 |
| GR 132 | 13 | 189 | 12.75 | 185 | 308 | 18.5 | 653 | 132 | 175 | 75 | 3140 | 6908 | 3470 | 7634 |
| GR 160 | 13 | 189 | 12.75 | 185 | 369 | 22.1 | 782 | 160 | 215 | 75 | 3547 | 7803 | 3877 | 8529 |
| GR 200 | 13 | 189 | 12.75 | 185 | 437 | 26.2 | 926 | 200 | 270 | 76 | 3547 | 7803 | 3877 | 8529 |
| GR 110 - 200 Two stage 20 bar | | | | | | | | | | | | | | |
| GR 110 | 20 | 290 | 19.75 | 286 | 211 | 12.6 | 447 | 110 | 150 | 72 | 3140 | 6908 | 3470 | 7634 |
| GR 200 | 20 | 290 | 19.75 | 286 | 385 | 23.1 | 816 | 200 | 270 | 75 | 3547 | 7803 | 3877 | 8529 |

* Unit performance measured according to ISO 1217, Annex C, Edition 4

Reference conditions:

- Absolute inlet pressure 1 bar (14.5 psi)
- Intake air temperature 20°C, 68°F

FAD is measured at the following working pressures:

- 7.5 bar versions at 7 bar
- 8.5 bar versions at 8 bar
- 10 bar versions at 9.5 bar
- 13 bar versions at 12.5 bar
- 20 bar versions at 20 bar
- 100 psi variants at 100 psi
- 125 psi variants at 125 psi
- 150 psi variants at 150 psi
- 200 psi variants at 200 psi
- 290 psi variants at 290 psi

** Noise Level

measured according to Pneurol/Cagi PN8NTC2.2 test code; tolerance ±3 dB(A)

Integrated Dryer:

Pressure dewpoint of integrated refrigerant dryer at reference conditions: 3 to 4°C

Integrated Filter:

Partial removal down to 1 micron and maximum remaining oil aerosol of 0.1mg/m³



| Type | Dimensions | | | | | |
|----------------|------------|-------|------|------|------|------|
| | A | | B | | C | |
| | mm | inch | mm | inch | mm | inch |
| GA 200 - 315 | 3386 | 133.3 | 2120 | 83.4 | 2400 | 94.4 |
| GA 315 - 500A* | 5855 | 230.5 | 2120 | 83.4 | 2500 | 98.4 |
| GA 315 - 500W* | 4173 | 164.3 | 2120 | 83.4 | 2500 | 98.4 |
| GA 315 VSD | 4000 | 157.4 | 2120 | 83.4 | 2400 | 94.4 |
| GR 110-200 | 2779 | 109.4 | 1886 | 74.3 | 1990 | 78.3 |

* W = Water-cooled

A = Air-cooled

GA VSD/ GR compressor range 60Hz

| Type | Max. working pressure | | | | Capacity FAD* | | | Installed motor power | | Noise Level** | Weight | | | |
|-------------------------------|-----------------------|------|--------------|------|--------------------|--------|------|-----------------------|-----|---------------|--------|-------|--------------|-------|
| | Pack | | Full feature | | Pack/ Full feature | | | | | | Pack | | Full feature | |
| | bar(e) | psig | bar(e) | psig | l/s | m³/min | cfm | kW | hp | dB(A) | kg | lb | kg | lb |
| GA 315 VSD | | | | | | | | | | | | | | |
| GA 315 VSD | 4 | 58 | 4 | 58 | 854 | 51.2 | 1810 | 290 | 390 | 75 | 6165 | 13563 | 6615 | 14553 |
| | 7 | 109 | 7 | 109 | 847 | 50.8 | 1795 | 290 | 390 | 75 | 6165 | 13563 | 6615 | 14553 |
| | 10 | 145 | 9.9 | 143 | 710 | 42.6 | 1505 | 290 | 390 | 75 | 6165 | 13563 | 6615 | 14553 |
| GR 110 - 200 Two stage 13 bar | | | | | | | | | | | | | | |
| GR 110-200 | 13.8 | 200 | 13.55 | 196 | 261 | 15.6 | 541 | 110 | 150 | 72 | 3140 | 6908 | 3470 | 7634 |
| GR 160-200 | 13.8 | 200 | 13.55 | 196 | 350 | 21.0 | 782 | 150 | 200 | 75 | 3547 | 7803 | 3877 | 8529 |
| GR 200-290 | 13.8 | 200 | 13.55 | 196 | 442 | 26.5 | 926 | 185 | 250 | 78 | 3547 | 7803 | 3877 | 8529 |
| GR 110 - 200 Two stage 20 bar | | | | | | | | | | | | | | |
| GR 110-290 | 20 | 290 | 19.75 | 286 | 224 | 13.4 | 475 | 110 | 150 | 72 | 3140 | 6908 | 3470 | 7634 |
| GR 200-290 | 20 | 290 | 19.75 | 286 | 384 | 23.0 | 814 | 200 | 270 | 78 | 3547 | 7803 | 3877 | 8529 |

* Unit performance measured according to ISO 1217, Annex C, Edition 4

Reference conditions:

- Absolute inlet pressure 1 bar (14.5 psi)
- Intake air temperature 20°C, 68°F

FAD is measured at the following working pressures:

- 7.5 bar versions at 7 bar
- 8.5 bar versions at 8 bar
- 10 bar versions at 9.5 bar
- 13 bar versions at 12.5 bar
- 20 bar versions at 20 bar
- 100 psi variants at 100 psi
- 125 psi variants at 125 psi
- 150 psi variants at 150 psi
- 200 psi variants at 200 psi
- 290 psi variants at 290 psi

** Noise Level


measured according to Pneurop/Cagi PN8NTC2.2 test code; tolerance ±3 dB(A)

Integrated Dryer:

Pressure dewpoint of integrated refrigerant dryer at reference conditions: 3 to 4°C

Integrated Filter:

Partial removal down to 1 micron and maximum remaining oil aerosol of 0.1mg/m³



| Type | Dimensions | | | | | |
|----------------|------------|-------|------|------|------|------|
| | A | | B | | C | |
| | mm | inch | mm | inch | mm | inch |
| GA 200 - 315 | 3386 | 133.3 | 2120 | 83.4 | 2400 | 94.4 |
| GA 315 - 500A* | 5855 | 230.5 | 2120 | 83.4 | 2500 | 98.4 |
| GA 315 - 500W* | 4173 | 164.3 | 2120 | 83.4 | 2500 | 98.4 |
| GA 315 VSD | 4000 | 157.4 | 2120 | 83.4 | 2400 | 94.4 |
| GR 110-200 | 2779 | 109.4 | 1886 | 74.3 | 1990 | 78.3 |

* W = Water-cooled

A = Air-cooled

Oil-lubricated high-pressure reciprocating compressors, up to 450 bar (a) (6500 psia), 37-150 kW

B&D

Atlas Copco's B&D series of oil-lubricated reciprocating compressors meet your needs for high-pressure compressed air up to 450 bar(a). These flexible compressors offer capacities from 150 m³/min to 2000 m³/min on certain configurations. Compact, with very low vibration levels and a sealed crankcase, B&D compressors are the perfect solution for the compression of air, nitrogen, natural gas, processed biogas, hydrogen, noble gases and other industrial gases.

CUSTOMER BENEFITS

- **Safety** – A sealed crankcase ensures no emission of gases to the atmosphere, even gases with a low molecular weight.

- **High reliability** – The B&D piston technology offers field-proven ruggedness and reliability. Low compression ratios in the individual stages result in low thermal load for high reliability and high volumetric efficiency.

- **Easy installation** – Very compact, frame-mounted and incorporating anti-vibration pads, B&D compressors come as complete all-in packages. All designs are submitted as turnkey installations, virtually assuring the equipment is ready for operation soon after its arrival. This is a testament to their ease of installation.

- **A wide array of solutions** – B&D compressors are available for inlet pressures from 1 to 14 bar, and 1- to 5-stage configurations.

- **Low maintenance** – An advanced maintenance concept ensures short downtimes and long intervals between maintenance.

- **Compliance to ATEX**



| Technical specifications | Metric | Imperial |
|--------------------------|--|--|
| Capacity FAD | 12 - 142 l/s | 12 - 142 l/s |
| Working pressure | 17 - 500 bar(e) | 250 - 7250 psig |
| Installed motor power | 15 - 165 kW | 20 - 220 hp |
| Capacity | 42 - 510 Nm ³ /h | 25 - 300 scfm |
| Inlet pressure | 0.06 - 2 bar | 1 - 30 psi |
| Gases handled | air, nitrogen, helium, hydrogen, methane, biomethane | air, nitrogen, helium, hydrogen, methane, biomethane |

Oil-lubricated high pressure trunk-piston compressors, up to 351 bar(a) (5090 psia), 22-200 kW

CU/CT/CN

Atlas Copco's CU/CT/CN is a complete series of oil-lubricated reciprocating compressors to meet your needs for high pressures up to 351 bar(a). Compact, with very low vibration levels and a sealed crankcase, CU/CT/CN compressors are the perfect solution for the compression of air, nitrogen, natural gas, processed biogas, hydrogen, noble gases and other industrial gases.

CUSTOMER BENEFITS

- **High level of safety** – A pressure-tight sealed crankcase ensures no emission of gases to the atmosphere, even gases with a low molecular weight.
- **High reliability** – The CU/CT/CN trunk-piston technology offers field-proven ruggedness and reliability. Low compression ratios in the

individual stages result in low thermal load for high reliability and high volumetric efficiency.

- **Easy installation** – Very compact, frame-mounted and incorporating anti-vibration pads, CT/CU/CN compressors come as complete all-in packages that are simple to install without the need for foundations.
- **Low maintenance** – An advanced maintenance concept ensures short downtimes and long intervals between maintenance.
- **A wide array of solutions** – CU/CT compressors are available for inlet pressures from 1 to 19 bars, and up to 5-stage configurations. Discharge pressures are up to 350 bar for CU and for CT, while CN units are available for inlet pressures from atmosphere to 1.35 bar(a) for pressures up to 350 bar. They are suitable for diverse applications: CNG car/bus refueling stations, H₂ refueling systems, bottle filling, air-blast circuit breakers. A specific range of CU/CT compressors has been designed for seismic applications, for installation onboard ships, with closed loop freshwater/seawater cooling and marine adaptations.

- **Compliance to ATEX**



| Technical specifications | Metric | Imperial |
|--------------------------|---|---|
| Capacity FAD | 4.2 - 453 l/s | 4.2 - 453 l/s |
| Working pressure | 1 - 351 bar(e) | 14.5 - 5100 psig |
| Installed motor power | 22 - 200 kW | 40 - 275 hp |
| Capacity | 15 - 1500 Nm ³ /h | 8.8 - 942 scfm |
| Inlet pressure | 1 - 19 bar | 14.5 - 275.5 psi |
| Gases handled | air, nitrogen, carbon monoxide, carbon dioxide, helium, hydrogen, argon, nitrous oxide, methane, biomethane | air, nitrogen, carbon monoxide, carbon dioxide, helium, hydrogen, argon, nitrous oxide, methane, biomethane |

Oil-lubricated gas screw compressors, 17 bar(a) (247 psia)

GG

Atlas Copco's lubricated gas screw compressors meet your needs for methane and biomethane applications for pressures up to 17 bar(a) 247 psia. Single-stage, water-cooled and directly-driven, these compressors benefit from the latest technologies with exclusive bearing arrangements and variable speed drive. They comply with ATEX design requirements.

CUSTOMER BENEFITS

- **Efficient capacity control** – Variable Speed Drive can regulate the capacity of the compressor to keep inlet and outlet pressures constant, depending on the application.

- **High efficiency and consistent performance** – The GG's highly efficient rotor profile maximizes the flow and minimizes the horsepower. Direct drive through a flexible coupling means no gear losses or wasted energy.

- **Sturdy design** – A triplex bearing arrangement has an L-10 calculated life of 130,000 hours. Superior shaft seal design and unparalleled precision manufacturing combine to ensure durable quality year after year. This makes the SG gas compressor the optimal solution for gas applications.

- **Compact and easy to install** – This single stage compressor takes up minimal floor space. Frame-mounted, the GG gas compressor comes as a complete all-in package which can easily be integrated in your process.

- **Compliance to ATEX**



| Technical specifications | Metric | Imperial |
|--------------------------|----------------------|----------------------|
| Capacity FAD | 136 - 278 l/s | 136 - 278 l/s |
| Capacity FAD | 489 - 1000 m³/h | 70 - 2689 cfm |
| Working pressure | 6 - 16 bar(e) | 22.4 - 217 psig |
| Installed motor power | 90 - 132 kW | 50 - 670 hp |
| Inlet pressure up to | 1.4 bar(a) | 20.31 psia |
| Capacity | 450 - 920 Nm³/h | 69 - 2652 scfm |
| Gases handled | processed biomethane | processed biomethane |

Car and bus refueling stations

S100/S750

Atlas Copco's S100/S750 car and bus modular refueling stations are compact high-performance installations designed for the refueling of passenger cars, indoor and light-duty vehicles, buses, heavy-duty trucks, ferries and special vehicles with natural gas (CNG/NGV), biogas and H₂.

CUSTOMER BENEFITS

- **High level of safety** – A pressure-tight sealed crankcase ensures no emission of gases to the atmosphere, even gases with a low molecular weight.
- **Total solution** – With Atlas Copco you get total customer service, from a comprehensive study of the station layout to the delivery of the complete units

- **A wide array of solutions** – We provide fast-fill, low-fill or mother-daughter systems to meet your needs for standard to customized stations

- **Based on our high-performance compressors:**

- CU/CT series – Lubricated trunk-piston technology, air- or water-cooled, with sealed crankcase – gas-tight up to 19 bar(a) (260 psig) – for capacities up to 1600 Nm³/h (1000 scfm).

- DM series – Oil-free, hermetically sealed compressors – gas-tight up to 40 bar(a) (570 psig) – for capacities up to 210 Nm³/h (125 scfm).

- **Compact** – Available in concrete or sheet metal housing, their compact design is an asset on site

- **Modular** – Our standard stations are adapted to:

- Up to 250 cars, 50 trucks or 25 buses per day
- Up to 150 cars, 30 trucks or 15 buses per day
- Up to 450 cars, 90 trucks or 45 buses per day



| Technical specifications | Metric | Imperial |
|--------------------------|------------------------------|----------------------|
| Capacity FAD | 136 - 278 l/s | 136 - 278 l/s |
| Capacity FAD | 489 - 1000 m ³ /h | 70 - 2689 cfm |
| Working pressure | 6 - 16 bar(e) | 22.4 - 217 psig |
| Installed motor power | 90 - 132 kW | 50 - 670 hp |
| Inlet pressure up to | 1.4 bar(a) | 20.31 psia |
| Capacity | 450 - 920 Nm ³ /h | 69 - 2652 scfm |
| Gases handled | processed biomethane | processed biomethane |

OIL-FREE COMPRESSORS

Oil-free air is used in all kinds of industries where air quality is paramount for the end-product and the production process. These applications include food and beverage processing, chemical and petrochemical processing, electronics manufacturing, medical sector, automotive paint spraying, textile manufacturing and many more.

Atlas Copco oil-free compressors eliminate the risk of air contamination and reduce the operating cost of compressed air in your business.

Oil-free compressed air

Atlas Copco is the first manufacturer of oil-free compressors that have achieved a compressed air quality of Class 0 in accordance with DIN-ISO 8573-1 – certified by the TÜV. This is because the air never comes into contact with oil throughout the compression stages of the Z compressors from Atlas Copco. Therefore, it does not have to be laboriously filtered again with a high power input. There is also no residual risk of contaminating the product during its contact with the compressed air.



We can provide a suitable oil-free solution for any application, any volume flow and (almost) any working pressure; from 0.4 bar, for example, for aerating sewage plants, up to 40 bar for producing PET bottles.

Potential options include:

Our ZR/ZT compressors, for the most popular applications and pressures (up to 13 bar), are available with rotary technology for medium volume flows or with screw compression for improved performance. Air or water-cooled. They are available with speed regulation (VSD - Variable Speed Drive), if required, allowing you to save up 35% power on average, and the additional costs for the integrated frequency converter usually pay for themselves within one to two years. If you want, you can choose the Full Feature version (FF), which also has an integrated refrigerant or desiccant dryer.

Or our ZB Turbos and ZS blower for applications with low pressure (from 0.4 to 1.7 bar working pressure). If you want to use pneumatic feed, ventilate biological clarifiers, or clean filters in power plants, these machines are the perfect solution. With the ZS+ blowers you can lower your power consumption, in comparison to conventional, belt-driven rotary piston blowers, by up to 40%, and the ZB centrifugal compressors with speed regulation save as much as 60% power compared to normal full-load/idle machines. This is because the turbo impellers are a very special patented development from Atlas Copco – with extremely high efficiency.

Our ZH Turbos are hard to beat when it comes to efficiency. They are suitable for heavy industry, where an extremely high amount of air with working pressures between 3.5 and 10.4 bar is continually required; for example, a few thousand to tens of thousands cubic meters per hour.



Compact oil-free piston compressors, 0.5-1.5 kW / 0.7-2 hp LFx series

The LFx ensures highly energy-efficient compressed air generation thanks to the patented "Super-flow" compressed air inlet system.

- LFx 0.7-2.0 | Page 55



Water-injected screw compressors, 15-55 kW / 20-75 hp AQ 30-55 / 15-55 VSD

Atlas Copco's AQ water-injected screw compressors, available in water-cooled and air-cooled versions, meet your precise needs for pure, oil-free air while offering high-pressure capability and improved energy efficiency.

- AQ 30-55 / 15-55 VSD | Page 62



Industrial oil-free aluminum piston compressors, 1.5-7.5 kW / 2-10 hp LF series

Atlas Copco's LF oil-free aluminium piston air compressors stand for exceptional reliability and extremely low operating costs and are virtually maintenance-free.

- LF | Page 57



Oil-free rotary tooth compressors, 15-55 kW / 20-75 hp ZT 15-22, ZR/ZT 30-45, ZR/ZT 22-37-55 VSD

Atlas Copco's ZR/ZT oil-free rotary tooth compressors meet your needs for pure oil-free air while offering wide pressure ranges and improved energy efficiency.

- ZT 15-22 | Page 65
- ZR/ZT 30-45 | Page 67
- ZR/ZT 22-37-55 VSD | Page 67



Oil-free scroll compressors, 1.5-22 kW / 2-30 hp SF series

Atlas Copco's SF oil-free scroll compressors provide 100% oil-free for critical applications in industries such as R&D laboratories, hospitals, universities, dental applications, food & beverage.

- SF 1 – 22 | Page 59



Oil-free air- and water-cooled rotary screw compressors, 55-935 kW / 75-1253 hp Z 55-900 (VSD)

Atlas Copco's Z 55-900 VSD Pack and Full Feature ranges power your production with ultimate reliability and efficiency under the harshest conditions.

- ZR 55 – 90 FF | Page 67
- ZR 75 – 90 VSD FF | Page 71
- ZR 110 – 750 | Page 71
- ZR 132 – 900 VSD | Page 74
- ZT 110 – 275 | Page 77
- ZT 132 – 315 VSD | Page 77



Oil-free centrifugal compressors, 355-2750 kW, 475-3500 hp

ZH / ZH+

Designed to save energy and guarantee reliability, Atlas Copco's ZH oil-free centrifugal compressors are provided as complete ready-to-integrate packages including internal piping, integrated coolers, motor, lubrication, inlet guide vanes, control system and 100% matched components.

• ZH / ZH+ | Page 78



Oil-free high-speed drive centrifugal compressors, 350 kW, 470 hp

ZH 350+

Atlas Copco's ZH 350+ oil-free centrifugal compressors are designed to save you energy. Operating at high speed and high efficiency, they are directly driven by a permanent magnet synchronous motor.

• ZH 350+ | Page 81



Energy recovery control unit for water-cooled oil-free air compressors from 90 to 900 kW.

ER 90-900

Atlas Copco energy recovery control units transfer the energy recovered in the cooling water of oil-free air compressors to your process.

• ER 90-900 | Page 82

Compact oil-free piston compressors, 0.5-1.5 kW / 0.7-2 hp

LFx 0.7 - 2.0 series

Atlas Copco's range of small-capacity piston compressors provides you a reliable, oil-free solution for your low air demands. The LFx ensures highly energy-efficient compressed air generation thanks to the patented "Super-flow" compressed air inlet system.

The LFx compressor's capacities range from from 1.02 up to 2.53 l/s (2.16 up to 5.36 cfm), with an optional 1- or 3-phase supply and a maximum working pressure of 10 bar (145 psi).

CUSTOMER BENEFITS

- **Flexible installation** – The LFx's small and compact design offer maximum installation flexibility. The LFx is both suitable for stand-alone use and integration in your OEM (Original Equipment Manufacturer) product.
- **High reliability** – Thanks to a unique, robust design and the optimal combination of quality materials, LFx compressors offer improved performance and extended product life.
- **Certified 100% oil-free air** – LFx piston compressors provide 100% pure, clean air, complying with ISO 8573-1 CLASS 0 (2010) certification. CLASS 0 means zero risk of contamination; zero risk of damaged or unsafe products; zero risk of losses from operational downtime; and zero risk of damaging your company's hard-won professional reputation. In 2006, Atlas Copco was the first manufacturer in the world to receive such certification for an oil-free compressor.
- **Easy maintenance** – All components and service points are easily accessible and your LFx requires no oil changes.
- **Quiet operation** – The LFx is standard outfitted with a silencing hood. These compressors achieve noise levels as low as 62 dB(A), allowing installation close at the point of use.





| Variants | Type | Maximum dimensions | | Weight | | Noise level |
|-------------------------------|-------------|--------------------|---------------------|--------|-----|-------------|
| | | mm (W x D x H) | inch (W x D x H) | kg | lbs | dB(A) |
| Powerbox | LFx 0.7/1.0 | 520 x 340 x 490 | 20.5 x 13.4 x 19.3 | 25 | 55 | 62-63 |
| | LFx 1.5/2.0 | 520 x 340 x 490 | 20.5 x 13.4 x 19.3 | 29 | 63 | 63-64 |
| Trolley (receiver 20 l) | LFx 0.7/1.0 | 520 x 440 x 824 | 20.5 x 17.3 x 32.4 | 44 | 97 | 62-64 |
| | LFx 1.5/2.0 | 520 x 440 x 824 | 20.5 x 17.3 x 32.4 | 48 | 105 | 62-64 |
| Tank mounted (vessel 50 l) | LFx 0.7/1.0 | 828 x 355 x 891 | 32.6 x 14 x 35 | 49 | 108 | 65-67 |
| | LFx 1.5/2.0 | 828 x 355 x 891 | 32.6 x 14 x 35 | 53 | 117 | 65-67 |
| Tank mounted (vessel 90 l) | LFx 0.7/1.0 | 960 x 364 x 973 | 37.8 x 14.3 x 38.3 | 64 | 141 | 65-67 |
| | LFx 1.5/2.0 | 960 x 364 x 973 | 37.8 x 14.3 x 38.3 | 68 | 149 | 65-67 |

* Unit performance measured according to ISO 1217, Ed.3, Annex C-1996.

** Mean noise level measured according to ISO 2151/Pneurop/Cagi PN8NTC2 test code; tolerance 2 dB(A).

Reference conditions:


- Absolute inlet pressure 1 bar (14.5 psi)
- Intake air temperature 20°C, 68°F

FAD is measured at 7 bar.

| Type | Max. working pressure | | Capacity FAD | | | Installed power | |
|---------|-----------------------|------|--------------|--------|------|-----------------|-----|
| | bar | psig | l/s | m³/min | cfm | kW | hp |
| LFx 0.7 | 10 | 145 | 1.02 | 0.06 | 2.16 | 0.55 | 0.7 |
| LFx 1.0 | 10 | 145 | 1.38 | 0.08 | 2.92 | 0.75 | 1 |
| LFx 1.5 | 10 | 145 | 2.07 | 0.18 | 4.38 | 1.1 | 1.5 |
| LFx 2.0 | 10 | 145 | 2.53 | 0.12 | 5.36 | 1.5 | 2 |

| Type | Max. working pressure | | Capacity FAD | | | Installed power | |
|---------|-----------------------|------|--------------|--------|------|-----------------|-----|
| | bar | psig | l/s | m³/min | cfm | kW | hp |
| LFx 0.7 | 10 | 145 | 1.35 | 0.081 | 2.86 | 0.55 | 0.7 |
| LFx 1.0 | 10 | 145 | 1.46 | 0.087 | 3.09 | 0.75 | 1 |
| LFx 1.5 | 10 | 145 | 2.39 | 0.14 | 5.06 | 1.1 | 1.5 |

Dimensions standard versions:



Industrial oil-free aluminum piston compressors, 1.5-7.5 kW / 2-10 hp LF

Looking for a durable, high-performance compressed air solution for your specific industrial application? Atlas Copco's LF oil-free aluminium piston air compressors stand for exceptional reliability and extremely low operating costs and are virtually maintenance-free. LF compressors are 100% oil-free, so are ideal for your applications where oil cannot be tolerated. Incorporating state-of-the-art technology, LF compressors deliver the lowest operating temperatures in the industry while offering superb quality air. High-quality materials ensure reliable performance and extra long life. The LF range is suitable for stand-alone use or easy integration in your OEM product. Also where maintenance-free compressed air is required, LF units are the best solution.

CUSTOMER BENEFITS

- **High reliability** – Thanks to a unique, robust design and the optimal combination of quality materials, LF compressors offer improved performance and extended product life.
- **Certified 100% oil-free air** – LF compressors provide 100% pure, clean air, complying with ISO 8573-1 CLASS 0 (2010) certification. CLASS 0 means zero risk of contamination; zero risk of damaged or unsafe products; zero risk of losses from operational downtime; and zero risk of damaging your company's hard-won professional reputation. In 2006, Atlas Copco was the first manufacturer in the world to receive such certification for an oil-free compressor.
- **Easy maintenance** – All components and service points are easily accessible.
- **Low running costs** – Operational costs are limited over a long product lifetime.
- **Saving floor space** – The compressor block which is directly coupled to the motor is manufactured using lightweight materials and provides excellent cooling characteristics: ideal for integration with limited space requirements.





LF basic unit


LF Pack-Version
Base frame with acoustic hood

LF Trolley
mobile versions with either electric or gasoline engine

LF unit
tank mounted

| Type | Maximum working pressure* | | FAD at normal working pressure and 1,500 rpm (50 Hz) | | | FAD at normal working pressure and 1,800 rpm (60 Hz) | | | Installed recommended power | | Noise level dB(A)** | |
|-----------|---------------------------|------|--|--------|------|--|--------|------|-----------------------------|-----|---------------------|-----------------------------|
| | bar(e) | psig | l/s | m³/min | cfm | l/s | m³/min | cfm | kW | hp | Unsilenced | Base-mount- ed, silenced |
| 10 BAR LF | | | | | | | | | | | | |
| LF 2-10 | 10 | 145 | 3.1 | 0.19 | 6.6 | 3.6 | 0.22 | 7.6 | 1.5 | 2 | 82/84 | 67/69 |
| LF 3-10 | 10 | 145 | 4 | 0.24 | 8.5 | 4.6 | 0.28 | 9.7 | 2.2 | 3 | 83/85 | 68/70 |
| LF 5-10 | 10 | 145 | 8.2 | 0.49 | 17.4 | 9.1 | 0.55 | 19.3 | 4 | 5.5 | 83/85 | 68/70 |
| LF 7-10 | 10 | 145 | 11 | 0.66 | 23.3 | 12 | 0.72 | 25.4 | 5.5 | 7.5 | 84/86 | 72/74 |
| LF 10-10 | 10 | 145 | 15.5 | 0.93 | 32.8 | 18.2 | 1.1 | 38.9 | 7.5 | 10 | 86/88 | 74/76 |

* Unit performance measured according to ISO 1217, Ed. 3, Annex C-1996.

** Mean noise level measured at a distance of 1 m according to ISO 2151/Pneurop/Cagi PN8NTC2 test code; tolerance 3 dB(A).

Reference conditions:

- Absolute inlet pressure 1 bar (14.5 psi).
- Intake air and coolant temperature 20°C, 68°F.

Receiver size 10, 15 & 20 bar (218, 290 or 435 psi) versions:
90, 250 & 475 l (24, 66 & 125 US gallon)

FAD is measured at the following working pressures:

- 10 bar versions at 7 bar.
- 15 bar versions at 12 bar.
- 20 bar versions at 20 bar.
- 30 bar versions at 30 bar.

Standard voltages available:

50 Hz: 1 ph 230 V, 3 ph 230, 400, 500 V
60 Hz: 1 ph 230 V, 3 ph 230, 460, 380, 575 V

Oil-free scroll compressors, 1.5-22 kW / 2-30 hp

SF 1-22

Atlas Copco's SF oil-free scroll compressors provide 100% oil-free for critical applications in industries such as R&D laboratories, hospitals, universities, dental applications, food & beverage. These ISO 8573-1 CLASS 0 certified compressors are easy to operate and maintain, and have a minimal footprint to save space in your facility. SF compressors eliminate the risks of oil contamination while providing an efficient, reliable and highly cost-effective source of pure oil-free air.

- **Extremely quiet operation** – The slow speed of the scroll compression elements ensures that the SF scroll compressors are exceptionally quiet. SF units are WorkPlace Air System™ compressors, making them suitable for installation in any working environment.

- **Energy efficiency** – SF scroll compressors are ideal for applications where flexibility and energy efficiency are crucial. Unloaded power consumption is eliminated thanks to the simple start/stop control. The SF 6-22 uses Variable Flow Technology to match the compressed air output to the air demand.

- **Low maintenance** – SF scroll compressors stand for simplicity and reliability. The scroll design has a minimal number of moving parts, ensuring a long operating life with a minimum number of service interventions.

CUSTOMER BENEFITS

- **Certified 100% oil-free air** – SF compressors provide 100% pure, clean air, complying with ISO 8573-1 CLASS 0 (2010) certification. CLASS 0 means zero risk of contamination; zero risk of damaged or unsafe products; zero risk of losses from operational downtime; and zero risk of damaging your company's hard-won professional reputation. In 2006, Atlas Copco was the first manufacturer in the world to receive such certification for an oil-free compressor.

- **Advanced control and monitoring** – To maximize efficiency and reliability on multi-module SFs, the Elektronikon® controls the main drive motor and regulates system pressure within a predefined and narrow pressure band. The Elektronikon® controller can be adapted to your specific needs with extra sensors, digital contacts, fieldbus, Internet and SMS communication functions. In combination with the ES multiple compressor controller, the operation of your complete compressor room is optimized.

Special design / options the SF series



SF 4 Twin-Version (T)
receiver mounted with two SF units and adsorption dryers



SF 4 Standard
receiver mounted with
acoustic enclosure

SF 4 Skid version on base
frame with acoustic enclosure



SF 4 full-feature version
(FF) with an integrated
membrane dryer and
soundproof canopy.
Receiver mounted.



SF Multicore 6-22 FF

oil-free scroll compressors



SF 15 FF



SF Multicore – flexibility through modular design

The Scroll Multicore concept further enhances the performance of the Scroll technology. Two to four compressor modules (PM version) are integrated into one unit and offer all the advantages of a modular system. For dry compressed air, a refrigerant dryer can be integrated as well as 2–4 compressor modules (PM/FF versions).



SF 8 FF



The specially designed software makes optimal use of the additional advantages which result from the Multicore concept: sequential operation, stage-less volume flow regulation for low power consumption – while the individual modules are controlled by software like a single SF aggregate.

| Type | Max. working pressure | | Capacity FAD* | | | Installed motor power | | Noise level** | Dimensions L x W x H | | Weight | |
|--|-----------------------|------|---------------|--------|------|-----------------------|----|---------------|--|--|--------|------|
| | bar(e) | psig | l/s | m³/min | cfm | kW | hp | dB(A) | mm | inch | kg | lbs |
| Skid versions | | | | | | | | | | | | |
| SF 1 | 8 | 116 | 2.7 | 0.16 | 5.7 | 1.5 | 2 | 65 | 800 x 600 x 540 (Receiver mounted) 1267 x 600 x 1154 | 31.5 x 23.6 x 21.3 (Receiver mounted) 49.9 x 23.6 x 45.4 | 105 | 232 |
| | 10 | 145 | 2.1 | 0.13 | 4.4 | 1.5 | 2 | 65 | | | 105 | 232 |
| SF 2 | 8 | 116 | 4.0 | 0.24 | 8.5 | 2.2 | 3 | 67 | | | 110 | 243 |
| | 10 | 145 | 3.4 | 0.20 | 7.2 | 2.2 | 3 | 67 | | | 110 | 243 |
| SF 4 | 8 | 116 | 6.6 | 0.40 | 14.0 | 3.7 | 5 | 68 | | | 120 | 265 |
| | 10 | 145 | 5.60 | 0.30 | 11.9 | 3.7 | 5 | 68 | | | 120 | 265 |
| Skid versions – duplex tank mounted | | | | | | | | | | | | |
| SF 6T | 8 | 116 | 10.6 | 0.64 | 22.5 | 5.9 | 8 | 72 | 2043 x 600 x 1154 | 80.4 x 23.6 x 45.4 | 365 | 805 |
| | 10 | 145 | 9.0 | 0.54 | 19.1 | 5.9 | 8 | 72 | | | 365 | 805 |
| SF 8T | 8 | 116 | 13.2 | 0.80 | 28.0 | 7.4 | 10 | 73 | | | 375 | 827 |
| | 10 | 145 | 11.2 | 0.67 | 23.7 | 7.4 | 10 | 73 | | | 375 | 827 |
| Fully silenced – WorkPlace air system™ | | | | | | | | | | | | |
| SF 1 | 8 | 116 | 2.7 | 0.16 | 5.7 | 1.5 | 2 | 53 | 590 x 600 x 850 | 23.2 x 23.6 x 33.5 | 97 | 214 |
| | 10 | 145 | 2.1 | 0.13 | 4.4 | 1.5 | 2 | 53 | | | 97 | 214 |
| SF 2 | 8 | 116 | 4.0 | 0.24 | 8.5 | 2.2 | 3 | 55 | | | 97 | 214 |
| | 10 | 145 | 3.4 | 0.20 | 7.2 | 2.2 | 3 | 55 | | | 97 | 214 |
| SF 4 | 8 | 116 | 6.6 | 0.40 | 14.0 | 3.7 | 5 | 57 | 1450 x 750 x 1040 | 57.1 x 29.5 x 40.9 | 102 | 225 |
| | 10 | 145 | 5.6 | 0.34 | 11.9 | 3.7 | 5 | 57 | | | 102 | 225 |
| SF 6 | 8 | 116 | 10.4 | 0.62 | 22.0 | 5.9 | 8 | 63 | | | 340 | 750 |
| | 10 | 145 | 8.8 | 0.53 | 18.6 | 5.9 | 8 | 63 | | | 340 | 750 |
| SF 8 | 8 | 116 | 13.4 | 0.80 | 28.4 | 7.4 | 10 | 63 | 1450 x 750 x 1844 | 57.1 x 29.5 x 72.6 | 345 | 761 |
| | 10 | 145 | 11.3 | 0.68 | 23.9 | 7.4 | 10 | 63 | | | 345 | 761 |
| SF 11 | 8 | 116 | 20.2 | 1.21 | 42.8 | 11 | 15 | 63 | | | 480 | 1058 |
| | 10 | 145 | 17.0 | 1.00 | 36.0 | 11 | 15 | 63 | | | 480 | 1058 |
| SF 15 | 8 | 116 | 26.4 | 1.58 | 55.0 | 15 | 20 | 63 | 1630 x 750 x 1850 | 64 x 29.4 x 72.7 | 560 | 1235 |
| | 10 | 145 | 22.8 | 1.37 | 48.3 | 15 | 20 | 63 | | | 560 | 1235 |
| SF 17 M | 8 | 116 | 30.6 | 1.8 | 64.7 | 17 | 23 | 64 | | | 572 | 1258 |
| SF 22 M | 8 | 116 | 40.6 | 2.4 | 85.6 | 22 | 30 | 65 | | | 662 | 1456 |
| SF 11 VZV | 8 | 116 | 9.7 | 0.6 | 20.5 | 5.5 | 7 | 63 | | | 503 | 1107 |
| SF 15 DM | 8 | 116 | 13.2 | 0.8 | 27.9 | 7.5 | 10 | 63 | | | 564 | 1241 |
| SF 22 DM | 8 | 116 | 19.5 | 1.2 | 41.1 | 11 | 15 | 65 | | | 683 | 1503 |

* Unit performance measured according to ISO 1217, Annex C, latest edition.

** Noise level measured at a distance of 1m according to Pneurop/Cagi PN8NTC2 test code.

Reference conditions:

- absolute inlet pressure 1 bar (14.5 psig)
- intake air temperature 20°C (68°F)

Water-injected screw compressors, 15-55 kW / 20-75 hp

AQ 30-55 / 15-55 VSD

Atlas Copco's AQ water-injected screw compressors, available in water-cooled and air-cooled versions, meet your precise needs for pure, oil-free air while offering high-pressure capability and improved energy efficiency. Developed especially for applications demanding the highest levels of purity, such as pharmaceutical production, food processing and critical electronics, AQ compressors eliminate the risks of oil contamination as well as the resulting extra costs. They ensure consistent 100% oil-free air while you benefit from lower operating and maintenance costs with an ISO 8573-1 CLASS 0 (2010) certified compressor.

- Load/no load transition losses are eliminated.
- Precise pressure control allows a tighter pressure band and a lower average working pressure, resulting in reduced energy consumption.

• **Certified 100% oil-free air**— AQ compressors provide 100% pure, clean air, complying with ISO 8573-1 CLASS 0 (2010) certification. CLASS 0 means zero risk of contamination; zero risk of damaged or unsafe products; zero risk of losses from operational downtime; and zero risk of damaging your company's hard-won professional reputation. In 2006, Atlas Copco was the first manufacturer in the world to receive such certification for an oil-free compressor.

• **Quiet operation**— AQ compressors are supplied in a sound-insulated canopy, thus avoiding the need for a separate compressor room and allowing installation in most working environments.

• **Advanced control and monitoring** — To maximize efficiency and reliability, the Elektronikon® controls the main drive motor and regulates system pressure within a predefined and narrow pressure band. The Elektronikon® controller can be adapted to your specific needs with extra sensors, digital contacts, fieldbus, Internet and SMS communication functions. In combination with the ES multiple compressor controller, the operation of your complete compressor room is optimized.

CUSTOMER BENEFITS

• **High efficiency** — Thanks to the superior cooling capability of water which ensures that the heat is removed efficiently at the source, more air per kW of power is generated. Energy savings of 35% on average are possible with the Variable Speed Drive versions:



AQ 55 VSD FF

PROVEN TECHNOLOGY



At the heart of the AQ series is a unique screw element with water-injection for a highly efficient, almost isothermal compression. The polymer ceramic rotors with an optimized rotor profile are guided by water-lubricated bearings; this ensures that the compressor element is not contaminated with oil, in order to produce oil-free air.

Rotors

A highly efficient compression process is achieved thanks to the polymer ceramic rotors with an optimized profile. The combination of corrosion-free, highly-efficient raw materials and the smooth water lubrication results in a much longer service life.

Element housing

The strength and long service life are achieved by using an element casing

made of aluminum bronze, which eliminates the risk of corrosion inside the housing.

Element bearings

Using hydrodynamic bearings ensures a long service life, because there are no friction points in the bearing; it just glides on a water film and does not need any oil or lubrication.

AQ 30-55, 50Hz version

| Type | Max. working pressure (bar(e)/psig) | | | Capacity FAD ^(*) | | | Installed motor power | | Noise level ^(**) | Weight (kg/lbs) | |
|--------------|--|--------------|-------------|-----------------------------|-----|-------|-----------------------|------|-----------------------------|--------------------|-------------|
| | Pack | Full feature | l/s | m³/min | cfm | kW | hp | Pack | | Full feature | |
| AIR-COOLED | | | | | | | | | | | |
| AQ 30 | 7.5 | 7.5 / 109 | 7.25 / 105 | 84.9 | 5.1 | 180.1 | 30 | 40 | 68 | 1226 / 2703 | 1320 / 2910 |
| | 10 | 10 / 145 | 9.75 / 141 | 68.3 | 4.1 | 144.8 | 30 | 40 | 68 | 1226 / 2703 | 1320 / 2910 |
| | 13 | 13 / 189 | 12.75 / 185 | 53 | 3.2 | 113 | 30 | 40 | 68 | 1226 / 2703 | 1320 / 2910 |
| AQ 37 | 7.5 | 7.5 / 109 | 7.25 / 105 | 102 | 6.1 | 215.4 | 37 | 50 | 69 | 1298 / 2862 | 1395 / 3075 |
| | 10 | 10 / 145 | 9.75 / 141 | 86.4 | 5.2 | 183.6 | 37 | 50 | 69 | 1298 / 2862 | 1395 / 3075 |
| | 13 | 13 / 189 | 12.75 / 185 | 69.2 | 4.2 | 148.3 | 37 | 50 | 69 | 1298 / 2862 | 1395 / 3075 |
| AQ 45 | 7.5 | 7.5 / 109 | 7.25 / 105 | 121.4 | 7.3 | 257.8 | 45 | 60 | 71 | 1321 / 2912 | 1416 / 3122 |
| | 10 | 10 / 145 | 9.75 / 141 | 98.1 | 5.9 | 208.4 | 45 | 60 | 71 | 1321 / 2912 | 1416 / 3122 |
| | 13 | 13 / 189 | 12.75 / 185 | 82.2 | 4.9 | 173 | 45 | 60 | 71 | 1321 / 2912 | 1416 / 3122 |
| AQ 55 | 7.5 | 7.5 / 109 | 7.25 / 105 | 139.1 | 8.4 | 296.6 | 55 | 75 | 72 | 1378 / 3038 | 1497 / 3300 |
| | 10 | 10 / 145 | 9.75 / 141 | 118.1 | 7.1 | 250.7 | 55 | 75 | 72 | 1378 / 3038 | 1497 / 3300 |
| | 13 | 13 / 189 | 12.75 / 185 | 98.4 | 5.9 | 208.4 | 55 | 75 | 72 | 1378 / 3038 | 1497 / 3300 |
| WATER-COOLED | | | | | | | | | | | |
| AQ 30 | 7.5 | 7.5 / 109 | 7.25 / 105 | 88.5 | 5.3 | 187.5 | 30 | 40 | 65 | 1121 / 2471 | 1215 / 2679 |
| | 10 | 10 / 145 | 9.75 / 141 | 71.2 | 4.3 | 151.8 | 30 | 40 | 65 | 1121 / 2471 | 1215 / 2679 |
| | 13 | 13 / 189 | 12.75 / 185 | 55 | 3.3 | 116.5 | 30 | 40 | 65 | 1121 / 2471 | 1215 / 2679 |
| AQ 37 | 7.5 | 7.5 / 109 | 7.25 / 105 | 107.1 | 6.4 | 226.9 | 37 | 50 | 66 | 1193 / 2630 | 1290 / 2844 |
| | 10 | 10 / 145 | 9.75 / 141 | 91.2 | 5.5 | 194.2 | 37 | 50 | 66 | 1193 / 2630 | 1290 / 2844 |
| | 13 | 13 / 189 | 12.75 / 185 | 72.9 | 4.4 | 155.4 | 37 | 50 | 66 | 1193 / 2630 | 1290 / 2844 |
| AQ 45 | 7.5 | 7.5 / 109 | 7.25 / 105 | 128.5 | 7.7 | 272.3 | 45 | 60 | 67 | 1216 / 2681 | 1313 / 2895 |
| | 10 | 10 / 145 | 9.75 / 141 | 108 | 6.5 | 230 | 45 | 60 | 67 | 1216 / 2681 | 1313 / 2895 |
| | 13 | 13 / 189 | 12.75 / 185 | 89.9 | 5.4 | 190.7 | 45 | 60 | 67 | 1216 / 2681 | 1313 / 2895 |
| AQ 55 | 7.5 | 7.5 / 109 | 7.25 / 105 | 152.7 | 9.2 | 323.6 | 55 | 75 | 68 | 1273 / 2806 | 1392 / 3069 |
| | 10 | 10 / 145 | 9.75 / 141 | 131.2 | 7.9 | 279 | 55 | 75 | 68 | 1273 / 2806 | 1392 / 3069 |
| | 13 | 13 / 189 | 12.75 / 185 | 109 | 6.5 | 230 | 55 | 75 | 68 | 1273 / 2806 | 1392 / 3069 |

(*) Unit performance measured according to ISO1217 Annex C, latest edition.

Reference conditions:

- Absolute inlet pressure 1 bar (14.5 psi)
- Intake air temperature 20°C (68°F)

(**) Noise level measured at a distance of 1m according to Pneurop/Cagi PN8NTC2 test code: 3dB(l)

FAD is measured at the following working pressure:

- 7 bar versions at 7.5 bar(e)

AQ 37-55 VSD

H: 1840 mm, 72"
W: 965 mm, 40"
L: 2435 mm, 96"



AQ 30-55 Hz, 60Hz version

| Type | Max. working pressure (bar(e)/psig) | | Capacity FAD ⁽¹⁾ | | | Installed motor power | | Noise level | Weight (kg/lbs) | |
|--------------|--|--------------|-----------------------------|---------------------|-----|-----------------------|----|-------------|--------------------|--------------|
| | - | Full feature | l/s | m ³ /min | cfm | kW | hp | dB(A) | Pack | Full feature |
| AIR-COOLED | | | | | | | | | | |
| AQ 30 | 7.4 | 7.4 / 107 | 7.15 / 104 | 87.8 | 5.3 | 187.2 | 30 | 40 | 68 | 1226 / 2703 |
| | 9.1 | 9.1 / 132 | 8.85 / 128 | 78.7 | 4.7 | 166.1 | 30 | 40 | 68 | 1226 / 2703 |
| | 10.8 | 10.8 / 157 | 10.55 / 153 | 67.5 | 4.1 | 144.8 | 30 | 40 | 68 | 1226 / 2703 |
| | 12.5 | 12.5 / 181 | 12.25 / 178 | 59.2 | 3.6 | 127.1 | 30 | 40 | 68 | 1226 / 2703 |
| AQ 37 | 7.4 | 7.4 / 107 | 7.15 / 104 | 105.5 | 6.3 | 222.5 | 37 | 50 | 69 | 1298 / 2862 |
| | 9.1 | 9.1 / 132 | 8.85 / 128 | 87.7 | 5.3 | 187.2 | 37 | 50 | 69 | 1298 / 2862 |
| | 10.8 | 10.8 / 157 | 10.55 / 153 | 83 | 5 | 176.6 | 37 | 50 | 69 | 1298 / 2862 |
| | 12.5 | 12.5 / 181 | 12.25 / 178 | 76.1 | 4.6 | 162.4 | 37 | 50 | 69 | 1298 / 2862 |
| AQ 45 | 7.4 | 7.4 / 107 | 7.15 / 104 | 122.4 | 7.3 | 257.8 | 45 | 60 | 71 | 1321 / 2912 |
| | 9.1 | 9.1 / 132 | 8.85 / 128 | 103 | 6.2 | 219.1 | 45 | 60 | 71 | 1321 / 2912 |
| | 10.8 | 10.8 / 157 | 10.55 / 153 | 96 | 5.8 | 204.8 | 45 | 60 | 71 | 1321 / 2912 |
| | 12.5 | 12.5 / 181 | 12.25 / 178 | 88.7 | 5.3 | 187.2 | 45 | 60 | 71 | 1321 / 2912 |
| AQ 55 | 7.4 | 7.4 / 107 | 7.15 / 104 | 146.8 | 8.8 | 310.8 | 55 | 75 | 72 | 1378 / 3038 |
| | 9.1 | 9.1 / 132 | 8.85 / 128 | 118.2 | 7.1 | 250.7 | 55 | 75 | 72 | 1378 / 3038 |
| | 10.8 | 10.8 / 157 | 10.55 / 153 | 119.6 | 7.2 | 254.3 | 55 | 75 | 72 | 1378 / 3038 |
| | 12.5 | 12.5 | 12.25 | 106 | 6.4 | 226 | 55 | 75 | 72 | 1378 / 3038 |
| WATER-COOLED | | | | | | | | | | |
| AQ 30 | 7.4 | 7.4 / 107 | 7.15 / 104 | 91.8 | 5.5 | 194.2 | 30 | 40 | 65 | 1121 / 2471 |
| | 9.1 | 9.1 / 132 | 8.85 / 128 | 82.7 | 5 | 176.6 | 30 | 40 | 65 | 1121 / 2471 |
| | 10.8 | 10.8 / 157 | 10.55 / 153 | 70.4 | 4.2 | 148.3 | 30 | 40 | 65 | 1121 / 2471 |
| | 12.5 | 12.5 / 181 | 12.25 / 178 | 61.7 | 3.7 | 130.7 | 30 | 40 | 65 | 1121 / 2471 |
| AQ 37 | 7.4 | 7.4 / 107 | 7.15 / 104 | 111.3 | 6.7 | 236.6 | 37 | 50 | 66 | 1193 / 2630 |
| | 9.1 | 9.1 / 132 | 8.85 / 128 | 93 | 5.6 | 197.8 | 37 | 50 | 66 | 1193 / 2630 |
| | 10.8 | 10.8 / 157 | 10.55 / 153 | 87.5 | 5.3 | 187.2 | 37 | 50 | 66 | 1193 / 2630 |
| | 12.5 | 12.5 / 181 | 12.25 / 178 | 80.7 | 4.8 | 169.5 | 37 | 50 | 66 | 1193 / 2630 |
| AQ 45 | 7.4 | 7.4 / 107 | 7.15 / 104 | 134 | 8 | 282.5 | 45 | 60 | 67 | 1216 / 2681 |
| | 9.1 | 9.1 / 132 | 8.85 / 128 | 115.2 | 6.9 | 243.7 | 45 | 60 | 67 | 1216 / 2681 |
| | 10.8 | 10.8 / 157 | 10.55 / 153 | 104.2 | 6.3 | 222.5 | 45 | 60 | 67 | 1216 / 2681 |
| | 12.5 | 12.5 / 181 | 12.25 / 178 | 97.8 | 5.9 | 208.4 | 45 | 60 | 67 | 1216 / 2681 |
| AQ 55 | 7.4 | 7.4 / 107 | 7.15 / 104 | 161.7 | 9.7 | 342.6 | 55 | 75 | 68 | 1273 / 2806 |
| | 9.1 | 9.1 / 132 | 8.85 / 128 | 132.7 | 8 | 282.5 | 55 | 75 | 68 | 1273 / 2806 |
| | 10.8 | 10.8 / 157 | 10.55 / 153 | 131.5 | 7.9 | 279.1 | 55 | 75 | 68 | 1273 / 2806 |
| | 12.5 | 12.5 | 12.25 | 118.7 | 7.1 | 250.7 | 55 | 75 | 68 | 1273 / 2806 |

AQ 37-55 VSD

| Type | Max. working pressure pressure ⁽¹⁾ | | Capacity FAD ⁽²⁾ | | | Installed motor power | | Noise level ⁽³⁾ | Weight (kg/lbs) | |
|-----------------|--|------|-----------------------------|---------------------|--------------|-----------------------|----|----------------------------|--------------------|--------------|
| | bar(e) | psig | l/s | m ³ /min | cfm | kW | hp | dB(A) | Pack | Full Feature |
| AIR-COOLED | | | | | | | | | | |
| AQ 37 VSD 13(1) | 13 | 175 | 42.0 – 104.0 | 2.5 – 6.2 | 89.0 – 220.4 | 37 | 50 | 69 | 1195 / 2635 | 1306 / 2879 |
| AQ 55 VSD 13(1) | 13 | 175 | 42.3 – 154.9 | 2.5 – 9.3 | 89.6 – 328.2 | 55 | 75 | 72 | 1195 / 2635 | 1314 / 2897 |
| WATER-COOLED | | | | | | | | | | |
| AQ 37 VSD 13(1) | 13 | 175 | 42.0 – 108.0 | 2.5 – 6.2 | 89.0 – 228.8 | 37 | 50 | 66 | 1090 / 2403 | 1201 / 2648 |
| AQ 55 VSD 13(1) | 13 | 175 | 41.9 – 160.9 | 2.5 – 9.3 | 88.8 – 340.9 | 55 | 75 | 69 | 1090 / 2403 | 1209 / 2665 |

(1) Full-Feature units max. working pressure 12.5 bar(e)/181 psig.

(2) Stated performance according ISO1217 ed 04 Annex E, measured at 7 bar.

(3) Mean sound level according to ISO2151, tolerance 3 dB(A).

Oil-free rotary tooth compressors, 15-55 kW / 20-75 hp

ZT 15-22, ZR/ZT 30-45, ZR/ZT 22-37-55 VSD

Atlas Copco's ZR/ZT oil-free rotary tooth compressors meet your needs for pure oil-free air while offering wide pressure ranges and improved energy efficiency. Developed especially for applications demanding the highest levels of purity, such as pharma-ceutical production, food processing and critical electronics, ZR/ZT compressors eliminate the risks of oil contamination as well as the resulting extra costs. These ISO 8573-1 CLASS 0 certified compressors are easy to operate and are available with Variable Speed Drive for further energy savings.

CUSTOMER BENEFITS

• **Certified 100% oil-free air** – ZR/ZT compressors provide 100% pure, clean air, complying with ISO 8573-1 CLASS 0 (2010) certification. CLASS 0 means zero risk of contamination; zero risk of damaged or unsafe products; zero risk of losses from operational downtime; and zero risk of damaging your company's hard-won professional reputation. In 2006, Atlas Copco was the first manufacturer in the world to receive such certification for an oil-free compressor.

• **VSD for direct energy savings** – Energy savings of 35% on average are possible with the Variable Speed Drive versions:

- Unload losses are reduced to a minimum.
- No blow-off of compressed air to the atmosphere.
- Load/no load transition losses are eliminated.
- Precise pressure control allows a tighter pressure band and a lower average working pressure, resulting in reduced energy consumption.

• **Quiet operation** – The vertical layout of the coolers reduces the noise levels from the fan, motor and element. Moreover, ZR/ZT compressors are supplied in a sound-insulated canopy, thus avoiding the need for a separate compressor room and allowing installation in most working environments.

• **Advanced control and monitoring** – To maximize efficiency and reliability, the Elektronikon® controls the main drive motor and regulates system pressure within a predefined and narrow pressure band. The Elektronikon® controller can be adapted to your specific needs with extra sensors, digital contacts, fieldbus, Internet and SMS communication functions. In combination with the ES multiple compressor controller, the operation of your complete compressor room is optimized.

• **Easy maintenance** – The robust air inlet filter offers a long lifetime and high reliability for long service intervals and low maintenance needs.



| Type | Max. working pressure | | Capacity FAD* | | | Installed motor power | | Noise level** | Weight without dryer*** | | Integrated dryer available |
|---------------------------------|-----------------------|------|---------------|---------|------------|-----------------------|----|---------------|-------------------------|------|----------------------------|
| | bar(e) | psig | l/s | m³/min | cfm | kW | hp | dB(A) | kg | lbs | |
| Air-cooled only | | | | | | | | | | | |
| ZT 15 | 7.5 | 109 | 37.6 | 2.3 | 80 | 15 | 20 | 65 | 1060 | 2337 | ID |
| | 8.6 | 125 | 34.9 | 2.1 | 74 | | | | | | |
| | 10 | 145 | 29.9 | 1.8 | 63 | | | | | | |
| ZT 18 | 7.5 | 109 | 48.0 | 2.9 | 102 | 18 | 25 | 67 | 1080 | 2381 | ID/IMD |
| | 8.6 | 125 | 45.7 | 2.7 | 97 | | | | | | |
| | 10 | 145 | 37.2 | 2.2 | 79 | | | | | | |
| ZT 22 | 7.5 | 109 | 59.0 | 3.5 | 125 | 22 | 30 | 69 | 1086 | 2394 | ID/IMD |
| | 8.6 | 125 | 53.2 | 3.2 | 113 | | | | | | |
| | 10 | 145 | 45.0 | 2.7 | 95 | | | | | | |
| Air- (ZT) and water-cooled (ZR) | | | | | | | | | | | |
| ZR/ZT 30 | 7.5 | 109 | 78.7 | 4.7 | 167 | 30 | 40 | 63 | 1432 | 3157 | ID/IMD |
| | 8.6 | 125 | 73.7 | 4.4 | 156 | | | | | | |
| ZR/ZT 37 | 7.5 | 109 | 96.5 | 5.8 | 204 | 37 | 50 | 65 | 1432 | 3157 | ID/IMD |
| | 8.6 | 125 | 92.1 | 5.5 | 195 | | | | | | |
| ZR/ZT 45 | 7.5 | 109 | 114.4 | 6.9 | 243 | 45 | 60 | 67 | 1432 | 3157 | ID/IMD |
| | 8.6 | 125 | 108.9 | 6.5 | 231 | | | | | | |
| ZT 22 VSD | 7.5 | 109 | 20.6-55.3 | 1.3-3.4 | 43.8-117.6 | 22 | 30 | 69 | 1120 | 2469 | ID |
| | 8.6 | 125 | 20.1-51.0 | 1.2-3.1 | 42.7-108.5 | | | | | | |
| | 10 | 145 | 19.7-47.0 | 1.2-2.8 | 41.9-100 | | | | | | |
| ZR/ZT 37 VSD | 7.5 | 109 | 41.3-101.2 | 2.5-6.2 | 87.8-215.2 | 37 | 50 | 68 | 1432 | 3157 | ID/IMD |
| | 8.6 | 125 | 41.2-97.3 | 2.5-5.9 | 87.6-206.9 | | | | | | |
| ZR/ZT 55 VSD | 7.5 | 109 | 41.3-142.5 | 2.5-8.7 | 87.6-303.1 | 55 | 75 | 68 | 1432 | 3157 | ID/IMD |
| | 8.6 | 125 | 41.2-138.8 | 2.5-8.4 | 87.6-295.2 | | | | | | |

* Unit performance measured according to ISO 1217, Ed 3, Annex C-1996

Reference conditions:

- absolute inlet pressure 1 bar (14.5 psi)

- intake air temperature 20°C (68°F)


** Noise level measured according to Pneurop/Cagi PN8NTC2, tolerance: 3 dB(A).

*** Integrated dryers will increase the weight.

**** For ZT air-cooled units: +3 dB(A).

FAD is measured at the following working pressure:

- 7.5 bar versions at 7 bar.
- 8.6 bar versions at 8 bar.
- 10 bar versions at 9.75 bar.



| | Dimensions (mm/inch) | | |
|-----------------|----------------------|--------------|--------------|
| | Length | Width | Height |
| ZT 15-22 | 1760 / 69.3" | 1026 / 40.4" | 1621 / 63.8" |
| ZR/ZT 30-45 | 2005 / 78.9" | 1026 / 40.4" | 1880 / 74.0" |
| ZT 22 VSD | 2195 / 86.4" | 1026 / 40.4" | 1621 / 63.8" |
| ZR/ZT 37-55 VSD | 2440 / 96.1" | 1026 / 40.4" | 1880 / 74.0" |

Oil-free air- and water-cooled rotary screw compressors, 55-935 kW / 75-1253 hp

Z 55-900 (VSD)

Atlas Copco's Z 55-900 VSD Pack and Full Feature ranges power your production with ultimate reliability and efficiency under the harshest conditions. The first air compressors in the world to be certified Class 0 according to ISO 8573-1 edition 2, 2010, they ensure completely oil-free air to protect your process and end products. Several energy saving features – Variable Speed Drive, energy-free MD dryers and energy recovery – are offered. Z 55-900 VSD compressors are all-inclusive, plug-and-play packages that ensure easy and low cost installation and a quick start-up.

CUSTOMER BENEFITS

• **Highest reliability** – For over 50 years, Z compressors stand for durability and reliability. They incorporate Atlas Copco's proven screw technology, stainless steel coolers, AGMA A4/DIN 5 gears and state-of-the-art electrical drive systems, all of which contribute to overall high reliability. Z compressors are built using long-standing internal engineering practices, and are manufactured and tested according to ISO 9001.

• **Certified 100% oil-free** – Z 55-900 compressors provide you with 100% pure, clean air that complies with ISO 8573-1 CLASS 0 (2010) certification. CLASS 0 means zero risk of contamination; zero risk of damaged or unsafe products; zero risk of losses from operational downtime; and zero risk of damaging your company's hard-won professional reputation. In 2006 Atlas Copco was the first manufacturer in the world to receive such certification on an oil-free compressor.

• **Maximum energy savings** – Atlas Copco's unique and time proven rotor coating ensures high efficiency over the compressors lifetime. The state-of-the-art air compressor element is powered by a high-efficiency electric motor, contributing to maximum compressor package efficiency. Further optimize your energy savings with our innovative and unique Variable Speed Drive, our energy recovery feature and energy-free MD dryers.

• **Easy installation** – The integrated design of the Z compressor includes internal piping, coolers, motor, lubrication and control system: all supplied as a ready-to-use package. Installation is fault-free, commissioning time is low and no external instrument air is required.

• **Advanced control and monitoring** – To maximize efficiency and reliability, the Elektronikon® controls the main drive motor and regulates system pressure within a predefined and narrow pressure band. The Elektronikon® controller can be adapted to your specific needs with extra sensors, digital contacts, fieldbus, Internet and SMS communication functions. In combination with the ES multiple compressor controller, the operation of your complete compressor room is optimized.




Technical Data

True performance:

Atlas Copco Z-compressors are measured according to ISO 1217, Edition 3, Annex C stipulating the FAD (Free Air Delivery) measurement at the outlet of the package, net of all losses.

Atlas Copco specifications correspond to the capacity and pressure that are effectively available to the user, not to the air volume that is sucked in. Differences can be substantial.



Dimensions & weight

| | A | B | C | Weight |
|-----------|------|------|------|--------|
| ZR 55 | 2180 | 1450 | 2184 | 1640 |
| ZR 75 | 2180 | 1450 | 2184 | 1715 |
| ZR 90 | 2180 | 1450 | 2184 | 1780 |
| ZR 75 VSD | 2630 | 1450 | 2184 | 2030 |
| ZR 90 VSD | 2630 | 1450 | 2184 | 2030 |
| ZT 55 | 2180 | 1450 | 2184 | 1760 |
| ZT 75 | 2180 | 1450 | 2184 | 1835 |
| ZT 90 | 2180 | 1450 | 2184 | 1900 |
| ZT 75 VSD | 2630 | 1450 | 2184 | 2100 |
| ZT 90 VSD | 2630 | 1450 | 2184 | 2100 |

| | A | B | C | Weight |
|--------------|------|------|------|--------|
| ZR 55 FF | 2180 | 1450 | 2184 | 1890 |
| ZR 75 FF | 2180 | 1450 | 2184 | 1965 |
| ZR 90 FF | 2180 | 1450 | 2184 | 2030 |
| ZR 75 VSD-FF | 2630 | 1450 | 2184 | 2280 |
| ZR 90 VSD-FF | 2630 | 1450 | 2184 | 2280 |
| ZT 55 FF | 2880 | 1450 | 2184 | 2360 |
| ZT 75 FF | 2880 | 1450 | 2184 | 2475 |
| ZT 90 FF | 2880 | 1450 | 2184 | 2500 |
| ZT 75 VSD-FF | 3330 | 1450 | 2184 | 2700 |
| ZT 90 VSD-FF | 3330 | 1450 | 2184 | 2700 |

| | A | B | C | Weight |
|----------------|------|------|------|--------|
| ZR 55 * | 2180 | 1450 | 2184 | 1640 |
| ZR 75 * | 2180 | 1450 | 2184 | 1715 |
| ZR 90 * | 2180 | 1450 | 2184 | 1780 |
| ZR 75 VSD * | 2630 | 1450 | 2184 | 2030 |
| ZR 90 VSD * | 2630 | 1450 | 2184 | 2030 |
| ZR 55 FF * | 2880 | 1450 | 2184 | 1990 |
| ZR 75 FF * | 2880 | 1450 | 2184 | 2065 |
| ZR 90 FF * | 2880 | 1450 | 2184 | 2130 |
| ZR 75 VSD-FF * | 3330 | 1450 | 2184 | 2370 |
| ZR 90 VSD-FF * | 3330 | 1450 | 2184 | 2370 |

- (1) Reference conditions:
- dry air
 - absolute inlet pressure 1 bar(a)
 - cooling and air intake temperature 20 °C
 - nominal working pressure
 - performance of the compressor package measured according to ISO 1217, Third Edition, Annex C

* Equipped with Energy Recovery system

- (2) Cooling water temperature rise of 15 °C

- (3) Max. capacity is at reference pressure and not at max. pressure

- (4) Pressure dewpoint is specified for
- 20 °C cooling air/water temperature
 - relative humidity of 60 %
 - nominal working pressure
 - load level of minimum 50 %
 - For VSD: at reference speed

- (5) ± 3 dB(A) measured at a distance of 1 m and according to ISO 2151:2004 and using ISO 9614-2

- (6) Maximum intake / cooling air temperature is 50 °C for HAT versions

- Conversions
- 1 kg = 2.2 lbs
 - 1 mm = 0.039 inch
 - °F = °C x 9/5 + 32



ZR 55-90 FF compressors

| ZR/ZR FF Watercooled oil-free compressors | Free air delivery ⁽¹⁾ | | | Installed motor power | | Cooling water consumption ⁽²⁾ | | Pressure dewpoint ⁽⁴⁾ | Sound pressure level ⁽⁵⁾ |
|--|----------------------------------|--------|-----|--------------------------|-----|---|-------|-------------------------------------|---|
| | | | | | | ZR | ZR-FF | ZR-FF | |
| Type | l/s | m³/min | cfm | kW | hp | l/s | l/s | °C | dB(A) |
| 50 Hz units | | | | | | | | | |
| ZR 55 - 7.5 | 143 | 8.6 | 303 | 55 | 75 | 0.9 | 1.3 | -24 | 65 |
| ZR 55 - 8.6 | 131 | 7.9 | 278 | 55 | 75 | 0.9 | 1.3 | -24 | 65 |
| ZR 55 - 10 | 121 | 7.3 | 257 | 55 | 75 | 0.9 | 1.3 | -25 | 65 |
| 60 Hz units | | | | | | | | | |
| ZR 55 - 7.25 | 155 | 9.3 | 329 | 55 | 75 | 1 | 1.4 | -24 | 65 |
| ZR 55 - 9 | 138 | 8.3 | 293 | 55 | 75 | 1 | 1.4 | -25 | 65 |
| ZR 55 - 10.4 | 128 | 7.7 | 271 | 55 | 75 | 1 | 1.4 | -25 | 65 |
| 50 Hz units | | | | | | | | | |
| ZR 75 - 7.5 | 194 | 11.6 | 411 | 75 | 100 | 1.2 | 1.8 | -26 | 65 |
| ZR 75 - 8.6 | 184 | 11.0 | 390 | 75 | 100 | 1.2 | 1.8 | -26 | 65 |
| ZR 75 - 10 | 174 | 10.4 | 369 | 75 | 100 | 1.2 | 1.8 | -27 | 65 |
| 60 Hz units | | | | | | | | | |
| ZR 75 - 7.25 | 213 | 12.8 | 452 | 75 | 100 | 1.3 | 1.9 | -26 | 65 |
| ZR 75 - 9 | 194 | 11.6 | 411 | 75 | 100 | 1.3 | 1.9 | -27 | 65 |
| ZR 75 - 10.4 | 185 | 11.1 | 392 | 75 | 100 | 1.3 | 1.9 | -27 | 65 |
| 50 Hz units | | | | | | | | | |
| ZR 90 - 7.5 | 234 | 14.0 | 496 | 90 | 120 | 1.4 | 2.1 | -27 | 65 |
| ZR 90 - 8.6 | 220 | 13.2 | 466 | 90 | 120 | 1.4 | 2.1 | -28 | 65 |
| ZR 90 - 10 | 209 | 12.5 | 443 | 90 | 120 | 1.4 | 2.1 | -28 | 65 |
| 60 Hz units | | | | | | | | | |
| ZR 90 - 7.25 | 262 | 15.7 | 555 | 90 | 120 | 1.6 | 2.3 | -26 | 65 |
| ZR 90 - 9 | 235 | 14.1 | 498 | 90 | 120 | 1.6 | 2.3 | -28 | 65 |
| ZR 90 - 10.4 | 224 | 13.4 | 475 | 90 | 120 | 1.6 | 2.3 | -29 | 65 |

ZR 75-90 VSD-FF compressors

| ZR VSD / ZR VSD-FF Watercooled oil-free compressors | Free air delivery ⁽¹⁾ | | | Cooling water consumption ⁽²⁾ | | Pressure dewpoint ⁽⁴⁾ | Sound pressure level ⁽⁵⁾ |
|---|----------------------------------|--------|-----|---|-------|-------------------------------------|---|
| | | | | ZR | ZR-FF | ZR-FF | |
| Types – 50/60 Hz | l/s | m³/min | cfm | l/s | l/s | °C | dB(A) |
| ZR 75 VSD-9 bar (e) | | | | 1.25 | 1.92 | -30 | 65 |
| Max ⁽³⁾ | 220 | 13.2 | 466 | | | | |
| Min | 75 | 4.5 | 159 | | | | |
| ZR 75 VSD-10.4 bar (e) | | | | 1.25 | 1.92 | -30 | 65 |
| Max ⁽³⁾ | 198 | 11.9 | 420 | | | | |
| Min | 98 | 5.9 | 208 | | | | |
| ZR 90 VSD-9 bar (e) | | | | 1.25 | 1.92 | -30 | 65 |
| Max ⁽³⁾ | 258 | 15.5 | 547 | | | | |
| Min | 75 | 4.5 | 159 | | | | |
| ZR 90 VSD-10.4 bar (e) | | | | 1.25 | 1.92 | -30 | 65 |
| Max ⁽³⁾ | 232 | 13.9 | 492 | | | | |
| Min | 98 | 5.9 | 208 | | | | |

- (1) Reference conditions:
- dry air
 - absolute inlet pressure 1 bar(a)
 - cooling and air intake temperature 20 °C
 - nominal working pressure
 - performance of the compressor package measured according to ISO 1217, Third Edition, Annex C

- (2) Cooling water temperature rise of 15 °C

- (3) Max. capacity is at reference pressure and not at max. pressure

- (4) Pressure dewpoint is specified for
- 20 °C cooling air/water temperature
 - relative humidity of 60 %

- nominal working pressure
- load level of minimum 50 %
- For VSD: at reference speed

- (5) ± 3 dB(A) measured at a distance of 1 m and according to ISO 2151:2004 and using ISO 9614-2

- (6) Maximum intake / cooling air temperature is 50 °C for HAT versions
- Conversions
- 1 kg = 2.2 lbs
 - 1 mm = 0.039 inch
 - °F = °C x 9/5 + 32

ZR 55-90 FF compressors

| ZT/ZT FF Aircooled oil-free compressors | Free air delivery ⁽¹⁾ | | | Installed motor power | | Installed fan motor | | Pressure dewpoint ⁽⁴⁾ | Sound pressure level ⁽⁵⁾ |
|--|----------------------------------|--------|-----|--------------------------|-----|------------------------|-------|-------------------------------------|---|
| | | | | | | ZT | ZT-FF | ZT-FF | |
| Type | l/s | m³/min | cfm | kW | hp | kW | kW | °C | dB(A) |
| 50 Hz | | | | | | | | | |
| ZT 55 - 7.5 | 142 | 8.5 | 301 | 55 | 75 | 2 | 3.1 | -28 | 72 |
| ZT 55 - 8.6 | 130 | 7.8 | 276 | 55 | 75 | 2 | 3.1 | -28 | 72 |
| ZT 55 - 8.6 HAT ⁽⁶⁾ | 120 | 7.2 | 254 | 55 | 75 | 2 | - | - | 72 |
| ZT 55 - 10 | 120 | 7.2 | 254 | 55 | 75 | 2 | 3.1 | -28 | 72 |
| 60 Hz | | | | | | | | | |
| ZT 55 - 7.25 | 154 | 9.2 | 326 | 55 | 75 | 2 | 3.6 | -28 | 72 |
| ZT 55 - 8.6 HAT ⁽⁶⁾ | 127 | 7.6 | 269 | 55 | 75 | 2 | - | - | 72 |
| ZT 55 - 9 | 137 | 8.2 | 290 | 55 | 75 | 2 | 3.6 | -28 | 72 |
| ZT 55 - 10.4 | 127 | 7.6 | 269 | 55 | 75 | 2 | 3.6 | -29 | 72 |
| 50 Hz | | | | | | | | | |
| ZT 75 - 7.5 | 193 | 11.6 | 409 | 75 | 100 | 3.6 | 4.7 | -30 | 72 |
| ZT 75 - 8.6 | 184 | 11.0 | 390 | 75 | 100 | 3.6 | 4.7 | -30 | 72 |
| ZT 75 - 8.6 HAT ⁽⁶⁾ | 174 | 10.4 | 369 | 75 | 100 | 3.6 | - | - | 72 |
| ZT 75 - 10 | 174 | 10.4 | 369 | 75 | 100 | 3.6 | 4.7 | -31 | 72 |
| 60 Hz units | | | | | | | | | |
| ZT 75 - 7.25 | 212 | 12.7 | 449 | 75 | 100 | 3.8 | 5.6 | -30 | 72 |
| ZT 75 - 8.6 HAT ⁽⁶⁾ | 184 | 11.1 | 390 | 75 | 100 | 3.8 | - | - | 72 |
| ZT 75 - 9 | 194 | 11.6 | 411 | 75 | 100 | 3.8 | 5.6 | -31 | 72 |
| ZT 75 - 10.4 | 184 | 11.0 | 390 | 75 | 100 | 3.8 | 5.6 | -31 | 72 |
| 50 Hz units | | | | | | | | | |
| ZT 90 - 7.5 | 233 | 14.0 | 494 | 90 | 120 | 3.6 | 4.7 | -31 | 72 |
| ZT 90 - 8.6 | 220 | 13.2 | 466 | 90 | 120 | 3.6 | 4.7 | -32 | 72 |
| ZT 90 - 8.6 HAT ⁽⁶⁾ | 208 | 12.5 | 441 | 90 | 120 | 3.6 | - | - | 72 |
| ZT 90 - 10 | 208 | 12.5 | 441 | 90 | 120 | 3.6 | 4.7 | -32 | 72 |
| 60 Hz units | | | | | | | | | |
| ZT 90 - 7.25 | 261 | 15.7 | 553 | 90 | 120 | 3.8 | 5.6 | -32 | 72 |
| ZT 90 - 8.6 HAT ⁽⁶⁾ | 222 | 13.3 | 470 | 90 | 120 | 3.8 | - | - | 72 |
| ZT 90 - 9 | 236 | 14.2 | 500 | 90 | 120 | 3.8 | 5.6 | -32 | 72 |
| ZT 90 - 10.4 | 222 | 13.3 | 471 | 90 | 120 | 3.8 | 5.6 | -33 | 72 |

ZT 75-90 VSD-FF compressors

| ZT VSD / ZT VSD-FF Aircooled oil-free compressors | Free air delivery ⁽¹⁾ | | | Pressure dewpoint ⁽⁴⁾ | Sound pressure level ⁽⁵⁾ |
|---|----------------------------------|--------|-----|-------------------------------------|--|
| | | | | ZT-FF | |
| Types – 50/60 Hz | l/s | m³/min | cfm | °C | dB(A) |
| ZT 75 VSD-9 bar (e) | | | | -30 | 72 |
| Max ⁽³⁾ | 220 | 13.2 | 466 | | |
| Min | 75 | 4.5 | 159 | | |
| ZT 75 VSD-10.4 bar (e) | | | | -30 | 72 |
| Max ⁽³⁾ | 198 | 11.9 | 420 | | |
| Min | 98 | 5.9 | 208 | | |
| ZT 90 VSD-9 bar (e) | | | | -30 | 72 |
| Max ⁽³⁾ | 258 | 15.5 | 547 | | |
| Min | 75 | 4.5 | 159 | | |
| ZT 90 VSD-10.4 bar (e) | | | | -30 | 72 |
| Max ⁽³⁾ | 232 | 13.9 | 492 | | |
| Min | 98 | 5.9 | 208 | | |

(1) Reference conditions:
 - dry air
 - absolute inlet pressure 1 bar(a)
 - cooling and air intake temperature 20 °C
 - nominal working pressure
 - performance of the compressor package
 measured according to ISO 1217, Third Edition,
 Annex C

(2) Cooling water temperature rise of 15 °C

(3) Max. capacity is at reference pressure and not at max. pressure

(4) Pressure dewpoint is specified for
 - 20 °C cooling air/water temperature
 - relative humidity of 60 %
 - nominal working pressure
 - load level of minimum 50 %
 For VSD: at reference speed

(5) ± 3 dB(A) measured at a distance of 1 m and
 according to ISO 2151:2004 and using ISO 9614-2

(6) Maximum intake / cooling air temperature is 50 °C for
 HAT versions
 Conversions
 - 1 kg = 2.2 lbs
 - 1 mm = 0.039 inch
 - °F = °C x 9/5 + 32

ZR 110-750 and ZR 132-900 VSD compressors - 50 Hz

| | ZR watercooled | Free air delivery ⁽¹⁾ | | | Installed motor power | Cooling water consumption ⁽²⁾ | Pressure dewpoint ⁽³⁾ | Sound pressure level ⁽⁴⁾ | | Weight | Dimensions | | |
|----------------------|--------------------|----------------------------------|--------|------|-----------------------|--|----------------------------------|-------------------------------------|-----------------|--------|------------|------|------|
| | Type | l/s | m³/min | cfm | kW | l/s | °C | w/o duct dB(A) | with duct dB(A) | kg | A mm | B mm | C mm |
| | 50 Hz - 7.5 bar(e) | | | | | | | | | | | | |
| FF (with IMD Dryer) | ZR 110 | 318 | 19.1 | 674 | 110 | 3.5 | -28 | 70 | 68 | 3265 | 3440 | 2000 | 1650 |
| | ZR 132 | 367 | 22.0 | 778 | 132 | 4.1 | -29 | 70 | 68 | 3390 | 3440 | 2000 | 1650 |
| | ZR 145 | 394 | 23.6 | 835 | 145 | 4.2 | -30 | 70 | 68 | 3530 | 3440 | 2000 | 1650 |
| | ZR 160 | 471 | 28.3 | 998 | 160 | 4.4 | -25 | 67 | 66 | 4705 | 4340 | 2000 | 1650 |
| | ZR 200 | 607 | 36.4 | 1286 | 200 | 5.1 | -25 | 67 | 66 | 5365 | 4340 | 2000 | 1650 |
| | ZR 250 | 726 | 43.6 | 1538 | 250 | 5.8 | -28 | 67 | 66 | 5360 | 4340 | 2000 | 1650 |
| | ZR 275 | 780 | 46.8 | 1653 | 275 | 6.2 | -30 | 67 | 66 | 5560 | 4340 | 2000 | 1650 |
| Pack (w/o IMD Dryer) | ZR 110 | 318 | 19.1 | 674 | 110 | 1.7 | - | 67 | 65 | 2635 | 2540 | 2000 | 1650 |
| | ZR 132 | 367 | 22.0 | 778 | 132 | 1.9 | - | 67 | 65 | 2760 | 2540 | 2000 | 1650 |
| | ZR 145 | 394 | 23.6 | 835 | 145 | 2.0 | - | 67 | 66 | 2900 | 2540 | 2000 | 1650 |
| | ZR 160 | 471 | 28.3 | 998 | 160 | 2.3 | - | 67 | 66 | 3795 | 3140 | 2000 | 1650 |
| | ZR 200 | 607 | 36.4 | 1286 | 200 | 3.0 | - | 67 | 66 | 3995 | 3140 | 2000 | 1650 |
| | ZR 250 | 726 | 43.6 | 1538 | 250 | 3.7 | - | 67 | 66 | 3990 | 3140 | 2000 | 1650 |
| | ZR 275 | 780 | 46.8 | 1653 | 275 | 4.1 | - | 67 | 66 | 4190 | 3140 | 2000 | 1650 |
| | ZR 300 | 775 | 46.5 | 1642 | 315 | 4.0 | - | 70 | 69 | 6650 | 3700 | 2400 | 2120 |
| | ZR 315 | 855 | 51.3 | 1812 | 315 | 4.4 | - | 71 | 69 | 6650 | 3700 | 2400 | 2120 |
| | ZR 355 | 949 | 56.9 | 2011 | 355 | 4.8 | - | 71 | 69 | 6950 | 3700 | 2400 | 2120 |
| | ZR 400 | 1049 | 62.9 | 2223 | 400 | 5.4 | - | 71 | 70 | 7050 | 3700 | 2400 | 2120 |
| | ZR 425 | 1162 | 69.7 | 2462 | 450 | 6.2 | - | 72 | 70 | 7250 | 3700 | 2400 | 2120 |
| | ZR 450 | 1257 | 75.4 | 2663 | 450 | 7.2 | - | 73 | 71 | 9500 | 4060 | 2400 | 2120 |
| | ZR 500 | 1387 | 83.2 | 2939 | 500 | 7.8 | - | 73 | 71 | 9500 | 4060 | 2400 | 2120 |
| | ZR 630 | 1726 | 103.6 | 3657 | 630 | 9.4 | - | 75 | 73 | 10225 | 4060 | 2400 | 2120 |
| | ZR 750 | 2075 | 124.5 | 4397 | 750 | 11.3 | - | 75 | 73 | 10325 | 4060 | 2400 | 2120 |

(1) Reference conditions:
 - dry air
 - absolute inlet pressure 1 bar(a)
 - cooling and air intake temperature 20 °C
 - nominal working pressure
 - performance of the compressor package measured according to ISO 1217, Third Edition, Annex C

(2) Cooling water temperature rise of 15 °C

(3) Max. capacity is at reference pressure and not at max. pressure

(4) Pressure dewpoint is specified for
 - 20 °C cooling air/water temperature
 - relative humidity of 60 %
 - nominal working pressure
 - load level of minimum 50 %
 For VSD: at reference speed

(5) ± 3 dB(A) measured at a distance of 1 m and according to ISO 2151:2004 and using ISO 9614-2

(6) Maximum intake / cooling air temperature is 50 °C for HAT versions
 Conversions
 - 1 kg = 2.2 lbs
 - 1 mm = 0.039 inch
 - °F = °C x 9/5 + 32

ZR 110-750 and ZR 132-900 VSD compressors - 50 Hz

| | ZR watercooled | Free air delivery ⁽¹⁾ | | | Installed motor power | Cooling water consump- tion ⁽²⁾ | Pressure dewpoint ⁽³⁾ | Sound pressure level ⁽⁴⁾ | | Weight | Dimensions | | |
|----------------------|--------------------|----------------------------------|--------|------|-----------------------------|---|--|--|--------------------|--------|------------|---------|---------|
| | Type | l/s | m³/min | cfm | kW | l/s | °C | w/o duct dB(A) | with duct dB(A) | kg | A mm | B mm | C mm |
| | 50 Hz - 8.6 bar(e) | | | | | | | | | | | | |
| FF (with IMD Dryer) | ZR 110 | 285 | 17.1 | 604 | 110 | 3.1 | -28 | 70 | 68 | 3265 | 3440 | 2000 | 1650 |
| | ZR 132 | 326 | 19.6 | 691 | 132 | 3.5 | -29 | 70 | 68 | 3390 | 3440 | 2000 | 1650 |
| | ZR 132 VSD | 372 | 22.3 | 778 | 132 | 3.9 | -28/-32 | 68-72 | 66-69 | 3500 | 3440 | 2000 | 1650 |
| | ZR 145 | 362 | 21.7 | 767 | 145 | 3.9 | -30 | 70 | 68 | 3530 | 3440 | 2000 | 1650 |
| | ZR 160 | 435 | 26.1 | 922 | 160 | 4.2 | -25 | 67 | 66 | 4705 | 4340 | 2000 | 1650 |
| | ZR 160 VSD | 431 | 25.9 | 913 | 160 | 4.2 | -28/-32 | 68-74 | 66-71 | 3500 | 3440 | 2000 | 1650 |
| | ZR 200 | 553 | 33.2 | 1172 | 200 | 4.8 | -25 | 67 | 66 | 5365 | 4340 | 2000 | 1650 |
| | ZR 250 | 691 | 41.5 | 1464 | 250 | 5.6 | -28 | 67 | 66 | 5360 | 4340 | 2000 | 1650 |
| | ZR 250 VSD | 721 | 43.3 | 1528 | 250 | 5.8 | -25/-30 | 63-73 | 62-71 | 6080 | 4340 | 2000 | 1650 |
| | ZR 275 | 723 | 43.4 | 1532 | 275 | 5.8 | -30 | 67 | 66 | 5560 | 4340 | 2000 | 1650 |
| Pack (w/o IMD Dryer) | ZR 315 VSD | 836 | 50.2 | 1771 | 299 | 6.8 | -25/-30 | 63-73 | 62-71 | 6080 | 4340 | 2000 | 1650 |
| | ZR 110 | 285 | 17.1 | 604 | 110 | 1.5 | - | 67 | 65 | 2635 | 2540 | 2000 | 1650 |
| | ZR 132 | 326 | 19.6 | 691 | 132 | 1.7 | - | 67 | 65 | 2760 | 2540 | 2000 | 1650 |
| | ZR 132 VSD | 376 | 22.6 | 797 | 132 | 1.9 | - | 62-68 | 61-66 | 2870 | 2540 | 2000 | 1650 |
| | ZR 145 | 362 | 21.7 | 767 | 145 | 1.9 | - | 67 | 66 | 2900 | 2540 | 2000 | 1650 |
| | ZR 160 | 435 | 26.1 | 922 | 160 | 2.2 | - | 67 | 66 | 3795 | 3140 | 2000 | 1650 |
| | ZR 160 VSD | 436 | 26.1 | 922 | 160 | 2.2 | - | 62-70 | 61-66 | 2870 | 2540 | 2000 | 1650 |
| | ZR 200 | 553 | 33.2 | 1172 | 200 | 2.8 | - | 67 | 66 | 3995 | 3140 | 2000 | 1650 |
| | ZR 250 | 691 | 41.5 | 1464 | 250 | 3.5 | - | 67 | 66 | 3990 | 3140 | 2000 | 1650 |
| | ZR 250 VSD | 721 | 43.3 | 1528 | 250 | 3.7 | - | 63-73 | 62-71 | 4710 | 3140 | 2000 | 1650 |
| | ZR 275 | 723 | 43.4 | 1532 | 275 | 3.8 | - | 67 | 66 | 4190 | 3140 | 2000 | 1650 |
| | ZR 300 | 723 | 43.4 | 1532 | 315 | 4.1 | - | 71 | 70 | 6650 | 3700 | 2400 | 2120 |
| | ZR 315 | 798 | 47.9 | 1691 | 315 | 4.5 | - | 72 | 70 | 6650 | 3700 | 2400 | 2120 |
| | ZR 315 VSD | 836 | 50.2 | 1771 | 299 | 4.3 | - | 63-73 | 62-71 | 4710 | 3140 | 2000 | 1650 |
| | ZR 355 | 886 | 53.2 | 1877 | 355 | 4.9 | - | 72 | 72 | 6950 | 3700 | 2400 | 2120 |
| | ZR 400 | 978 | 58.7 | 2072 | 400 | 5.4 | - | 72 | 71 | 7050 | 3700 | 2400 | 2120 |
| | ZR 400 VSD | 1114 | 66.9 | 2361 | 425 | 6.4 | - | 68-75 | 66-73 | 8350 | 4060 | 2470 | 2120 |
| | ZR 425 | 1081 | 64.9 | 2291 | 450 | 6.2 | - | 73 | 71 | 7250 | 3700 | 2400 | 2120 |
| | ZR 450 | 1166 | 70.0 | 2471 | 450 | 7.1 | - | 74 | 72 | 9500 | 4060 | 2400 | 2120 |
| | ZR 500 | 1291 | 77.5 | 2735 | 500 | 7.7 | - | 74 | 72 | 9500 | 4060 | 2400 | 2120 |
| | ZR 500 VSD | 1318 | 79.1 | 2793 | 525 | 7.6 | - | 68-76 | 66-74 | 8350 | 4060 | 2470 | 2120 |
| FF (with IMD Dryer) | ZR 630 | 1602 | 96.1 | 3394 | 630 | 9.3 | - | 76 | 74 | 10225 | 4060 | 2400 | 2120 |
| | ZR 700 VSD | 2063 | 123.8 | 4371 | 700 | 11.6 | - | 70-78 | 68-76 | 11850 | 4675 | 2470 | 2120 |
| | ZR 750 | 1850 | 111.0 | 3920 | 750 | 10.7 | - | 76 | 74 | 10325 | 4060 | 2400 | 2120 |
| | ZR 900 VSD | 2456 | 147.4 | 5204 | 935 | 13.2 | - | 68-78 | 68-76 | 11850 | 4675 | 2470 | 2120 |
| | 50 Hz - 10 bar(e) | | | | | | | | | | | | |
| | ZR 110 | 265 | 15.9 | 562 | 110 | 3.3 | -28 | 70 | 68 | 3265 | 3440 | 2000 | 1650 |
| | ZR 132 | 313 | 18.8 | 663 | 132 | 3.8 | -29 | 70 | 68 | 3390 | 3440 | 2000 | 1650 |
| | ZR 132 VSD | 330 | 19.8 | 699 | 132 | 4.1 | 0.875 | 68-72 | 66-69 | 3500 | 3440 | 2000 | 1650 |
| | ZR 145 | 334 | 20.0 | 708 | 145 | 4.1 | -30 | 70 | 68 | 3530 | 3440 | 2000 | 1650 |
| | ZR 160 | 402 | 24.1 | 852 | 160 | 4.3 | -25 | 67 | 66 | 4705 | 4340 | 2000 | 1650 |
| Pack (w/o IMD Dryer) | ZR 160 VSD | 392 | 23.5 | 831 | 160 | 4.4 | 0.875 | 68-74 | 66-71 | 3500 | 3440 | 2000 | 1650 |
| | ZR 200 | 504 | 30.2 | 1068 | 200 | 4.9 | -25 | 67 | 66 | 4905 | 4340 | 2000 | 1650 |
| | ZR 250 | 629 | 37.7 | 1333 | 250 | 5.6 | -28 | 67 | 66 | 5360 | 4340 | 2000 | 1650 |
| | ZR 250 VSD | 648 | 38.9 | 1373 | 250 | 5.8 | -25/-30 | 67-73 | 65-71 | 6080 | 4340 | 2000 | 1650 |
| | ZR 275 | 689 | 41.3 | 1460 | 275 | 6.0 | -30 | 67 | 66 | 5560 | 4340 | 2000 | 1650 |
| | ZR 315 VSD | 746 | 44.8 | 1581 | 299 | 6.7 | -25/-30 | 67-73 | 65-71 | 6080 | 4340 | 2000 | 1650 |
| | ZR 110 | 265 | 15.9 | 562 | 110 | 1.6 | - | 67 | 65 | 2380 | 2540 | 2000 | 1650 |
| | ZR 132 | 313 | 18.8 | 663 | 132 | 1.8 | - | 67 | 65 | 2440 | 2540 | 2000 | 1650 |
| | ZR 132 VSD | 333 | 20.0 | 706 | 132 | 1.9 | - | 62-68 | 61-66 | 2590 | 2540 | 2000 | 1650 |
| | ZR 145 | 334 | 20.0 | 708 | 145 | 1.9 | - | 67 | 66 | 2580 | 2540 | 2000 | 1650 |
| | ZR 160 | 402 | 24.1 | 852 | 160 | 2.3 | - | 67 | 66 | 3795 | 3140 | 2000 | 1650 |
| | ZR 160 VSD | 394 | 23.6 | 835 | 160 | 2.1 | - | 62-70 | 61-66 | 2590 | 2540 | 2000 | 1650 |
| | ZR 200 | 504 | 30.2 | 1068 | 200 | 2.9 | - | 67 | 66 | 3995 | 3140 | 2000 | 1650 |
| | ZR 250 | 629 | 37.7 | 1333 | 250 | 3.6 | - | 67 | 66 | 3990 | 3140 | 2000 | 1650 |
| | ZR 250 VSD | 648 | 38.9 | 1373 | 250 | 3.7 | - | 64-70 | 65-68 | 4710 | 3140 | 2000 | 1650 |
| | ZR 275 | 689 | 41.3 | 1460 | 275 | 4.0 | - | 67 | 66 | 4190 | 3140 | 2000 | 1650 |
| | ZR 300 | 689 | 41.3 | 1460 | 315 | 4.2 | - | 71 | 70 | 6650 | 3700 | 2400 | 2120 |
| | ZR 315 | 765 | 45.9 | 1621 | 315 | 4.5 | - | 72 | 70 | 6650 | 3700 | 2400 | 2120 |
| | ZR 315 VSD | 746 | 44.8 | 1581 | 299 | 4.3 | - | 63-73 | 62-71 | 4710 | 3140 | 2000 | 1650 |
| | ZR 355 | 846 | 50.8 | 1793 | 355 | 4.9 | - | 73 | 71 | 6950 | 3700 | 2400 | 2120 |
| | ZR 400 | 939 | 56.3 | 1990 | 400 | 5.4 | - | 73 | 71 | 7050 | 3700 | 2400 | 2120 |
| FF (with IMD) | ZR 400 VSD | 979 | 58.7 | 2074 | 425 | 5.7 | - | 69-76 | 66-73 | 8350 | 4060 | 2470 | 2120 |
| | ZR 450 | 1047 | 62.8 | 2218 | 450 | 7.1 | - | 74 | 72 | 9500 | 4060 | 2400 | 2120 |
| | ZR 500 | 1199 | 71.9 | 2541 | 500 | 7.9 | - | 74 | 72 | 9500 | 4060 | 2400 | 2120 |
| | ZR 500 VSD | 1150 | 69.0 | 2437 | 525 | 7.6 | - | 69-77 | 66-74 | 8350 | 4060 | 2470 | 2120 |
| | ZR 630 | 1474 | 88.4 | 3123 | 630 | 9.3 | - | 76 | 74 | 10225 | 4060 | 2400 | 2120 |
| | ZR 700 VSD | 1859 | 111.5 | 3939 | 700 | 11.4 | - | 70-78 | 68-76 | 11850 | 4675 | 2470 | 2120 |
| | ZR 750 | 1704 | 102.2 | 3611 | 750 | 10.5 | - | 76 | 74 | 10325 | 4060 | 2400 | 2120 |
| | ZR 900 VSD | 2057 | 123.4 | 4359 | 935 | 12.5 | - | 68-79 | 68-77 | 11850 | 4675 | 2470 | 2120 |
| | 50 Hz - 13 bar(e) | | | | | | | | | | | | |
| | ZR 145 | 297 | 17.8 | 629 | 145 | 4.2 | -30 | 75 | 72 | 3530 | 3440 | 2000 | 1650 |
| Pack (w/o IMD) | ZR 250 | 505 | 30.3 | 1070 | 250 | 5.4 | -28 | 72 | 70 | 5360 | 4340 | 2000 | 1650 |
| | ZR 275 | 550 | 33.0 | 1165 | 275 | 5.7 | -30 | 72 | 70 | 5560 | 4340 | 2000 | 1650 |
| | ZR 145 | 297 | 17.8 | 629 | 145 | 2.0 | - | 75 | 72 | 2900 | 2540 | 2000 | 1650 |
| | ZR 250 | 505 | 30.3 | 1070 | 250 | 3.4 | - | 72 | 70 | 3990 | 3140 | 2000 | 1650 |
| Pack (w/o IMD) | ZR 275 | 551 | 33.1 | 1168 | 275 | 3.7 | - | 72 | 70 | 4190 | 3140 | 2000 | 1650 |

ZR 110-750 and ZR 132-900 VSD compressors - 60 Hz

| | ZR watercooled | Free air delivery ⁽¹⁾ | | | Installed motor power | Cooling water consumption ⁽²⁾ | Pressure dewpoint ⁽³⁾ | Sound pressure level ⁽⁴⁾ | | Weight | Dimensions | | |
|----------------------|----------------|----------------------------------|--------|------|-----------------------|--|----------------------------------|-------------------------------------|-----------------|--------|------------|------|------|
| | Type | l/s | m³/min | cfm | HP | l/s | °C | w/o duct dB(A) | with duct dB(A) | kg | A mm | B mm | C mm |
| 60 Hz - 7 bar(e) | | | | | | | | | | | | | |
| FF (with IMD Dryer) | ZR 110 | 352 | 21.1 | 746 | 150 | 3.9 | -28 | 70 | 68 | 3265 | 3440 | 2000 | 1650 |
| | ZR 160 | 463 | 27.8 | 981 | 200 | 4.4 | -25 | 67 | 66 | 4695 | 4340 | 2000 | 1650 |
| | ZR 200 | 574 | 34.4 | 1216 | 250 | 4.9 | -25 | 67 | 66 | 5305 | 4340 | 2000 | 1650 |
| | ZR 250 | 667 | 40.0 | 1413 | 300 | 5.4 | -28 | 67 | 66 | 5515 | 4340 | 2000 | 1650 |
| | ZR 275 | 752 | 45.1 | 1593 | 350 | 5.9 | -30 | 67 | 66 | 5635 | 4340 | 2000 | 1650 |
| Pack (w/o IMD Dryer) | ZR 110 | 352 | 21.1 | 746 | 150 | 1.9 | - | 67 | 65 | 2635 | 2540 | 2000 | 1650 |
| | ZR 160 | 463 | 27.8 | 981 | 200 | 2.3 | - | 67 | 66 | 3785 | 3140 | 2000 | 1650 |
| | ZR 200 | 574 | 34.4 | 1216 | 250 | 2.9 | - | 67 | 66 | 3935 | 3140 | 2000 | 1650 |
| | ZR 250 | 667 | 40.0 | 1413 | 300 | 3.4 | - | 67 | 66 | 4145 | 3140 | 2000 | 1650 |
| | ZR 275 | 752 | 45.1 | 1593 | 350 | 3.8 | - | 67 | 66 | 4265 | 3140 | 2000 | 1650 |
| 60 Hz - 8.6 bar(e) | | | | | | | | | | | | | |
| FF (with IMD Dryer) | ZR 110 | 321 | 19.3 | 679 | 150 | 3.8 | -28 | 70 | 68 | 3265 | 3440 | 2000 | 1650 |
| | ZR 132 VSD | 372 | 22.3 | 778 | 175 | 3.9 | -28/-32 | 68-72 | 66-69 | 3500 | 3440 | 2000 | 1650 |
| | ZR 145 | 398 | 23.9 | 843 | 200 | 4.1 | -30 | 70 | 68 | 3530 | 3440 | 2000 | 1650 |
| | ZR 160 | 419 | 25.1 | 888 | 200 | 4.4 | -25 | 67 | 66 | 4695 | 4340 | 2000 | 1650 |
| | ZR 160 VSD | 431 | 25.9 | 913 | 215 | 4.2 | -28/-32 | 68-74 | 66-71 | 3500 | 3440 | 2000 | 1650 |
| | ZR 200 | 516 | 31.0 | 1093 | 250 | 4.6 | -25 | 67 | 66 | 5305 | 4340 | 2000 | 1650 |
| | ZR 250 | 619 | 37.1 | 1312 | 300 | 5.2 | -28 | 67 | 66 | 5515 | 4340 | 2000 | 1650 |
| | ZR 250 VSD | 721 | 43.3 | 1528 | 335 | 5.8 | -25/-30 | 63-73 | 62-71 | 6080 | 4340 | 2000 | 1650 |
| | ZR 275 | 726 | 43.6 | 1538 | 350 | 5.8 | -30 | 67 | 66 | 5635 | 4340 | 2000 | 1650 |
| | ZR 315 VSD | 836 | 50.2 | 1771 | 400 | 6.8 | -25/-30 | 63-73 | 62-71 | 6080 | 4340 | 2000 | 1650 |
| Pack (w/o IMD Dryer) | ZR 110 | 321 | 19.3 | 679 | 150 | 1.7 | - | 67 | 65 | 2635 | 2540 | 2000 | 1650 |
| | ZR 132 VSD | 376 | 22.6 | 797 | 175 | 1.9 | - | 62-68 | 61-66 | 2870 | 2540 | 2000 | 1650 |
| | ZR 145 | 398 | 23.9 | 843 | 200 | 2.1 | - | 68 | 66 | 2900 | 2540 | 2000 | 1650 |
| | ZR 160 | 419 | 25.1 | 888 | 200 | 2.1 | - | 67 | 66 | 3785 | 3140 | 2000 | 1650 |
| | ZR 160 VSD | 436 | 26.1 | 922 | 215 | 2.2 | - | 62-70 | 61-66 | 2870 | 2540 | 2000 | 1650 |
| | ZR 200 | 516 | 31.0 | 1093 | 250 | 2.6 | - | 67 | 66 | 3935 | 3140 | 2000 | 1650 |
| | ZR 250 | 619 | 37.1 | 1312 | 300 | 3.1 | - | 67 | 66 | 4145 | 3140 | 2000 | 1650 |
| | ZR 250 VSD | 721 | 43.3 | 1528 | 335 | 3.7 | - | 63-73 | 62-71 | 4710 | 3140 | 2000 | 1650 |
| | ZR 275 | 726 | 43.6 | 1538 | 350 | 3.7 | - | 67 | 66 | 4265 | 3140 | 2000 | 1650 |
| | ZR 300 | 755 | 45.3 | 1600 | 350 | 4.1 | - | 71 | 70 | 6550 | 3700 | 2400 | 2120 |
| | ZR 315 | 850 | 51.0 | 1801 | 400 | 4.6 | - | 72 | 70 | 6550 | 3700 | 2400 | 2120 |
| | ZR 315 VSD | 836 | 50.2 | 1771 | 400 | 4.3 | - | 63-73 | 62-71 | 4710 | 3140 | 2000 | 1650 |
| | ZR 355 | 955 | 57.3 | 2024 | 450 | 5.1 | - | 72 | 70 | 6950 | 3700 | 2400 | 2120 |
| | ZR 400 | 1043 | 62.6 | 2210 | 500 | 5.6 | - | 72 | 71 | 7050 | 3700 | 2400 | 2120 |
| | ZR 400 VSD | 1114 | 66.9 | 2361 | 570 | 6.4 | - | 68-75 | 66-73 | 8320 | 4060 | 2470 | 2120 |
| | ZR 450 | 1306 | 78.4 | 2767 | 600 | 7.8 | - | 74 | 72 | 9300 | 4060 | 2400 | 2120 |
| | ZR 500 | 1538 | 92.3 | 3259 | 700 | 8.9 | - | 74 | 72 | 9500 | 4060 | 2400 | 2120 |
| | ZR 500 VSD | 1318 | 79.1 | 2793 | 703 | 7.6 | - | 68-76 | 66-74 | 8320 | 4060 | 2470 | 2120 |
| | ZR 630 | 1700 | 102.0 | 3602 | 800 | 9.9 | - | 76 | 74 | 10225 | 4060 | 2400 | 2120 |
| | ZR 700 VSD | 2063 | 123.8 | 4371 | 938 | 11.6 | - | 70-78 | 68-76 | 11850 | 4675 | 2470 | 2120 |
| | ZR 750 | 1939 | 116.3 | 4109 | 900 | 11.2 | - | 76 | 74 | 10225 | 4060 | 2400 | 2120 |
| | ZR 900 VSD | 2456 | 147.4 | 5204 | 1253 | 13.2 | - | 68-78 | 68-76 | 11850 | 4675 | 2470 | 2120 |

(1) Reference conditions:

- dry air
- absolute inlet pressure 1 bar(a)
- cooling and air intake temperature 20 °C
- nominal working pressure
- performance of the compressor package measured according to ISO 1217, Third Edition, Annex C

(2) Cooling water temperature rise of 15 °C

(3) Max. capacity is at reference pressure and not at max. pressure

- (4) Pressure dewpoint is specified for
- 20 °C cooling air/water temperature
 - relative humidity of 60 %
 - nominal working pressure
 - load level of minimum 50 %
- For VSD: at reference speed

(5) ± 3 dB(A) measured at a distance of 1 m and according to ISO 2151:2004 and using ISO 9614-2

- (6) Maximum intake / cooling air temperature is 50 °C for HAT versions
- Conversions
- 1 kg = 2.2 lbs
 - 1 mm = 0.039 inch
 - °F = °C x 9/5 + 32

ZR 110-750 and ZR 132-900 VSD compressors - 60 Hz

| | ZR watercooled | Free air delivery ⁽¹⁾ | | | Installed motor power | Cooling water consumption ⁽²⁾ | Pressure dewpoint ⁽³⁾ | Sound pressure level ⁽⁴⁾ | | Weight | Dimensions | | |
|----------------------|----------------|----------------------------------|--------|------|-----------------------|--|----------------------------------|-------------------------------------|-----------------|--------|------------|------|------|
| | Type | l/s | m³/min | cfm | HP | l/s | °C | w/o duct dB(A) | with duct dB(A) | kg | A mm | B mm | C mm |
| 60 Hz - 10.4 bar(e) | | | | | | | | | | | | | |
| FF (with IMD Dryer) | ZR 110 | 287 | 17.2 | 608 | 150 | 3.5 | -28 | 70 | 68 | 3265 | 3440 | 2000 | 1650 |
| | ZR 132 VSD | 330 | 19.8 | 699 | 175 | 3.9 | -28/-32 | 68-72 | 66-69 | 3500 | 3440 | 2000 | 1650 |
| | ZR 145 | 336 | 20.2 | 712 | 200 | 4.1 | -30 | 70 | 68 | 3530 | 3440 | 2000 | 1650 |
| | ZR 160 | 375 | 22.5 | 795 | 200 | 4.4 | -25 | 67 | 66 | 4695 | 4340 | 2000 | 1650 |
| | ZR 160 VSD | 392 | 23.5 | 831 | 215 | 4.2 | -28/-32 | 68-74 | 66-71 | 3500 | 3440 | 2000 | 1650 |
| | ZR 200 | 459 | 27.5 | 973 | 250 | 4.7 | -25 | 67 | 66 | 4845 | 4340 | 2000 | 1650 |
| | ZR 250 | 548 | 32.9 | 1161 | 300 | 5.2 | -28 | 67 | 66 | 5515 | 4340 | 2000 | 1650 |
| | ZR 250 VSD | 648 | 38.9 | 1373 | 335 | 5.8 | -25/-30 | 67-73 | 65-71 | 6080 | 4340 | 2000 | 1650 |
| | ZR 275 | 641 | 38.5 | 1358 | 350 | 5.7 | -30 | 67 | 66 | 5635 | 4340 | 2000 | 1650 |
| | ZR 315 VSD | 746 | 44.8 | 1581 | 400 | 6.7 | -25/-30 | 67-73 | 65-71 | 6080 | 4340 | 2000 | 1650 |
| Pack (w/o IMD Dryer) | ZR 110 | 287 | 17.2 | 608 | 150 | 1.7 | - | 67 | 65 | 2635 | 2540 | 2000 | 1650 |
| | ZR 132 VSD | 333 | 20.0 | 706 | 214 | 1.9 | - | 62-68 | 61-66 | 2590 | 2540 | 2000 | 1650 |
| | ZR 145 | 336 | 20.2 | 712 | 200 | 2.0 | - | 67 | 66 | 2900 | 2540 | 2000 | 1650 |
| | ZR 160 | 375 | 22.5 | 795 | 200 | 2.2 | - | 67 | 66 | 3785 | 3140 | 2000 | 1650 |
| | ZR 160 VSD | 394 | 23.6 | 835 | 215 | 2.1 | - | 62-70 | 61-66 | 2590 | 2540 | 2000 | 1650 |
| | ZR 200 | 459 | 27.5 | 973 | 250 | 2.6 | - | 67 | 66 | 3935 | 3140 | 2000 | 1650 |
| | ZR 250 | 548 | 32.9 | 1161 | 300 | 3.1 | - | 67 | 66 | 4145 | 3140 | 2000 | 1650 |
| | ZR 250 VSD | 648 | 38.9 | 1373 | 335 | 3.7 | - | 64-70 | 65-68 | 4710 | 3140 | 2000 | 1650 |
| | ZR 275 | 641 | 38.5 | 1358 | 350 | 3.6 | - | 67 | 66 | 4265 | 3140 | 2000 | 1650 |
| | ZR 300 | 677 | 40.6 | 1434 | 350 | 4.3 | - | 71 | 70 | 6550 | 3700 | 2400 | 2120 |
| | ZR 315 | 762 | 45.7 | 1615 | 400 | 4.6 | - | 72 | 70 | 6550 | 3700 | 2400 | 2120 |
| | ZR 315 VSD | 746 | 44.8 | 1581 | 400 | 4.3 | - | 63-73 | 62-71 | 4710 | 3140 | 2000 | 1650 |
| | ZR 355 | 858 | 51.5 | 1818 | 450 | 5.1 | - | 73 | 71 | 6950 | 3700 | 2400 | 2120 |
| | ZR 400 | 945 | 56.7 | 2002 | 500 | 5.5 | - | 73 | 71 | 7050 | 3700 | 2400 | 2120 |
| | ZR 400 VSD | 979 | 58.7 | 2074 | 570 | 5.7 | - | 69-76 | 66-73 | 8350 | 4060 | 2470 | 2120 |
| | ZR 450 | 1144 | 68.6 | 2424 | 600 | 7.7 | - | 74 | xx | 9300 | 4060 | 2400 | 2120 |
| | ZR 500 | 1332 | 79.9 | 2822 | 700 | 8.7 | - | 75 | xx | 9500 | 4060 | 2400 | 2120 |
| | ZR 500 VSD | 1150 | 69.0 | 2437 | 703 | 7.6 | - | 69-77 | 66-74 | 8350 | 4060 | 2470 | 2120 |
| | ZR 630 | 1474 | 88.4 | 3123 | 800 | 9.4 | - | 76 | 74 | 10225 | 4060 | 2400 | 2120 |
| | ZR 700 VSD | 1859 | 111.5 | 3939 | 938 | 11.4 | - | 70-78 | 68-76 | 11850 | 4675 | 2470 | 2120 |
| | ZR 750 | 1739 | 104.3 | 3685 | 900 | 10.8 | - | 76 | 74 | 10225 | 4060 | 2400 | 2120 |
| | ZR 900 VSD | 2057 | 123.4 | 4359 | 1253 | 12.5 | - | 68-79 | 68-77 | 11850 | 4675 | 2470 | 2120 |
| 60 Hz - 13 bar(e) | | | | | | | | | | | | | |
| FF (with IMD Dryer) | ZR 145 | 299 | 17.9 | 634 | 200 | 4.3 | -28 | 75 | 72 | 3530 | 3440 | 2000 | 1650 |
| | ZR 250 | 491 | 29.5 | 1040 | 300 | 5.4 | -28 | 72 | 70 | 5515 | 4340 | 2000 | 1650 |
| | ZR 275 | 550 | 33.0 | 1165 | 350 | 5.8 | -30 | 72 | 70 | 5635 | 4340 | 2000 | 1650 |
| Pack (w/o IMD Dryer) | ZR 145 | 299 | 17.9 | 634 | 200 | 2.0 | - | 75 | 72 | 2900 | 2540 | 2000 | 1650 |
| | ZR 250 | 491 | 29.5 | 1040 | 300 | 3.4 | - | 72 | 70 | 4145 | 3140 | 2000 | 1650 |
| | ZR 275 | 550 | 33.0 | 1165 | 350 | 3.8 | - | 72 | 70 | 4265 | 3140 | 2000 | 1650 |

(1) Reference conditions:
 - dry air
 - absolute inlet pressure 1 bar(a)
 - cooling and air intake temperature 20 °C
 - nominal working pressure
 - performance of the compressor package measured according to ISO 1217, Third Edition, Annex C

(2) Cooling water temperature rise of 15 °C

(3) Max. capacity is at reference pressure and not at max. pressure

(4) Pressure dewpoint is specified for
 - 20 °C cooling air/water temperature
 - relative humidity of 60 %
 - nominal working pressure
 - load level of minimum 50 %
 For VSD: at reference speed

(5) ± 3 dB(A) measured at a distance of 1 m and according to ISO 2151:2004 and using ISO 9614-2

(6) Maximum intake / cooling air temperature is 50 °C for HAT versions
 Conversions
 - 1 kg = 2.2 lbs
 - 1 mm = 0.039 inch
 - °F = °C x 9/5 + 32

ZT 110-275 and ZT 132-315 VSD compressors - 50 Hz

| | ZT aircooled | Free air delivery ⁽¹⁾ | | | Installed motor power | Installed fan motor | Pressure dewpoint ⁽³⁾ | Sound pressure level ⁽⁴⁾ | | Weight | Dimensions | | |
|----------------------|--------------|----------------------------------|--------|------|-----------------------|---------------------|----------------------------------|-------------------------------------|-----------------|--------|------------|------|------|
| | Type | l/s | m³/min | cfm | kW | kW | °C | w/o duct dB(A) | with duct dB(A) | kg | A mm | B mm | C mm |
| 50 Hz - 7.5 bar(e) | | | | | | | | | | | | | |
| FF (with IMD Dryer) | ZT 110 | 312 | 18.7 | 661 | 110 | 4.8 | -28 | 72 | 70 | 4095 | 4040 | 2000 | 1650 |
| | ZT 132 | 360 | 21.6 | 763 | 132 | 4.8 | -29 | 73 | 70 | 4220 | 4040 | 2000 | 1650 |
| | ZT 145 | 390 | 23.4 | 826 | 145 | 4.8 | -30 | 73 | 71 | 4360 | 4040 | 2000 | 1650 |
| | ZT 160 | 460 | 27.57 | 973 | 160 | 8.8 | -30 | 77 | 75 | 5625 | 5040 | 2100 | 1650 |
| | ZT 200 | 563 | 33.75 | 1191 | 200 | 8.8 | -25 | 77 | 75 | 6285 | 5040 | 2100 | 1650 |
| | ZT 250 | 705 | 42.31 | 1493 | 250 | 8.8 | -28 | 77 | 75 | 6280 | 5040 | 2100 | 1650 |
| Pack (w/o IMD Dryer) | ZT 110 | 314 | 18.8 | 665 | 110 | 4.8 | - | 71 | 70 | 3585 | 4040 | 2000 | 1650 |
| | ZT 132 | 362 | 21.7 | 767 | 132 | 4.8 | - | 72 | 70 | 3710 | 4040 | 2000 | 1650 |
| | ZT 145 | 392 | 23.5 | 829 | 145 | 4.8 | - | 72 | 70 | 3850 | 4040 | 2000 | 1650 |
| | ZT 160 | 460 | 27.6 | 973 | 160 | 8.8 | - | 77 | 75 | 5185 | 5040 | 2100 | 1650 |
| | ZT 200 | 563 | 33.8 | 1191 | 200 | 8.8 | - | 77 | 75 | 5385 | 5040 | 2100 | 1650 |
| | ZT 250 | 705 | 42.3 | 1493 | 250 | 8.8 | - | 77 | 75 | 5380 | 5040 | 2100 | 1650 |
| Pack (w/o IMD Dryer) | ZT 275 | 740 | 44.4 | 1566 | 275 | 8.8 | - | 77 | 75 | 5580 | 5040 | 2100 | 1650 |
| 50 Hz - 8.6 bar(e) | | | | | | | | | | | | | |
| FF (with IMD Dryer) | ZT 110 | 281 | 16.9 | 595 | 110 | 4.8 | -28 | 72 | 70 | 4095 | 4040 | 2000 | 1650 |
| | ZT 132 | 322 | 19.3 | 682 | 132 | 4.8 | -29 | 73 | 70 | 4220 | 4040 | 2000 | 1650 |
| | ZT 132 VSD | 349 | 20.9 | 739 | 132 | 4.8 | -25/-30 | 67-71 | 66-70 | 4330 | 4040 | 2000 | 1650 |
| | ZT 145 | 361 | 21.6 | 785 | 145 | 4.8 | -30 | 73 | 71 | 4360 | 4040 | 2000 | 1650 |
| | ZT 160 | 422 | 25.3 | 894 | 160 | 8.8 | -30 | 77 | 75 | 5625 | 5040 | 2100 | 1650 |
| | ZT 160 VSD | 404 | 24.2 | 856 | 160 | 4.8 | -25/-30 | 67-74 | 66-71 | 4330 | 4040 | 2000 | 1650 |
| | ZT 200 | 510 | 30.6 | 1081 | 200 | 8.8 | -25 | 77 | 75 | 6285 | 5040 | 2100 | 1650 |
| | ZT 250 | 661 | 39.7 | 1401 | 250 | 8.8 | -28 | 77 | 75 | 6280 | 5040 | 2100 | 1650 |
| | ZT 250 VSD | 699 | 41.9 | 1480 | 250 | 18.5 | -25/-30 | 70-77 | 68-75 | 6660 | 5040 | 2100 | 1650 |
| | ZT 275 | 696 | 41.8 | 1475 | 275 | 18.5 | -30 | 77 | 75 | 6630 | 5040 | 2100 | 1650 |
| Pack (w/o IMD Dryer) | ZT 315 VSD | 789 | 47.4 | 1672 | 299 | 18.5 | -25/-30 | 70-78 | 68-76 | 6660 | 5040 | 2100 | 1650 |
| | ZT 110 | 281 | 16.9 | 595 | 110 | 4.8 | - | 71 | 70 | 3585 | 4040 | 2000 | 1650 |
| | ZT 132 | 322 | 19.3 | 682 | 132 | 4.8 | - | 72 | 70 | 3710 | 4040 | 2000 | 1650 |
| | ZT 132 VSD | 354 | 21.2 | 750 | 132 | 4.8 | - | 67-74 | 66-71 | 3820 | 4040 | 2000 | 1650 |
| | ZT 145 | 361 | 21.6 | 785 | 145 | 4.8 | - | 72 | 70 | 3850 | 4040 | 2000 | 1650 |
| | ZT 160 | 422 | 25.3 | 894 | 160 | 8.8 | - | 77 | 75 | 5185 | 5040 | 2100 | 1650 |
| | ZT 160 VSD | 410 | 24.6 | 869 | 160 | 4.8 | - | 67-74 | 66-71 | 3820 | 4040 | 2000 | 1650 |
| | ZT 200 | 510 | 30.6 | 1081 | 200 | 8.8 | - | 77 | 75 | 5385 | 5040 | 2100 | 1650 |
| | ZT 250 | 661 | 39.7 | 1401 | 250 | 8.8 | - | 77 | 75 | 5380 | 5040 | 2100 | 1650 |
| | ZT 250 VSD | 699 | 41.9 | 1480 | 250 | 8.8 | - | 70-77 | 68-75 | 6130 | 5040 | 2100 | 1650 |
| Pack (w/o IMD Dryer) | ZT 275 | 696 | 41.8 | 1475 | 275 | 8.8 | - | 77 | 75 | 5580 | 5040 | 2100 | 1650 |
| | ZT 315 VSD | 789 | 47.4 | 1672 | 299 | 8.8 | - | 70-78 | 68-76 | 6130 | 5040 | 2100 | 1650 |
| 50 Hz - 10 bar(e) | | | | | | | | | | | | | |
| FF (with IMD Dryer) | ZT 110 | 260 | 15.6 | 551 | 110 | 4.8 | -28 | 72 | 70 | 4095 | 4040 | 2000 | 1650 |
| | ZT 132 | 313 | 18.8 | 662 | 132 | 4.8 | -29 | 73 | 70 | 4220 | 4040 | 2000 | 1650 |
| | ZT 132 VSD | 316 | 19.0 | 670 | 132 | 4.8 | -25/-30 | 67-71 | 66-70 | 4330 | 4040 | 2000 | 1650 |
| | ZT 145 | 334 | 20.0 | 707 | 145 | 4.8 | -30 | 73 | 70 | 4360 | 4040 | 2000 | 1650 |
| | ZT 160 | 389 | 23.3 | 823 | 160 | 8.8 | -30 | 78 | 76 | 5625 | 5040 | 2100 | 1650 |
| | ZT 160 VSD | 370 | 22.2 | 784 | 160 | 4.8 | -25/-30 | 67-74 | 66-71 | 4330 | 4040 | 2000 | 1650 |
| | ZT 200 | 490 | 29.4 | 1038 | 200 | 8.8 | -30 | 78 | 76 | 5825 | 5040 | 2100 | 1650 |
| | ZT 250 | 608 | 36.5 | 1287 | 250 | 8.8 | -28 | 78 | 76 | 6280 | 5040 | 2100 | 1650 |
| | ZT 250 VSD | 622 | 37.3 | 1316 | 250 | 18.5 | -25/-30 | 71-78 | 69-76 | 6660 | 5040 | 2100 | 1650 |
| | ZT 275 | 671 | 40.2 | 1420 | 275 | 18.5 | -30 | 78 | 76 | 6630 | 5040 | 2100 | 1650 |
| Pack (w/o IMD Dryer) | ZT 315 VSD | 709 | 42.5 | 1501 | 299 | 18.5 | -25/-30 | 71-79 | 69-77 | 6660 | 5040 | 2100 | 1650 |
| | ZT 110 | 261 | 15.7 | 553 | 110 | 4.8 | - | 71 | 70 | 3560 | 4040 | 2000 | 1650 |
| | ZT 132 | 314 | 18.8 | 665 | 132 | 4.8 | - | 72 | 70 | 3700 | 4040 | 2000 | 1650 |
| | ZT 132 VSD | 320 | 19.2 | 678 | 132 | 4.8 | - | 67-71 | 66-70 | 4050 | 4040 | 2000 | 1650 |
| | ZT 145 | 336 | 20.1 | 711 | 145 | 4.8 | - | 72 | 70 | 3850 | 4040 | 2000 | 1650 |
| | ZT 160 | 389 | 23.3 | 823 | 160 | 8.8 | - | 78 | 76 | 5185 | 5040 | 2100 | 1650 |
| | ZT 160 VSD | 384 | 23.0 | 814 | 160 | 4.8 | - | 67-74 | 66-71 | 4050 | 4040 | 2000 | 1650 |
| | ZT 200 | 490 | 29.4 | 1038 | 200 | 8.8 | - | 78 | 76 | 5385 | 5040 | 2100 | 1650 |
| | ZT 250 | 608 | 36.5 | 1287 | 250 | 8.8 | - | 78 | 76 | 5380 | 5040 | 2100 | 1650 |
| | ZT 250 VSD | 622 | 37.3 | 1316 | 250 | 8.8 | - | 71-78 | 69-76 | 6130 | 5040 | 2100 | 1650 |
| Pack (w/o IMD Dryer) | ZT 275 | 671 | 40.2 | 1420 | 275 | 8.8 | - | 78 | 76 | 5580 | 5040 | 2100 | 1650 |
| | ZT 315 VSD | 709 | 42.5 | 1501 | 299 | 8.8 | - | 71-79 | 69-77 | 6130 | 5040 | 2100 | 1650 |

ZT 110-275 and ZT 132-315 VSD compressors - 50 Hz

| | ZR watercooled | Free air delivery ⁽¹⁾ | | | Installed motor power | Cooling water consumption ⁽²⁾ | Pressure dewpoint ⁽³⁾ | Sound pressure level ⁽⁴⁾ | | Weight | Dimensions | | |
|----------------------|----------------|----------------------------------|--------|------|-----------------------|--|----------------------------------|-------------------------------------|-----------------|--------|------------|------|------|
| | Type | l/s | m³/min | cfm | HP | l/s | °C | w/o duct dB(A) | with duct dB(A) | kg | A mm | B mm | C mm |
| 60 Hz - 10.4 bar(e) | | | | | | | | | | | | | |
| FF (with IMD Dryer) | ZR 110 | 287 | 17.2 | 608 | 150 | 3.5 | -28 | 70 | 68 | 3265 | 3440 | 2000 | 1650 |
| | ZR 132 VSD | 330 | 19.8 | 699 | 175 | 3.9 | -28/-32 | 68-72 | 66-69 | 3500 | 3440 | 2000 | 1650 |
| | ZR 145 | 336 | 20.2 | 712 | 200 | 4.1 | -30 | 70 | 68 | 3530 | 3440 | 2000 | 1650 |
| | ZR 160 | 375 | 22.5 | 795 | 200 | 4.4 | -25 | 67 | 66 | 4695 | 4340 | 2000 | 1650 |
| | ZR 160 VSD | 392 | 23.5 | 831 | 215 | 4.2 | -28/-32 | 68-74 | 66-71 | 3500 | 3440 | 2000 | 1650 |
| | ZR 200 | 459 | 27.5 | 973 | 250 | 4.7 | -25 | 67 | 66 | 4845 | 4340 | 2000 | 1650 |
| | ZR 250 | 548 | 32.9 | 1161 | 300 | 5.2 | -28 | 67 | 66 | 5515 | 4340 | 2000 | 1650 |
| | ZR 250 VSD | 648 | 38.9 | 1373 | 335 | 5.8 | -25/-30 | 67-73 | 65-71 | 6080 | 4340 | 2000 | 1650 |
| | ZR 275 | 641 | 38.5 | 1358 | 350 | 5.7 | -30 | 67 | 66 | 5635 | 4340 | 2000 | 1650 |
| | ZR 315 VSD | 746 | 44.8 | 1581 | 400 | 6.7 | -25/-30 | 67-73 | 65-71 | 6080 | 4340 | 2000 | 1650 |
| Pack (w/o IMD Dryer) | ZR 110 | 287 | 17.2 | 608 | 150 | 1.7 | - | 67 | 65 | 2635 | 2540 | 2000 | 1650 |
| | ZR 132 VSD | 333 | 20.0 | 706 | 214 | 1.9 | - | 62-68 | 61-66 | 2590 | 2540 | 2000 | 1650 |
| | ZR 145 | 336 | 20.2 | 712 | 200 | 2.0 | - | 67 | 66 | 2900 | 2540 | 2000 | 1650 |
| | ZR 160 | 375 | 22.5 | 795 | 200 | 2.2 | - | 67 | 66 | 3785 | 3140 | 2000 | 1650 |
| | ZR 160 VSD | 394 | 23.6 | 835 | 215 | 2.1 | - | 62-70 | 61-66 | 2590 | 2540 | 2000 | 1650 |
| | ZR 200 | 459 | 27.5 | 973 | 250 | 2.6 | - | 67 | 66 | 3935 | 3140 | 2000 | 1650 |
| | ZR 250 | 548 | 32.9 | 1161 | 300 | 3.1 | - | 67 | 66 | 4145 | 3140 | 2000 | 1650 |
| | ZR 250 VSD | 648 | 38.9 | 1373 | 335 | 3.7 | - | 64-70 | 65-68 | 4710 | 3140 | 2000 | 1650 |
| | ZR 275 | 641 | 38.5 | 1358 | 350 | 3.6 | - | 67 | 66 | 4265 | 3140 | 2000 | 1650 |
| | ZR 300 | 677 | 40.6 | 1434 | 350 | 4.3 | - | 71 | 70 | 6550 | 3700 | 2400 | 2120 |
| | ZR 315 | 762 | 45.7 | 1615 | 400 | 4.6 | - | 72 | 70 | 6550 | 3700 | 2400 | 2120 |
| | ZR 315 VSD | 746 | 44.8 | 1581 | 400 | 4.3 | - | 63-73 | 62-71 | 4710 | 3140 | 2000 | 1650 |
| | ZR 355 | 858 | 51.5 | 1818 | 450 | 5.1 | - | 73 | 71 | 6950 | 3700 | 2400 | 2120 |
| | ZR 400 | 945 | 56.7 | 2002 | 500 | 5.5 | - | 73 | 71 | 7050 | 3700 | 2400 | 2120 |
| | ZR 400 VSD | 979 | 58.7 | 2074 | 570 | 5.7 | - | 69-76 | 66-73 | 8350 | 4060 | 2470 | 2120 |
| | ZR 450 | 1144 | 68.6 | 2424 | 600 | 7.7 | - | 74 | xx | 9300 | 4060 | 2400 | 2120 |
| | ZR 500 | 1332 | 79.9 | 2822 | 700 | 8.7 | - | 75 | xx | 9500 | 4060 | 2400 | 2120 |
| | ZR 500 VSD | 1150 | 69.0 | 2437 | 703 | 7.6 | - | 69-77 | 66-74 | 8350 | 4060 | 2470 | 2120 |
| | ZR 630 | 1474 | 88.4 | 3123 | 800 | 9.4 | - | 76 | 74 | 10225 | 4060 | 2400 | 2120 |
| | ZR 700 VSD | 1859 | 111.5 | 3939 | 938 | 11.4 | - | 70-78 | 68-76 | 11850 | 4675 | 2470 | 2120 |
| | ZR 750 | 1739 | 104.3 | 3685 | 900 | 10.8 | - | 76 | 74 | 10225 | 4060 | 2400 | 2120 |
| | ZR 900 VSD | 2057 | 123.4 | 4359 | 1253 | 12.5 | - | 68-79 | 68-77 | 11850 | 4675 | 2470 | 2120 |
| 60 Hz - 13 bar(e) | | | | | | | | | | | | | |
| FF (with IMD Dryer) | ZR 145 | 299 | 17.9 | 634 | 200 | 4.3 | -28 | 75 | 72 | 3530 | 3440 | 2000 | 1650 |
| | ZR 250 | 491 | 29.5 | 1040 | 300 | 5.4 | -28 | 72 | 70 | 5515 | 4340 | 2000 | 1650 |
| | ZR 275 | 550 | 33.0 | 1165 | 350 | 5.8 | -30 | 72 | 70 | 5635 | 4340 | 2000 | 1650 |
| Pack (w/o IMD Dryer) | ZR 145 | 299 | 17.9 | 634 | 200 | 2.0 | - | 75 | 72 | 2900 | 2540 | 2000 | 1650 |
| | ZR 250 | 491 | 29.5 | 1040 | 300 | 3.4 | - | 72 | 70 | 4145 | 3140 | 2000 | 1650 |
| | ZR 275 | 550 | 33.0 | 1165 | 350 | 3.8 | - | 72 | 70 | 4265 | 3140 | 2000 | 1650 |

(1) Reference conditions:
 - dry air
 - absolute inlet pressure 1 bar(a)
 - cooling and air intake temperature 20 °C
 - nominal working pressure
 - performance of the compressor package measured according to ISO 1217, Third Edition, Annex C

(2) Cooling water temperature rise of 15 °C

(3) Max. capacity is at reference pressure and not at max. pressure

(4) Pressure dewpoint is specified for
 - 20 °C cooling air/water temperature
 - relative humidity of 60 %
 - nominal working pressure
 - load level of minimum 50 %
 For VSD: at reference speed

(5) ± 3 dB(A) measured at a distance of 1 m and according to ISO 2151:2004 and using ISO 9614-2

(6) Maximum intake / cooling air temperature is 50 °C for HAT versions
 Conversions
 - 1 kg = 2.2 lbs
 - 1 mm = 0.039 inch
 - °F = °C x 9/5 + 32

ZT 110-275 and ZT 132-315 VSD compressors - 50 Hz

| | ZT aircooled | Free air delivery ⁽¹⁾ | | | Installed motor power | Installed fan motor | Pressure dewpoint ⁽³⁾ | Sound pressure level ⁽⁴⁾ | | Weight | Dimensions | | |
|----------------------|--------------|----------------------------------|---------------------|------|-----------------------|---------------------|----------------------------------|-------------------------------------|-----------------|--------|------------|------|------|
| | Type | l/s | m ³ /min | cfm | kW | kW | °C | w/o duct dB(A) | with duct dB(A) | kg | A mm | B mm | C mm |
| 50 Hz - 7.5 bar(e) | | | | | | | | | | | | | |
| FF (with IMD Dryer) | ZT 110 | 312 | 18.7 | 661 | 110 | 4.8 | -28 | 72 | 70 | 4095 | 4040 | 2000 | 1650 |
| | ZT 132 | 360 | 21.6 | 763 | 132 | 4.8 | -29 | 73 | 70 | 4220 | 4040 | 2000 | 1650 |
| | ZT 145 | 390 | 23.4 | 826 | 145 | 4.8 | -30 | 73 | 71 | 4360 | 4040 | 2000 | 1650 |
| | ZT 160 | 460 | 27.57 | 973 | 160 | 8.8 | -30 | 77 | 75 | 5625 | 5040 | 2100 | 1650 |
| | ZT 200 | 563 | 33.75 | 1191 | 200 | 8.8 | -25 | 77 | 75 | 6285 | 5040 | 2100 | 1650 |
| | ZT 250 | 705 | 42.31 | 1493 | 250 | 8.8 | -28 | 77 | 75 | 6280 | 5040 | 2100 | 1650 |
| Pack (w/o IMD Dryer) | ZT 275 | 740 | 44.38 | 1566 | 315 | 18.5 | -30 | 77 | 75 | 6630 | 5040 | 2100 | 1650 |
| | ZT 110 | 314 | 18.8 | 665 | 110 | 4.8 | - | 71 | 70 | 3585 | 4040 | 2000 | 1650 |
| | ZT 132 | 362 | 21.7 | 767 | 132 | 4.8 | - | 72 | 70 | 3710 | 4040 | 2000 | 1650 |
| | ZT 145 | 392 | 23.5 | 829 | 145 | 4.8 | - | 72 | 70 | 3850 | 4040 | 2000 | 1650 |
| | ZT 160 | 460 | 27.6 | 973 | 160 | 8.8 | - | 77 | 75 | 5185 | 5040 | 2100 | 1650 |
| | ZT 200 | 563 | 33.8 | 1191 | 200 | 8.8 | - | 77 | 75 | 5385 | 5040 | 2100 | 1650 |
| Pack (w/o IMD Dryer) | ZT 250 | 705 | 42.3 | 1493 | 250 | 8.8 | - | 77 | 75 | 5380 | 5040 | 2100 | 1650 |
| | ZT 275 | 740 | 44.4 | 1566 | 275 | 8.8 | - | 77 | 75 | 5580 | 5040 | 2100 | 1650 |
| 50 Hz - 8.6 bar(e) | | | | | | | | | | | | | |
| FF (with IMD Dryer) | ZT 110 | 281 | 16.9 | 595 | 110 | 4.8 | -28 | 72 | 70 | 4095 | 4040 | 2000 | 1650 |
| | ZT 132 | 322 | 19.3 | 682 | 132 | 4.8 | -29 | 73 | 70 | 4220 | 4040 | 2000 | 1650 |
| | ZT 132 VSD | 349 | 20.9 | 739 | 132 | 4.8 | -25/-30 | 67-71 | 66-70 | 4330 | 4040 | 2000 | 1650 |
| | ZT 145 | 361 | 21.6 | 785 | 145 | 4.8 | -30 | 73 | 71 | 4360 | 4040 | 2000 | 1650 |
| | ZT 160 | 422 | 25.3 | 894 | 160 | 8.8 | -30 | 77 | 75 | 5625 | 5040 | 2100 | 1650 |
| | ZT 160 VSD | 404 | 24.2 | 856 | 160 | 4.8 | -25/-30 | 67-74 | 66-71 | 4330 | 4040 | 2000 | 1650 |
| | ZT 200 | 510 | 30.6 | 1081 | 200 | 8.8 | -25 | 77 | 75 | 6285 | 5040 | 2100 | 1650 |
| | ZT 250 | 661 | 39.7 | 1401 | 250 | 8.8 | -28 | 77 | 75 | 6280 | 5040 | 2100 | 1650 |
| | ZT 250 VSD | 699 | 41.9 | 1480 | 250 | 18.5 | -25/-30 | 70-77 | 68-75 | 6660 | 5040 | 2100 | 1650 |
| | ZT 275 | 696 | 41.8 | 1475 | 275 | 18.5 | -30 | 77 | 75 | 6630 | 5040 | 2100 | 1650 |
| Pack (w/o IMD Dryer) | ZT 315 VSD | 789 | 47.4 | 1672 | 299 | 18.5 | -25/-30 | 70-78 | 68-76 | 6660 | 5040 | 2100 | 1650 |
| | ZT 110 | 281 | 16.9 | 595 | 110 | 4.8 | - | 71 | 70 | 3585 | 4040 | 2000 | 1650 |
| | ZT 132 | 322 | 19.3 | 682 | 132 | 4.8 | - | 72 | 70 | 3710 | 4040 | 2000 | 1650 |
| | ZT 132 VSD | 354 | 21.2 | 750 | 132 | 4.8 | - | 67-74 | 66-71 | 3820 | 4040 | 2000 | 1650 |
| | ZT 145 | 361 | 21.6 | 785 | 145 | 4.8 | - | 72 | 70 | 3850 | 4040 | 2000 | 1650 |
| | ZT 160 | 422 | 25.3 | 894 | 160 | 8.8 | - | 77 | 75 | 5185 | 5040 | 2100 | 1650 |
| | ZT 160 VSD | 410 | 24.6 | 869 | 160 | 4.8 | - | 67-74 | 66-71 | 3820 | 4040 | 2000 | 1650 |
| | ZT 200 | 510 | 30.6 | 1081 | 200 | 8.8 | - | 77 | 75 | 5385 | 5040 | 2100 | 1650 |
| | ZT 250 | 661 | 39.7 | 1401 | 250 | 8.8 | - | 77 | 75 | 5380 | 5040 | 2100 | 1650 |
| | ZT 250 VSD | 699 | 41.9 | 1480 | 250 | 8.8 | - | 70-77 | 68-75 | 6130 | 5040 | 2100 | 1650 |
| Pack (w/o IMD Dryer) | ZT 275 | 696 | 41.8 | 1475 | 275 | 8.8 | - | 77 | 75 | 5580 | 5040 | 2100 | 1650 |
| | ZT 315 VSD | 789 | 47.4 | 1672 | 299 | 8.8 | - | 70-78 | 68-76 | 6130 | 5040 | 2100 | 1650 |
| 50 Hz - 10 bar(e) | | | | | | | | | | | | | |
| FF (with IMD Dryer) | ZT 110 | 260 | 15.6 | 551 | 110 | 4.8 | -28 | 72 | 70 | 4095 | 4040 | 2000 | 1650 |
| | ZT 132 | 313 | 18.8 | 662 | 132 | 4.8 | -29 | 73 | 70 | 4220 | 4040 | 2000 | 1650 |
| | ZT 132 VSD | 316 | 19.0 | 670 | 132 | 4.8 | -25/-30 | 67-71 | 66-70 | 4330 | 4040 | 2000 | 1650 |
| | ZT 145 | 334 | 20.0 | 707 | 145 | 4.8 | -30 | 73 | 70 | 4360 | 4040 | 2000 | 1650 |
| | ZT 160 | 389 | 23.3 | 823 | 160 | 8.8 | -30 | 78 | 76 | 5625 | 5040 | 2100 | 1650 |
| | ZT 160 VSD | 370 | 22.2 | 784 | 160 | 4.8 | -25/-30 | 67-74 | 66-71 | 4330 | 4040 | 2000 | 1650 |
| | ZT 200 | 490 | 29.4 | 1038 | 200 | 8.8 | -30 | 78 | 76 | 5825 | 5040 | 2100 | 1650 |
| | ZT 250 | 608 | 36.5 | 1287 | 250 | 8.8 | -28 | 78 | 76 | 6280 | 5040 | 2100 | 1650 |
| | ZT 250 VSD | 622 | 37.3 | 1316 | 250 | 18.5 | -25/-30 | 71-78 | 69-76 | 6660 | 5040 | 2100 | 1650 |
| | ZT 275 | 671 | 40.2 | 1420 | 275 | 18.5 | -30 | 78 | 76 | 6630 | 5040 | 2100 | 1650 |
| Pack (w/o IMD Dryer) | ZT 315 VSD | 709 | 42.5 | 1501 | 299 | 18.5 | -25/-30 | 71-79 | 69-77 | 6660 | 5040 | 2100 | 1650 |
| | ZT 110 | 261 | 15.7 | 553 | 110 | 4.8 | - | 71 | 70 | 3560 | 4040 | 2000 | 1650 |
| | ZT 132 | 314 | 18.8 | 665 | 132 | 4.8 | - | 72 | 70 | 3700 | 4040 | 2000 | 1650 |
| | ZT 132 VSD | 320 | 19.2 | 678 | 132 | 4.8 | - | 67-71 | 66-70 | 4050 | 4040 | 2000 | 1650 |
| | ZT 145 | 336 | 20.1 | 711 | 145 | 4.8 | - | 72 | 70 | 3850 | 4040 | 2000 | 1650 |
| | ZT 160 | 389 | 23.3 | 823 | 160 | 8.8 | - | 78 | 76 | 5185 | 5040 | 2100 | 1650 |
| | ZT 160 VSD | 384 | 23.0 | 814 | 160 | 4.8 | - | 67-74 | 66-71 | 4050 | 4040 | 2000 | 1650 |
| | ZT 200 | 490 | 29.4 | 1038 | 200 | 8.8 | - | 78 | 76 | 5385 | 5040 | 2100 | 1650 |
| | ZT 250 | 608 | 36.5 | 1287 | 250 | 8.8 | - | 78 | 76 | 5380 | 5040 | 2100 | 1650 |
| | ZT 250 VSD | 622 | 37.3 | 1316 | 250 | 8.8 | - | 71-78 | 69-76 | 6130 | 5040 | 2100 | 1650 |
| Pack (w/o IMD Dryer) | ZT 275 | 671 | 40.2 | 1420 | 275 | 8.8 | - | 78 | 76 | 5580 | 5040 | 2100 | 1650 |
| | ZT 315 VSD | 709 | 42.5 | 1501 | 299 | 8.8 | - | 71-79 | 69-77 | 6130 | 5040 | 2100 | 1650 |

Oil-free centrifugal compressors, 355-2750 kW, 475-3500 hp

ZH / ZH⁺

Designed to save energy and guarantee reliability, Atlas Copco's ZH/ZH⁺ oil-free centrifugal compressors are provided as complete ready-to-integrate packages including internal piping, integrated coolers, motor, lubrication, inlet guide vanes, control system and 100% matched components. They are just what you need for large compressor rooms of 1-20 MW and for processes with a fluctuating or constant air demand. Choose the ZH/ZH⁺ and put your mind at rest: air is 100% certified oil-free according to ISO 8573-1 CLASS 0 (2010), and the compressors operate reliably even in extremes of temperature and humidity.

CUSTOMER BENEFITS

- **Maximum uptime** – All ZH/ZH⁺ components are easy to maintain, dismantle and re-assemble if required, thus reducing downtime. Advanced control and monitoring possibilities ensure that production interruptions are minimized. In addition, easily accessible major components, minimal service interventions and long overhaul intervals reduce maintenance time and costs.

- **Maximum energy savings** – All components of the ZH/ZH⁺, such as the backward leaning impeller, carbon ring air seals and inlet guide vanes, are designed to lower the pressure drops and provide the highest air volume with the lowest energy requirement.

- **Easy installation** – The design of the ZH/ZH⁺ includes internal piping, coolers, motor, lubrication, inlet guide vanes and control system: all ready for integration on site. Delivered as a plug-and-run integrated package, the ZH⁺ ensures a low commissioning time, fault-free installation and no external instrument air is required.


- **Advanced control monitoring** – To maximize efficiency and reliability, the Elektronikon® controls the main drive motor and regulates system pressure within a predefined and narrow pressure band. The Elektronikon® controller can be adapted to your specific needs with extra sensors, digital contacts, fieldbus, Internet and SMS communication functions. In combination with the ES multiple compressor controller, the operation of your complete compressor room is optimized.

- **Certified 100% oil-free** – ZH/ZH⁺ compressors provide you with 100% pure, clean air that complies with ISO 8573-1 CLASS 0 (2010) certification. CLASS 0 means zero risk of contamination; zero risk of damaged or unsafe products; zero risk of losses from operational downtime; and zero risk of damaging your company's hard-won professional reputation. In 2006 Atlas Copco was the first manufacturer in the world to receive such certification on an oil-free compressor.



Functional diagram for the ZH (3-stage) series

- | | | | |
|--------------------|---------------|--------------------|--------------|
| 1 Air filter | 4 Intercooler | 7 Aftercooler | a Oil pump |
| 2 Inlet guide vane | 5 Turbo stage | 8 Blow-off muffler | b Oil cooler |
| 3 Turbo stage | 6 Turbo stage | 9 Oil tank | c Oil filter |



Power-saving inlet guide vane and actuator



Effectively positioned before the 1st stage, with a constant delivery pressure in the control range, it adjusts the volume flow to the exact compressed air requirement, saving up to 9% power compared to conventional valve regulation. The reliable servo-motor based actuator looks after an accurate alignment with the variable air demand to ensure these energy savings.

Blow-off regulation for constant pressure applications

The volume flow control range of the turbo expands considerably at a constant delivery pressure due to the blow-off function.

The most flexible volume flow adaption for constant pressure processes.

| Type | Maximum working pressure | Volume flow ¹⁾ | | Motor rated power | Sound pressure level ²⁾ | Approx. weight ³⁾ | Dimensions ³⁾ L × W × H |
|---|--------------------------|---------------------------|---------------|-------------------|------------------------------------|------------------------------|------------------------------------|
| | bar | l/s | m³/hr | kW | db(A) | kg | mm |
| ZH 355-900 & ZH6000/10000 - 9000/15000 - 16000/26000 Centrifugal compressors | | | | | | | |
| ZH 355 | 3.5 - 4.6 | 1320 - 1578 | 4750 - 5681 | 355 | 83 | 6325 | 3970 X 2230 X 2230 |
| ZH 400 | 3.5 - 8 | 1234 - 1814 | 4443 - 6531 | 400 | 83 | 6625 - 7225 | 3970 X 2230 X 2230 |
| ZH 450 | 3.5 - 9 | 1297 - 2052 | 4670 - 7388 | 450 | 83 | 6725 - 7325 | 3970 X 2230 X 2230 |
| ZH 500 | 3.5 - 10.4 | 1349 - 2280 | 4855 - 8208 | 500 | 83 | 6875 - 7475 | 3970 X 2230 X 2230 |
| ZH 560 | 3.5 - 13 | 1368 - 2548 | 4924 - 9174 | 560 | 83 | 7475 - 8075 | 3970 X 2230 X 2230 |
| ZH 630 | 7 - 13 | 1555 - 2063 | 5599 - 7428 | 630 | 83 | 8825 | 3970 X 2230 X 2230 |
| ZH 710 | 7 - 13 | 1770 - 2331 | 6371 - 8390 | 710 | 83 | 9475 | 3970 X 2230 X 2230 |
| ZH 800 | 7 - 13 | 2011 - 2620 | 7240 - 9432 | 800 | 83 | 9425 | 3973 X 2230 X 2230 |
| ZH 900 | 9 - 10.4 | 2570 - 2588 | 9253 - 9316 | 900 | 83 | 9425 | 3974 X 2230 X 2230 |
| ZH6000/10000 2stage | 3.5 - 4.6 | 1450 - 3275 | 5200 - 11800 | 500 - 710 | 80 - 85 | 13710-14570 | 5250x2000x2340 |
| ZH6000/10000 3stage | 7 - 10.4 | 1450 - 3275 | 5200 - 11800 | 630 - 1120 | 80 - 85 | 13710-14570 | 5250x2000x2340 |
| ZH9000/15000 2stage | 3.5 - 4.6 | 2225 - 5000 | 8000 - 18000 | 710 - 1250 | 80 - 85 | 16000-18310 | 5800x2250x2570 |
| ZH9000/15000 3stage | 7 - 10.4 | 2225 - 5000 | 8000 - 18000 | 1000 - 1850 | 80 - 85 | 16000-18310 | 5800x2250x2570 |
| ZH16000/26000 3stage | 7 - 10.4 | 3325 - 7500 | 12000 - 27000 | 1600 - 2750 | 80 - 85 | 38500 | 7300x3000x3630 |
| | | | | | | | |
| ZH 350 + | 3.5 - 4.6 | 1320 - 1578 | 4750 - 5681 | 355 | 72 | 8050 | 5270 x 2230 x 2230 |
| ZH 400 + | 3.5 - 8 | 1234 - 1814 | 4443 - 6531 | 400 | 72 | 8350 - 8950 | 5270 x 2230 x 2230 |
| ZH 450 + | 3.5 - 9 | 1297 - 2052 | 4670 - 7388 | 450 | 72 | 8450 - 9050 | 5270 x 2230 x 2230 |
| ZH 500 + | 3.5 - 10.4 | 1349 - 2280 | 4855 - 8208 | 500 | 72 | 8600 - 9200 | 5270 x 2230 x 2230 |
| ZH 560 + | 3.5 - 13 | 1368 - 2548 | 4924 - 9174 | 560 | 72 | 9200 - 9800 | 5270 x 2230 x 2230 |
| ZH 630 + | 7 - 13 | 1555 - 2063 | 5599 - 7428 | 630 | 72 | 9950 | 5270 x 2230 x 2230 |
| ZH 710 + | 7 - 13 | 1770 - 2331 | 6371 - 8390 | 710 | 72 | 10200 | 5270 x 2230 x 2230 |
| ZH 800 + | 7 - 13 | 2011 - 2620 | 7240 - 9432 | 800 | 72 | 11150 | 5270 x 2230 x 2230 |
| ZH 900+ | 9 - 10.4 | 2570 - 2588 | 9253 - 9316 | 900 | 72 | 11150 | 5270 x 2230 x 2230 |
| ZH6000/10000+ 2stage | 3.5 - 4.6 | 1450 - 3275 | 5200 - 11800 | 500 - 710 | 80 - 85 | 13710-15120 | 5250x2120x2400 |
| ZH6000/10000+ 3stage | 7 - 10.4 | 1450 - 3275 | 5200 - 11800 | 630 - 1120 | 80 - 85 | 13710-15120 | 5250x2120x2400 |
| ZH9000/15000+ 2stage | 3.5 - 4.6 | 2225 - 5000 | 8000 - 18000 | 710 - 1250 | 80 - 85 | 16900-19210 | 5800x2370x2630 |
| ZH9000/15000+ 3stage | 7 - 10.4 | 2225 - 5000 | 8000 - 18000 | 1000 - 1850 | 80 - 85 | 16900-19210 | 5800x2370x2630 |
| ZH16000/26000+ 3stage | 7 - 10.4 | 3325 - 7500 | 12000 - 27000 | 1600 - 2750 | 80 - 85 | 40100 | 7300x3120x3500 |

Oil-free high-speed drive centrifugal compressors, 350 kW, 470 hp

ZH 350⁺

Atlas Copco's ZH 350⁺ oil-free centrifugal compressors are designed to save you energy. Operating at high speed and high efficiency, they are directly driven by a permanent magnet synchronous motor. Optimal 3-stage compression reduces operating costs to previously unattainable low levels. A further major benefit is that air is 100% certified oil-free according to ISO 8573-1 CLASS 0 (2010). With the ZH 350⁺ you get a complete plug-and-run package including internal piping, integrated coolers, motor, control system and 100% matched components.

CUSTOMER BENEFITS

- **Maximum energy savings** – All components of the ZH 350⁺ are designed to save energy. The high-speed drive means no oil lubrication, no intermediate gears and fewer rotating components, all of which drive down energy costs. The backward leaning impeller and the carbon ring air seals are designed to lower the pressure drops and provide the highest air volume with the lowest energy requirement.

- **Advanced control monitoring** – The compressor controller maxi-

mizes efficiency and reliability of the ZH 350⁺ by controlling the main drive motor and regulating system pressure within a predefined and narrow pressure band. The controller can be adapted to your specific needs with extra sensors, digital contacts, fieldbus, Internet and SMS communication functions. In combination with the ES multiple compressor controller, the operation of your complete compressor room is optimized.

- **Maximum uptime** – All ZH 350⁺ components are easy to maintain, dismantle and re-assemble if required, thus reducing downtime. Advanced control and monitoring possibilities ensure that production interruptions are minimized. In addition, easily accessible major components, minimal service interventions and long overhaul intervals reduce maintenance time and costs.

- **Plug-and-run package** – The integrated design of the ZH 350⁺ includes internal piping, coolers, motor, and control system: all supplied as a ready-to-use package. Installation is fault-free, commissioning time is low and no external instrument air is required. You simply plug and run.

- **Certified 100% oil-free** – ZH 350⁺ compressors provide you with 100% pure, clean air that complies with ISO 8573-1 CLASS 0 (2010) certification. CLASS 0 means zero risk of contamination; zero risk of damaged or unsafe products; zero risk of losses from operational downtime; and zero risk of damaging your company's hard-won professional reputation. In 2006 Atlas Copco was the first manufacturer in the world to receive such certification on an oil-free compressor.



| 50/60 Hz | Working pressure | | Free air delivery (1) | | | | | | Installed motor power | | Dimensions | | | | | |
|---------------------|------------------|--------|-----------------------|------|------|------|------|------|-----------------------|-----|------------|------|------|-------|-------|-------|
| | bar(e) | psig | l/s | | cfm | | m³/h | | kW | hp | mm | | | in | | |
| | | | Min | Max | Min | Max | Min | Max | | | A | B | C | A | B | C |
| ZH 350 ⁺ | 6-9 | 87-130 | 700 | 1100 | 1483 | 2330 | 2520 | 3960 | 350 | 470 | 2400 | 2000 | 2017 | 94.49 | 78.74 | 79.42 |

Energy recovery control unit for water-cooled oil-free air compressors from 90 to 900 kW.

ER 90-900

Atlas Copco energy recovery control units transfer the energy recovered in the cooling water of oil-free air compressors to your process. The control unit is installed between the compressor and your cooling and heating circuit. The design ensures perfect and easy integration of energy recovery systems in a wide variety of different applications.

CUSTOMER BENEFITS

- Specifically designed to transfer the energy recovered from the oil-free compressor to your process.
- Ultimate reliability under the harshest operating conditions.
- Single interface between your compressed air system and your process.
- Regulation of compressor cooling water pressure and temperature to keep the compressed air system working optimally.
- Compressors operate independently from your heat requirement process.
- Easy to guarantee optimal quality of cooling water from compressor(s).
- Up to four ZR compressors can be connected to one energy recovery control unit.
- Standard set-up can be extended with a number of application specific options.
- Designed, manufactured and tested in accordance with ISO 9001 and ISO 1400.
- Superior quality by design ensures long and trouble-free life at the lowest operating costs:
 - Stainless steel plate heat exchangers.
 - Variable-speed driven pumps.
 - State-of-the-art control system.
- Maximum efficiency and reliability:
 - Elektronikon® controller can be adapted to specific needs with digital contacts, fieldbus, Internet and SMS communication functions.



Serving the mining industry with energy efficient solutions



OIL-FREE COMPRESSORS FOR LOW & HIGH PRESSURE APPLICATIONS

We have an energy efficient solution for every demand, be it waste water treatment, pneumatic conveying, mining, PET bottle blowing or any application requiring low or high pressure compressed air.

Atlas Copco's continuous drive for energy efficiency to reduce your energy cost, has made innovation the heart of Atlas Copco's values and for a century now, we have been at the forefront of compression technology thanks to a number of ground-breaking introductions.

Solutions for low and high pressures

For operations which require a lot of air but with a low over-pressure, it is worth using special low-pressure systems.

They provide stable system pressure and an efficient air supply without disruptive pulsations or power drops, which occur when the compressed air diverts from the normal air network and the demand is controlled by a buffer container and a blow-off system. Our low-pressure systems are suitable for pressure increases of just above 0, up to 4 bar. So you can supply powders and granules, for example, gently cool and dry products, or aerate sewage plants.

We also offer efficient compressors for high pressures from 20 to 40 bar. We would even go so far as to say that, with our Class 0 certificate for oil-free machines and some constructive subtleties, our ZD high pressure compressor is a safe and energy-efficient compressed air solution for manufacturing PET bottles!

The risk of bottle manufacturers and bottlers contaminating their products with traces of oil due to unclean compressed air is reduced to zero. You'll find details of these and other machines for high and low pressure on the following pages.

The design of our ZB centrifugal compressors is particularly efficient. With the contactless electromagnetic position of the motor, which is located on the motor shaft itself along with the impeller, they achieve efficiencies of over 90%. The gearless machines are non-wearing and keep maintenance costs low. A precise analysis of the requirements will show which solution is best for the application in question. Investing more in an expensive system often pays for itself in the first one to two years due to the improved energy efficiency.



**Oil-free rotary screw compressors,
22-500 kW / 40-700 hp**

ZE/ZA (VSD)

Page 87



**Oil-free positive displacement
screw blowers, 7-132 kW,
10-180 hp**

ZS

Page 88



**Oil-free Variable Speed Drive
positive displacement screw
blowers, 18-160 kW, 25-215 hp**

ZS+ VSD

Page 89



**Oil-free Variable Speed Drive
centrifugal air compressors,
7-132kW, 10-180hp**

ZB 100-160 VSD

Page 90



**Oil-less reciprocating trunk-
piston compressors, up to 351
bar (a) (5090 psia), 30 kW**

ZM

Page 91



**Oil-free reciprocating
compressors**

HX / HN

Page 94



**Oil-less reciprocating trunk-
piston compressors, up to 351
bar (a) (5090 psia), 30 kW**

DM

Page 92



**Oil-free reciprocating piston
compressors, up to 40 bar (580
psig), 37-275 kW / 50-368 hp**

P

Page 95



**Oil-free reciprocating piston
compressors, up to 45 bar (652
psig) 30-315 kW / 40-422 hp**

DX / DN

Page 93



**Oil-free screw and reciprocating
piston compressors, up to 40 bar
(580 psig), 136-770 kW / 182-1032
hp**

ZD

Page 97

Oil-free rotary screw compressors, 22-500 kW / 40-700 hp ZE/ZA (VSD)

Especially in harsh and dusty environments, a reliable supply of 100% certified oil-free compressed air is critical to ensure production continuity. Atlas Copco's low pressure ZE/ZA compressors fulfill this demand by offering a constant air flow at minimal energy costs. Integrated Variable Speed Drive (VSD) variants precisely and automatically tune the compressor flow to the process air demand and hence limit the energy consumption to the absolute minimum possible.

CUSTOMER BENEFITS

• **Highest reliability** – ZE/ZA compressors stand for durability and reliability. They incorporate Atlas Copco's proven screw technology, stainless steel coolers, AGMA A4/DIN 5 gears and state-of-the-art electrical drive systems, all of which contribute to overall high reliability. ZE/ZA compressors are built using long-standing internal engineering practices, and are manufactured and tested according to ISO 9001.

• **Certified 100% oil-free** – ZE/ZA compressors provide you with 100% pure, clean air that complies with ISO 8573-1 CLASS 0 (2010) certification. CLASS 0 means zero risk of contamination; zero risk of damaged or unsafe products; zero risk of losses from operational downtime; and zero risk of damaging your company's hard-won professional reputation. In 2006 Atlas Copco was the first manufacturer in the world to receive such certification on an oil-free compressor.

• **Reduced energy costs** – With an air circuit designed to avoid and reduce pressure drops, the ZE/ZA is built to save energy. Features like VSD drive and state-of-the-art oil-free compression element greatly enhance energy savings.

• **Easy installation** – The compact design eliminates the need for extras and reduces installation to an absolute minimum, saving you time and money. Built for easy integration in your existing compressed air network, ZE/ZA compressors are up and running in no time.



| Technical specifications | Metric | Imperial |
|--------------------------|------------------|----------------------|
| Capacity FAD | 87 - 855 l/s | 87 - 855 l/s |
| Capacity FAD | 311 - 3078 m³/h | 183.18 - 1812.94 cfm |
| Working pressure | 2.5 - 3.5 bar(e) | 36.26 - 50.76 psig |
| Installed motor power | 22 - 500 kW | 40 - 700 hp |

Oil-free positive displacement screw blowers, 7-132kW, 10 -180hp ZS

Atlas Copco's ZS blowers provide a continuous and reliable supply of 100% oil-free air – certified according to ISO 8573-1 CLASS 0 (2010). Integrating the proven benefits of screw technology, the ZS range will cut your energy costs by an average of 30% when compared to lobe technology.

CUSTOMER BENEFITS

• **Reliability** – Incorporating our proven screw technology and long-standing internal engineering practices, and designed, manufactured and tested in accordance with ISO 9001, the ZS gives you 24/7 reliability over its long lifetime.

• **High efficiency** – Integrating the proven benefits of screw technology, the ZS range reduces energy costs by an average of 30% when compared to lobe technology.

• **Certified 100% oil-free** – ZS blowers provide you with 100% pure, clean air that complies with ISO 8573-1 CLASS 0 (2010) certification. CLASS 0 means zero risk of contamination; zero risk of damaged or unsafe products; zero risk of losses from operational downtime; and zero risk of damaging your company's hard-won professional reputation. In 2006 Atlas Copco was the first manufacturer in the world to receive such certification on an oil-free compressor.

• **Easy installation** – Built for smooth integration in your existing compressed air network, ZS blowers are up and running in no time.



| Technical specifications | Metric | Imperial |
|--------------------------|-----------------|---------------|
| Capacity FAD | 75 - 1292 l/s | 75 - 1292 l/s |
| Capacity FAD | 271 - 4651 m³/h | 48 - 2731 cfm |
| Working pressure | 0.3 - 1 bar(e) | 4 - 14.5 psig |
| Installed motor power | 18.5 - 160 kW | 25 - 200 hp |

Oil-free Variable Speed Drive positive displacement screw blowers, 18-160 kW, 25-215 hp

ZS⁺ VSD

Atlas Copco's ZS⁺ VSD blowers balance the two key prerequisites when choosing a blower: reliability and energy efficiency. Integrating the proven benefits of screw technology, the ZS⁺ VSD reduces energy costs by an average of 30% when compared to lobe technology. But that's not all. The ZS⁺ VSD offers 100% oil-free air – TÜV-certified according to ISO 8573-1 CLASS 0 (2010) – which is absolutely essential to avoid contamination and keep your production running smoothly. The ZS⁺ VSD is supplied as a state-of-the-art, ready-to-run package with completely integrated VSD convertor and proven Elektronikon® controller.

CUSTOMER BENEFITS

- **High reliability** – Incorporating our proven screw technology and long-standing internal engineering practices, and designed, manufactured and tested in accordance with ISO 9001, the ZS⁺ VSD gives you 24/7 reliability over its long lifetime.

- **Maximum energy savings** – Integrating the proven benefits of screw technology, the ZS⁺ VSD range reduces energy costs by an average of 30% when compared to lobe technology. VSD technology closely follows the air demand by automatically adjusting the motor speed and lowering system pressure, giving you even greater energy savings.

- **Certified 100% oil-free** – ZS⁺ VSD blowers provide you with 100% pure, clean air that complies with ISO 8573-1 CLASS 0 (2010) certification. CLASS 0 means zero risk of contamination; zero risk of damaged or unsafe products; zero risk of losses from operational downtime; and zero risk of damaging your company's hard-won professional reputation. In 2006 Atlas Copco was the first manufacturer in the world to receive such certification on an oil-free compressor.

- **Easy installation** – Delivered ready for use, ZS⁺ VSD blowers come as all-in-one packages including the state-of-the-art Elektronikon® controller, integrated converter, forklift slots, check valve, air filter and silencers. The compact design eliminates the need for extras and reduces installation to an absolute minimum, saving you time and money.

- **Quiet operation** – Vibration and noise levels are low, resulting in a pleasant working environment for your operators.



| Technical specifications | Metric | Imperial |
|--------------------------|------------------|----------------|
| Capacity FAD | 79 - 1272 l/s | 79 - 1272 l/s |
| Capacity FAD | 284 - 4578 m³/h | 152 - 2695 cfm |
| Working pressure | 0.3 - 1.2 bar(e) | 4 - 17 psig |
| Installed motor power | 22 - 160 kW | 30 - 200 hp |

Oil-free Variable Speed Drive centrifugal air compressors, 100-160 kW, 135-215 hp

ZB 100-160 VSD

Atlas Copco's low pressure ZB 100-160 VSD blowers guarantee a continuous, highly reliable, energy-efficient and 100% oil-free air supply – certified according to ISO 8573-1 CLASS 0 (2010). These blowers are directly driven by a permanent magnet synchronous motor, which is vastly superior to conventional types. Moreover, the unique stainless steel backward lean impeller has integrated labyrinth seals which lead to high efficiency and minimal air leakage. The ZB 100-160 VSD is supplied as an all-in-one, ready-to-run package with a small footprint. Vibration and noise levels are low, resulting in an agreeable working environment for your operators.

• **Certified 100% oil-free** – All ZB blowers provide you with 100% pure, clean air that complies with ISO 8573-1 CLASS 0 (2010) certification. CLASS 0 means zero risk of contamination; zero risk of damaged or unsafe products; zero risk of losses from operational downtime; and zero risk of damaging your company's hard-won professional reputation. In 2006 Atlas Copco was the first manufacturer in the world to receive such certification on an oil-free compressor.

• **Easy installation** – ZB 100-160 blowers are delivered ready for use. The all-in-one package includes a powerful PLC controller, integrated VSD, forklift slots, check valve, air filter, blow-off valve and silencers.

• **Easy maintenance** – ZB 100-160 blowers will save you time and costs due to easy serviceability.

• **Quiet operation** – Low vibration and noise levels provides a pleasant working environment for your operators.

CUSTOMER BENEFITS

• **High reliability** – Thanks to innovative magnetic bearings, low vibration turbo technology and integrated Variable Speed Drive, ZB 100-160 VSD blowers provide exceptional reliability and production continuity.

• **Maximum energy savings** – Install a ZB 100-160 VSD and benefit from reduced costs. The magnetic bearing design coupled with the turbo compression system provides the highest air volume at the lowest energy consumption. Enjoy extra energy savings with integrated Variable Speed Drive technology, which automatically tunes the compressed air flow precisely to air demand.



ZB 100 VSD



The ZB module concept

For larger volume flows, multiple ZB VSD units can be connected in parallel.

- Higher availability
- Reliability through redundancy
- Wider operating range and high efficiency
- Extremely low sound pressure level
- Space-saving
- Expandable

The unique stainless steel turbo impeller with backward-curved blade design is a registered Atlas Copco patent with labyrinth seals for maximum efficiency and minimal air loss.



ZB – Turbo power



Oil-free multistage centrifugal pressure and vacuum blowers 1 to 2,600 kW / 1 to 3,600 hp

ZM 31-246

Atlas Copco's ZM oil-free multistage centrifugal blowers are working successfully in thousands of installations around the world. These reliable blowers are ideal for applications ranging from air to gas and pressure to vacuum. The ZM are equipped with all the necessary accessories such as motor, valves, filters and skid as well as local or networked control panels to provide a complete working system.

• **Extensive product choice** – Configuration options ensure we can offer the best possible solution possible to meet your need.

• **Wide application range** – ZM centrifugal blowers are working reliably in thousands of installations around the world. They are suitable both for air and gas applications and operate in pressure or vacuum configurations.

• **Complete solution** – ZM blowers are equipped with all the necessary accessories such as motor, valves, filters and skid as well as local or networked control panels to provide a complete working system matched to the application.

CUSTOMER BENEFITS


• **Durability and Performance** – Solidly constructed out of premium components they will run continuously with unbeatable cost-effectiveness.

• **Minimum maintenance requirements** – Save time and cost due to minimal downtime.



Process Control

Atlas Copco has developed complete control systems to manage entire processes. Adding a smart sequencer to automate multiple units in operation will both save time in operating, but also improve the efficiency of your entire system. These smart systems are sufficiently advanced to monitor and control your entire process such as waste-water aeration, or virtually any application that requires flow to be matched to the process requirements.



Oil-free reciprocating trunk-piston compressors, up to 351 bar (a) (5090 psia), 30 kW

DM

Atlas Copco's DM oil free reciprocating compressors will meet your needs for high pressure compression up to 351 bar(a). Compact, with very low vibration levels and a sealed crankcase, DM compressors are ideal for the compression of natural gas, processed biogas, hydrogen.

CUSTOMER BENEFITS

- **High degree of safety** – Its revolutionary “oil-less” technology guarantees that oil does not contaminate the gas. Its hermetically sealed crankcase ensures no emission of gases to the atmosphere, even gases with a low molecular weight.
- **High reliability** – Low compression ratios in the individual stages result in low thermal load and high reliability. The Scotch yoke principle means balanced forces and minimal vibration.

- **Easy installation** – Very compact, frame-mounted and incorporating anti-vibration pads, DM compressors come as complete all-in packages with a small footprint and are simple to install without the need for complex piping arrangements.

- **Low cost of ownership** due to no water consumption and high efficiency.

- **Low maintenance** – An advanced maintenance concept ensures short downtimes.

- **A wide array of solutions** – DM compressors are available for inlet pressures of 1 to 40 bars, and 2 to 5 stage configurations. They are suitable for diverse applications such as CNG refueling stations and gas applications (e.g. Ex-zone 2 or optionally Ex-zone 1).



| Technical specifications | Metric | Imperial |
|--------------------------|---|--|
| Capacity FAD | 7.5 - 61.4 l/s | 7.5 - 61.4 l/s |
| Working pressure | 1 - 350 bar(e) | 14.5 - 6483 psig |
| Installed motor power | 30 kW | 40.23 hp |
| Capacity | 27 - 203 Nm ³ /h | 16 - 124 scfm |
| Inlet pressure | 1 - 40 bar | 14.5 - 580 psi |
| Gases handled | natural gas, processed biogas, hydrogen | natural gas, processed biogas, hydrogen |

Oil-free reciprocating piston compressors, up to 45 bar (652 psig) 30-315 kW / 40-422 hp

DX / DN

Atlas Copco's DX/DN oil-free reciprocating booster is the alliance of an extremely robust design with the best of technology in terms of packaging and equipment. DX/DN is your best partner in air and nitrogen compression from 7 to 45 bars. Available as a mono-stage or two-stage machine, it perfectly suits a wide variety of requirements in terms of flow and pressures. You will appreciate its canopy for its silencing properties and you will easily adopt the concrete frame that makes installation so easy. DX/DN compressors can be fitted downstream from an Atlas Copco Z compressor to create a complete package running from 1 to 40/45 bar.

CUSTOMER BENEFITS

• **Certified 100% oil-free** – DX/DN boosters provide you with 100% pure, clean air that complies with ISO 8573-1 CLASS 0 (2010) certification. CLASS 0 means zero risk of contamination; zero risk of damaged or unsafe products; zero risk of losses from operational downtime; and zero risk of damaging your company's hard-won professional reputation.

• **Nitrogen-ready** – We adapt the piston rings and packing rings to nitrogen composition, dew point and purity. We supply DX/DN with or without a canopy (gas detection). Inlet dewpoints from -10°C/+14°F to "bone dry" gas are handled.

• **Energy savings** – DX/DN boosters are also available in Variable Speed Drive versions, allowing for 35% energy savings due to:

- Unload losses are reduced to a minimum
- Load/no load transition losses are eliminated
- Precise pressure control allows a tighter pressure band and a lower average working pressure, resulting in reduced energy consumption.

• **Easy installation** – Fitted on a concrete base-plate, the DX/DN booster comes as an all-in-one package. The compact design eliminates the need for extras and accelerates installation, saving you time and money.

• **High reliability** – Low piston speed and low interstage temperatures preserve the inner parts of the machines. The horizontal design ensures a low vibration/pulsation level for increased reliability. Design is close to API 618.

• **Advanced control and monitoring** – The advanced Elektronikon® system helps you keep control of costs by monitoring overall system performance through service indications, malfunctions alarms and safety shutdowns.

| Technical specifications | Metric | Imperial |
|--------------------------|------------------|-----------------|
| Capacity FAD | 75 - 2870 l/s | 75 - 2870 l/s |
| Working pressure | 12 - 42 bar(e) | 174 - 609 psig |
| Installed motor power | 37 - 315 kW | 50 - 422 HP |
| Capacity FAD | 271 - 10329 m³/h | 160 - 6083 cfm |
| Capacity | 250 - 9500 Nm³/h | 158 - 6000 scfm |
| Inlet pressure | 6 - 25 bar | 87 - 363 psi |
| Gases handled | air,nitrogen | air,nitrogen |



Oil-free reciprocating compressors

HX / HN

Atlas Copco's HX/HN oil-free reciprocating compressors are extremely reliable solutions for air, nitrogen, CO/CO₂, methane, hydrogen and argon. Designed for 24/24 industrial service, with minimal maintenance cost and long overhaul intervals, HX/HN compressors can work in a most efficient and cost-effective way under difficult site conditions.

CUSTOMER BENEFITS

- **Oil-free** – Thanks to their PTFE piston rings and long distance pieces, the compression chambers are perfectly oil-free. HX/HN compressors are the right solution when compressed air is in contact with the end product (drinkable water, gases).

- **Energy saving** – Reciprocating technology ensures excellent volumetric efficiency and economic operation in terms of energy.

- **Flexibility** – A wide variety of regulation systems adjust the flow rate according to the real utilization of the machine: by stepped regulation (valve unloading); by-pass valve; variable speed drive; or a combination of the above solutions.

- **High reliability** – Low piston speed and low interstage temperatures preserve the inner parts of the machines. The horizontal design ensures a low vibration/pulsation for increased reliability. Design is close to API 618.

- **Adaptability to your application** – We can adapt the machine's internal parts and material to your gas composition requirements or to different inlet pressures. We can also adapt containers for rental equipment or in complete packages including dryer, filters and control panels. HX/HN compressors can work in difficult environments: outdoor, indoor, refineries, deserts (high inlet temperatures) and sandy environments.

- **Easy maintenance** – Horizontal design – safe and comfortable for operators – long service intervals (up to 8000 h/year without service intervention).



| Technical specifications | Metric | Imperial |
|--------------------------|---|---|
| Capacity FAD | 45 - 3020 l/s | 45 - 3020 l/s |
| Working pressure | 10 - 100 bar(e) | 145 - 1450 psig |
| Installed motor power | 37 - 560 kW | 50 - 750 HP |
| Capacity FAD | 163 - 10873 m³/h | 96 - 6400 cfm |
| Capacity | 150 - 10000 Nm³/h | 94 - 6315 scfm |
| Inlet pressure | 1 - 24 bar | 14.5 - 348 psi |
| Gases handled | air, nitrogen, argon, carbon monoxide, carbon dioxide, hydrogen, argon, methane, biomethane | air, nitrogen, argon, carbon monoxide, carbon dioxide, hydrogen, argon, methane, biomethane |

Oil-free reciprocating piston compressors, up to 40 bar (580 psig), 37-275 kW / 50-368 hp

P

Atlas Copco's P oil-free reciprocating compressors are a reference in the market for reliability and low cost of ownership. They deliver high-purity oil-free air for discharge pressures between 25 and 40 bar. Sturdy and designed for continuous industrial operation, P compressors deliver air safely, constantly and at low cost. Up to 160 kW, P compressors come as very compact 3-stage machines. Above 160 kW, with the addition of an oil free screw unit in the first stage, they come as 4-stage machines. This innovative approach results in unrivalled benefits, maximizing flow in compact plug & play units.

CUSTOMER BENEFITS

- **100% oil-free** – Thanks to PTFE piston rings and long-distance pieces, the compression chambers are perfectly oil-free.
- **Maximum energy savings** – Reciprocating technology ensures excellent volumetric efficiency and economic operation in terms of energy. In addition, with the Elektronikon® controller you can adjust the required discharge pressure between 25 bar (362 psig) and 40 bar (580 psig) to reduce energy costs.
- **Advanced control and monitoring** – The advanced Elektronikon® system helps you keep control of costs by monitoring overall system performance through service indications, malfunction alarms and safety shutdowns.
- **High reliability** – Low piston speed and low inter-stage temperatures preserve the internal components. The horizontal design ensures low vibration/pulsation levels for increased reliability. Design is close to API 618.
- **Low maintenance** – The horizontal design is safe and comfortable for operators and maintenance personnel. Long service intervals reduce maintenance time and cost.
- **Easy installation** – Each P compressor is delivered as a complete package with no reassembly on site. Installation is fast, straightforward and safe. P compressors are fitted on a skid and can be installed on a suitable industrial floor with chemical bolts. This eliminates skid vibrations and preserves the motor and mechanical parts.



| Model | Discharge pressure | | Flow | | |
|----------|--------------------|------|-------|--------|-------|
| | bar(e) | psig | l/s** | m³/h** | cfm** |
| 50 Hz | | | | | |
| P 37-50 | 40 | 580 | 45 | 162 | 96 |
| P 45-50 | 40 | 580 | 58 | 209 | 123 |
| P 55-50 | 40 | 580 | 72 | 259 | 153 |
| P 65-50 | 40 | 580 | 89 | 320 | 189 |
| P 90-50 | 40 | 580 | 125 | 450 | 265 |
| P 110-50 | 40 | 580 | 159 | 572 | 337 |
| P 132-50 | 40 | 580 | 190 | 684 | 403 |
| P 160-50 | 40 | 580 | 217 | 781 | 460 |
| P 180-50 | 40 | 580 | 247 | 889 | 523 |
| P 230-50 | 40 | 580 | 328 | 1181 | 695 |
| P 275-50 | 40 | 580 | 381 | 1372 | 807 |
| 60 Hz | | | | | |
| P 37-60 | 40 | 580 | 52 | 187 | 110 |
| P 45-60 | 40 | 580 | 69 | 248 | 146 |
| P 65-60 | 40 | 580 | 90 | 324 | 191 |
| P 75-60 | 40 | 580 | 119 | 428 | 252 |
| P 90-60 | 40 | 580 | 150 | 540 | 318 |
| P 110-60 | 40 | 580 | 183 | 659 | 388 |
| P 132-60 | 40 | 580 | 205 | 738 | 434 |
| P 160-60 | 40 | 580 | 218 | 785 | 462 |
| P 180-60 | 40 | 580 | 234 | 842 | 496 |
| P 230-60 | 40 | 580 | 323 | 1163 | 684 |
| P 255-60 | 40 | 580 | 367 | 1321 | 778 |

Reference conditions

Ambient temperature & cooling water: 20°C, 68°F

Suction pressure: 1 bar(e) (14.5 psig)

Relative humidity: 0%

Reference conditions according to ISO 1217, Edition 4, Annex C stipulating the Free Air

Delivery measurement at the outlet of the package, net of all losses.

Standard limitations:

Altitude: 1000 m (3200 feet)

Standard equipment: up to 50°C (122°F) ambient temperature

Oil-free screw and reciprocating piston compressors, up to 40 bar (580 psig), 136-770 kW / 182-1032 hp

ZD

Atlas Copco's ZD is the alliance of the world renowned ZR screw compressor, which delivers quality dry air at medium pressure, and the highly efficient D booster which brings the air to 40 bar. ZD represents a quantum leap in reciprocating technology. It is a champion in energy saving and its design is revolutionary. You will appreciate its silencing canopy and its concrete baseplate that makes installation so easy. With its numerous versions and versatility, ZD brings tremendous benefits to your bottom line.

CUSTOMER BENEFITS

- **Certified 100% oil-free** – ZD compressors provide you with 100% pure, clean air that complies with ISO 8573-1 CLASS 0 (2010) certification. CLASS 0 means zero risk of contamination; zero risk of damaged or unsafe products; zero risk of losses from operational downtime; and zero risk of damaging your company's hard-won professional reputation. In 2006 Atlas Copco was the first manufacturer in the world to receive such certification on an oil-free compressor.
- **High reliability** – The ZD's reliability is based on several fundamentals. The first compression stages are rotary, which are world renowned for reliability. Air is dried at the outlet of the screw

compressor, so only dry air enters the D booster, eliminating problems linked to condensates. The D booster's horizontal design, with low vibration levels, ensures long life of internal components.

- **Maximum energy savings** – Being a 4-stage configuration, the ZD is 7% more efficient in terms of energy than the typical 3-stage configuration. In addition you can further reduce energy costs by adjusting the required discharge pressure between 25 bar (362 psig) and 40 bar (580 psig). ZD is also available in a Variable Speed Drive (VSD) version, enabling 35% energy savings. For blowing machines equipped with air recovery systems, re-injecting the air back to the booster allows further significant energy savings.
- **Advanced control and monitoring** – To maximize efficiency and reliability, the Elektronikon® controls the main drive motor and regulates system pressure within a predefined and narrow pressure band. The Elektronikon® controller can be adapted to your specific needs with extra sensors, digital contacts, fieldbus and SMS communication functions. In combination with the ES multiple compressor controller, the operation of your complete compressor room is optimized.
- **A wide array of solutions for your compressor room** – ZD allows you to manage your medium pressure and high pressure networks separately, which optimizes your investment and floor space.
- **Low maintenance** – For air-cooled versions, no external cooling system is needed, saving on investment, maintenance and water consumption.



The below data are for a discharge pressure of 40 bar (e)

| Discharge pressure 40 bar /580 PSIG | Available with | | FAD* | | | Shaft input at ref. cond. | Pressure dew point at 40 bar > to | Sound pressure level*** |
|--|-------------------------|------------------------------|----------|-----------|----------|------------------------------|---|----------------------------|
| | Low voltage motor | Medium voltage motor** | l/s | m³/h | cfm | kW | °C | dB(A) |
| 50 Hz | | | | | | | | |
| ZD 800-50 | • | | 220 | 792 | 466 | 143 | 3 | 73.7 |
| ZD 1000-50 | • | | 264 | 950 | 560 | 166 | 3 | 75.6 |
| ZD 1200-50 | • | | 334 | 1202 | 708 | 210 | 3 | 76.0 |
| ZD 1400-50 | • | | 401 | 1444 | 849 | 254 | 3 | 75.9 |
| ZD 1600-50 | • | | 445 | 1602 | 943 | 281 | 3 | 75.9 |
| ZD 2100-50 | • | • | 627 | 2257 | 1329 | 384 | 3 | 81.2 |
| ZD 2500-50 | • | • | 687 | 2473 | 1456 | 422 | 3 | 81.2 |
| ZD 2750-50 | • | • | 779 | 2804 | 1651 | 488 | 3 | 82.2 |
| ZD 3050-50 | • | • | 844 | 3038 | 1788 | 512 | 3 | 81.2 |
| ZD 3350-50 | • | • | 937 | 3373 | 1986 | 571 | 3 | 81.2 |
| ZD 3750-50 | • | • | 1074 | 3866 | 2276 | 678 | 3 | 83.1 |
| ZD 4000-50 | • | • | 1114 | 4010 | 2360 | 712 | 3 | 84.0 |
| 60 HZ | | | | | | | | |
| ZD 800-60 | • | | 235 | 846 | 498 | 153 | 3 | 73.9 |
| ZD 1000-60 | • | | 287 | 1033 | 608 | 182 | 3 | 75.7 |
| ZD 1200-60 | • | | 317 | 1141 | 672 | 200 | 3 | 76.6 |
| ZD 1400-60 | • | | 398 | 1433 | 843 | 253 | 3 | 77.3 |
| ZD 1600-60 | • | | 457 | 1645 | 968 | 288 | 3 | 75.9 |
| ZD 1900-60 | • | • | 547 | 1969 | 1159 | 389 | 3 | 80.7 |
| ZD 2300-60 | • | • | 639 | 2300 | 1354 | 489 | 3 | 82.2 |
| ZD 2500-60 | • | • | 725 | 2610 | 1536 | 441 | 3 | 81.7 |
| ZD 3100-60 | • | • | 857 | 3085 | 1816 | 520 | 3 | 81.7 |
| ZD 3500-60 | • | • | 951 | 3424 | 2016 | 585 | 3 | 83.8 |
| ZD 4000-60 | • | • | 1141 | 4108 | 2418 | 722 | 3 | 84.0 |
| VSD**** | | | | | | | | |
| ZD 1200 VSD | • | | 146/320 | 529/1152 | 311/678 | 94/208 | 3 | 77.3 |
| ZD 1400 VSD | • | | 139/382 | 500/1375 | 294/809 | 94/255 | 3 | 77.3 |
| ZD 2300 VSD | • | | 308/625 | 1109/2250 | 652/1324 | 193/397 | 3 | 83.9 |
| ZD 2800 VSD | • | | 308/738 | 1109/2657 | 652/1564 | 193/481 | 3 | 83.9 |
| ZD 3500 VSD | • | | 440/978 | 1584/3521 | 932/2072 | 270/607 | 3 | 83.9 |
| ZD 4100 VSD | • | | 440/1099 | 1584/3957 | 932/2329 | 270/699 | 3 | 83.9 |

| ZD models | Overall dimensions (machines side by side) | | |
|------------------|--|-----------|-----------|
| | A | B | C |
| 50 Hz | mm | mm | mm |
| ZD 800-50 | 3460 | 4390 | 2185 |
| ZD 1000-50 | 3900 | 4590 | 2130 |
| ZD 1200-50 | 3900 | 4590 | 2130 |
| ZD 1400-50 | 4826 | 5003 | 2083 |
| ZD 1600-50 | 4826 | 5003 | 2083 |
| ZD 2100-50 | 4886 | 5345 | 2134 |
| ZD 2500-50 | 4886 | 5345 | 2134 |
| ZD 2750-50 | 4886 | 5345 | 2134 |
| ZD 3050-50 | 5980 | 5688 | 2400 |
| ZD 3350-50 | 5980 | 5688 | 2400 |
| ZD 3750-50 | 6843 | 5885 | 2578 |
| ZD 4000-50 | 6843 | 5885 | 2578 |
| 60 HZ | | | |
| ZD 800-60 | 3460 | 4390 | 2185 |
| ZD 1000-60 | 3900 | 4590 | 2130 |
| ZD 1200-60 | 3900 | 4590 | 2130 |
| ZD 1400-60 | 3905 | 4920 | 2083 |
| ZD 1600-60 | 4826 | 5003 | 2083 |
| ZD 1900-60 | 4886 | 5345 | 2134 |
| ZD 2300-60 | 4886 | 5345 | 2134 |
| ZD 2500-60 | 4886 | 5345 | 2134 |
| ZD 3100-60 | 5980 | 5688 | 2400 |
| ZD 3500-60 | 5980 | 5688 | 2400 |
| ZD 4000-60 | 6843 | 5885 | 2578 |
| VSD**** | | | |
| ZD 1200 VSD***** | 3900 | 4590 | 2130 |
| ZD 1400 VSD | 3905 | 4920 | 2083 |
| ZD 2300 VSD | 4886 | 5345 | 2134 |
| ZD 2800 VSD | 4886 | 5345 | 2134 |
| ZD 3500 VSD | 6843 | 5885 | 2578 |
| ZD 4100 VSD | 6843 | 5885 | 2083 |

At reference conditions and according to ISO 1217.

Medium voltage motors (3 KV, 3.3 KV, 6 KV, 6.6 KV) for Japan only

A-weighted sound pressure level LpA, sound power level LwA, uncertainty + 3dB, reference 20 µPa, according to ISO 3746 (for low voltage motors)

At minimum/maximum speeds

Please consult Atlas Copco

Reference conditions:

- Inlet pressure: 1 bar(a)
- Relative air humidity: 0%
- Air inlet temperature: 20°C
- Cooling water inlet temperature: 20°C
- Nominal effective working pressure: 40 bar

ZD plus and ZD RI ranges offer numerous combinations. Please contact your local Atlas Copco Customer Centre at www.atlascopco.com for a customized selection.

Serving the automotive industry with energy efficient solutions



MEDICAL EQUIPMENT

Whether you work in a hospital, a dental practice, a veterinary lab or a clinical work environment, maximum reliability is your main priority.

To successfully perform clinical work and make sure your equipment functions effectively, you rely on ultra-clean air. Set to meet your specific demands and suit a variety of applications, Atlas Copco offers a full range of state-of-the-art solutions to produce pure medical, breathing and surgical air as well as vacuum.



**Medical air purifiers
MED / MED+**

Page 102



**Screw compressors for
medical applications
GA MED**

Page 104



**Medical Air Plant
uAIR**

Page 106



**Medical Vacuum Plant
mVAC**

Page 109



**Medical Oxygen
Plant
Oxyplant**

Page 112



**Oil-free scroll compressors
for medical applications.
SF MED**

Page 114



**Oil-free piston compressors
for medical applications
Lfx MED**

Page 115

Medical Air Purifiers

MED / MED⁺

The critical field of patient care requires ultra-clean, purified, medical air delivered to operating theaters and hospital beds with absolute reliability. The Atlas Copco MED/MED⁺ series of Medical Air Purifiers offers unique multi-stage filtration that converts regular compressed air from any type of compressor into internationally certified medical air. These innovative devices provide clean air for all your medical and surgical applications.

CUSTOMER BENEFITS

• **Assured reliability** – Built to the most exacting standards, the MED/MED⁺ series is engineered to provide certified medical air even in areas with high ambient pollution. These air purifiers ensure high air quality in 'worst case' but real-life pollution scenarios. With the assurance of Atlas Copco's excellent worldwide after-sales service, the MED series offers the complete solution for critical air environments.

• **Medically certified** – The medical sector is more tightly regulated than ever before. Atlas Copco's MED/MED⁺ air purifiers are pre-certified to international regulations including Pharmacopoeia and quality norms such as ISO 13485. Pre-certification simplifies organization and inspection by regulatory bodies, saving the hospital time and money and reducing the risk of a rework of the system to satisfy requirements. MED/MED⁺ air purifiers surpass the requirements of the most demanding standards and regulations such as:

- Medical Device Directive MDD 93/42/EEC.
- EN ISO 7396-1.
- ISO 14971.
- Health Technical Memorandums HTM 02-01 and HTM 2022.

Furthermore, they are designed and manufactured according to ISO 9001, ISO 14001 and the ISO 13485:2003 quality management system.

• **Energy-efficient** – The MED⁺ incorporates state-of-the-art energy management control with built-in purge control as standard (optionally available on the MED series). This purge control makes the purifiers more efficient, leading to energy savings of up to 90%, depending on installation and usage. The principle is simple. Although the regeneration time remains constant, the delay before switching from one tower to the other is controlled via the PDP sensor. As soon as the target PDP is reached, the dryer cycle that was on hold will resume by switching to the dry tower.

• **Assured purity** – MED/MED⁺ air purifiers provide the ultra clean air you require. Their innovative filtration system is the definitive medical air solution, while a small footprint allows you to make the most of the space available. The MED/MED⁺ offers unparalleled air purity through 7 stages of active purification.

Seven steps to quality medical air:

- A water separator to remove liquid water
- A bulk aerosol filter eliminates oil and water
- A fine coalescing filter removes even smaller particles of oil and water
- A desiccant dryer takes out any remaining water and CO₂
- Activated carbon removes gaseous impurities
- A catalyst takes care of a CO oxidation
- A bacteria filter eliminates bacteria and fine particles. This bacteria filter is an Atlas Copco PDp filter, which has been externally tested and certified as a bacterial filter.



MED/ MED⁺ 060313

| Type | Inlet pressure | | Max. inlet flow | | | Purge | Pressure drop | |
|------------------------------|----------------|------|-----------------|-------|-------|-------|---------------|------|
| | bar(e) | psig | l/s | m³/h | cfm | % | dP, mbar | psi |
| MED / MED ⁺ | | | | | | | | |
| MED7 / MED7 ⁺ | 7 | 102 | 7.0 | 25.2 | 14.8 | 19.0 | 510 | 7.4 |
| | 10 | 145 | 8.4 | 30.2 | 17.8 | 15.8 | 510 | 7.4 |
| | 13 | 188 | 9.4 | 33.8 | 19.9 | 14.1 | 510 | 7.4 |
| MED13 / MED13 ⁺ | 7 | 102 | 13.0 | 46.8 | 27.5 | 19.0 | 530 | 7.7 |
| | 10 | 145 | 15.6 | 56.2 | 33.1 | 15.8 | 530 | 7.7 |
| | 13 | 188 | 17.5 | 63.0 | 37.1 | 14.1 | 530 | 7.7 |
| MED25 / MED25 ⁺ | 7 | 102 | 25.0 | 90.0 | 53.0 | 18.0 | 560 | 8.1 |
| | 10 | 145 | 30.0 | 108.0 | 63.6 | 15.0 | 560 | 8.1 |
| | 13 | 188 | 33.8 | 121.7 | 71.6 | 13.3 | 560 | 8.1 |
| MED35 / MED35 ⁺ | 7 | 102 | 35.0 | 126.0 | 74.2 | 18.0 | 600 | 8.7 |
| | 10 | 145 | 42.0 | 151.2 | 89.0 | 15.0 | 600 | 8.7 |
| | 13 | 188 | 47.3 | 170.3 | 100.2 | 13.3 | 600 | 8.7 |
| MED50 / MED50 ⁺ | 7 | 102 | 50.0 | 180.0 | 106.0 | 19.0 | 820 | 11.9 |
| | 10 | 145 | 60.0 | 216.0 | 127.1 | 15.8 | 820 | 11.9 |
| | 13 | 188 | 67.5 | 243.0 | 143.0 | 14.1 | 820 | 11.9 |
| MED70 / MED70 ⁺ | 7 | 102 | 70.0 | 252.0 | 148.3 | 18.0 | 660 | 9.6 |
| | 10 | 145 | 84.0 | 302.4 | 178.0 | 15.0 | 660 | 9.6 |
| | 13 | 188 | 94.5 | 340.2 | 200.2 | 13.3 | 660 | 9.6 |
| MED80 / MED80 ⁺ | 7 | 102 | 80.0 | 288.0 | 169.5 | 18.0 | 700 | 10.2 |
| | 10 | 145 | 96.0 | 345.6 | 203.4 | 15.0 | 700 | 10.2 |
| | 13 | 188 | 108.0 | 388.8 | 228.9 | 13.3 | 700 | 10.2 |
| MED100 / MED100 ⁺ | 7 | 102 | 100.0 | 360.0 | 211.9 | 19.0 | 820 | 11.9 |
| | 10 | 145 | 120.0 | 432.0 | 254.3 | 15.8 | 820 | 11.9 |
| | 13 | 188 | 135.0 | 486.0 | 286.1 | 14.1 | 820 | 11.9 |
| MED145 / MED145 ⁺ | 7 | 102 | 145.0 | 522.0 | 307.3 | 19.0 | 800 | 11.6 |
| | 10 | 145 | 174.0 | 626.4 | 368.7 | 15.8 | 800 | 11.6 |
| | 13 | 188 | 195.8 | 704.9 | 414.9 | 14.1 | 800 | 11.6 |

| Type | MED | | | | | MED ⁺ | | | | |
|------------------------------|------------|------------|-----------|------------|----------------|------------------|------------|-----------|------------|----------------|
| | Weight, kg | Length, mm | Width, mm | Height, mm | NTP connection | Weight, kg | Length, mm | Width, mm | Height, mm | NTP connection |
| MED7 / MED7 ⁺ | 184 | 950 | 650 | 885 | 1/2" | 214 | 950 | 650 | 1851 | 1/2" |
| MED13 / MED13 ⁺ | 201 | 950 | 650 | 1075 | 1/2" | 231 | 950 | 650 | 1851 | 1/2" |
| MED25 / MED25 ⁺ | 245 | 950 | 650 | 1300 | 1/2" | 275 | 950 | 650 | 1851 | 1/2" |
| MED35 / MED35 ⁺ | 271 | 950 | 650 | 1545 | 1/2" | 301 | 950 | 650 | 1851 | 1/2" |
| MED50 / MED50 ⁺ | 315 | 950 | 650 | 1915 | 1" | 345 | 950 | 650 | 1858 | 1" |
| MED70 / MED70 ⁺ | 446 | 1250 | 850 | 1545 | 1" | 476 | 1250 | 850 | 1840 | 1" |
| MED80 / MED80 ⁺ | 494 | 1250 | 850 | 1915 | 1 1/2" | 524 | 1250 | 850 | 1840 | 1" |
| MED100 / MED100 ⁺ | 502 | 1250 | 850 | 1915 | 1 1/2" | 532 | 1250 | 850 | 1840 | 1" |
| MED145 / MED145 ⁺ | 620 | 1250 | 850 | 1915 | 1 1/2" | 650 | 1250 | 850 | 1856 | 1" |

Additional options

| Description | MED | MED ⁺ |
|--|-----|------------------|
| EWD on filters and water drain | ○ | ○ |
| Inlet solenoid for remote control | - | ○ |
| NPT connection | ○ | ○ |
| QDT quality indicator | ○ | ○ |
| Catalyst(CO to CO ₂) | ○ | ○ |
| CO sensor | ○ | ○ |
| CO ₂ sensor | ○ | ○ |
| O ₂ sensor | ○ | - |
| Overflow protection(nozzle) | ○ | ○ |
| AirContact and Combox-e with visualisation | - | ○ |
| Gateway(Profibus, Modbus) | - | ○ |

- : Not applicable

○ : Optional

Screw compressors for medical applications

GA MED

Designed precisely for medical applications, GA MED oil-injected compressors bring you proven reliability and Atlas Copco's latest high-efficiency compression element. You benefit from outstanding performance, flexible operation and the highest productivity, along with minimal total cost of ownership.

CUSTOMER BENEFITS

- Highest reliability** – Three premium compressor series – GA 5-11 MED, GA 5-15 VSD MED and GA 15-22 MED – are designed, manufactured and tested in accordance with ISO 9001, ISO 14001 and ISO 1217, Ed. 3, Annex C. Ensuring a long and trouble-free life at the lowest operating cost, each GA MED contains the latest generation of Atlas Copco's innovative oil-injected screw element.
- Peace of mind** – All GA MED compressors are equipped with additional safety protections. Even in case of a single fault condition, the air demand is always assured.
- VSD** – Driving down energy costs. Energy typically represents over 80% of a compressor's life cycle cost. Looking continuously to innovate and reduce customer costs, Atlas Copco pioneered Variable Speed Drive (VSD) technology in 1994. The GA 5-11 VSD MED range is the ideal solution for a fluctuating air demand. By monitoring the outlet pressure, the air flow is adjusted to the demand. Energy savings of 35% on average become a reality thanks to the high turndown ratio and the new fan saver cycle.
- Air system integration** – The GA MED can be placed where you need it. Its low noise operation and dedicated air treatment equipment ensure a healthier environment in the plant room. Moreover, all GA MED compressors are delivered ready for use, significantly reducing installation costs.
- Advanced control and monitoring** – To maximize efficiency and reliability, the Elektronikon® controls the main drive motor and regulates system pressure within a predefined and narrow pressure band. The Elektronikon® controller can be adapted to your specific needs with extra sensors, digital contacts, fieldbus, Internet and SMS communication functions. In combination with the ES multiple compressor controller, the operation of your complete compressor room is optimized.
- Integrated purity** – When partnered with a dedicated MED+ or MED air purifying system, the GA MED generates compressed air into pure breathing quality air. You rest assured at all times that the air quality delivered by the system accords to what the doctor ordered.



GA 5-22 MED

| Type | | Max.working pressure | | Capacity FAD* | | | Installed power | | Noise level | Weight | Length | Width | Height |
|-----------|-----|----------------------|------|---------------|-------|-------|-----------------|-----|-------------|--------|--------|-------|--------|
| | | bar(e) | psig | l/s | m³/h | cfm | kW | hp | dB(A) | kg | mm | mm | mm |
| 50 Hz | | | | | | | | | | | | | |
| GA 5 MED | 7.5 | 7.5 | 109 | 15.0 | 54.0 | 31.8 | 5.5 | 7.5 | 60 | 257 | 1142 | 699 | 1240 |
| | 10 | 10 | 145 | 11.7 | 42.1 | 24.8 | 5.5 | 7.5 | 60 | 257 | 1142 | 699 | 1240 |
| | 13 | 13 | 189 | 8.4 | 30.2 | 17.7 | 5.5 | 7.5 | 60 | 257 | 1142 | 699 | 1240 |
| GA 7 MED | 7.5 | 7.5 | 109 | 21.8 | 78.5 | 46.2 | 7.5 | 10 | 61 | 270 | 1142 | 699 | 1240 |
| | 10 | 10 | 145 | 17.2 | 61.9 | 36.4 | 7.5 | 10 | 61 | 270 | 1142 | 699 | 1240 |
| | 13 | 13 | 189 | 14.2 | 51.1 | 30.1 | 7.5 | 10 | 61 | 270 | 1142 | 699 | 1240 |
| GA 11 MED | 7.5 | 7.5 | 109 | 30.7 | 110.5 | 65.0 | 11 | 15 | 62 | 293 | 1142 | 699 | 1240 |
| | 10 | 10 | 145 | 26.0 | 93.6 | 55.1 | 11 | 15 | 62 | 293 | 1142 | 699 | 1240 |
| | 13 | 13 | 189 | 22.0 | 79.2 | 46.6 | 11 | 15 | 62 | 293 | 1142 | 699 | 1240 |
| GA 15 MED | 7.5 | 7.5 | 109 | 43.0 | 154.8 | 91.1 | 15 | 20 | 72 | 375 | 1285 | 680 | 932 |
| | 10 | 10 | 145 | 36.3 | 130.7 | 76.9 | 15 | 20 | 72 | 375 | 1285 | 680 | 932 |
| | 13 | 13 | 189 | 30.1 | 108.4 | 63.8 | 15 | 20 | 72 | 375 | 1285 | 680 | 932 |
| GA 18 MED | 7.5 | 7.5 | 109 | 52.5 | 189.0 | 111.2 | 18.5 | 25 | 73 | 395 | 1285 | 680 | 932 |
| | 10 | 10 | 145 | 44.0 | 156.6 | 92.2 | 18.5 | 25 | 73 | 395 | 1285 | 680 | 932 |
| | 13 | 13 | 189 | 37.2 | 133.9 | 78.8 | 18.5 | 25 | 73 | 395 | 1285 | 680 | 932 |
| GA 22 MED | 7.5 | 7.5 | 109 | 60.2 | 216.7 | 127.6 | 22 | 30 | 74 | 410 | 1285 | 680 | 932 |
| | 10 | 10 | 145 | 51.7 | 186.1 | 109.5 | 22 | 30 | 74 | 410 | 1285 | 680 | 932 |
| | 13 | 13 | 189 | 45.0 | 162.0 | 95.3 | 22 | 30 | 74 | 410 | 1285 | 680 | 932 |
| 60 Hz | | | | | | | | | | | | | |
| GA 5 MED | 100 | 7.4 | 107 | 15.0 | 54.0 | 31.8 | 5.5 | 7.5 | 60 | 257 | 1142 | 699 | 1240 |
| | 150 | 10.8 | 157 | 11.7 | 42.1 | 24.8 | 5.5 | 7.5 | 60 | 257 | 1142 | 699 | 1240 |
| | 175 | 12.5 | 181 | 8.5 | 30.6 | 18.0 | 5.5 | 7.5 | 60 | 257 | 1142 | 699 | 1240 |
| GA 7 MED | 100 | 7.4 | 107 | 21.0 | 75.6 | 44.5 | 7.5 | 10 | 61 | 270 | 1142 | 699 | 1240 |
| | 150 | 10.8 | 157 | 17.2 | 61.9 | 36.4 | 7.5 | 10 | 61 | 270 | 1142 | 699 | 1240 |
| | 175 | 12.5 | 181 | 14.2 | 51.1 | 30.1 | 7.5 | 10 | 61 | 270 | 1142 | 699 | 1240 |
| GA 11 MED | 100 | 7.4 | 107 | 30.4 | 109.4 | 64.4 | 11 | 15 | 62 | 293 | 1142 | 699 | 1240 |
| | 150 | 10.8 | 157 | 24.9 | 89.6 | 52.8 | 11 | 15 | 62 | 293 | 1142 | 699 | 1240 |
| | 175 | 12.5 | 181 | 22.0 | 79.2 | 46.6 | 11 | 15 | 62 | 293 | 1142 | 699 | 1240 |
| GA 15 MED | 100 | 7.4 | 107 | 42.5 | 153.0 | 90.1 | 15 | 20 | 72 | 375 | 1285 | 680 | 932 |
| | 150 | 10.8 | 157 | 35.8 | 128.9 | 75.9 | 15 | 20 | 72 | 375 | 1285 | 680 | 932 |
| | 175 | 12.5 | 181 | 29.3 | 105.5 | 62.1 | 15 | 20 | 72 | 375 | 1285 | 680 | 932 |
| GA 18 MED | 100 | 7.4 | 107 | 51.3 | 184.7 | 108.7 | 18.5 | 25 | 73 | 395 | 1285 | 680 | 932 |
| | 150 | 10.8 | 157 | 43.3 | 155.9 | 91.7 | 18.5 | 25 | 73 | 395 | 1285 | 680 | 932 |
| | 175 | 12.5 | 181 | 37.8 | 136.1 | 80.1 | 18.5 | 25 | 73 | 395 | 1285 | 680 | 932 |
| GA 22 MED | 100 | 7.4 | 107 | 60.6 | 218.2 | 128.4 | 22 | 30 | 74 | 410 | 1285 | 680 | 932 |
| | 150 | 10.8 | 157 | 50.7 | 182.5 | 107.4 | 22 | 30 | 74 | 410 | 1285 | 680 | 932 |

GA 5-22 MED

| Type | Max.working pressure | | Capacity FAD* | | | Installed power | | Noise level | Weight | Length | Width | Height |
|---------------|----------------------|------|---------------|------------|-----------|-----------------|-----|-------------|--------|--------|-------|--------|
| | bar(e) | psig | l/s | m³/h | cfm | kW | hp | dB(A) | kg | mm | mm | mm |
| 50 / 60 Hz | | | | | | | | | | | | |
| GA 5 VSD MED | 7.5 | 109 | 5.7-15.0 | 20.5-54.0 | 12.1-31.8 | 5.5 | 7.5 | 62 | 278 | 1395 | 699 | 1240 |
| | 10 | 145 | 7.1-13.2 | 25.6-47.5 | 15.0-28.0 | 5.5 | 7.5 | 62 | 278 | 1395 | 699 | 1240 |
| | 13 | 188 | 8.9-10.0 | 32.0-36.0 | 18.9-21.2 | 5.5 | 7.5 | 62 | 278 | 1395 | 699 | 1240 |
| GA 7 VSD MED | 7.5 | 109 | 4.9-20.3 | 14.4-73.0 | 10.4-43.0 | 7.5 | 10 | 64 | 280 | 1395 | 699 | 1240 |
| | 10 | 145 | 7.2-16.8 | 25.9-60.5 | 15.3-35.6 | 7.5 | 10 | 64 | 280 | 1395 | 699 | 1240 |
| | 13 | 188 | 5.1-13.8 | 23.0-49.7 | 10.8-29.2 | 7.5 | 10 | 64 | 280 | 1395 | 699 | 1240 |
| GA 11 VSD MED | 7.5 | 109 | 6.5-30.7 | 23.4-110.5 | 13.8-65.0 | 11 | 15 | 66 | 293 | 1395 | 699 | 1240 |
| | 10 | 145 | 8.7-24.1 | 31.3-86.8 | 18.4-51.1 | 11 | 15 | 66 | 293 | 1395 | 699 | 1240 |
| | 13 | 188 | 7.9-20.7 | 28.4-74.5 | 16.7-43.9 | 11 | 15 | 66 | 293 | 1395 | 699 | 1240 |
| GA 15 VSD MED | 7.5 | 109 | 9.1-37.1 | 32.8-133.6 | 19.3-78.6 | 7.5 | 10 | 69 | 300 | 1395 | 699 | 1240 |
| | 10 | 145 | 8.8-30.9 | 31.7-111.2 | 18.6-65.5 | 7.5 | 10 | 69 | 300 | 1395 | 699 | 1240 |
| | 13 | 188 | 8.5-24.8 | 30.6-89.3 | 18.0-52.5 | 7.5 | 10 | 69 | 300 | 1395 | 699 | 1240 |

* Unit performance measured according to ISO 1217, Annex C, latest edition.

** Mean noise level measured at a distance of 1 m according to ISO 2151; tolerance 3 dB(A).

Reference conditions:

- Absolute inlet pressure 1 bar (14.5 psi)
- Intake air temperature 20°C, 68°F

FAD is measured at the following working pressures:

- 7.5 bar versions at 7 bar(e)
- 10 bar versions at 9.5 bar(e)
- 13 bar versions at 12.5 bar(e)

Maximum working pressure for VSD machines:

- 13 bar(e) (188 psig)

Medical Air Plant

uAIR

Atlas Copco introduces a new range of Medical Air Plants, consisting of 2-6 dedicated compressors, two air purifiers and the Medical Central controller. Medical Air Plant are available both for medical air and surgical air applications and are designed for continuous operation with frequent start/stop.

Medically certified

Atlas Copco's uAir Medical Air Plant are pre-certified to international regulations including Pharmacopoeia and quality norms such as ISO 13485. Pre-certification simplifies organization and inspection by regulatory bodies, saving the hospital time and money. Medical Air Plant comply with the requirements of the most demanding medical standards and regulations such as:

| | |
|--|-------------------------|
| Medical Device Directive MDD 93/42/EEC | ISO 14971 |
| EN ISO 7396-1 | HTM 02-01 and HTM 2022. |


ES-Medical central controller

The advanced ES-Medical central controller supervises the complete medical installation (including compressors, dryers and vessels) and is specially designed to make plant complying with medical regulations.

- Full compliance with ISO7396-1, Chapter #6 "Monitoring and Alarm signals"
- Monitoring "Medical" and "Surgical" air lines
- Full integration with Building Management System and external Alarms systems
- Remote monitoring and connectivity functions
- Already preconfigured and tested
- Plug and play
- Internet-based visualization using a simple Ethernet connection
- Increased reliability, new safety function implemented: Emergency Force Local, internal logging and others
- Easy readout of the CO / CO₂ / flow sensors



ES-Medical central controller



Medical Air Plant

uAIR Medical Air Plant (7-145 l/s / 15-307 cfm)

According to ISO 7396-1 three sources of supply should be foreseen. For this reason there are two compressors and one dryer reserved as a backup.

50 Hz

| Type | Pressure, bar | Plant flow, ISO7396-1 | | Compressors | | Dryers | | Min. vessel | |
|-----------------------|---------------|-----------------------|--------|-------------|-------|---------|-------|-------------|------|
| | | l/s | l/m | Type | Q-ty | Type | Q-ty | Volume | Q-ty |
| 4/8 | 7.1 | 426 | GA5-10 | 1(+2) | MED7* | 1(+1) | 250 | 2 | 2 |
| | 4/8 | 13.4 | 804 | GA7-10 | 1(+2) | MED13* | 1(+1) | 250 | 2 |
| | 4/8 | 21.5 | 1290 | GA11-10 | 1(+2) | MED25* | 1(+1) | 250 | 2 |
| | 4/8 | 30 | 1800 | GA15-10 | 1(+2) | MED35* | 1(+1) | 500 | 2 |
| | 4/8 | 35.7 | 2142 | GA18-10 | 1(+2) | MED35* | 1(+1) | 500 | 2 |
| | 4/8 | 42.2 | 2532 | GA22-10 | 1(+2) | MED50* | 1(+1) | 500 | 2 |
| | 4/8 | 50.5 | 3030 | GA15-10 | 2(+2) | MED50* | 1(+1) | 500 | 2 |
| | 4/8 | 60 | 3600 | GA15-10 | 2(+2) | MED70* | 1(+1) | 500 | 2 |
| | 4/8 | 81.6 | 4896 | GA22-10 | 2(+2) | MED80* | 1(+1) | 500 | 2 |
| | 4/8 | 146.5 | 8790 | GA18-10 | 4(+2) | MED145* | 1(+1) | 500 | 2 |
| | 4/8 | 168.2 | 10092 | GA22-10 | 4(+2) | MED145* | 1(+1) | 500 | 2 |
| uAIR-GF 4 / 11 bar | 4/11 | 7.7 | 462 | GA5-13 | 1(+2) | MED7* | 1(+1) | 250 | 2 |
| | 4/11 | 11.7 | 702 | GA7-13 | 1(+2) | MED13* | 1(+1) | 250 | 2 |
| | 4/11 | 15.1 | 906 | GA11-13 | 1(+2) | MED13* | 1(+1) | 250 | 2 |
| | 4/11 | 25.6 | 1536 | GA15-13 | 1(+2) | MED25* | 1(+1) | 250 | 2 |
| | 4/11 | 29.3 | 1758 | GA18-13 | 1(+2) | MED25* | 1(+1) | 500 | 2 |
| | 4/11 | 30.9 | 1854 | GA18-13 | 1(+2) | MED35* | 1(+1) | 500 | 2 |
| | 4/11 | 38.7 | 2322 | GA22-13 | 1(+2) | MED35* | 1(+1) | 500 | 2 |
| | 4/11 | 41 | 2460 | GA15-13 | 2(+2) | MED35* | 1(+1) | 250 | 2 |
| | 4/11 | 50.7 | 3042 | GA15-13 | 2(+2) | MED50* | 1(+1) | 250 | 2 |
| | 4/11 | 77.4 | 4644 | GA22-13 | 2(+2) | MED70* | 1(+1) | 500 | 2 |
| | 4/11 | 81.9 | 4914 | GA18-13 | 3(+2) | MED70* | 1(+1) | 500 | 2 |
| | 4/11 | 116 | 6960 | GA22-13 | 3(+2) | MED100* | 1(+1) | 500 | 2 |
| | 4/11 | 152.4 | 9144 | GA22-13 | 4(+2) | MED145* | 1(+1) | 500 | 2 |

According to ISO 7396-1 three source of supply should be foreseen.

For this purpose in our plant we reserve two compressors and one additional dryer as a backup.

Another configurations and flow can be created by simple entering requirements in Medical Calculation Tool.

Tool available on web site: <http://www.atlascopco.com/Medical>

uAIR Medical Air Plant (7-145 l/s / 15-307 cfm)

60 Hz

| Type | Pressure, bar | Plant flow, ISO7396-1 | | | | | | Min. vessel | |
|-----------------------|---------------|-----------------------|-------|----------|-------|---------|--------|-------------|------|
| | | l/s | l/m | Type | Q-ty* | Type | Q-ty * | Volume | Q-ty |
| uAIR-GF 4 / 8 bar | 4/8 | 7.6 | 456 | GA5-150 | 1(+2) | MED7* | 1(+1) | 250 | 2 |
| | 4/8 | 13.1 | 786 | GA7-150 | 1(+2) | MED13* | 1(+1) | 250 | 2 |
| | 4/8 | 20.4 | 1224 | GA11-150 | 1(+2) | MED25* | 1(+1) | 250 | 2 |
| | 4/8 | 25.5 | 1530 | GA15-150 | 1(+2) | MED25* | 1(+1) | 500 | 2 |
| | 4/8 | 29.5 | 1770 | GA15-150 | 1(+2) | MED35* | 1(+1) | 500 | 2 |
| | 4/8 | 35.7 | 2142 | GA18-150 | 1(+2) | MED35* | 1(+1) | 500 | 2 |
| | 4/8 | 41.2 | 2472 | GA22-150 | 1(+2) | MED50* | 1(+1) | 500 | 2 |
| | 4/8 | 50.5 | 3030 | GA15-150 | 2(+2) | MED50* | 1(+1) | 500 | 2 |
| | 4/8 | 59 | 3540 | GA15-150 | 2(+2) | MED70* | 1(+1) | 500 | 2 |
| | 4/8 | 81.6 | 4896 | GA22-150 | 2(+2) | MED80* | 1(+1) | 500 | 2 |
| | 4/8 | 88.4 | 5304 | GA15-150 | 3(+2) | MED100* | 1(+1) | 500 | 2 |
| | 4/8 | 145.7 | 8742 | GA18-150 | 4(+2) | MED145* | 1(+1) | 500 | 2 |
| | 4/8 | 168.2 | 10092 | GA22-150 | 4(+2) | MED145* | 1(+1) | 500 | 2 |
| uAIR-GF 4 / 11 bar | 4/11 | 7.2 | 432 | GA5-175 | 1(+2) | MED7* | 1(+1) | 250 | 2 |
| | 4/11 | 11.7 | 702 | GA7-175 | 1(+2) | MED13* | 1(+1) | 250 | 2 |
| | 4/11 | 15.1 | 906 | GA11-175 | 1(+2) | MED13* | 1(+1) | 250 | 2 |
| | 4/11 | 24.8 | 1488 | GA15-175 | 1(+2) | MED25* | 1(+1) | 250 | 2 |
| | 4/11 | 29.3 | 1758 | GA18-175 | 1(+2) | MED25* | 1(+1) | 500 | 2 |
| | 4/11 | 31.5 | 1890 | GA18-175 | 1(+2) | MED35* | 1(+1) | 500 | 2 |
| | 4/11 | 40.3 | 2418 | GA22-175 | 1(+2) | MED35* | 1(+1) | 500 | 2 |
| | 4/11 | 41 | 2460 | GA15-175 | 2(+2) | MED35* | 1(+1) | 250 | 2 |
| | 4/11 | 49.1 | 2946 | GA15-175 | 2(+2) | MED50* | 1(+1) | 250 | 2 |
| | 4/11 | 58 | 3480 | GA18-175 | 2(+2) | MED50* | 1(+1) | 500 | 2 |
| | 4/11 | 80.6 | 4836 | GA22-175 | 2(+2) | MED70* | 1(+1) | 500 | 2 |
| | 4/11 | 81.9 | 4914 | GA18-175 | 3(+2) | MED70* | 1(+1) | 500 | 2 |
| | 4/11 | 116 | 6960 | GA22-175 | 3(+2) | MED100* | 1(+1) | 500 | 2 |
| | 4/11 | 158.8 | 9528 | GA22-175 | 4(+2) | MED145* | 1(+1) | 500 | 2 |

According to ISO 7396-1, three sources of supply should be foreseen.

For this purpose, we recommend two compressors as a backup.

More configurations and flows can be created by simply entering your requirements into the online Medical Calculation Tool:

<http://www.atlascopco.com/Medical>

Medical Vacuum Plant

mVAC

Atlas Copco's mVAC Medical Vacuum Systems consist of 2 to 6 air-cooled, oil-lubricated rotary vane type vacuum pumps and a central controller with an intelligent graphical user interface. They provide a highly reliable medical vacuum (suction) for a variety of applications, mainly in operating theaters and intensive care, emergency and respiratory units. The mVAC system offers (multiple) backup supply in case of failure of individual functional components.

reliable vacuum to meet all its needs. Furthermore, using AIRConnect™ Visualization you can connect to extensive monitoring and status information to get the most out of your mVAC system.

- **Energy-efficient** – The mVAC incorporates a multi-pump arrangement to better match the flow demand. In this arrangement, the advanced Elektronikon® Graphic controller maximizes energy efficiency by controlling the individual vacuum pumps and regulating the overall vacuum. Uniform wear is ensured at all times.

- **Cost-effective** – Our unique Elektronikon® control system gives you the means to effectively manage and optimize your mVAC system. Device status is monitored in real time, required services are delivered rapidly, breakdowns can be prevented and downtime shortened. In short, it provides all you need to keep operational costs to a minimum.

- **Easy installation** – All interconnection piping and copper connections are supplied as an integral part of the mVAC system. This 'plug and play' approach makes installation even easier.

CUSTOMER BENEFITS

- **Solid reliability** – The carbon composite material of our mVAC pumps will not break down or wear out like laminated blades. Even if the central controller should fail, every pump still has its own controller.

- **Highly connectable** – Up to six vacuum pumps can be connected in one mVAC system to ensure that even a large hospital always has a



mVAC 250-8000

| HTM 2022 - 50 Hz | | | | | | | | |
|------------------|---|---|-----------------------|---------------|-----------------------------------|-----------------------------------|-------------------------|--------------------------|
| Type | System FAA @ -600 mbar(e) referred to 0 bar(e), 20°C | System flow (referred to suction pressure) | Number of pumps | Pump power | Dimensions* (filters included) | Weight** (filters included) | Number of vessels | Total vessel capacity |
| | l/min | m³/h | | kW | LxWxH (mm) | kg | | l |
| mVAC-250-DH | 250 | 40 | 2 | 1.1 | 2040x980x1650 | 540 | 1 | 500 |
| mVAC-500-TH | 500 | 79 | 3 | 1.1 | 2300x980x1650 | 650 | 1 | 500 |
| mVAC-660-TH | 660 | 105 | 3 | 1.5 | 2400x980x1900 | 800 | 1 | 1000 |
| mVAC-1000-TH | 1000 | 159 | 3 | 2.2 | 2400x980x1900 | 860 | 1 | 1000 |
| mVAC-1500-Q | 1500 | 238 | 4 | 2.2 | 1830x980x1700 | 750 | 1 | 1500 |
| mVAC-2560-T | 2560 | 406 | 3 | 5.5 | 2600x1200x1600 | 1365 | 2 | 3000 |
| mVAC-3840-Q | 3840 | 609 | 4 | 5.5 | 2600x1200x1990 | 1700 | 2 | 4000 |
| mVAC-4950-Q | 4950 | 786 | 4 | 7.5 | 3400x1250x1700 | 1800 | 3 | 6000 |
| mVAC-6000-P | 6000 | 952 | 5 | 7.5 | 4100x1250x1700 | 2050 | 3 | 6000 |
| mVAC-6600-P | 6600 | 1047 | 5 | 7.5 | 4100x1250x1700 | 2050 | 4 | 8000 |
| mVAC-8000-H | 8000 | 1270 | 6 | 7.5 | 4100x1250x1990 | 2360 | 4 | 8000 |

mVAC 300-9200

| HTM 2022 - 60 Hz | | | | | | | | |
|------------------|---|---|-----------------------|---------------|-----------------------------------|-----------------------------------|-------------------------|--------------------------|
| Type | System FAA @ -600 mbar(e) referred to 0 bar(e), 20°C | System flow (referred to suction pressure) | Number of pumps | Pump power | Dimensions* (filters included) | Weight** (filters included) | Number of vessels | Total vessel capacity |
| | l/min | m³/h | | kW | LxWxH (mm) | kg | | l |
| mVAC-300-DH | 300 | 48 | 2 | 1.5 | 2040x980x1650 | 540 | 1 | 500 |
| mVAC-500-TH | 500 | 79 | 3 | 1.5 | 2300x980x1650 | 650 | 1 | 500 |
| mVAC-800-TH | 800 | 127 | 3 | 2.2 | 2400x980x1900 | 800 | 1 | 1000 |
| mVAC-1200-T | 1200 | 190 | 3 | 3.0 | 1910x980x1700 | 610 | 1 | 1500 |
| mVAC-1860-Q | 1860 | 295 | 4 | 3.0 | 2200x1200x1700 | 1050 | 1 | 2000 |
| mVAC-3000-T | 3000 | 476 | 3 | 7.5 | 2600x1200x1600 | 1365 | 2 | 3000 |
| mVAC-4500-Q | 4500 | 714 | 4 | 7.5 | 3400x1250x1990 | 1825 | 3 | 4500 |
| mVAC-5850-Q | 5850 | 928 | 4 | 9.2 | 3400x1250x1990 | 1800 | 3 | 6000 |
| mVAC-7800-P | 7800 | 1238 | 5 | 9.2 | 4100x1250x1990 | 2160 | 4 | 8000 |
| mVAC-9200-H | 9200 | 1460 | 6 | 9.2 | 4100x1250x1990 | 2360 | 5 | 10000 |

* When available, horizontal vessels are included.

** Packaging included, vertical vessels excluded.

Additional options

| |
|--|
| AirConnect™ Visualization and Notification package |
| Customized software setting for different norms (HTM / ISO / AS) |
| Oil level switch |
| Synthetic oil |
| Painted vessels |

mVAC 250-6600

| HTM 02-01 / ISO 7396-150 Hz | | | | | | | | |
|-----------------------------|---|---|-----------------------|---------------|-----------------------------------|-----------------------------------|-------------------------|--------------------------|
| Type | System FAA @ -600 mbar(e) referred to 0 bar(e), 20°C | System flow (referred to suction pressure) | Number of pumps | Pump power | Dimensions* (filters included) | Weight** (filters included) | Number of vessels | Total vessel capacity |
| | l/min | m³/h | | kW | LxWxH (mm) | kg | | l |
| mVAC-250-TH | 250 | 40 | 3 | 1.1 | 2300x980x1650 | 650 | 1 | 500 |
| mVAC-330-TH | 330 | 52 | 3 | 1.5 | 2300x980x1650 | 690 | 1 | 500 |
| mVAC-500-TH | 500 | 79 | 3 | 2.2 | 2400x980x1650 | 750 | 1 | 500 |
| mVAC-660-Q | 660 | 105 | 4 | 1.5 | 1910x980x1430 | 660 | 2 | 1000 |
| mVAC-1000-Q | 1000 | 159 | 4 | 2.2 | 1910x980x1700 | 740 | 2 | 1000 |
| mVAC-1280-T | 1280 | 203 | 3 | 5.5 | 2200x1100x1450 | 1025 | 3 | 1500 |
| mVAC-2560-Q | 2560 | 406 | 4 | 5.5 | 2600x1200x1700 | 1625 | 2 | 3000 |
| mVAC-3300-Q | 3300 | 524 | 4 | 7.5 | 2600x1200x1700 | 1625 | 2 | 4000 |
| mVAC-3840-P | 3840 | 609 | 5 | 5.5 | 3300x1200x1990 | 1950 | 2 | 4000 |
| mVAC-4950-P | 4950 | 786 | 5 | 7.5 | 4100x1250x1700 | 2050 | 3 | 6000 |
| mVAC-6000-H | 6000 | 952 | 6 | 7.5 | 4100x1250x1700 | 2250 | 3 | 6000 |
| mVAC-6600-H | 6600 | 1047 | 6 | 7.5 | 4100x1250x1700 | 2250 | 4 | 8000 |

mVAC 300-7800

| HTM 02-01 / ISO 7396-160 Hz | | | | | | | | |
|-----------------------------|---|---|-----------------------|---------------|-----------------------------------|-----------------------------------|-------------------------|--------------------------|
| Type | System FAA @ -600 mbar(e) referred to 0 bar(e), 20°C | System flow (referred to suction pressure) | Number of pumps | Pump power | Dimensions* (filters included) | Weight** (filters included) | Number of vessels | Total vessel capacity |
| | l/min | m³/h | | kW | LxWxH (mm) | kg | | l |
| mVAC-300-TH | 300 | 48 | 3 | 1.5 | 2300x980x1650 | 650 | 1 | 500 |
| mVAC-400-TH | 400 | 63 | 3 | 2.2 | 2300x980x1650 | 690 | 1 | 500 |
| mVAC-620-T | 620 | 98 | 3 | 3.0 | 1910x980x1430 | 750 | 2 | 1000 |
| mVAC-800-Q | 800 | 127 | 4 | 2.2 | 1910x980x1700 | 660 | 2 | 1000 |
| mVAC-1200-Q | 1200 | 190 | 4 | 3 | 1910x980x1430 | 740 | 2 | 2000 |
| mVAC-1500-T | 1500 | 238 | 3 | 7.5 | 2200x1100x1450 | 1025 | 2 | 2000 |
| mVAC-3000-Q | 3000 | 476 | 4 | 7.5 | 2600x1200x1700 | 1640 | 2 | 3000 |
| mVAC-3900-Q | 3900 | 619 | 4 | 9.2 | 2600x1200x1990 | 1700 | 2 | 4000 |
| mVAC-4500-P | 4500 | 714 | 5 | 7.5 | 4100x1250x1990 | 2075 | 3 | 4500 |
| mVAC-5850-P | 5850 | 928 | 5 | 9.2 | 4100x1250x1700 | 2050 | 3 | 6000 |
| mVAC-7800-H | 7800 | 1238 | 6 | 9.2 | 4100x1250x1990 | 2360 | 4 | 8000 |

* When available, horizontal vessels are included.

** Packaging included, vertical vessels excluded.



mVAC-500-TH



mVAC-1280-T



mVAC-6000-H

Medical Oxygen Plant

Oxyplant

Medical oxygen is an irreplaceable requirement for many basic medical procedures and treatments, and an invaluable adjunct to many other treatments. It is one of the drugs medical facilities cannot be without.

Cylinder Oxygen is bulky, which makes transportation difficult and even dangerous. Oxygen in liquid form is both voluminous and has very limited storage life. A solution of these inconveniences is to produce oxygen on site using Atlas Copco's new Medical Oxygen Plant (Oxyplant). A key element of Oxyplant is our PSA module which separates the oxygen from ambient air and allows the facility to have a stand alone oxygen production capability right on the facility site.

CUSTOMER BENEFITS

- Modules are individually controlled and monitored for simplex or duplex PSA arrangements.
- Modules can be operated at ideal pressure for oxygen production without affecting the delivery pressure.
- Full electronic controls display output and all control parameters, allowing you control of each module.
- Noise is minimized and the safety of workers can be protected against nitrogen exhaust.
- Standard installed oxygen analyzers continuously monitor oxygen quality giving you peace of mind.
- Offering (multiple) backup supply in case of a failure in individual functional components
- One-stop-shop for medical solutions. We manufacture all main components ourselves(compressors, dryers, filters and PSA generators).
- Ambient temperature up to 45°C.

KEY FEATURES

- Typical Medical Oxygen Plant consisting of two independent oxygen generation lines, bank of cylinders and high pressure booster.
- Plant setup according to ISO10083 Figure A.5.
- Oxygen quality according to European Pharmacopeia Oxygen 93%.



| Type | Capacity [Nm ³ /h] | Compressor | Refrigerant dryer | Air filter sets | Air buffer Vessel | Oxygen generator | Buffer, | Oxygen filter sets (PDp & Sterile) | | Booster | Filling station |
|-------------|----------------------------------|-------------------|-------------------|-----------------|-------------------|------------------|--------------------------|------------------------------------|--------|---------------------------------------|-----------------|
| | | | | | | | incl. pressure regulator | | | | |
| Oxyplant 4 | 3.4 | GA5 | FX6 | 17 | 150L | OGP4 | 150L | 9 | Type 1 | 2-stage, up to 3.2Nm ³ /h | 4 outlets |
| Oxyplant 6 | 5.5 | GA7 | FX7 | 32 | 150L | OGP6 | 150L | 9 | Type 1 | 2-stage, up to 3.2Nm ³ /h | 4 outlets |
| Oxyplant 8 | 7.2 | GA11 | FX9 | 32 | 280L | OGP8 | 280L | 9 | Type 1 | 3-stage, up to 7.2Nm ³ /h | 4 outlets |
| Oxyplant 10 | 8.8 | GA11 ⁺ | FX10 | 44 | 500L | OGP10 | 500L | 9 | Type 1 | 3-stage, up to 8.8Nm ³ /h | 4 outlets |
| Oxyplant 14 | 13.2 | GA15 ⁺ | FX11 | 60 | 500L | OGP14 | 500L | 9 | Type 1 | 3-stage, up to 13.2Nm ³ /h | 4 outlets |
| Oxyplant 18 | 18 | GA18 ⁺ | FX12 | 60 | 500L | OGP18 | 500L | 9 | Type 1 | 4-stage, up to 18Nm ³ /h | 6 outlets |
| Oxyplant 20 | 19 | GA22 ⁺ | FX15 | 120 | 1000L | OGP20 | 1000L | 17 | Type 2 | 4-stage, up to 19Nm ³ /h | 6 outlets |
| Oxyplant 29 | 27.1 | GA30 ⁺ | FX16 | 120 | 1000L | OGP29 | 1000L | 17 | Type 2 | 4-stage, up to 27Nm ³ /h | 10 outlets |
| Oxyplant 45 | 42 | GA45 ⁺ | FX18 | 150 | 2000L | OGP45 | 2000L | 32 | Type 2 | 4-stage, up to 27Nm ³ /h | 10 outlets |
| Oxyplant 55 | 51 | GA55 ⁺ | FX19 | 175 | 2000L | OGP55 | 2000L | 32 | Type 2 | 4-stage, up to 27Nm ³ /h | 10 outlets |

Specifications:

- Unit outlet oxygen purity 93%
- 4-5 bar(e) outlet pressure
- 400V 50Hz & 380V 60Hz

Set-up include:

- 2 compressors
- 2 refrigerant dryers

- 2 filter sets (PD/DD/QDT)
- 2 air buffer vessels
- 2 oxygen generators,
- 2 oxygen buffer vessels
- 2 pressure regulator, PDp and sterile filter
- 1 booster
- 1 filling station

Oxygen Standards

Atlas Copco Medical Oxygen Plant is able to produce oxygen compliant with the European Pharmacopeia (EurPh) monograph for Oxygen 93 or the United States Pharmacopeia (USP) monograph for Oxygen 93. Both standards were created explicitly to permit the use of PSA produced oxygen.

| Parameters | Eur Ph | ISO10083 | USP | Laboratory Assay of Oxyplant |
|-----------------|------------|----------|------------|------------------------------|
| | Oxygen 93% | | Oxygen 93% | |
| Oxygen | 93.0% ± 3 | >90% | >90.0 | 90-95% |
| | | | < 96.0% | |
| Carbon monoxide | 5 ppm | 5 ppm | 0.00% | 0,11 ppm |
| Carbon dioxide | 300 ppm | 300 ppm | 0.03% | 0,82 ppm |
| Water | 67 ppm | 67 ppm | N/S | 3 ppm |

Compliance

Today's medical arena is more tightly regulated than ever. Atlas Copco's medical oxygen generators are manufactured according to Medical Device - Quality Management System ISO 13485:2003 and ISO 9001. It could be also certified as ISO 10083 compliant.

Oil-free scroll compressors for medical applications

SF MED

Your medical practice or laboratory processes depend on 100% clean compressed air to safeguard your patient's health and protect your valuable equipment. Designed for the specific needs of medical practices, clinical laboratories and other medical point-of-use surgical air applications, SF MED air compressor solutions provide the 100% oil-free, dry and filtered air that you need. In addition, they offer reliable performance, unsurpassed purity and lifetime with minimal maintenance.

- **User-friendly** – SF MED compressors are easy to operate and offer extremely low noise and vibration levels.

- **Perfectly hygienic and aseptic environment.**

- **Easy to maintain due to full front access.**

CUSTOMER BENEFITS

- **Easy installation at point of use** – SF MED solutions fit into any space or setting thanks to their compact design. A totally integrated, pre-assembled set-up minimizes installation time and costs.

- **Certified 100% oil-free air** – SF MED compressors provide 100% pure, clean air, complying with ISO 8573-1 CLASS 0 (2010) certification. CLASS 0 means zero risk of contamination; zero risk of damaged or unsafe products; zero risk of losses from operational downtime; and zero risk of damaging your company's hard-won professional reputation. In 2006, Atlas Copco was the first manufacturer in the world to receive such certification for an oil-free compressor.



| Technical data | Metric | Imperial |
|--------------------------|---------------|-------------------|
| Weight | 115 - 532 kg | 253 - 1173 lbs |
| Motor power | 1.5 - 3.7 kW | 2 - 5 HP |
| Maximum working pressure | 8 bar(e) | 116 psig |
| Capacity FAD | 5.7 - 14 cfm | 5.7 - 14 cfm |
| Capacity FAD | 2.7 - 6.7 l/s | 0.16 - 0.4 m³/min |
| Noise level | 53 - 57 dB(A) | 53 - 57 dB(A) |

Oil-free piston compressors for medical applications

LFx MED

Your medical practice or laboratory processes depend on 100% clean compressed air to safeguard your patient's health and protect your valuable equipment. Designed for the low air demands of medical practices, clinical laboratories and other medical point-of-use surgical air applications, LFx MED air compressor solutions provide the 100% oil-free, ultra-dry and filtered air that you need. In addition, they offer unmatched performance, durability and lifetime with minimal maintenance.

CUSTOMER BENEFITS

- **Easy installation at point of use** – LFx MED solutions fit into any space or setting thanks to their compact design. A totally integrated, pre-assembled set-up minimizes installation time and costs.
- **Solid reliability** – Through durable engineering and tests, the LFx MED guarantees the generation of 50% more air as well as a 50% longer lifetime compared to similar products on the market.

- **Simple to use** – LFx MED compressors are easy to operate and offer extremely low noise and vibration levels.
- **Perfectly hygienic and aseptic environment.**
- **Easy to maintain due to full front access.**
- **Full compliance** – LFx MED systems are pre-certified to simplify your certification process on installation. They are designed and manufactured according to ISO 9001, ISO 14001 and the ISO 13485:2003 quality management system, and surpass the requirements of the most demanding standards and regulations such as:
 - Medical Device Directive MDD 93/42/EEC
 - European pharmacopoeia
 - EN ISO 7396-1
 - ISO 14971
 - Health Technical Memorandums HTM 02-01 and HTM 2022 (as part of a system)
 - Class 0 certificate



| Technical data | Metric | Imperial |
|--------------------------|-----------------|--------------------|
| Weight | 47 - 65 kg | 104 - 143 lbs |
| Motor power | 0.55 - 1.5 kW | 0.75 - 2 HP |
| Maximum working pressure | 8 bar(e) | 116 psig |
| Capacity FAD | 2.16 - 5.36 cfm | 2.16 - 5.36 cfm |
| Capacity FAD | 1.02 - 2.53 l/s | 0.06 - 0.15 m³/min |
| Noise level | 61 - 64 dB(A) | 61 - 64 dB(A) |

Custom solutions from Atlas Copco – used all over the world

Compressors for railway, marine and ski slope applications

Atlas Copco compressors have an almost infinite number of potential applications. As well as being used in trade and industry, compressors from Atlas Copco are ideal for use on trains, trams, subways and ships, or can be employed as reliable and economical air compressors for snowmaking. Such applications call for compressors with a special degree of versatility and expertise.

... on railways

Designed for the toughest environments: On locomotives, railcars and trams, they can brake, open and close doors and raise and lower the pantographs. They are totally reliable, even under the toughest conditions, and are specially designed and built to match customer requirements.

- GAR screw compressors with up to 37 kW rated motor power
- SFR scroll compressors with up to 6.1 kW rated motor power
- LFXR piston compressors with up to 1.5 kW rated motor power
- LFR/LTR/LGR - oil-lubricated and oilfree piston compressors with up to 9.4 kW rated motor power



Download a QR Reader and scan the code for more information on our railway offerings.

<http://www.atlascopco.com/railway>



SFR

... at sea

They are ideal for use as ships' starting air compressors and are available with many different certifications. From 2.2 to 315 kW rated motor power, with 30 bar working pressure and volume flows of 2 to 781 l/s. Atlas Copco also offers the right compressors for use in working air applications on ships.

- MAS GA screw compressors with up to 315 kW rated motor power
- LT piston compressors with up to 15 kW rated motor power
- SF - Scroll compressors (up to 15kW)
- ZT- Oil-free tooth compressors (up to 45 kW)



Download a QR Reader and scan the code for more information on our marine offerings.

<http://www.atlascopco.com/marine>



GA 160 W

... on ski slopes

Set up as centralized or decentralized compressors, they supply compressed air for snow cannons, which turn water into snow. The compressors help create the right conditions on the slope and, naturally, are oil-free.

- LE piston compressors with up to 7.5 kW rated motor power
- LF piston compressors with up to 7.5 kW rated motor power



LF

AIR AND GAS TREATMENT

A dry compressed air system is essential to maintain the reliability of production processes and the quality of end products. Untreated air can cause corrosion in pipe work, premature failure of pneumatic equipment, and product spoilage. Atlas Copco offers a full range of air and gas dryers , filters, and generators that will protect your systems and processes.

Compressed air treatment

Do you already know which compressor you want, but you're just missing the appropriate processing systems? A dryer for example? On the following pages you'll find a wide selection to suit every requirement, partly adapted to our compressors, to make your whole system more efficient. This is particularly sensible if the refrigerant or desiccant dryer is directly integrated in the compressor casing. This saves you time and floor space, and you'll have less installation expenditure.

Intake air from the compressor always contains moisture. With the compression and subsequent cooling, the compressed air is always saturated to 100% with moisture. Anyone who sends compressed air through a pipe network needs to protect against corrosion in order to prevent machine failures or production waste.

As a result, each compressed air system includes at least one dryer and/or other processing components, such as filters or condensate separators. Different drying technologies are available: refrigerant dryers for simple applications and desiccant dryers for high to extremely high standards.

Refrigerant dryers are very reliable and economical. They work with built-in refrigerant compressors, which cool the air via heat exchangers, separate the resulting condensate and produce dry air with a pressure dewpoint of 3°C, so your systems are reliably protected from corrosion.

For industries, in which – for example – products have to be supplied or dried with compressed air, desiccant dryers are recommended and may even be indispensable. The air is not just cooled, the moisture is actively withdrawn via a desiccant, the so-called adsorption material. As soon as the desiccant is saturated, no more moisture can be withdrawn and it must be regenerated.

In order to guarantee a continuous air supply, rather than interrupting your manufacturing processes, desiccant dryers work with two containers or at least one container, which is separated into two sections.

The air is dried in one, and the desiccant is regenerated in the other. Desiccant dryers are available with pressure dewpoints of –20°C, –40°C and even –70°C. This means the residual moisture of the processed air only condenses below the specified temperatures, such as, for example, below –70°C. This type of dry air is required in the production of electronic components, such as computer hard drives, etc.

Obviously, these applications have a higher energy requirement than simple applications, and, just like compressors, this also applies to dryers: The biggest cost factor in the lifecycle is power, not the initial investment. But whatever your requirements, and whether you choose a refrigerant or desiccant dryer, we can assure you that all of our compressed air processing systems are so well designed and so efficient, that your utility bills will be less of an issue in the coming years.

DRYING PROCESS

Water is a problem for your compressed air system. It can corrode and freeze compressed air pipes and tools, disturb your production process, and contaminate products. Thus, it can significantly increase maintenance costs and reduce productivity.

The drying process is the only way to remove almost all the moisture from the compressed air.



**Refrigerant air dryers, 7-1236 l/s,
14-2516 cfm**

FX

Page 122



**Blower purge desiccant air
dryers, 100-3000 l/s, 212-6360
cfm**

BD+

Page 132



**Refrigerant air dryers, 6-4000 l/s,
13-8480 cfm**

FD

Page 124



**Heat of compression rotary
drum dryers, 88-2500 l/s, 185-
5297 cfm**

MD

Page 136



**Heatless desiccant air dryers,
32-1600 l/s, 68-3392 cfm**

CD

Page 128



**Heat of compression rotary
drum dryers, 88-2500 l/s,
185-5297 cfm**

ND

Page 138



**Heatless desiccant air dryers,
1-1400 l/s, 2-2968 cfm**

CD+

Page 130



**Heat-of-compression desiccant
air dryers, 1400-7000 l/s, 2970-
14840 cfm**

XD+

Page 141



**Blower purge desiccant air dryers,
360-1600 l/s, 763-3392 cfm**

BD

Page 132



Membrane dryers

SD

Page 142



**Purification units for breathable air
BAP / BAP⁺**

Page 144



DD⁺, DDp⁺, PD⁺, PDp⁺, QD⁺ filters

(Standard and high pressure)

Compressed air filters

Page 153



**PSA nitrogen generators, capacity
1-300 l/s, flow 4-1100 Nm³/h, purity
95-99.999%
NGP series**

Page 147



**WSD 25-750 / WD 80 / EWD
50-1500**

Water separators and drains

Page 156



**Membrane nitrogen generators,
capacity 1.4-140 l/s, flow 5-500
Nm³/h, purity 95-99%
NGM 1-7**

Page 149



**Activated carbon tower, 20-310
l/s, 42-657 cfm**

QDT

Page 158



**PSA oxygen generators,
capacity 0.6-56 l/s, flow 2-200
Nm³/h, purity 90-95%
OGP series**

Page 151



**Oil/water separator systems for
the condensate treatment**

OSC and OSD

Page 160

Refrigerant air dryers, 7-1236 l/s, 14-2516 cfm

FX

Dry, quality air is vital for long-term, troublefree operation of your processes. Atlas Copco's FX dryers protect your products and systems against damage or corrosion. They remove moisture from compressed air with a dew point as low as 3°C/37,4°F. Easy to install, simple to operate and reliable, they provide the dry air you need, allowing you to concentrate on your core business.

CUSTOMER BENEFITS

- **Reliability** – FX dryers offer a steady pressure dew point down to 3°F/37,4°F, with no freezing of condensed moisture, and no chance of moisture entering the compressed air system. They are constructed from generously sized, quality components. A simple and proven design is backed up by an effective control system (hot gas bypass) to ensure reliable performance.
- **Reduced energy costs** – Designed to ensure a low pressure drop, the FX dryer gives you dry air at low cost.
- **Easy installation** – Thanks to a plug and play concept, installation of your FX dryer could not be easier. You only need a single electrical connection. All units are pre-commissioned and self-regulating.
- **Low maintenance** – Long service intervals, few component replacements and an ergonomic design for fast access to key components combine to reduce the need for maintenance to an absolute minimum.



EFFICIENCY



Substantial cost savings

- Increased reliability and service life of tools and machines.
- Fewer leaks in the piping, resulting in lower energy consumption.
- Fewer repairs to tools, machines and piping.
- Few inconvenient machine breakdowns and interruptions.



FX 8

FX 1 – 21 Refrigeration Dryers

| Type | Maximum working pressure | Volume flow ¹⁾ | | Pressure loss | Pressure dewpoint | Power consumption | Refrigerant | Inlet/outlet connections | Approx. weight | Dimensions L x W x H |
|-----------------------------------|--------------------------|---------------------------|--------|---------------|-------------------|-------------------|-------------|--------------------------|----------------|----------------------|
| | bar | l/s | m³/min | mbar | approx. °C | kW | | | kg | mm |
| FX – Refrigerant dryer air-cooled | | | | | | | | | | |
| FX 1 | 16 | 6 | 0.36 | 150 | 3 | 0.13 | R 134 a | G 3/4" | 19 | 350 x 500 x 484 |
| FX 2 | 16 | 10 | 0.60 | 250 | 3 | 0.16 | R 134 a | G 3/4" | 19 | 350 x 500 x 484 |
| FX 3 | 16 | 14 | 0.84 | 250 | 3 | 0.19 | R 134 a | G 3/4" | 20 | 350 x 500 x 484 |
| FX 4 | 16 | 20 | 1.20 | 250 | 3 | 0.27 | R 134 a | G 3/4" | 25 | 350 x 500 x 484 |
| FX 5 | 16 | 30 | 1.80 | 300 | 3 | 0.28 | R 134 a | G 3/4" | 27 | 350 x 500 x 484 |
| FX 6 | 16 | 39 | 2.34 | 320 | 3 | 0.61 | R 404 a | G 1" | 51 | 370 x 500 x 804 |
| FX 7 | 13 | 50 | 3.00 | 320 | 3 | 0.67 | R 404 a | G 1" | 51 | 370 x 500 x 804 |
| FX 8 | 13 | 60 | 3.60 | 180 | 3 | 0.79 | R 404 a | G 1 1/2" | 61 | 460 x 560 x 829 |
| FX 9 | 13 | 68 | 4.08 | 250 | 3 | 0.87 | R 404 a | G 1 1/2" | 68 | 460 x 560 x 829 |
| FX 10 | 13 | 87 | 5.22 | 180 | 3 | 1.07 | R 404 a | G 1 1/2" | 73 | 460 x 560 x 829 |
| FX 11 | 13 | 108 | 6.48 | 200 | 3 | 1.19 | R 404 a | G 1 1/2" | 90 | 580 x 560 x 939 |
| FX 12 | 13 | 128 | 7.68 | 270 | 3 | 1.45 | R 404 a | G 1 1/2" | 90 | 580 x 560 x 939 |
| FX 13 | 13 | 167 | 10.02 | 250 | 3 | 1.80 | R 410 a | G 2" | 128 | 735 x 898 x 1002 |
| FX 14 | 13 | 200 | 12.00 | 300 | 3 | 2.10 | R 410 a | G 2" | 146 | 735 x 898 x 1002 |
| FX 15 | 13 | 250 | 15.00 | 300 | 3 | 2.65 | R 410 a | G 2" | 158 | 735 x 898 x 1002 |
| FX 16 | 13 | 300 | 18.00 | 300 | 3 | 3.50 | R 410 a | G 2" | 185 | 735 x 898 x 1002 |
| FX 17 | 13 | 400 | 24.00 | 250 | 3 | 4.70 | R404 a | G 3" | 325 | 1020 x 1023 x 1560 |
| FX 18 | 13 | 500 | 30.00 | 300 | 3 | 5.30 | R404 a | G 3" | 335 | 1020 x 1023 x 1560 |
| FX 19 | 13 | 583 | 34.98 | 350 | 3 | 6.40 | R404 a | G 3" | 350 | 1020 x 1023 x 1560 |
| FX 19.5 | 13 | 750 | 45 | 250 | 3 | 6.7 | R404 a | DN 125 | 380 | 1123 x 1020 x 1560 |
| FX 20 | 13 | 833 | 49.98 | 300 | 3 | 8.40 | R404 a | DN 125 | 550 | 1020 x 2099 x 1560 |
| FX 21 | 13 | 1166 | 69.96 | 250 | 3 | 11.80 | R404 a | DN 125 | 600 | 1020 x 2099 x 1560 |

¹⁾ Volume flow based on 20°C, 1 bar. Reference conditions: working pressure 7 bar, compressed air temperature 35°C, ambient temperature 25°C, relative humidity on entry 100%, pressure dewpoint 3°C.

Refrigerant air dryers, 6-4000 l/s, 13-8480 cfm

FD

The compressed air you use must be clean and dry. Moisture can cause corrosion in pipe work, premature failure of pneumatic equipment, or product spoilage. Based on direct expansion technology with cycling, non-cycling and Variable Speed variants, Atlas Copco's FD dryers remove moisture from compressed air with a dewpoint as low as $+3^{\circ}\text{C}/+37.4^{\circ}\text{F}$. They are highly energy-efficient, easy to install, and among the most environmentally friendly and quietest in their class. Most importantly, they deliver dry air to protect your air system and finished products.

CUSTOMER BENEFITS

- **High reliability** – Atlas Copco's FD refrigerant dryers eliminate system failures, production downtime and costly repairs by removing moisture from compressed air with a pressure dewpoint as low as $+3^{\circ}\text{C}/+37.4^{\circ}\text{F}$. Separate components undergo severe endurance tests while the unique design of the heat exchanger significantly improves dryer lifetime. Advanced control functions ensure dry air at all conditions and prevent freezing at low loads.

- **Maximum energy savings** – Atlas Copco's refrigerant dryers incorporate energy-saving features that cut your carbon footprint. Incorporating unique heat exchanger technology and Saver Cycle Control, the FD ensures a low pressure drop of typically below 0.2 bar/2.9 psi and minimal energy consumption. Integrated Variable Speed Drive (VSD) technology variants offer even further energy savings by automatically tuning the energy input to the precise demand. The FD offers an extremely low total cost of ownership.

- **Easy installation** – FD dryers have a small footprint thanks to an innovative all-in-one design. Delivered ready for use, installation is straightforward, minimizing costly production downtime. On some models, in- and outlet connections are positioned on top of the unit, enabling installation against a wall.

- **Environmentally friendly** – Enclosed in a sound suppression canopy to reduce noise levels, FD dryers stand out by being among the most environmentally friendly and quietest in their class. They fully comply with ISO 14001 standards and Montreal Protocol regulations, and use CFC-free refrigerants to prevent any damage to the earth's ozone layer. FD dryers have an ozone depletion potential of zero.



Reducing energy costs

The refrigerant dryers from Atlas Copco have different integrated energy-saving functions, which improve the CO_2 balance and reduce costs. Thanks to a unique heat exchange technology and saver-cycle control, the FD series provides a lower pressure drop of an average of under 0.2 bar at minimal energy requirement. The speed regulation (VSD, Variable Speed Drive) allows additional energy savings because the energy consumption is automatically tailored to the requirements. This results in low costs over the entire service life.



FD 185



FD 5–2000



FD 120–285 and FD 610–1010



FD 95

Saver-Cycle control

To save energy, FD dryers from Atlas Copco adapt their working cycle to the actual load, so the ambient temperature and the pressure dewpoint are constantly monitored and compared. With lower heat input, the refrigerant compressor stops, significantly reducing the power consumption.

| Type | Maximum working pressure | Volume flow ¹⁾ | | Pressure loss | Pressure dewpoint | Power consumption | Refrigerant | Inlet/outlet connections | Approx. weight | Dimensions L × W × H |
|------------------------------------|--------------------------|---------------------------|--------|---------------|-------------------|-------------------|-------------|--------------------------|----------------|----------------------|
| | bar | l/s | m³/min | mbar | approx. °C | kW | | | kg | mm |
| FD – Refrigerant dryer, air-cooled | | | | | | | | | | |
| FD 5 | 16 | 6 | 0.36 | 70 | 3 | 0.20 | R 134 a | G 3/4" | 27 | 496 × 377 × 461 |
| FD 10 | 16 | 10 | 0.60 | 110 | 3 | 0.20 | R 134 a | G 3/4" | 27 | 496 × 377 × 461 |
| FD 15 | 16 | 15 | 0.90 | 120 | 3 | 0.33 | R 134 a | G 3/4" | 32 | 496 × 377 × 461 |
| FD 20 | 16 | 20 | 1.20 | 120 | 3 | 0.41 | R 134 a | G 3/4" | 34 | 496 × 377 × 461 |
| FD 25 | 16 | 25 | 1.50 | 170 | 3 | 0.41 | R 134 a | G 3/4" | 34 | 496 × 377 × 461 |
| FD 30 | 16 | 30 | 1.80 | 250 | 3 | 0.41 | R 134 a | G 3/4" | 34 | 496 × 377 × 461 |
| FD 40 | 16 | 40 | 2.40 | 200 | 3 | 0.48 | R 134 a | G 1" | 57 | 688 × 389 × 604 |
| FD 50 | 16 | 50 | 3.00 | 200 | 3 | 0.69 | R 134 a | G 1" | 58 | 688 × 389 × 604 |
| FD 60 | 13 | 60 | 3.60 | 220 | 3 | 0.63 | R 134 a | G 1" | 80 | 726 × 482 × 804 |
| FD 70 | 13 | 70 | 4.20 | 220 | 3 | 0.87 | R 134 a | G 1" | 81 | 726 × 482 × 804 |
| FD 95 | 13 | 95 | 5.70 | 220 | 3 | 1.18 | R 134 a | G 1" | 87 | 726 × 482 × 804 |
| FD 120 | 14 | 120 | 7.20 | 110 | 3 | 1.00 | R 410 a | G 1 1/2" | 170 | 836 × 661 × 982 |
| FD 150 | 14 | 150 | 9.00 | 150 | 3 | 1.00 | R 410 a | G 1 1/2" | 170 | 836 × 661 × 982 |
| FD 185 | 14 | 185 | 11.10 | 220 | 3 | 1.40 | R 410 a | G 2 1/2" | 185 | 916 × 802 × 982 |
| FD 220 | 14 | 220 | 13.20 | 120 | 3 | 1.70 | R 410 a | G 2 1/2" | 197 | 916 × 802 × 982 |
| FD 245 | 14 | 245 | 14.70 | 180 | 3 | 1.90 | R 410 a | G 2 1/2" | 197 | 916 × 802 × 982 |
| FD 285 | 14 | 285 | 17.10 | 220 | 3 | 2.10 | R 410 a | G 2 1/2" | 197 | 916 × 802 × 982 |
| FD 310 – 40°C | 14 | 310 | 18.60 | 230 | 3 | 2.80 | R 410 a | G 3" | 198 | 850 × 986 × 1190 |
| FD 310 – 46°C | 14 | 310 | 18.60 | 230 | 3 | 2.80 | R 410 a | G 3" | 200 | 850 × 986 × 1190 |
| FD 310 – 50°C | 14 | 310 | 18.60 | 230 | 3 | 2.90 | R 410 a | G 3" | 202 | 850 × 986 × 1190 |
| FD 410 – 40°C | 14 | 410 | 24.60 | 210 | 3 | 3.00 | R 410 a | G 3" | 220 | 850 × 986 × 1375 |
| FD 410 – 46°C | 14 | 410 | 24.60 | 210 | 3 | 4.60 | R 410 a | G 3" | 240 | 850 × 1250 × 1375 |
| FD 410 – 50°C | 14 | 410 | 24.60 | 210 | 3 | 4.80 | R 410 a | G 3" | 290 | 850 × 1525 × 1375 |
| FD 510 – 40°C | 14 | 510 | 30.60 | 200 | 3 | 4.50 | R 410 a | G 3" | 260 | 850 × 1250 × 1375 |
| FD 510 – 46°C | 14 | 510 | 30.60 | 200 | 3 | 6.40 | R 410 a | G 3" | 310 | 850 × 1525 × 1375 |
| FD 510 – 50°C | 14 | 510 | 30.60 | 200 | 3 | 6.90 | R 410 a | G 3" | 315 | 850 × 1525 × 1375 |
| FD 610 | 14 | 610 | 36.60 | 170 | 3 | 4.80 | R 410 a | DN 100 | 320 | 1040 × 1060 × 1580 |
| FD 760 | 14 | 760 | 45.60 | 170 | 3 | 5.30 | R 410 a | DN 100 | 380 | 1245 × 1060 × 1580 |
| FD 870 | 14 | 870 | 52.20 | 150 | 3 | 6.60 | R 410 a | DN 150 | 400 | 1245 × 1060 × 1580 |
| FD 1010 | 14 | 1010 | 60.60 | 170 | 3 | 7.40 | R 410 a | DN 150 | 460 | 1580 × 1060 × 1580 |
| FD 1250 | 13 | 1250 | 75.00 | 240 | 3 | 8.30 | R 404 a | DN 150 | 860 | 1350 × 1640 × 1880 |
| FD 1400 | 13 | 1400 | 84.00 | 240 | 3 | 8.50 | R 404 a | DN 200 | 940 | 1350 × 1640 × 1880 |
| FD 1600 | 13 | 1600 | 96.00 | 130 | 3 | 13.6 | R 404 a | DN 200 | 1280 | 1350 × 1640 × 1880 |
| FD 2000 | 13 | 2000 | 120.00 | 220 | 3 | 20.00 | R 404 a | DN 200 | 1345 | 1350 × 1640 × 1880 |

¹⁾ Volume flow based on 20°C, 1 bar. Reference conditions: working pressure 7 bar, compressed air temperature 35°C, ambient temperature 25°C, relative humidity on entry 100%, pressure dewpoint 3°C.

| Type | Maximum working pressure | Volume flow ¹⁾ | | Pressure loss | Pressure dewpoint | Power consumption | Refrigerant | Inlet/outlet connections | Approx. weight | Dimensions L × W × H |
|--|--------------------------|---------------------------|--------|---------------|-------------------|-------------------|-------------|--------------------------|----------------|----------------------|
| | bar | l/s | m³/min | mbar | approx. °C | kW | | | kg | mm |
| FD – Refrigerant dryer, air-cooled, 20-bar versions | | | | | | | | | | |
| FD 5–20 | 20 | 7.3 | 0.44 | 40 | 3 | 0.20 | R 134 a | G 3/4" | 27 | 496 × 377 × 461 |
| FD 10–20 | 20 | 14.4 | 0.87 | 90 | 3 | 0.20 | R 134 a | G 3/4" | 27 | 496 × 377 × 461 |
| FD 15–20 | 20 | 21.8 | 1.31 | 100 | 3 | 0.33 | R 134 a | G 3/4" | 32 | 496 × 377 × 461 |
| FD 20–20 | 20 | 27.6 | 1.65 | 100 | 3 | 0.41 | R 134 a | G 3/4" | 34 | 496 × 377 × 461 |
| FD 25–20 | 20 | 34.8 | 2.09 | 140 | 3 | 0.70 | R 134 a | G 3/4" | 34 | 496 × 377 × 461 |
| FD 30–20 | 20 | 43.5 | 2.61 | 200 | 3 | 0.70 | R 134 a | G 1" | 34 | 496 × 377 × 461 |
| FD 40–20 | 20 | 58.0 | 3.48 | 160 | 3 | 0.70 | R 134 a | G 1" | 57 | 688 × 389 × 604 |
| FD 50–20 | 20 | 72.5 | 4.35 | 160 | 3 | 0.70 | R 134 a | G 1" | 58 | 688 × 389 × 604 |
| FD – Refrigerant dryer, water-cooled | | | | | | | | | | |
| FD 310W | 14 | 310 | 18.6 | 230 | 3 | 2.00 | R 410 a | G 3" | 180 | 850 × 986 × 1190 |
| FD 410W | 14 | 410 | 24.6 | 210 | 3 | 2.40 | R 410 a | G 3" | 240 | 850 × 1250 × 1375 |
| FD 510W | 14 | 510 | 30.6 | 200 | 3 | 4.10 | R 410 a | G 3" | 260 | 850 × 1250 × 1375 |
| FD 610W | 14 | 610 | 36.6 | 170 | 3 | 3.10 | R 410 a | DN 100 | 350 | 1245 × 1060 × 1580 |
| FD 760W | 14 | 760 | 45.6 | 170 | 3 | 3.60 | R 410 a | DN 100 | 360 | 1245 × 1060 × 1580 |
| FD 870W | 14 | 870 | 52.2 | 150 | 3 | 4.50 | R 410 a | DN 150 | 370 | 1245 × 1060 × 1580 |
| FD 1010W | 14 | 1010 | 60.6 | 170 | 3 | 5.10 | R 410 a | DN 150 | 380 | 1245 × 1060 × 1580 |
| FD 1250W | 13 | 1250 | 75.0 | 240 | 3 | 8.30 | R 404 a | DN 150 | 860 | 1350 × 1640 × 1880 |
| FD 1400W | 13 | 1400 | 84.0 | 200 | 3 | 8.50 | R 404 a | DN 200 | 940 | 1350 × 1640 × 1880 |
| FD 1600W | 13 | 1600 | 96.0 | 200 | 3 | 13.60 | R 404 a | DN 200 | 1280 | 1350 × 1640 × 1880 |
| FD 2000W | 13 | 2000 | 120.0 | 250 | 3 | 20.00 | R 404 a | DN 200 | 1345 | 1350 × 1640 × 1880 |

¹⁾ Volume flow based on 20°C, 1 bar. Reference conditions: working pressure 7 bar, compressed air temperature 35°C, ambient temperature 25°C, relative humidity on entry 100%, pressure dewpoint 3°C.


FD Refrigerant air dryers, 6-4000 l/s, 13-8480 cfm



FD 4000 W VSD


Integrated speed regulation (VSD)

Some FD refrigerant dryers have a built-in VSD control, which adapts the energy consumption to the actual used compressed air, significantly reducing energy consumption. Compared to conventional dryers, this saves up to 70%. The compressor runs with variable speeds to maintain a stable dewpoint. The speed of the refrigerant compressor is adapted to the inlet conditions, so less energy is needed for lower loads.



Functional diagram for the FD-VSD series

- | | |
|----------------------------------|-------------------------------|
| 1 Liquid separator | 7 Water separator |
| 2 Refrigerant compressor | 8 Air heat exchanger |
| 3 Condenser | 9 Outlet for dried air |
| 4 Refrigerant dryer/filter | a Inlet for moist air |
| 5 Control device | b Elektronikon® |
| 6 Air/refrigerant heat exchanger | (control and regulating unit) |



FD 2000 VSD

FD VSD Refrigeration dryers - with speed control

| Type | Maximum working pressure | Volume flow ¹⁾ | | Pressure loss | Pressure dewpoint | Power consump- tion | Refrigerant | Inlet/outlet connections | Approx. weight | Dimensions L × W × H |
|--|--------------------------------|---------------------------|-------------|------------------|----------------------|---------------------------|-------------|-----------------------------|-------------------|-------------------------|
| | bar | l/s | m³/min | mbar | approx. °C | kW | | | kg | mm |
| FD – VSD series – Refrigerant dryer, air-cooled | | | | | | | | | | |
| FD 760 VSD | 14 | up to 760 | up to 45.6 | 170 | 3 | 5.3 | R 410 a | DN 100 | 380 | 1245 × 1060 × 1580 |
| FD 870 VSD | 14 | up to 870 | up to 52.2 | 150 | 3 | 5.8 | R 410 a | DN 150 | 400 | 1245 × 1060 × 1580 |
| FD 1010 VSD | 14 | up to 1010 | up to 60.6 | 170 | 3 | 6.6 | R 410 a | DN 150 | 460 | 1580 × 1060 × 1580 |
| FD 1250 VSD | 13 | up to 1250 | up to 75.0 | 240 | 3 | 10.1 | R 404 a | DN 200 | 750 | 1300 × 1350 × 1880 |
| FD 1400 VSD | 13 | up to 1400 | up to 84.0 | 240 | 3 | 9.1 | R 404 a | DN 200 | 820 | 1300 × 1350 × 1880 |
| FD 1600 VSD | 13 | up to 1600 | up to 96.0 | 130 | 3 | 13.3 | R 404 a | DN 200 | 1110 | 2120 × 1350 × 1880 |
| FD 2000 VSD | 13 | up to 2000 | up to 120.0 | 220 | 3 | 19.5 | R 404 a | DN 200 | 1155 | 2120 × 1350 × 1880 |
| FD – VSD series – Refrigerant dryer, water-cooled | | | | | | | | | | |
| FD 760 W VSD | 14 | up to 760 | up to 45.6 | 90 | 3 | 3.3 | R 410 a | DN 100 | 410 | 1580 × 1060 × 1580 |
| FD 870 W VSD | 14 | up to 870 | up to 52.2 | 120 | 3 | 4.2 | R 410 a | DN 150 | 410 | 1580 × 1060 × 1580 |
| FD 1010 W VSD | 14 | up to 1010 | up to 60.6 | 170 | 3 | 5.6 | R 410 a | DN 150 | 410 | 1580 × 1060 × 1580 |
| FD 1250 W VSD | 13 | up to 1250 | up to 75.0 | 240 | 3 | 9.9 | R 404 a | DN 200 | 750 | 1300 × 1350 × 1880 |
| FD 1400 W VSD | 13 | up to 1400 | up to 84.0 | 240 | 3 | 8.5 | R 404 a | DN 200 | 820 | 1300 × 1350 × 1880 |
| FD 1600 W VSD | 13 | up to 1600 | up to 96.0 | 130 | 3 | 9.3 | R 404 a | DN 200 | 1110 | 2120 × 1350 × 1880 |
| FD 2000 W VSD | 13 | up to 2000 | up to 120.0 | 220 | 3 | 13.5 | R 404 a | DN 200 | 1155 | 2120 × 1350 × 1880 |
| FD 2400 W VSD | 13 | up to 2400 | up to 144.0 | 230 | 3 | 18.3 | R 404 a | DN 200 | 1180 | 2000 × 1350 × 1880 |
| FD 4000 W VSD | 13 | up to 4000 | up to 240.0 | 220 | 3 | 28.9 | R 404 a | DN 250 | 2010 | 2200 × 2300 × 1910 |

¹⁾ Volume flow based on 20°C, 1 bar. Reference conditions: working pressure 7 bar, compressed air temperature 35°C, ambient temperature 25°C, relative humidity on entry 100%, pressure dewpoint 3°C.

Heatless desiccant air dryers, 32-1600 l/s, 68-3392 cfm

CD

Atlas Copco's CD heatless desiccant air dryers are designed for a long lifetime of reliable operation. Using only compressed air as a purge, they provide you with the clean, dry air you need to extend the life of your equipment and ensure the quality of your end product. They are available in a range of sizes with a pressure dewpoint as low as -40°C/-40°F, and come in an IP54 protected cubicle.

CUSTOMER BENEFITS

• **Reliability** – Atlas Copco's CD desiccant dryers eliminate system failures, production downtime and costly repairs by removing moisture from compressed air with a pressure dewpoint as low as -40°C/-40°F.

• **Reduced energy costs** – Optimally sized pipes and valves ensure a limited pressure drop. Options are available to increase the efficiency and reduce the energy consumption of your CD dryer.

• **Space-saving** – The CD's all-in-one design leads to a small footprint, saving valuable space in your facility.

• **Efficient control** – The control system – fitted in an IP54 cubicle for easy cabling and safety – ensures proper operation of your CD dryer.

• **Low maintenance** – Delivered ready for use, installation of your CD dryer is straightforward, cutting costly production downtime. All internal components are easily accessible to facilitate maintenance. The use of high-grade desiccant and high-quality valves results in three-year maintenance intervals.



CD 3+ – 1400+



CD 630

| Type | Inlet volume flow: 7 bar [100 psig] | | Pressure loss (without filter) | Filter sizes (recommended) | | | Weight | Dimensions | | |
|--|--|-------|-----------------------------------|----------------------------|---------------------|-------------|--------|------------|------|------|
| | | | | Pre-filter | | Afterfilter | | mm | | |
| | l/s | m³/hr | bar | 1 µm 0.1 ppm | 0.01 µm 0.01 ppm | 1 µm | kg | L | W | H |
| Heatless desiccant air dryers, 360-1600 l/s, 763-3392 cfm. | | | | | | | | | | |
| CD 360 | 360 | 1296 | 0.19 | DD310* | PD310+ | DDp310+ | 650 | 1173 | 1116 | 1854 |
| CD 480 | 480 | 1728 | 0.14 | DD425+ | PD425+ | DDp425+ | 970 | 1776 | 988 | 2549 |
| CD 630 | 630 | 2268 | 0.14 | DD630 | PD630 | DDp520 | 1240 | 1884 | 843 | 2604 |
| CD 970 | 970 | 3492 | 0.12 | DD970 | PD970 | DDp780 | 2010 | 2359 | 1039 | 2643 |
| CD 1260 | 1260 | 4536 | 0.12 | DD1260 | PD1260 | DDp1260 | 2470 | 2472 | 1039 | 2636 |
| CD 1600 | 1600 | 5760 | 0.11 | DD1600 | PD1600 | DDp1600 | 3560 | 2693 | 1428 | 2576 |

Heatless desiccant air dryers, 1-1400 l/s, 2-2968 cfm

CD⁺

Atlas Copco's CD⁺ heatless desiccant dryers protect your systems and processes. Their robust design ensures they operate with total reliability and deliver a constant, stable dewpoint in full load conditions and even during a temporary overload. The result is dry and clean compressed air for a broad range of industrial applications. Technological innovations ensure that this air is produced reliably and cost-effectively. Our CD⁺ dryers are available in a range of sizes with a guaranteed dewpoint down to -40°C/-40°F (optionally -70°C/-100°F), and come in an IP54 protected cubicle.

CUSTOMER BENEFITS

• **High reliability** – Atlas Copco's CD⁺ desiccant dryers eliminate system failures, production downtime and costly repairs by removing moisture from compressed air with a pressure dewpoint as low as -70°C/-100°F. Up to 30% desiccant overfill and the long lifetime of the desiccant further enhance reliability.

• **Maximum energy savings** – CD⁺ dryers incorporate energy-saving features that cut your carbon footprint. A low pressure drop below 0.2 bar/2.9 psi drives down energy costs. Dewpoint sensing and control adapts the energy consumption to the real load of the dryer.

• **Easy installation** – Your CD⁺ dryer is delivered ready for use with silencers, sensors and the control unit already wired and connected.

• **Advanced control and monitoring** – The advanced Elektronikon® control and monitoring system takes continuous care of your CD⁺ dryer to ensure optimal efficiency.

• **Minimum maintenance** – All internal components are easily accessible to facilitate maintenance. The use of high-grade desiccant and durable valves extends maintenance intervals beyond the standard three years.

• **Durability** – A proven, rugged design for the switching valves, the most important moving components in the dryer, significantly improves the lifetime of your CD⁺ dryer.




CD 185⁺



CD 630



CD 25⁺



Heatless desiccant air dryers

Dry air from the outlet of the dryer container is released to the outside air pressure and guided through the saturated desiccant, where it takes up the adsorbed moisture.

After the desorption the blow-off valve is closed, and the container is put under pressure again.

| Type | Inlet volume flow: 7 bar [100 psig] | | Pressure loss (without filter) | Filter sizes (recommended) | | | Weight | Dimensions | | |
|--|--|--------------------|-----------------------------------|----------------------------|---------------------|-------------|--------|------------|------|------|
| | I/s | m ³ /hr | | Pre-filter | | Afterfilter | | mm | | |
| | | | bar | 1 µm 0.1 ppm | 0.01 µm 0.01 ppm | 1 µm | kg | L | W | H |
| Heatless desiccant air dryers, 25-1400 l/s, 53-2968 cfm. | | | | | | | | | | |
| CD 1 ⁺ | 1 | 3.6 | 0.20 | DD3 | PD3 | integrated | 7 | 106 | 172 | 540 |
| CD 1.5 ⁺ | 1.5 | 5.4 | 0.20 | DD3 | PD3 | integrated | 8 | 106 | 172 | 590 |
| CD 2 ⁺ | 2 | 7.2 | 0.20 | DD3 | PD3 | integrated | 9 | 106 | 172 | 720 |
| CD 2.5 ⁺ | 2.5 | 9.0 | 0.20 | DD3 | PD3 | integrated | 10 | 106 | 172 | 835 |
| CD 3 ⁺ | 3 | 10.8 | 0.20 | DD3 | PD3 | integrated | 11 | 106 | 172 | 855 |
| CD 5 ⁺ | 5 | 18.0 | 0.20 | DD3 | PD3 | integrated | 19 | 149 | 295 | 640 |
| CD 7 ⁺ | 7 | 25.2 | 0.20 | DD3 | PD3 | integrated | 22 | 149 | 295 | 725 |
| CD 10 ⁺ | 10 | 36.0 | 0.20 | DD3 | PD3 | integrated | 25 | 149 | 295 | 875 |
| CD 12 ⁺ | 12 | 43.2 | 0.20 | DD3 | PD3 | integrated | 29 | 149 | 295 | 1015 |
| CD 17 ⁺ | 17 | 61.2 | 0.20 | DD3 | PD3 | integrated | 35 | 149 | 295 | 1270 |
| CD 22 ⁺ | 22 | 79.2 | 0.35 | DD3 | PD3 | integrated | 44 | 149 | 295 | 1505 |
| CD 25 ⁺ | 25 | 90 | 0.06 | DD32 | PD32 | DDp32 | 50 | 550 | 201 | 1233 |
| CD 30 ⁺ | 30 | 108 | 0.09 | DD32 | PD32 | DDp32 | 50 | 550 | 201 | 1233 |
| CD 35 ⁺ | 35 | 126 | 0.10 | DD32 | PD32 | DDp32 | 60 | 550 | 201 | 1478 |
| CD 50 ⁺ | 50 | 180 | 0.32 | DD60 | PD60 | DDp60 | 80 | 550 | 201 | 1846 |
| CD 60 ⁺ | 60 | 216 | 0.12 | DD60 | PD60 | DDp60 | 100 | 550 | 364 | 1233 |
| CD 70 ⁺ | 70 | 252 | 0.16 | DD60 | PD60 | DDp60 | 120 | 550 | 364 | 1479 |
| CD 80 ⁺ | 80 | 288 | 0.33 | DD120 | PD120 | DDp120 | 160 | 550 | 364 | 1846 |
| CD 100 ⁺ | 100 | 360 | 0.35 | DD120 | PD120 | DDp120 | 160 | 550 | 364 | 1846 |
| CD 145 ⁺ | 145 | 522 | 0.43 | DD150 | PD150 | DDp150 | 240 | 550 | 526 | 1846 |
| CD 110 ⁺ | 107 | 385 | 0.12 | DD120 | PD120 | DDp120 | 340 | 950 | 728 | 1695 |
| CD 150 ⁺ | 150 | 540 | 0.16 | DD150 | PD150 | DDp150 | 415 | 1089 | 848 | 1731 |
| CD 185 ⁺ | 185 | 666 | 0.20 | DD175 | PD175 | DDp175 | 445 | 1089 | 848 | 1731 |
| CD 250 ⁺ | 250 | 900 | 0.14 | DD280 | PD280 | DDp280 | 600 | 1106 | 960 | 1816 |
| CD 300 ⁺ | 300 | 1080 | 0.19 | DD280 | PD280 | DDp280 | 650 | 1173 | 1116 | 1854 |
| CD 330 ⁺ | 330 | 1188 | 0.10 | DD310+ | PD310+ | DDp310+ | 950 | 1088 | 1776 | 2537 |
| CD 400 ⁺ | 400 | 1440 | 0.10 | DD425+ | PD425+ | DDp425+ | 1030 | 1088 | 1776 | 2537 |
| CD 550 ⁺ | 550 | 1980 | 0.10 | DD550+ | PD550+ | DDp550+ | 1310 | 1091 | 1884 | 2592 |
| CD 850 ⁺ | 850 | 3060 | 0.10 | DD850+ | PD850+ | DDp850+ | 2120 | 1259 | 2359 | 2655 |
| CD 1100 ⁺ | 1100 | 3960 | 0.10 | DD1100+ | PD1100+ | DDp1100+ | 2600 | 1259 | 2472 | 2637 |
| CD 1400 ⁺ | 1400 | 5040 | 0.11 | DD1400+ | PD1400+ | DDp1400+ | 3700 | 1428 | 2693 | 2576 |

Blower purge desiccant air dryers, 360-1600 l/s, 763-3392 cfm

BD

Atlas Copco's BD blower purge desiccant air dryers are designed for a long lifetime of reliable operation. They use a combination of air from an external blower, heat and minimal compressed air, and incorporate unique, patented technological innovations and energy-saving options. BD dryers provide you with the clean, dry air you need to extend the life of your equipment and ensure the quality of your end product. They are available in a range of sizes with a pressure dewpoint as low as -40°C/-40°F, and come in an IP54 protected cubicle.

CUSTOMER BENEFITS


- **Reliability** – Atlas Copco's BD desiccant dryers eliminate system failures, production downtime and costly repairs by removing moisture from compressed air with a pressure dewpoint as low as -40°C/-40°F.
- **Reduced energy costs** – Optimally sized pipes and valves ensure a limited pressure drop. Options are available to increase the efficiency and reduce the energy consumption of your BD dryer.
- **Space-saving** – The BD's all-in-one design leads to a small footprint, saving valuable space in your facility.
- **Efficient control** – The control system – fitted in an IP54 cubicle for easy cabling and safety – ensures proper operation of your BD dryer.
- **Low maintenance** – Delivered ready for use, installation of your BD dryer is straightforward, cutting costly production downtime. All internal components are easily accessible to facilitate maintenance. The use of high-grade desiccant and high-quality valves results in three-year maintenance intervals.



BD 970

Electronic dewpoint control

When the dewpoint reaches a preset value, the dryer automatically switches between the towers. This extends the drying time and results in considerable power savings, instead of changing the tower functions periodically. The power savings can be as high as 70%. The dewpoint is continuously monitored and indicated on the dryer display.



Functional diagram for the BD desiccant dryer

Blower purge desiccant air dryers

The blower sucks in ambient air and blows it across the external heating element. The heated air is then guided from top to bottom through the saturated desiccant and absorbs the adsorbed moisture.

Cooling

Purging: After heating, the hot desiccant is cooled in the container. For the cooling, dry compressed air is passed from the outlet of the adsorption container from top to bottom through the hot reactivated container, and thus released.

| Type | Inlet volume flow: 7 bar | | Average power input | Pressure loss (without filter) | Filter sizes (recommended) | | | Weight | Dimensions | | |
|-----------------------------------|--------------------------|-------|---------------------|--------------------------------|----------------------------|---------------------|-------------|--------|------------|------|------|
| | | | | | Pre-filter | | Afterfilter | | mm | | |
| | l/s | m³/hr | kW | bar | 1 µm 0.1 ppm | 0.01 µm 0.01 ppm | 1 µm | kg | L | W | H |
| Blower purge desiccant air dryers | | | | | | | | | | | |
| BD 360 | 360 | 1296 | 8.4 | 0.16 | DD310+ | PD310+ | DDp310+ | 1160 | 1100 | 1028 | 1829 |
| BD 480 | 480 | 1728 | 10.4 | 0.16 | DD425+ | PD425+ | DDp425+ | 1275 | 1764 | 1024 | 2558 |
| BD 630 | 630 | 2268 | 14.8 | 0.16 | DD630 | PD630 | DDp630 | 1560 | 1884 | 1024 | 2612 |
| BD 970 | 970 | 3492 | 21.8 | 0.16 | DD970 | PD970 | DDp970 | 2540 | 2359 | 1175 | 2702 |
| BD 1260 | 1260 | 4536 | 27.7 | 0.16 | DD1260 | PD1260 | DDp1260 | 3035 | 2472 | 1175 | 2681 |
| BD 1600 | 1600 | 5760 | 35.3 | 0.11 | DD1600 | PD1600 | DDp1600 | 4100 | 2720 | 2199 | 2548 |

Blower purge desiccant air dryers, 100-3000 l/s, 212-6360 cfm

BD⁺

Atlas Copco's BD⁺ blower purge desiccant air dryers are designed for outstanding industrial performance and a long lifetime of reliable operation. They eliminate moisture completely before it can cause any damage to your compressed air net or production equipment. BD⁺ dryers use a combination of air from an external blower, heat and minimal compressed air, and incorporate unique, patented technological innovations and energy-saving options. BD⁺ dryers are available in a range of sizes with a guaranteed dewpoint down to -40°C / -40°F (optionally -70°C / -100°F), and come in an IP54 protected cubicle.

CUSTOMER BENEFITS

- **High reliability** – BD⁺ dryers eliminate system failures, production downtime and costly repairs by removing moisture from compressed air with a pressure dewpoint as low as -70°C / -100°F. Up to 30% desiccant overfill and the long lifetime of the desiccant further enhance reliability.

- **Maximum energy savings** – BD⁺ dryers incorporate energy-saving features that cut your carbon footprint. A low pressure drop below 0.2 bar / 2.9 psi drives down energy costs. Dewpoint sensing and control adapts the energy consumption to the real load of the dryer.

- **Easy installation** – Your BD⁺ dryer is delivered ready for use with heaters, sensors and the control unit already wired and connected.

- **Advanced control and monitoring** – The advanced Elektronikon® control and monitoring system gives clear indication of dryer status, operation cycle and alarms. It includes alarms for low inlet pressure, blower, heater and valve operation, plus limit switches, pressure and temperature sensors.

- **Minimum maintenance** – All internal components are easily accessible to facilitate maintenance. The use of high-grade desiccant and high-quality valves extends maintenance intervals beyond three years.

- **Durability** – A proven, rugged design for the switching valves and the blower, the most important moving components in the dryer, significantly improves the lifetime of your BD⁺ dryer.



BD 360



BD 1100+

| Type | Inlet volume flow: 7 bar | | Average power input | Pressure loss (without filter) | Filter sizes (recommended) | | | Weight | Dimensions | | |
|-------------------------------------|--------------------------|-------|---------------------|--------------------------------|----------------------------|---------------------|-------------|--------|------------|------|------|
| | | | | | Pre-filter | | Afterfilter | | mm | | |
| | l/s | m³/hr | kW | bar | 1 µm 0.1 ppm | 0.01 µm 0.01 ppm | 1 µm | kg | L | W | H |
| Purge air cooling | | | | | | | | | | | |
| BD 100+ | 100 | 360 | 3.0 | 0.20 | DD120 | PD120 | DDp120 | 640 | 1250 | 770 | 1720 |
| BD 150+ | 150 | 540 | 3.0 | 0.20 | DD150 | PD150 | DDp150 | 680 | 1300 | 870 | 1770 |
| BD 185+ | 185 | 666 | 5.0 | 0.20 | DD175 | PD175 | DDp175 | 710 | 1300 | 870 | 1770 |
| BD 250+ | 250 | 900 | 5.5 | 0.20 | DD280 | PD280 | DDp280 | 775 | 1345 | 955 | 1816 |
| BD 300+ | 300 | 1080 | 5.5 | 0.20 | DD310+ | PD310+ | DDp310+ | 820 | 1425 | 1010 | 1853 |
| BD 330+ | 330 | 1188 | 9.3 | 0.12 | DD310+ | PD310+ | DDp310+ | 1190 | 1764 | 1024 | 2558 |
| BD 400+ | 400 | 1440 | 10.2 | 0.12 | DD425+ | PD425+ | DDp425+ | 1300 | 1764 | 1024 | 2558 |
| BD 550+ | 550 | 1980 | 12.0 | 0.12 | DD550+ | PD550+ | DDp550+ | 1620 | 1884 | 1024 | 2612 |
| BD 850+ | 850 | 3060 | 17.1 | 0.12 | DD850+ | PD850+ | DDp850+ | 2600 | 2359 | 1175 | 2702 |
| BD 1100+ | 1100 | 3960 | 24.2 | 0.12 | DD1100+ | PD1100+ | DDp1100+ | 3040 | 2472 | 1175 | 2681 |
| BD 1400+ | 1400 | 5040 | 33.0 | 0.10 | DD1400+ | PD1400+ | DDp1400+ | 4100 | 2720 | 2199 | 2548 |
| BD 1800+ | 1800 | 6480 | 39.0 | 0.16 | DD1800+ | PD1800+ | DDp1800+ | 4700 | 2793 | 2199 | 2548 |
| BD 2200+ | 2200 | 7920 | 55.0 | 0.22 | DD2200+ | PD2200+ | DDp2200+ | 5600 | 2993 | 2199 | 2548 |
| BD 3000+ | 3000 | 10800 | 69.0 | 0.18 | DD3000+ | PD3000+ | DDp3000+ | 7600 | 3350 | 2417 | 2893 |
| Purge-free air cooling (Zero Purge) | | | | | | | | | | | |
| BD 330+ | 330 | 1188 | 8.6 | 0.12 | DD310+ | PD310+ | DDp390 | 1420 | 1764 | 1024 | 2558 |
| BD 400+ | 400 | 1440 | 10.7 | 0.12 | DD425+ | PD425+ | DDp390 | 1545 | 1764 | 1024 | 2558 |
| BD 550+ | 550 | 1980 | 13.2 | 0.12 | DD550+ | PD550+ | DDp520 | 1910 | 1884 | 1024 | 2612 |
| BD 850+ | 850 | 3060 | 23.4 | 0.12 | DD850+ | PD850+ | DDp780 | 2960 | 2359 | 1175 | 2702 |
| BD 1100+ | 1100 | 3960 | 32.4 | 0.12 | DD1100+ | PD1100+ | DDp1050 | 3490 | 2472 | 1175 | 2681 |
| BD 1400+ | 1400 | 5040 | 37.0 | 0.10 | DD1400+ | PD1400+ | DDp1400 | 4450 | 2720 | 2639 | 2548 |
| BD 1800+ | 1800 | 6480 | 45.0 | 0.16 | DD1800+ | PD1800+ | DDp1800 | 5050 | 2793 | 2663 | 2548 |
| BD 2200+ | 2200 | 7920 | 62.0 | 0.22 | DD2200+ | PD2200+ | DDp2100 | 5950 | 2993 | 2775 | 2548 |
| BD 3000+ | 3000 | 10800 | 79.0 | 0.18 | DD3000+ | PD3000+ | DDp3150 | 7950 | 3350 | 2923 | 2893 |

Heat of compression rotary drum dryers, 88-2500 l/s, 185-5297 cfm

MD

For high-quality, dry air downstream from your oil-free screw and centrifugal compressors, Atlas Copco's MD rotary drum dryers meet your needs perfectly. Using heat of compression – which requires negligible energy input – they are the perfect solution for a wide range of applications requiring pressure dewpoints as low as $-25^{\circ}\text{C}/-13^{\circ}\text{F}$. MD dryers are also often selected for applications where refrigerated dryers are suitable ($+3^{\circ}\text{C}/37^{\circ}\text{F}$ PDP) due to the significant energy savings they offer. You benefit from a reliable process, impeccable end products, and the lowest total cost of ownership. Compared to other desiccant dryers that can consume up to 15% of the compressed air, the MD dryer guarantees 100% flow capacity at the output.

CUSTOMER BENEFITS

- **Maximum energy savings** – The energy consumption of MD dryers is negligible: only 0.12 kW (water cooled version). MD dryers are characterized by no loss of compressed air, zero purge by design, low pressure drop and no pre- and after-filtration requirements. These factors contribute to additional energy savings and increased efficiency. A Variable Speed Drive (VSD) dryer version is available to match VSD compressors.
- **Low maintenance** – The combination of an easy to service vessel, minimal maintenance downtime and long service intervals reduces your maintenance time and costs.
- **Environmentally friendly** – MD dryers are totally oil-free and use no Freon or CFCs, and a minimal amount of desiccant (only 5-10% of conventional adsorption dryers). 95% of all components can be recycled, and the units have very low noise levels.
- **Small footprint** – The small footprint of MD dryers means they take up minimal space in your facility.



MD 2500 VSD

| Type | Compressor type | Max. operating pressure | Dewpoint ⁽¹⁾ | Input | Weight approximately | Dimensions L × B × H |
|--|-----------------|-------------------------|-------------------------|-------|----------------------|----------------------|
| | | bar | °C | kW | kg | mm |
| MD - Heat of compression rotary drum dryers, air cooled | | | | | | |
| MD 200 | ZT 55-90 | 10.5 | −30 | 1.04 | 460 | 852 × 1433 × 1347 |
| MD 300 | ZT 110-145 | 10.5 | −30 | 1.04 | 500 | 852 × 1442 × 1545 |
| MD 400 | ZT 160-200 | 10.5 | −30 | 1.04 | 500 | 852 × 1442 × 1545 |
| MD 600 | ZT 200-275 | 10.5 | −30 | 1.34 | 950 | 1194 × 1893 × 1796 |
| MD - Heat of compression rotary drum dryers, air cooled and speed control | | | | | | |
| MD 200 VSD | ZT 75-90 VD | 10.5 | −25 | 1.04 | 460 | 852 × 1442 × 1545 |
| MD 400 VSD | ZT 132-160 VSD | 10.5 | −25 | 1.04 | 500 | 852 × 1442 × 1545 |
| MD 800 VSD | ZT 250-315 VSD | 10.5 | −25 | 1.34 | 950 | 1194 × 1893 × 1796 |
| MD - Heat of compression rotary drum dryers, water cooled | | | | | | |
| MD 200W | ZR 55-90 | 10.5 | −30 | 0.12 | 410 | 819 × 990 × 1347 |
| MD 300W | ZR 110-145 | 10.5 | −30 | 0.12 | 440 | 819 × 997 × 1545 |
| MD 400W | ZR 160-200 | 10.5 | −30 | 0.12 | 440 | 819 × 997 × 1545 |
| MD 600W | ZR 200-275 | 10.5 | −30 | 0.12 | 900 | 1163 × 1345 × 1609 |
| MD 1000W | ZR 300-425 | 10.5 | −30 | 0.12 | 1000 | 1156 × 1369 × 2057 |
| MD 1800W | ZR 450-750 | 10.5 | −30 | 0.12 | 1500 | 1290 × 1716 × 2283 |
| MD - Heat of compression rotary drum dryers, water cooled and speed control | | | | | | |
| MD 200W VSD | ZR 75-90 VSD | 10.5 | −25 | 0.15 | 410 | 819 × 990 × 1347 |
| MD 400W VSD | ZR 132-160 VSD | 10.5 | −25 | 0.15 | 440 | 819 × 997 × 1545 |
| MD 800W VSD | ZR 250-315 VSD | 10.5 | −25 | 0.15 | 900 | 1163 × 1346 × 1796 |
| MD 1100W VSD | ZR 400 VSD | 10.5 | −25 | 0.15 | 1000 | 1156 × 1369 × 2057 |
| MD 1300W VSD | ZR 500 VSD | 10.5 | −25 | 0.15 | 1000 | 1156 × 1369 × 2057 |
| MD 2100W VSD | ZR 700 VSD | 10.5 | −25 | 0.15 | 1500 | 1289 × 1721 × 2353 |
| MD 2500W VSD | ZR 900 VSD | 10.5 | −25 | 0.15 | 1500 | 1289 × 1721 × 2353 |

⁽¹⁾ At full load and at reference conditions: working pressure 7 bar inlet pressure 1 bar, intake and coolant temperature 20 °C, rel. Humidity of the intake 60%

Heat of compression rotary drum dryers, 1800-2500 l/s, 3816-5297 cfm

ND

For high quality, dry air downstream from your oil-free compressor, Atlas Copco's ND rotary drum dryers meet your needs perfectly. Providing energy-efficient drying by using heat of compression, they are the perfect solution for applications requiring pressure dew points as low as $-45^{\circ}\text{C}/-49^{\circ}\text{F}$. You benefit from a reliable process, impeccable end products, and the lowest total cost of ownership. What's more, they offer outstanding energy efficiency. Compared to other desiccant dryers that can consume up to 15% of the compressed air, the ND dryer guarantees 100% flow capacity at the output.

CUSTOMER BENEFITS

- **High efficiency** – ND dryers are characterized by no loss of compressed air, zero purge by design, low pressure drop and no filtration requirements, all of which contribute to increased efficiency. A Variable Speed Drive (VSD) dryer version is available to match VSD compressors.
- **Low maintenance** – The combination of an easy to service vessel, minimal maintenance downtime and long service intervals reduces your maintenance time and costs.
- **Environmentally friendly** – ND dryers are totally oil-free and use no Freon or CFCs, and a minimal amount of desiccant (only 5-10% of conventional adsorption dryers). 95% of all components can be recycled, and the units have very low noise levels.
- **Small footprint** – The small footprint of ND dryers means they take up minimal space in your facility.



| Options |
|--|
| Stainless steel interconnecting piping |
| Pressure dew point sensor |
| Variable Speed Drive variant (for VSD compressors) |
| By-pass for ND 1000 |
| Silicone-free rotor |

| Type | Inlet flow 7 bar(e)/100 psi(g) | | | Rated heater power* | | Outlet connections | Dimensions | | | | | | Weight | |
|-------------|-----------------------------------|-------|------|------------------------|----|-----------------------|------------|------|------|----|----|----|--------|------|
| | | | | | | | mm | | | in | | | | |
| | l/s | m³/hr | cfm | kW | hp | | flanged | A | B | C | A | B | C | kg |
| ND 1000 | 1080 | 3888 | 2290 | 9 | 12 | DIN 100/ANSI 4" | 1337 | 1711 | 2058 | 53 | 67 | 81 | 1300 | 2870 |
| ND 1100 VSD | 1145 | 4122 | 2430 | 9 | 12 | DIN 100/ANSI 4" | 1337 | 1711 | 2058 | 53 | 67 | 81 | 1300 | 2870 |
| ND 1300 VSD | 1275 | 4590 | 2700 | 9 | 12 | DIN 100/ANSI 4" | 1337 | 1711 | 2058 | 53 | 67 | 81 | 1300 | 2870 |
| ND 1800 | 2075 | 7470 | 4399 | 15 | 20 | DIN 125/ANSI 6" | 1497 | 1879 | 2322 | 59 | 74 | 91 | 1750 | 3850 |
| ND 2000 | 2100 | 7560 | 4452 | 36 | 48 | DIN 125/ANSI 6" | 1497 | 1879 | 2411 | 59 | 74 | 95 | 1800 | 3960 |
| ND 2100VSD | 2100 | 7560 | 4452 | 15 | 20 | DIN 125/ANSI 6" | 1497 | 1879 | 2392 | 59 | 74 | 94 | 1750 | 3850 |
| ND 2500VSD | 2500 | 9000 | 5300 | 15 | 20 | DIN 125/ANSI 6" | 1497 | 1879 | 2392 | 59 | 74 | 94 | 1750 | 3850 |

* Actual power consumption is lower than the stated heater power and would depend on the conditions.

Reference conditions:

Performance data per ISO 7183:2007.

Heat-of-compression desiccant air dryers, 550-3600 l/s, 1165 - 7628 cfm

XD⁺

Atlas Copco's XD⁺ heat-of-compression desiccant dryers combine high drying performance with minimal energy use. The result is best-in-class air quality for the ZH centrifugal compressor series, Z screw compressors and other oil-free air compressors. They guarantee a stable pressure dew point down to -40°C/-40°F (optionally -70°C/-100°F) without temperature or dew point peaks.

CUSTOMER BENEFITS

- **Maximum energy savings** – The XD's patented zero purge solution does not consume any compressed air, while the high-performance desiccant minimizes energy consumption during regeneration. The low pressure drop of all individual components results in an overall low pressure drop. Advanced controls further reduce your total energy bill.

- **Optimal uptime** – XD⁺ dryers are renowned for their durability. Coolers, process valves, heaters and strainer are all made from stainless steel; all piping is fully galvanized; and the cooler shells are internally coated. Corrosion resistance results in extended lifetime and minimum maintenance downtime.

- **High reliability** – The high-performance desiccant has a low sensitivity to aging and a high resistance to acid condensate, which translate into a long lifetime. All process stainless steel valves are standard equipped with reliable inductive limit switches.

- **Easy installation and maintenance** – The modular design, consisting of a flanged piping skid and instrumentation and two flanged vessels, allows easy installation on site, reducing the installation cost to a minimum and ensuring quick commissioning. All controls and switches are connected to the Elektronikon® controller, which arrives fully programmed on site to cut installation time and cost.

- **Low noise** – The patented zero purge dryers exclude all need for purge air. As there is no purge, noise levels are extremely low.



XD 1100 ZP

| Type | Working pressure | Volume flow ¹⁾ | | After-heater | Pressure dewpoint ¹⁾ | Approx. weight | Dimensions L × W × H |
|---|------------------|---------------------------|--------|--------------|---------------------------------|----------------|-------------------------|
| | bar | l/s | m³/min | | °C | kg | mm |
| XD+ – Desiccant dryer, water-cooled – WITHOUT power requirement/variants: P/ZP | | | | | | | |
| XD+ 1400 S | 11 | 1400 | 84.0 | without | –5 up to –25 | 4800 | 2988 × 3026 × 3306 |
| XD+ 1800 S | 11 | 1800 | 108.0 | without | –5 up to –25 | 5000 | 3068 × 3126 × 3307 |
| XD+ 2400 S | 11 | 2400 | 144.0 | without | –5 up to –25 | 7000 | 3529 × 3326 × 3374 |
| XD+ 3000 S | 11 | 3000 | 180.0 | without | –5 up to –25 | 8200 | 3674 × 4000 × 3417 |
| XD+ 3600 S | 11 | 3600 | 130.0 | without | –5 up to –25 | 10000 | 3963 × 4100 × 3444 |
| XD+ 4000 S | 11 | 4000 | 240.0 | without | –5 up to –25 | 10400 | 4042 × 4200 × 3448 |
| XD+ 4500 S | 11 | 4500 | 270.0 | without | –5 up to –25 | 10700 | 4163 × 4300 × 3460 |
| XD+ 5000 S | 11 | 5000 | 300.0 | without | –5 up to –25 | 16600 | 4659 × 5012 × 3760 |
| XD+ 6000 S | 11 | 6000 | 360.0 | without | –5 up to –25 | 17700 | 4859 × 5212 × 3755 |
| XD+ 7000 S | 11 | 7000 | 420.0 | without | –5 up to –25 | 18300 | 4959 × 5312 × 3783 |
| XD+ – Desiccant dryer, water-cooled – WITH guaranteed pressure dewpoint/variants: P/ZP | | | | | | | |
| XD+ 1400 G | 11 | 1400 | 84.0 | with | up to –40 | 5160 | 2988 × 3026 × 3415 |
| XD+ 1800 G | 11 | 1800 | 108.0 | with | up to –40 | 5360 | 3068 × 3126 × 3430 |
| XD+ 2400 G | 11 | 2400 | 144.0 | with | up to –40 | 7390 | 3529 × 3326 × 3492 |
| XD+ 3000 G | 11 | 3000 | 180.0 | with | up to –40 | 8630 | 3674 × 4000 × 3531 |
| XD+ 3600 G | 11 | 3600 | 130.0 | with | up to –40 | 10400 | 3963 × 4100 × 3563 |
| XD+ 4000 G | 11 | 4000 | 240.0 | with | up to –40 | 10800 | 4042 × 4200 × 3589 |
| XD+ 4500 G | 11 | 4500 | 270.0 | with | up to –40 | 11100 | 4163 × 4300 × 3616 |
| XD+ 5000 G | 11 | 5000 | 300.0 | with | up to –40 | 17100 | 4659 × 5012 × 3911 |
| XD+ 6000 G | 11 | 6000 | 360.0 | with | up to –40 | 18200 | 4859 × 5212 × 3915 |
| XD+ 7000 G | 11 | 7000 | 420.0 | with | up to –40 | 18800 | 4959 × 5312 × 3940 |

Versions: P = PURGE cooling with compressed air loss/ZP = ZERO PURGE cooling without compressed air losses

¹⁾ Volume flow based on reference conditions: working pressure 7 bar, compressed air inlet 120°C, relative humidity 10%, coolant temperature 26,7°C, version P

Membrane dryers

SD

Atlas Copco's SD membrane dryers with pre-filters remove oil, particles and moisture from compressed air in the most demanding conditions. They ensure the lowest pressure drop and purge air loss for the highest possible efficiency – saving you time and money through your production process. From small spaces to environments with fluctuating ambient temperatures, SD dryers can perform in a wide variety of harsh and critical conditions. Two models are available, each with a range of performance, to offer you the exact air treatment you require.

CUSTOMER BENEFITS

- **Versatility** – SD dryers perform in all sorts of areas: small spaces, areas where flexible mounting is required, high vibration areas and in widely fluctuating temperatures.
- **Safety assurance** – SD dryers provide dry air in environments with strict safety or environmental requirements. These include low flow environments, areas without an electrical supply, explosion-proof facilities, noise-sensitive and corrosion-sensitive areas.

- **Clean and dry air for critical applications** – Because they are not powered by electricity, SD dryers function safely in environments that must be explosion-proof, such as laboratories. Thanks to their quiet operation, they can be used close to the workplace.

- **Optimal efficiency** – SD membrane dryers contain thousands of hollow fibers with an innovative inner coating. Compared to conventional membrane dryers, this unique coating increases the separation efficiency between water vapor and oxygen and nitrogen, giving an unprecedented low air leakage and the lowest purge air loss.

- **Flexibility in choice** – SD dryers are available in two models, each with a different Pressure Dew Point Suppression. This choice of performance ensures that, regardless of your production environment and demands, there is an SD dryer to meet your needs.

- **Energy savings** – Due to the straightforward design of the SD dryer, compressed air has no twists and turns to make inside the housing. This leads to minimal pressure drop and utmost efficiency throughout the drying process.



| SDP - Membrane Dryer - pressure dew point 32 ° C | | | | | | | | | |
|--|-----------------------------|--------------------|--------|------------------------------------|------------------|-------------------------|--------------------|--|---------------------|
| Type | Max. working pressure | Flow ¹⁾ | | Pressure dew point reduction | Pressure drop | Pneumatic connection | Supplied filter | Weight ²⁾ approx- imately | Dimensions Ø / L |
| | bar | l/s | m³/min | ca. °C | mbar | | | kg | mm |
| SD 1 P | 7 | 3.0 | 0.16 | 32 | 0.10 | G 3/8" | DD+PD 9 | 3.0 | 55 / 532 |
| SD 2 P | 7 | 5.0 | 0.30 | 32 | 0.17 | G 3/8" | DD+PD 9 | 3.0 | 55 / 532 |
| SD 3 P | 7 | 9.0 | 0.54 | 32 | 0.17 | G 1/2" | DD+PD 9 | 4.0 | 78 / 733 |
| SD 4 P | 7 | 14.0 | 0.84 | 32 | 0.27 | G 1/2" | DD+PD 17 | 4.2 | 78 / 733 |
| SD 5 P | 7 | 19.0 | 1.14 | 32 | 0.17 | G 1/2" | DD+PD 17 | 5.3 | 99 / 709 |
| SD 6 P | 7 | 25.0 | 1.50 | 32 | 0.24 | G 1/2" | DD+PD 32 | 5.3 | 99 / 709 |
| SD 7 P | 7 | 35.0 | 2.10 | 32 | 0.18 | G 1/2" | DD+PD 32 | 7.9 | 125 / 732 |

1) Based on 25 ° C, 1 bar, 100% relative humidity. Reference conditions: Working pressure: 7, 10, 13 bar, temperature 35 ° C, relative humidity 100%.

2) weight (net) including DD / PD filters combination

| SDP - Membrane Dryer - pressure dew point 32 ° C | | | | | | | | | |
|--|-----------------------|--------------------|--------|------------------------------|---------------|----------------------|-----------------|------------------------------------|------------------|
| Type | Max. working pressure | Flow ¹⁾ | | Pressure dew point reduction | Pressure drop | Pneumatic connection | Supplied filter | Weight ²⁾ approximately | Dimensions Ø / L |
| | bar | l/s | m³/min | ca. °C | mbar | | | kg | mm |
| SD 1 P | 10 | 4.0 | 0.24 | 32 | 0.10 | G 3/8" | DD + PD 9 | 3.0 | 55 / 532 |
| SD 2 P | 10 | 7.0 | 0.42 | 32 | 0.17 | G 3/8" | DD + PD 9 | 3.0 | 55 / 532 |
| SD 3 P | 10 | 12.0 | 0.72 | 32 | 0.17 | G 1/2" | DD + PD 9 | 4.0 | 78 / 733 |
| SD 4 P | 10 | 19.0 | 1.14 | 32 | 0.27 | G 1/2" | DD + PD 17 | 4.2 | 78 / 733 |
| SD 5 P | 10 | 25.0 | 1.50 | 32 | 0.17 | G 1/2" | DD + PD 17 | 5.3 | 99 / 709 |
| SD 6 P | 10 | 34.0 | 2.04 | 32 | 0.24 | G 1/2" | DD + PD 32 | 5.3 | 99 / 709 |
| SD 7 P | 10 | 44.0 | 2.64 | 32 | 0.20 | G 1/2" | DD + PD 32 | 7.9 | 125 / 732 |
| SD 1 P | 13 | 5.0 | 0.30 | 32 | 0.10 | G 3/8" | DD + PD 9 | 3.0 | 55 / 532 |
| SD 2 P | 13 | 8.5 | 0.51 | 32 | 0.17 | G 3/8" | DD + PD 9 | 3.0 | 55 / 532 |
| SD 3 P | 13 | 14.0 | 0.84 | 32 | 0.17 | G 1/2" | DD + PD 9 | 4.0 | 78 / 733 |
| SD 4 P | 13 | 22.0 | 1.32 | 32 | 0.27 | G 1/2" | DD + PD 17 | 4.2 | 78 / 733 |
| SD 5 P | 13 | 32.0 | 1.92 | 32 | 0.18 | G 1/2" | DD + PD 32 | 5.7 | 99 / 709 |
| SD 6 P | 13 | 42.0 | 2.52 | 32 | 0.25 | G 1/2" | DD + PD 32 | 5.3 | 99 / 709 |
| SD 7 P | 13 | 55.0 | 3.30 | 32 | 0.19 | G 3/4" | DD + PD 44 | 8.9 | 125 / 732 |

1) Based on 25 ° C, 1 bar, 100% relative humidity. Reference conditions: Working pressure: 7, 10, 13 bar, temperature 35 ° C, relative humidity 100%.

2) weight (net) including DD / PD filters combination

| SD / N - Membrane Dryer - pressure dew point 55 ° C | | | | | | | | | |
|---|-----------------------|--------------------|--------|------------------------------|---------------|----------------------|-----------------|------------------------------------|------------------|
| Type | Max. working pressure | Flow ¹⁾ | | Pressure dew point reduction | Pressure drop | Pneumatic connection | Supplied filter | Weight ²⁾ approximately | Dimensions Ø / L |
| | bar | l/s | m³/min | ca. °C | mbar | | | kg | mm |
| SD 1 N | 7 | 1.5 | 0.09 | 55 | 0.08 | G 3/8" | DD + PD 9 | 3.0 | 55 / 715 |
| SD 2 N | 7 | 3.5 | 0.21 | 55 | 0.25 | G 3/8" | DD + PD 9 | 3.2 | 55 / 1020 |
| SD 3 N | 7 | 6.0 | 0.36 | 55 | 0.16 | G 1/2" | DD + PD 9 | 4.7 | 78 / 1076 |
| SD 4 N | 7 | 9.0 | 0.54 | 55 | 0.25 | G 1/2" | DD + PD 9 | 4.7 | 78 / 1076 |
| SD 5 N | 7 | 13.0 | 0.78 | 55 | 0.18 | G 1/2" | DD + PD 17 | 6.1 | 99 / 1076 |
| SD 6 N | 7 | 17.0 | 1.02 | 55 | 0.25 | G 1/2" | DD + PD 17 | 6.1 | 99 / 1076 |
| SD 7 N | 7 | 26.0 | 1.56 | 55 | 0.25 | G 1/2" | DD + PD 32 | 9.7 | 125 / 1113 |
| SD 1 N | 10 | 2.0 | 0.12 | 55 | 0.08 | G 3/8" | DD + PD 9 | 3.0 | 55 / 715 |
| SD 2 N | 10 | 4.5 | 0.27 | 55 | 0.24 | G 3/8" | DD + PD 9 | 3.2 | 55 / 1020 |
| SD 3 N | 10 | 8.0 | 0.48 | 55 | 0.15 | G 1/2" | DD + PD 9 | 4.7 | 78 / 1076 |
| SD 4 N | 10 | 12.0 | 0.72 | 55 | 0.24 | G 1/2" | DD + PD 9 | 4.7 | 78 / 1076 |
| SD 5 N | 10 | 18.0 | 1.08 | 55 | 0.19 | G 1/2" | DD + PD 17 | 6.1 | 99 / 1076 |
| SD 6 N | 10 | 22.0 | 1.32 | 55 | 0.24 | G 1/2" | DD + PD 17 | 6.1 | 99 / 1076 |
| SD 7 N | 10 | 35.0 | 2.10 | 55 | 0.24 | G 1/2" | DD + PD 32 | 9.7 | 125 / 1113 |
| SD 1 N | 13 | 2.5 | 0.15 | 55 | 0.08 | G 3/8" | DD + PD 9 | 3.0 | 55 / 715 |
| SD 2 N | 13 | 5.5 | 0.33 | 55 | 0.24 | G 3/8" | DD + PD 9 | 3.2 | 55 / 1020 |
| SD 3 N | 13 | 10.0 | 0.60 | 55 | 0.15 | G 1/2" | DD + PD 9 | 4.7 | 78 / 1076 |
| SD 4 N | 13 | 15.0 | 0.90 | 55 | 0.24 | G 1/2" | DD + PD 9 | 4.7 | 78 / 1076 |
| SD 5 N | 13 | 23.0 | 1.38 | 55 | 0.19 | G 1/2" | DD + PD 17 | 6.1 | 99 / 1076 |
| SD 6 N | 13 | 28.0 | 1.68 | 55 | 0.25 | G 1/2" | DD + PD 17 | 6.1 | 99 / 1076 |
| SD 7 N | 13 | 45.0 | 2.70 | 55 | 0.25 | G 1/2" | DD + PD 32 | 9.7 | 125 / 1113 |

1) Based on 25 ° C, 1 bar, 100% relative humidity. Reference conditions: Working pressure: 7, 10, 13 bar, temperature 35 ° C, relative humidity 100%.

2) weight (net) including DD / PD filters combination

Purification units for breathable air

BAP / BAP⁺

Breathing air purifiers turn compressed air into certified breathing air. High quality air is of vital importance to many industries but even more so in breathing air applications. Atlas Copco BAP/BAP⁺ breathing air purifiers are designed to offer protection against a range of contaminants that may be present in a compressed air fed breathing air system. These include fumes, oil, vapors, gases, solid particles and micro-organisms. Complying with International Breathing Air standards, the BAP/BAP⁺ breathing air purifier range assures a safe working environment in a wide range of applications.

CUSTOMER BENEFITS

• **Breathtaking air quality** – High quality air is of vital importance to many industries, but nowhere as literally as in breathing air applications. The purity of the compressed air for breathing air is crucial to assure a safe working environment in a wide range of applications like asbestos removal, tank cleaning, sand blasting and others.

For this reason, Atlas Copco has designed the BAP/BAP⁺ breathing air purifier range. The BAP/BAP⁺ takes air from any regular compressor and treats it to become ultra clean. It consists of a number of components, which together, after proper commissioning, produce air with a quality matching the Pharmacopoeia that will comply with the European Norm EN 12021 (Compressed air for breathing apparatus).

• **Clean air in seven-step filtration** – The BAP/BAP⁺ purification package for converting a compressed air source into breathing quality air. Your BAP/BAP⁺ package is independently certified to provide medical air in compliance with the European Pharmacopoeia.

The BAP/BAP⁺ has 7 stages of active purification:

- A water separator to remove liquid water
- A bulk aerosol filter eliminates oil and water
- A fine coalescing filter removes even smaller particles of oil and water
- A desiccant dryer takes out any remaining water and CO₂
- Activated carbon removes gaseous impurities
- A catalyst takes care of a CO oxidation
- A bacteria filter eliminates bacteria and fine particles. This bacteria filter is an Atlas Copco PDp filter, which has been externally tested and certified as a bacterial filter.

• More advantages of the BAP

- Compact system, offering reliable breathing air
- Every BAP/BAP⁺ breathing air purifier comes pre-assembled and tested to provide simple installation
- Complying with the European Norm EN 12021 (Compressed air for breathing apparatus)
- Challenge test to ensure the BAP meets international regulations



International compliance

Atlas Copco's Breathing Air Purifiers comply with OSHA Grade D, NFPA-99, CSA Z180.1-00, CGA G7.1-1997, EN12021, BS 4275, European Pharmacopoeia and other International Breathing Air Standards.

7-145 BAP / BAP⁺

| Type | Inlet pressure | | Max. inlet flow | | | Purge | Pressure drop | |
|--------------------------------|----------------|------|-----------------|-------------------|-------|-------|---------------|------|
| | bar(e) | psig | l/s | m ³ /h | cfm | % | dP, mbar | psi |
| BAP 7 | 7 | 102 | 7.0 | 25.2 | 14.8 | 19.0 | 510 | 7.4 |
| | 10 | 145 | 8.4 | 30.2 | 17.8 | 15.8 | 510 | 7.4 |
| | 13 | 188 | 9.4 | 33.8 | 19.9 | 14.1 | 510 | 7.4 |
| BAP 13 | 7 | 102 | 13.0 | 46.8 | 27.5 | 19.0 | 530 | 7.7 |
| | 10 | 145 | 15.6 | 56.2 | 33.1 | 15.8 | 530 | 7.7 |
| | 13 | 188 | 17.5 | 63.0 | 37.1 | 14.1 | 530 | 7.7 |
| BAP 25 / BAP 25 ⁺ | 7 | 102 | 25.0 | 90.0 | 53.0 | 18.0 | 560 | 8.1 |
| | 10 | 145 | 30.0 | 108.0 | 63.6 | 15.0 | 560 | 8.1 |
| | 13 | 188 | 33.8 | 121.7 | 71.6 | 13.3 | 560 | 8.1 |
| BAP 35 / BAP 35 ⁺ | 7 | 102 | 35.0 | 126.0 | 74.2 | 18.0 | 600 | 8.7 |
| | 10 | 145 | 42.0 | 151.2 | 89.0 | 15.0 | 600 | 8.7 |
| | 13 | 188 | 47.3 | 170.3 | 100.2 | 13.3 | 600 | 8.7 |
| BAP 50 / BAP 50 ⁺ | 7 | 102 | 50.0 | 180.0 | 106.0 | 19.0 | 820 | 11.9 |
| | 10 | 145 | 60.0 | 216.0 | 127.1 | 15.8 | 820 | 11.9 |
| | 13 | 188 | 67.5 | 243.0 | 143.0 | 14.1 | 820 | 11.9 |
| BAP 70 / BAP 70 ⁺ | 7 | 102 | 70.0 | 252.0 | 148.3 | 18.0 | 660 | 9.6 |
| | 10 | 145 | 84.0 | 302.4 | 178.0 | 15.0 | 660 | 9.6 |
| | 13 | 188 | 94.5 | 340.2 | 200.2 | 13.3 | 660 | 9.6 |
| BAP 80 / BAP 80 ⁺ | 7 | 102 | 80.0 | 288.0 | 169.5 | 18.0 | 700 | 10.2 |
| | 10 | 145 | 96.0 | 345.6 | 203.4 | 15.0 | 700 | 10.2 |
| | 13 | 188 | 108.0 | 388.8 | 228.9 | 13.3 | 700 | 10.2 |
| BAP 100 / BAP 100 ⁺ | 7 | 102 | 100.0 | 360.0 | 211.9 | 19.0 | 820 | 11.9 |
| | 10 | 145 | 120.0 | 432.0 | 254.3 | 15.8 | 820 | 11.9 |
| | 13 | 188 | 135.0 | 486.0 | 286.1 | 14.1 | 820 | 11.9 |
| BAP 145 / BAP 145 ⁺ | 7 | 102 | 145.0 | 522.0 | 307.3 | 19.0 | 800 | 11.6 |
| | 10 | 145 | 174.0 | 626.4 | 368.7 | 15.8 | 800 | 11.6 |
| | 13 | 188 | 195.8 | 704.9 | 414.9 | 14.1 | 800 | 11.6 |

| Type | MED | | | | | MED ⁺ | | | | |
|--------------------------------|------------|------------|-----------|------------|----------------|------------------|------------|-----------|------------|----------------|
| | Weight, kg | Length, mm | Width, mm | Height, mm | NTP connection | Weight, kg | Length, mm | Width, mm | Height, mm | NTP connection |
| BAP 7 / BAP 7 ⁺ | 184 | 950 | 650 | 885 | 1/2" | 214 | 950 | 650 | 1851 | 1/2" |
| BAP 13 / BAP 13 ⁺ | 201 | 950 | 650 | 1075 | 1/2" | 231 | 950 | 650 | 1851 | 1/2" |
| BAP 25 / BAP 25 ⁺ | 245 | 950 | 650 | 1300 | 1/2" | 275 | 950 | 650 | 1851 | 1/2" |
| BAP 35 / BAP 35 ⁺ | 271 | 950 | 650 | 1545 | 1/2" | 301 | 950 | 650 | 1851 | 1/2" |
| BAP 50 / BAP 50 ⁺ | 315 | 950 | 650 | 1915 | 1" | 345 | 950 | 650 | 1858 | 1" |
| BAP 70 / BAP 70 ⁺ | 446 | 1250 | 850 | 1545 | 1" | 476 | 1250 | 850 | 1840 | 1" |
| BAP 80 / BAP 80 ⁺ | 494 | 1250 | 850 | 1915 | 1 1/2" | 524 | 1250 | 850 | 1840 | 1" |
| BAP 100 / BAP 100 ⁺ | 502 | 1250 | 850 | 1915 | 1 1/2" | 532 | 1250 | 850 | 1840 | 1" |
| BAP 145 / BAP 145 ⁺ | 620 | 1250 | 850 | 1915 | 1 1/2" | 650 | 1250 | 850 | 1856 | 1" |

Compressed air purification

Something else you should consider

Could the finest oil drops or moisture or the smallest dust grain affect your manufacturing processes? Or even affect the quality of your products; in the worst case scenario, destroying your products or rendering them useless? Then you need to process the compressed air accordingly. Suitable dust filters, activated carbon absorbers, condensate drains & oil-water separators.

Your compressed air system will include diverse processing components; particularly if you produce your compressed air with oil-lubricated or oil-injected compressors. But even if you are using oil-free compressors, you may need filters, a modern piping system or other accessories. The following pages present a variety of solutions for the most varied requirements.

Our dust, fine, ultra-fine and activated carbon filters eliminate even the smallest foreign particles or aerosols. You no longer need to worry about impurities when you pass your compressed air through these processing components, as we can effectively and safely separate out dust particles up to 0.01 μm in diameter and oil carry-over up to 0.003 mg/m³ of air.

You can use our oil-water separators to process your condensate from oil-injected compressors, because this condensate always structurally contains a proportion of oil, which you must remove before you can guide water into the public sewage network. You'll also save disposal costs. You should install oil-water separators when you order a compressor.

To remove the condensate itself from the compressed air network, we provide reliable condensate drains – with electronic measuring of the level in the reservoir and automatic discharge.

You'll find a very special "separation technology" in our nitrogen generators: these units retain the oxygen from the (compressed) air using a carbon molecular sieve, producing nitrogen with purity levels of up to 99.999%. The machines pay for themselves quickly compared to the widespread way of working with hired bottle bundles.

PSA nitrogen generators, capacity 1-300 l/s, flow 4-1100 Nm³/h purity 95-99.999%

NGP series

Atlas Copco's NGP nitrogen generation systems provide a cost-effective, reliable and secure supply of nitrogen. The nitrogen generator's working principle is based on Pressure Swing Adsorption technology, which entails carbon molecular sieves that selectively separate oxygen from nitrogen. The NGP nitrogen generator is perfect for applications such as food and beverage, metal processing, electronics, etc.

CUSTOMER BENEFITS

- **Cost savings** – Our NGP systems are characterized by low operating expenses, operating expenses, and the absence of additional costs such as order processing, refills and delivery charges. Maintenance costs are kept to a minimum too.
- **Convenience** – NGP systems are continuously available, 24/7, to eliminate the risk of a production breakdown due to gas running out.
- **High purity** – We guarantee the nitrogen supply according to your needs, from 95 to 99.999% nitrogen purity.
- **Plug-and-play** – The NGP is delivered ready to use, you only need a supply of dry compressed air.



| 99.5% | Nitrogen capacity* | | | Air consumption | | |
|----------|--------------------|-------|--------|-----------------|--------|---------|
| | l/s | cfm | Nm³/h | l/s | cfm | Nm³/h |
| NGP 4 | 1.1 | 2.4 | 4.0 | 4.0 | 8.5 | 14.40 |
| NGP 9 | 2.5 | 5.3 | 9.0 | 8.3 | 17.7 | 30.00 |
| NGP 11 | 3.1 | 6.5 | 11.0 | 10.0 | 21.2 | 36.00 |
| NGP 15 | 4.2 | 8.8 | 15.0 | 15.0 | 31.8 | 54.00 |
| NGP 21 | 5.8 | 12.4 | 21.0 | 20.0 | 42.4 | 72.00 |
| NGP 30 | 8.3 | 17.7 | 30.0 | 28.3 | 60.0 | 102.00 |
| NGP 40 | 11.1 | 23.5 | 40.0 | 39.2 | 83.0 | 141.00 |
| NGP 47 | 13.1 | 27.7 | 47.0 | 43.0 | 91.1 | 154.80 |
| NGP 62 | 17.2 | 36.5 | 62.0 | 52.5 | 111.2 | 189.00 |
| NGP 73 | 20.3 | 43.0 | 73.0 | 60.0 | 127.1 | 216.00 |
| NGP 92 | 25.6 | 54.1 | 92.0 | 90.0 | 190.7 | 324.00 |
| NGP 112 | 31.1 | 65.9 | 112.0 | 106.7 | 226.0 | 384.00 |
| NGP 185 | 51.4 | 108.9 | 185.0 | 165.0 | 349.6 | 594.00 |
| NGP 250 | 69.4 | 147.1 | 250.0 | 226.9 | 480.8 | 817.00 |
| NGP 420 | 116.7 | 247.2 | 420.0 | 396.7 | 840.5 | 1428.00 |
| NGP 550 | 151.4 | 320.8 | 545.0 | 510.0 | 1080.6 | 1836.00 |
| NGP 900 | 250.0 | 529.7 | 900.0 | 800.0 | 1695.0 | 2880.00 |
| NGP 1100 | 305.6 | 647.4 | 1100.0 | 1066.7 | 2260.1 | 3840.00 |

* Performance +/- 5%.

Reference conditions:

Ambient temperature - 20°C

Ambient pressure - 1013 mbar

Unit inlet temperature - 20°C

Inlet pressure - 7.5 bar(g)

Unit outlet nitrogen purity - 99.50%

Compressed air inlet quality - ISO8573-1 class 1-4-1

Outputs:

Maximum compressed air inlet temperature - 45°C

Maximum ambient temperature - 45°C

Minimum compressed air inlet temperature - 5°C

Minimum ambient temperature - 0°C

Minimum compressed air inlet pressure - 4 bar(g)

Maximum compressed air inlet pressure - 10 bar(g)

Minimum nitrogen purity - 95%

Maximum nitrogen purity - 99.999%



For further references, please go through the following link:

www.atlascopco.com/n2o2

Membrane nitrogen generators, capacity 1.4-140 l/s, flow 5-500 Nm³/h, purity 95-99%

NGM 1-7

Atlas Copco's NGM membrane nitrogen generators provide a cost-effective, reliable and secure supply of nitrogen. The nitrogen generator's working principle is based on membrane air separation. The membrane allows nitrogen to pass and other gases (like oxygen, water vapor and CO₂) to permeate. The NGM series delivers flows from 5 to 500 Nm³/h and purities from 95% to 99%. These features make the NGM ideal for applications such as fire prevention, tire inflation, oil & gas, marine, packaging and more.

- **Convenience** – NGM systems are continuously available, 24/7, to eliminate the risk of a production breakdown due to gas running out.
- **High purity** – We guarantee the nitrogen supply according to your needs, from 95% to 99% nitrogen purity.
- **Optimal flexibility** – The NGM is available in many sizes and thanks to its modular design, your NGM set-up can be adapted to your specific needs.
- **Efficient control** – To guarantee maximum uptime, continuous surveillance is a must. By properly monitoring your system with the NGM's electronic panel, you decrease downtime as well as save energy, reduce maintenance and increase production throughput.

CUSTOMER BENEFITS

- **Cost savings** – Our NGM systems are characterized by low operating expenses, and the absence of additional costs such as order processing, refills and delivery charges. Maintenance costs are kept to a minimum too.



| 95% | 20°C | | | 7 bar(g) | | |
|-----|----------|-------|-------|-----------------|-------|-------|
| NGM | Capacity | | | Air consumption | | |
| | l/s | cfm | m³/h | l/s | cfm | m³/h |
| 1 | 3.2 | 6.7 | 11.5 | 8.2 | 17.4 | 29.5 |
| 2 | 6.3 | 13.3 | 22.7 | 16.4 | 34.7 | 59.0 |
| 3 | 11.1 | 23.5 | 39.9 | 28.9 | 61.2 | 104.0 |
| 4 | 22.2 | 47.0 | 80.0 | 57.8 | 122.5 | 208.1 |
| 5 | 33.3 | 70.6 | 119.9 | 86.7 | 183.7 | 312.1 |
| 6 | 44.4 | 94.0 | 159.8 | 115.6 | 244.9 | 416.2 |
| 7 | 55.6 | 117.8 | 200.2 | 144.4 | 305.9 | 519.8 |

Reference conditions:

Ambient temperature: 20°C

Ambient pressure: 1013 mbar

Unit inlet temperature: 20°C

Membrane working pressure: 7 bar(g)

Unit outlet nitrogen purity: 95%

Compressed air inlet quality: ISO8573-1 class 1-4-1

Outputs (Min/Max):

Maximum compressed air inlet temperature: 50°C

Maximum ambient temperature: 50°C

Minimum compressed air inlet temperature: 5°C

Minimum ambient temperature: 0°C

Minimum compressed air inlet pressure: 4 bar(g)

Maximum compressed air inlet pressure: 13 bar(g)

Minimum nitrogen purity: 90%

Maximum nitrogen purity: 99.5%

Correction Factors for Nitrogen Capacity

| Membrane pressure (barg) | Correction factor |
|--------------------------|-------------------|
| 7 | 1.0 |
| 8 | 1.2 |
| 9 | 1.4 |
| 10 | 1.6 |
| 11 | 1.8 |
| 12 | 2.0 |
| 13 | 2.1 |

| Inlet temperature (°C) | Purity (% N2) | | | | | |
|------------------------|---------------|-----|-----|-----|-----|------|
| | 95 | 96 | 97 | 98 | 99 | 99.5 |
| 5 | 0.9 | 0.9 | 0.9 | 0.9 | 0.9 | 0.9 |
| 10 | 0.9 | 0.9 | 0.9 | 0.9 | 0.9 | 0.9 |
| 20 | 1.0 | 1.0 | 1.0 | 1.0 | 1.0 | 1.0 |
| 30 | 1.0 | 1.0 | 1.0 | 1.0 | 1.0 | 1.0 |
| 40 | 1.1 | 1.1 | 1.0 | 1.0 | 0.8 | 0.6 |
| 50 | 1.2 | 1.1 | 1.1 | 1.0 | 0.8 | 0.6 |



For further references, please go through the following link:

www.atlascopco.com/n2o2

Sizing example:

NGM 4: 95%, 11 bar, 40°C

Capacity: $22.2 \text{ l/s} \times 1.8 \times 1 = 40 \text{ l/s}$

Air consumption: $57.8 \text{ l/s} \times 1.8 \times 1.2 = 124.8 \text{ l/s}$

PSA oxygen generators, capacity 0.6-56 l/s, flow 2-200 Nm³/h, purity 90-95%

OGP series

Atlas Copco's OGP oxygen generation systems provide a cost-effective, reliable and secure supply of oxygen. The oxygen generator's working principle is based on Pressure Swing Adsorption technology, with zeolite pellets that selectively isolate oxygen molecules from other molecules in compressed air. The OGP oxygen generator is perfect for applications such as ozone production, waste water treatment, health care, glass industry, etc.

CUSTOMER BENEFITS

- **Cost savings** – Our OGP systems are characterized by low operating expenses and the absence of additional costs such as order processing, refills and delivery charges. Maintenance costs are kept to a minimum too.
- **Convenience** – OGP systems are continuously available, 24/7, to eliminate the risk of a production breakdown due to gas running out.
- **High purity** – We guarantee the oxygen supply according to your needs, from 90 to 95% oxygen purity.
- **Plug-and-play** – The OGP is delivered ready to use, you only need a supply of dry compressed air.



| 90.00% | Oxygen capacity* | | | Air consumption | | |
|---------|------------------|-------|-------|-----------------|--------|---------|
| | l/s | cfm | Nm³/h | l/s | cfm | Nm³/h |
| OGP 2 | 0.6 | 1.3 | 2.0 | 6.7 | 14.1 | 22.20 |
| OGP 3 | 0.9 | 1.9 | 3.0 | 9.0 | 19.1 | 30.00 |
| OGP 4 | 1.1 | 2.4 | 3.7 | 10.8 | 22.9 | 36.00 |
| OGP 5 | 1.4 | 2.9 | 4.5 | 16.2 | 34.4 | 54.00 |
| OGP 6 | 2.0 | 4.1 | 6.5 | 21.6 | 45.8 | 72.00 |
| OGP 8 | 2.3 | 5.0 | 7.8 | 30.6 | 64.9 | 102.00 |
| OGP 10 | 2.9 | 6.0 | 9.5 | 30.6 | 64.9 | 102.00 |
| OGP 14 | 4.2 | 8.9 | 14.0 | 46.5 | 98.5 | 154.80 |
| OGP 18 | 5.5 | 11.6 | 18.2 | 56.8 | 120.2 | 189.00 |
| OGP 20 | 6.0 | 12.7 | 20.0 | 64.9 | 137.4 | 216.00 |
| OGP 23 | 6.9 | 14.6 | 23.0 | 75.7 | 160.3 | 252.00 |
| OGP 29 | 8.6 | 18.3 | 28.8 | 97.3 | 206.1 | 324.00 |
| OGP 35 | 10.4 | 21.9 | 34.5 | 108.1 | 229.0 | 360.00 |
| OGP 45 | 13.4 | 28.3 | 44.5 | 153.1 | 324.5 | 510.00 |
| OGP 55 | 16.5 | 35.0 | 55.0 | 187.4 | 397.0 | 624.00 |
| OGP 65 | 19.5 | 41.4 | 65.0 | 236.0 | 500.1 | 786.00 |
| OGP 84 | 25.2 | 53.4 | 84.0 | 290.1 | 614.6 | 966.00 |
| OGP 105 | 31.5 | 66.8 | 105.0 | 367.5 | 778.7 | 1224.00 |
| OGP 160 | 46.5 | 98.6 | 155.0 | 551.3 | 1168.1 | 1836.00 |
| OGP 200 | 60.1 | 127.2 | 200.0 | 663.0 | 1404.8 | 2208.00 |

* Performance +/- 5%.

Reference conditions:

Ambient temperature
Ambient pressure
Unit inlet temperature
Inlet pressure
Unit outlet oxygen purity
Compressed air inlet quality

20°C
1013 mbar
20°C
7.5 bar(g)
90%
ISO8573-1 class 1-4-1

Outputs

Maximum compressed air inlet temperature
Maximum ambient temperature
Minimum compressed air inlet temperature
Minimum ambient temperature
Minimum compressed air inlet pressure
Maximum compressed air inlet pressure
Minimum oxygen purity
Maximum oxygen purity

45°C
45°C
5°C
0°C
4 bar(g)
10 bar(g)
90%
95%



For further references, please go through the following link:

www.atlascopco.com/n2o2

Compressed air filters

DD+, DDp+, PD+, PDp+, QD+ filters

Atlas Copco's DD+, DDp+, PD+, PDp+ and QD+ filters efficiently reduce all types of contamination in your compressed air stream to protect your investment, equipment and processes. Our innovative filtration solutions are engineered to cost effectively provide the best quality air and meet today's increasing quality demands.

CUSTOMER BENEFITS

- **Reduced energy costs** – Designed for maximum contaminant removal, our filter range offers significant energy savings thanks to their optimal air flow path with low resistance. The filters' carefully engineered housing and cartridge ensure minimal pressure drops.

- **Solid reliability** – High performance stainless steel filter cores ensure durability of the cartridges. Protection paper avoids direct contact between the filter media and the stainless steel filter core.

- **High efficiency** – Top quality filter media in a deep-wrap layered composition ensure extremely high filtration efficiency, a low pressure drop and long cartridge lifetime. The flow path through housing and cartridge is optimized to reduce air turbulence and pressure drop.

- **Low running costs** – A unique and highly efficient head design reduces pressure drop and cuts your operational costs.



Compressed air filters: + range 7 bar

| Filter size | Inlet capacity | | Pressure | | Connections | Dimensions | | | | | | Weight | | | |
|---------------------------|----------------|-------|----------|------|-------------|------------|-------|------|-------|------|-------|--------|-------|------|--------|
| | | | | | | A | | B | | C | | D | | | |
| | l/s | cfm | bar(e) | psig | | mm | in | mm | in | mm | in | mm | in | kg | lbs |
| DD+, DDp+, PD+, PDp+, QD+ | | | | | | | | | | | | | | | |
| 10 | 10 | 21 | 7 | 102 | 3/8 | 90 | 3.54 | 61 | 2.40 | 268 | 10.55 | 75 | 2.95 | 1 | 2.2 |
| 20 | 20 | 42 | 7 | 102 | 1/2 | 90 | 3.54 | 61 | 2.40 | 268 | 10.55 | 75 | 2.95 | 1.1 | 2.4 |
| 35 | 35 | 74 | 7 | 102 | 1/2 | 90 | 3.54 | 61 | 2.40 | 323 | 12.72 | 75 | 2.95 | 1.3 | 2.9 |
| 50 | 50 | 106 | 7 | 102 | 3/4 & 1 | 110 | 4.33 | 98.5 | 3.88 | 374 | 14.72 | 75 | 2.95 | 1.6 | 4.2 |
| 70 | 70 | 148 | 7 | 102 | 1 | 110 | 4.33 | 98.5 | 3.88 | 414 | 16.3 | 75 | 2.95 | 2.1 | 4.6 |
| 130 | 130 | 275 | 7 | 102 | 1-1/2 | 140 | 5.51 | 105 | 4.13 | 520 | 20.47 | 100 | 3.94 | 4.2 | 9.3 |
| 170 | 170 | 360 | 7 | 102 | 1-1/2 | 140 | 5.51 | 105 | 4.13 | 603 | 23.74 | 100 | 3.94 | 4.5 | 9.9 |
| 210 | 210 | 445 | 7 | 102 | 1-1/2 | 140 | 5.51 | 105 | 4.13 | 603 | 23.74 | 100 | 3.94 | 4.6 | 10.1 |
| 310 | 310 | 657 | 7 | 102 | 2 & 2-1/2 | 179 | 7.05 | 121 | 4.76 | 689 | 27.13 | 150 | 5.91 | 6.9 | 15.2 |
| 425 | 425 | 901 | 7 | 102 | 3 | 210 | 8.27 | 128 | 5.04 | 791 | 31.14 | 200 | 7.87 | 11 | 24.2 |
| 550 | 550 | 1165 | 7 | 102 | 3 | 210 | 8.27 | 128 | 5.04 | 961 | 37.83 | 200 | 7.87 | 12.6 | 27.8 |
| 550F | 520 | 1102 | 7 | 102 | DN80 | 330 | 12.99 | 189 | 7.44 | 1292 | 50.87 | 728 | 29.66 | 71 | 156.5 |
| 780F | 780 | 1653 | 7 | 102 | DN100 | 460 | 18.11 | 228 | 8.98 | 1320 | 51.97 | 686 | 27.01 | 127 | 280.0 |
| 1050F | 1050 | 2225 | 7 | 102 | DN100 | 460 | 18.11 | 228 | 8.98 | 1320 | 51.97 | 686 | 27.01 | 128 | 282.0 |
| 1400F | 1400 | 2967 | 7 | 102 | DN150 | 550 | 21.65 | 287 | 11.30 | 1464 | 57.64 | 672 | 26.46 | 189 | 416.7 |
| 1800F | 1800 | 3814 | 7 | 102 | DN150 | 570 | 22.44 | 282 | 11.10 | 1467 | 57.76 | 681 | 26.81 | 210 | 463.0 |
| 2100F | 2100 | 4450 | 7 | 102 | DN150 | 620 | 24.41 | 291 | 11.46 | 1499 | 59.02 | 676 | 26.61 | 251 | 553.4 |
| 2700F | 2700 | 5721 | 7 | 102 | DN200 | 740 | 29.13 | 352 | 13.86 | 1634 | 64.33 | 692 | 27.24 | 328 | 723.1 |
| 3150F | 3150 | 6675 | 7 | 102 | DN200 | 740 | 29.13 | 352 | 13.86 | 1634 | 64.33 | 692 | 27.24 | 329 | 725.3 |
| 4800F | 4800 | 10171 | 7 | 102 | DN250 | 740 | 29.13 | 410 | 16.14 | 1662 | 65.43 | 800 | 31.5 | 507 | 1118.0 |
| 7200F | 7200 | 15257 | 7 | 102 | DN300 | 1000 | 39.37 | 485 | 19.09 | 1755 | 69.09 | 850 | 33.46 | 675 | 1488.0 |

| | DD+ | DDp+ | PD+ | PDp+ | QD+ |
|---|------|-------|-------|-------|-------|
| Dry pressure drop (mbar) | NA | 85 | NA | 100 | 140 |
| Wet pressure drop (mbar) | 180 | NA | 215 | NA | NA |
| Max oil carry-over (mg/m ³) | 0.07 | NA | 0.008 | NA | 0.003 |
| Count efficiency (% at MPPS) | NA | 99.92 | NA | 99.98 | NA |

* inlet oil concentration 10 mg/m³

** after DD+ PD+

| | | | | | | | | | | | | |
|-----------------------|------|------|------|------|------|------|-----|------|-----|------|------|-----|
| Inlet pressure (bar) | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 10 | 12 | 14 | 16 |
| Inlet pressure (psig) | 15 | 29 | 44 | 58 | 72.5 | 87 | 102 | 116 | 145 | 174 | 203 | 232 |
| Correction factor | 0.38 | 0.53 | 0.65 | 0.75 | 0.83 | 0.92 | 1 | 1.06 | 1.2 | 1.31 | 1.41 | 1.5 |

Compressed air filters: + range 20 bar

| Filter size | Inlet capacity | | Pressure | | Connections | Dimensions | | | | | | Weight | | | |
|---------------------------|----------------|-------|----------|------|-------------|------------|-------|------|-------|------|-------|--------|-------|------|--------|
| | | | | | | A | | B | | C | | D | | | |
| | l/s | cfm | bar(e) | psig | | mm | in | mm | in | mm | in | mm | in | kg | lbs |
| DD+, DDp+, PD+, PDp+, QD+ | | | | | | | | | | | | | | | |
| 10 | 10 | 21 | 7 | 102 | 3/8 | 90 | 3.54 | 61 | 2.40 | 268 | 10.55 | 75 | 2.95 | 1 | 2.2 |
| 20 | 20 | 42 | 7 | 102 | 1/2 | 90 | 3.54 | 61 | 2.40 | 268 | 10.55 | 75 | 2.95 | 1.1 | 2.4 |
| 35 | 35 | 74 | 7 | 102 | 1/2 | 90 | 3.54 | 61 | 2.40 | 323 | 12.72 | 75 | 2.95 | 1.3 | 2.9 |
| 50 | 50 | 106 | 7 | 102 | 3/4 & 1 | 110 | 4.33 | 98.5 | 3.88 | 374 | 14.72 | 75 | 2.95 | 1.6 | 4.2 |
| 70 | 70 | 148 | 7 | 102 | 1 | 110 | 4.33 | 98.5 | 3.88 | 414 | 16.3 | 75 | 2.95 | 2.1 | 4.6 |
| 130 | 130 | 275 | 7 | 102 | 1-1/2 | 140 | 5.51 | 105 | 4.13 | 520 | 20.47 | 100 | 3.94 | 4.2 | 9.3 |
| 170 | 170 | 360 | 7 | 102 | 1-1/2 | 140 | 5.51 | 105 | 4.13 | 603 | 23.74 | 100 | 3.94 | 4.5 | 9.9 |
| 210 | 210 | 445 | 7 | 102 | 1-1/2 | 140 | 5.51 | 105 | 4.13 | 603 | 23.74 | 100 | 3.94 | 4.6 | 10.1 |
| 310 | 310 | 657 | 7 | 102 | 2 & 2-1/2 | 179 | 7.05 | 121 | 4.76 | 689 | 27.13 | 150 | 5.91 | 6.9 | 15.2 |
| 425 | 425 | 901 | 7 | 102 | 3 | 210 | 8.27 | 128 | 5.04 | 791 | 31.14 | 200 | 7.87 | 11 | 24.2 |
| 550 | 550 | 1165 | 7 | 102 | 3 | 210 | 8.27 | 128 | 5.04 | 961 | 37.83 | 200 | 7.87 | 12.6 | 27.8 |
| 550F | 520 | 1102 | 7 | 102 | DN80 | 330 | 12.99 | 189 | 7.44 | 1292 | 50.87 | 728 | 29.66 | 71 | 156.5 |
| 780F | 780 | 1653 | 7 | 102 | DN100 | 460 | 18.11 | 228 | 8.98 | 1320 | 51.97 | 686 | 27.01 | 127 | 280.0 |
| 1050F | 1050 | 2225 | 7 | 102 | DN100 | 460 | 18.11 | 228 | 8.98 | 1320 | 51.97 | 686 | 27.01 | 128 | 282.0 |
| 1400F | 1400 | 2967 | 7 | 102 | DN150 | 550 | 21.65 | 287 | 11.30 | 1464 | 57.64 | 672 | 26.46 | 189 | 416.7 |
| 1800F | 1800 | 3814 | 7 | 102 | DN150 | 570 | 22.44 | 282 | 11.10 | 1467 | 57.76 | 681 | 26.81 | 210 | 463.0 |
| 2100F | 2100 | 4450 | 7 | 102 | DN150 | 620 | 24.41 | 291 | 11.46 | 1499 | 59.02 | 676 | 26.61 | 251 | 553.4 |
| 2700F | 2700 | 5721 | 7 | 102 | DN200 | 740 | 29.13 | 352 | 13.86 | 1634 | 64.33 | 692 | 27.24 | 328 | 723.1 |
| 3150F | 3150 | 6675 | 7 | 102 | DN200 | 740 | 29.13 | 352 | 13.86 | 1634 | 64.33 | 692 | 27.24 | 329 | 725.3 |
| 4800F | 4800 | 10171 | 7 | 102 | DN250 | 740 | 29.13 | 410 | 16.14 | 1662 | 65.43 | 800 | 31.5 | 507 | 1118.0 |
| 7200F | 7200 | 15257 | 7 | 102 | DN300 | 1000 | 39.37 | 485 | 19.09 | 1755 | 69.09 | 850 | 33.46 | 675 | 1488.0 |

| | DD+ | DDp+ | PD+ | PDp+ | QD+ |
|---|------|-------|-------|-------|-------|
| Dry pressure drop (mbar) | NA | 85 | NA | 100 | 140 |
| Wet pressure drop (mbar) | 180 | NA | 215 | NA | NA |
| Max oil carry-over (mg/m ³) | 0.07 | NA | 0.008 | NA | 0.003 |
| Count efficiency (% at MPPS) | NA | 99.92 | NA | 99.98 | NA |

* inlet oil concentration 10 mg/m³

** after DD+ PD+

| | | | | | | | | | | | | |
|-----------------------|------|------|------|------|------|------|-----|------|-----|------|------|-----|
| Inlet pressure (bar) | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 10 | 12 | 14 | 16 |
| Inlet pressure (psig) | 15 | 29 | 44 | 58 | 72.5 | 87 | 102 | 116 | 145 | 174 | 203 | 232 |
| Correction factor | 0.38 | 0.53 | 0.65 | 0.75 | 0.83 | 0.92 | 1 | 1.06 | 1.2 | 1.31 | 1.41 | 1.5 |

Water separators and drains

WSD 25-750 / WD 80 / EWD 50-1500

Atlas Copco's WSD water separators are delivered as standard with our HD and TD after-coolers. They can also be installed in any point of your air net. The WD 80 drain valve provides completely automatic drainage of the condensate which collects at the bottom of the air receiver. The range of EWD electronically controlled condensate drains provides safe, dependable and economical condensate management.

CUSTOMER BENEFITS

- **Minimal maintenance** – Maintenance-free with no moving parts, the water separators have an automatic and manual drain.
- **High reliability** – The reliable automatic drain devices prevent condensed water from building up in the coolers.
- **Energy savings** – The intelligent drain function monitors condensate build-up with liquid level sensors and evacuates the condensate only when necessary, thus avoiding wastage of compressed air and giving considerable energy savings.
- **Flexible installation** – A wide range of different EWD drains is available for oil contaminated condensate and also may be provided with additional hard coating for use with oil-free and aggressive condensate.



WSD 25–750



TD 08–650



WD 80



HD 4–96

| Type | Maximum working pressure | Volume flow ¹⁾ | | Operating temperature | | Compressed air connection | Approx. weight | Dimensions L × W × H |
|--|--------------------------|---------------------------|--------|-----------------------|--------|---------------------------|----------------|----------------------|
| | bar | l/s | m³/min | min °C | max °C | | kg | mm |
| WSD – Water separator with automatic and manual drain | | | | | | | | |
| WSD 25 | 20 | 25 | 1.5 | 1 | 70 | G 1" | 2.5 | 150 × 85 × 275 |
| WSD 80 | 20 | 80 | 4.8 | 1 | 70 | G 1 1/2" | 3.5 | 185 × 130 × 432 |
| WSD 250 | 20 | 250 | 15.0 | 1 | 70 | G 2 1/2" | 12.5 | 230 × 160 × 532 |
| WSD 750 | 16 | 750 | 45.0 | 1 | 70 | ²⁾ | 15.0 | 298 × 194 × 627 |
| WD – Condensate drain | | | | | | | | |
| WD 80 | 16 | 80 | 4.8 | 1 | 70 | G 1/2" | 2.7 | 132 × 132 × 182 |

¹⁾ Based on 20°C, 1 bar. Reference conditions: 7 bar working pressure, inlet temperature 30°C.

| Type | Maximum working pressure ¹⁾ | Volume flow ²⁾ | | Pressure loss | Compressed air outlet temperature | Motor rated power | Compressed air connection | Approx. weight | Dimensions L × W × H |
|-------------------------------------|--|---------------------------|--------|---------------|-----------------------------------|-------------------|---------------------------|----------------|----------------------|
| | bar | l/s | m³/min | bar | °C | kW | | kg | mm |
| TD – Aftercooler, air-cooled | | | | | | | | | |
| TD 08 | 10.5/20 | 8 | 0.48 | 0.12 | 35 | 0.05 | G 1/2" | 6 | 270 × 130 × 225 |
| TD 25 | 10.5/20 | 25 | 1.50 | 0.13 | 35 | 0.12 | G 1" | 19 | 460 × 391 × 658 |
| TD 50 | 10.5/20 | 50 | 3.00 | 0.21 | 35 | 0.18 | G 1" | 23 | 560 × 437 × 735 |
| TD 150 | 10.5/20 | 150 | 9.00 | 0.13 | 35 | 0.75 | G 2 1/2" | 53 | 740 × 479 × 1160 |
| TD 300 | 10.5/20 | 300 | 18.00 | 0.14 | 35 | 0.75 | G 2" | 73 | 960 × 493 × 1280 |
| TD 650 | 10.5/20 | 650 | 39.00 | 0.16 | 35 | 2.20 | DN 100 | 185 | 1410 × 770 × 1525 |

¹⁾ 20 bar up to maximum compressed air inlet temperature 130°C, 10.5 bar up to maximum 200°C.

²⁾ Based on 20°C, 1 bar, with reference conditions: working pressure 7 bar, inlet temperature 160°C, ambient temperature 20°C.

Note: DL = Compressed air. Voltage 400 V/50 Hz (TD 08 and 230 V). Other voltages available on request.

| Type | Maximum working pressure ¹⁾ | Volume flow ²⁾ | | Pressure loss | Compressed air outlet temperature | Water connection | Compressed air connection | | Approx. weight | Dimensions L × W × H |
|---------------------------------------|--|---------------------------|--------|---------------|-----------------------------------|------------------|---------------------------|-----------|----------------|----------------------|
| | bar | l/s | m³/min | bar | °C | | Inlet | Outlet | kg | |
| HD – Aftercooler, water-cooled | | | | | | | | | | |
| HD 4 | 20.0 | 67 | 4 | 150 | 27 | G 3/8" | G 1 1/2" | G 1 1/2" | 55 | 344 × 170 × 1840 |
| HD 8 | 20.0 | 133 | 8 | 200 | 27 | G 1/2" | DN 65 | DN 65 | 78 | 475 × 215 × 1973 |
| HD 11 | 20.0 | 183 | 11 | 190 | 26 | G 1/2" | DN 65 | DN 65 | 85 | 483 × 230 × 1975 |
| HD 16 | 10.5 | 267 | 16 | 160 | 28 | G 3/4" | DN 100 | DN 80 | 180 | 645 × 500 × 2083 |
| HD 32 | 10.5 | 533 | 32 | 190 | 28 | G 1" | DN 100 | DN 80 | 210 | 635 × 500 × 2083 |
| HD 48 | 10.5 | 800 | 48 | 190 | 28 | G 1 1/4" | DN 150 | 2 × DN 80 | 380 | 1032 × 490 × 2112 |
| HD 64 | 10.5 | 1067 | 64 | 190 | 28 | G 1 1/4" | DN 150 | 2 × DN 80 | 410 | 1032 × 490 × 2112 |
| HD 96 | 10.5 | 1600 | 96 | 190 | 28 | G 1 1/2" | DN 175 | 3 × DN 80 | 430 | 1412 × 490 × 2139 |

¹⁾ Maximum compressed air inlet temperature: 220°C.

²⁾ Based on 20°C, 1 bar, with reference conditions: water inlet temperature of 20°C, water heating of 15°C, working pressure 7 bar, inlet temperature 160°C.

Note: DL = Compressed air

Activated carbon tower, 20-310 l/s, 42-657 cfm QDT

In the pharmaceutical, food & beverage, electronic and other industries where air purity is critical, you often need to remove residual oil vapors and odors from the compressed air supply. That is exactly what Atlas Copco's high-efficiency carbon filter does. The QDT activated carbon towers will, through the process of adsorption, reduce the residual oil content to lower than 0.003 mg/m³ at 35°C/95°F and 7 bar inlet pressure. The pressure drop is low and stays minimal during the lifetime of the filter. Only an activated carbon tower is able to provide Class 1 clean air in accordance with ISO 8573-1.



CUSTOMER BENEFITS

- Maximum oil vapor removal
- Pressure drop stays low
- Highest reliability
- Easy maintenance

| Filter size | Nominal capacity ⁽¹⁾ | | Connections G or NPt | Dimension | | | | | | Weight | |
|-------------|---------------------------------|-----|-------------------------|-----------|----|--------|----|-------|----|--------|-----|
| | | | | Height | | Length | | Width | | | |
| | l/s | cfm | | mm | in | mm | in | mm | in | kg | lbs |
| QDT | | | | | | | | | | | |
| QDT 20 | 20 | 42 | 1/2 | 490 | 19 | 223 | 9 | 190 | 7 | 10 | 22 |
| QDT 45 | 45 | 95 | 1 | 715 | 28 | 223 | 9 | 190 | 7 | 15 | 33 |
| QDT 60 | 60 | 127 | 1 | 840 | 33 | 223 | 9 | 190 | 7 | 18 | 40 |
| QDT 95 | 95 | 201 | 1 | 715 | 28 | 387 | 15 | 190 | 7 | 29 | 64 |
| QDT 125 | 125 | 265 | 1 1/2 | 840 | 33 | 387 | 15 | 190 | 7 | 34 | 75 |
| QDT 150 | 150 | 318 | 1 1/2 | 715 | 28 | 551 | 22 | 190 | 7 | 42 | 93 |
| QDT 185 | 185 | 392 | 1 1/2 | 840 | 33 | 551 | 22 | 190 | 7 | 50 | 110 |
| QDT 245 | 245 | 519 | 1 1/2 | 840 | 33 | 715 | 28 | 190 | 7 | 67 | 148 |
| QDT 310 | 310 | 657 | 1 1/2 | 840 | 33 | 879 | 35 | 190 | 7 | 84 | 185 |

(1) At reference conditions:

Inlet pressure 7 bar(g)/102 psig, inlet temperature 35°C/95°F.

For other compressed air inlet temperatures, please multiply the filter capacity by the following correction factor (Kt):

| | | | | | | | | | |
|----------------------|------|------|------|----|------|------|------|------|------|
| Inlet temperature °C | 20 | 25 | 30 | 35 | 40 | 45 | 50 | 55 | 60 |
| Inlet temperature °F | 68 | 77 | 86 | 95 | 104 | 113 | 122 | 131 | 140 |
| Correction factor | 1.67 | 1.43 | 1.25 | 1 | 0.71 | 0.56 | 0.37 | 0.25 | 0.19 |

For other compressed air inlet pressures, please multiply the filter capacity by the following correction factor (Kp):

| | | | | | | | | | | | |
|---------------------|------|------|------|----|-----|-----|-----|------|------|------|------|
| Inlet pressure bar | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 |
| Inlet pressure psig | 44 | 58 | 73 | 87 | 102 | 116 | 131 | 145 | 160 | 174 | 189 |
| Correction factor | 0.57 | 0.77 | 0.83 | 1 | 1 | 1 | 1 | 1.05 | 1.05 | 1.11 | 1.18 |

Example:

What is the capacity of a QDT 60, working at 8 bar(g)/116 psig with an inlet temperature of 40°C/104°F?

$K_p = 1$ $K_t = 0.71$

Actual capacity = $60 \times 1 \times 0.71 = 42.6$ l/s or 90.3 cfm



Oil/water separator systems for the condensate treatment

OSC and OSD

Atlas Copco's OSD and OSC condensate separators efficiently separate the oil from the water in condensates. The harmless water is drained away and the oil disposed of in an environmentally friendly manner. The OSD condensate treatment package is fully integrated into the compressor, reducing both installation costs and complexity. The OSC free standing units can separate all kinds of condensate from all compressor technologies, giving unparalleled performance and reliability for minimal maintenance.

- Minimal maintenance.
- Reducing lifetime costs.
- Simple, fast and clean cartridge exchange.

• Benefits of the OSD free-standing units

- No oil collection bottle required, so no chance to ruin previously separated condensate.
- Multiple oil condensate can be easily separated, Polyglycol condensate can be separated, Most condensate emulsions can be separated.




OSC 600

CUSTOMER BENEFITS

• Benefits of the OSD integrated solution

- High efficiency separation for worry-free condensate discharge.
- Performance independent of filter age.
- No installation required, saving time and money.
- Zero footprint, saving space and simplifying placing.



| Type | Volume flow ¹⁾ [Cold climate] | | Volume flow ¹⁾ [Mild climate] | | Volume flow ¹⁾ [Hot climate] | | Oil carry-over condensate | Approx. weight | Dimensions L × W × H |
|--|---|--------|---|--------|--|--------|---------------------------|----------------|-------------------------|
| | l/s | m³/min | l/s | m³/min | l/s | m³/min | mg/l | kg | mm |
| OSC – Oil-water separator (values for systems with compressors, air receivers, dryers and filters) | | | | | | | | | |
| OSC 35 | 65 | 3.9 | 35 | 2.1 | 17 | 1.0 | < 20 | 4 | 470 × 165 × 600 |
| OSC 95 | 180 | 10.8 | 95 | 5.7 | 45 | 2.7 | < 20 | 13 | 680 × 255 × 750 |
| OSC 145 | 270 | 16.2 | 145 | 8.7 | 70 | 4.2 | < 20 | 15 | 680 × 255 × 750 |
| OSC 355 | 665 | 39.9 | 355 | 21.3 | 170 | 10.2 | < 20 | 25 | 750 × 546 × 900 |
| OSC 600 | 1150 | 69.0 | 605 | 36.3 | 290 | 17.4 | < 20 | 26 | 750 × 546 × 1030 |
| OSC 825 | 1550 | 93.0 | 825 | 49.5 | 400 | 24.0 | < 20 | 28 | 945 × 650 × 1100 |
| OSC 1200 | 2220 | 133.2 | 1180 | 70.8 | 570 | 34.2 | < 20 | 30 | 945 × 695 × 1100 |
| OSC 2400 | 4440 | 266.4 | 2360 | 141.6 | 1145 | 68.7 | < 20 | 60 | 945 × 1185 × 1100 |
| Type | Volume flow ¹⁾ [Cold climate] | | Volume flow ¹⁾ [Mild climate] | | Volume flow ¹⁾ [Hot climate] | | Oil carry-over condensate | Approx. weight | Dimensions L × W × H |
| | l/s | m³/min | l/s | m³/min | l/s | m³/min | mg/l | kg | mm |
| OSC – Oil-water separator (Values for systems with compressors, air receivers and filters) | | | | | | | | | |
| OSC 35 | 105 | 6.3 | 45 | 2.7 | 20 | 1.2 | < 20 | 4 | 470 × 165 × 600 |
| OSC 95 | 280 | 16.8 | 118 | 7.1 | 50 | 3.0 | < 20 | 13 | 680 × 255 × 750 |
| OSC 145 | 415 | 24.9 | 175 | 10.5 | 75 | 4.5 | < 20 | 15 | 680 × 255 × 750 |
| OSC 355 | 1035 | 62.1 | 435 | 26.1 | 190 | 11.4 | < 20 | 25 | 750 × 546 × 900 |
| OSC 600 | 1800 | 108.0 | 760 | 46.8 | 330 | 19.8 | < 20 | 26 | 750 × 546 × 1030 |
| OSC 825 | 2410 | 144.6 | 1020 | 61.2 | 440 | 26.4 | < 20 | 28 | 945 × 650 × 1100 |
| OSC 1200 | 3450 | 207.0 | 1455 | 87.3 | 630 | 37.8 | < 20 | 30 | 945 × 695 × 1100 |
| OSC 2400 | 6895 | 413.7 | 2910 | 174.6 | 1260 | 75.6 | < 20 | 60 | 945 × 1185 × 1100 |

| Type | Volume flow ¹⁾ | | Oil content in effluent | Oil canister capacity | Approx. weight | Dimensions L × W × H |
|---------------------------------------|---------------------------|--------|-------------------------|-----------------------|----------------|--------------------------|
| | l/s | m³/min | mg oil/l | L | kg | mm |
| OSD – Oil-water separator, integrated | | | | | | |
| OSD 22 | 60 | 3.6 | < 20 | 1 | 8 | integrated in compressor |
| OSD 90 | 250 | 15.0 | < 20 | 2 | 9 | integrated in compressor |
| OSD 315 | 770 | 46.2 | < 20 | 2 | 13 | integrated in compressor |

¹⁾ With reference conditions: suction temperature 35°C, 70% relative humidity. In addition, depending on your compressor type and oil type.

²⁾ Dimensions: integrated in compressor (depending on type).

VACUUM PUMPS

Vacuum is critical in a wide variety of applications – and the need for vacuum continues to grow, for example in the development of hightech composite materials used in wind farms, aircraft manufacture etc.

Atlas Copco has been developing state-of-the-art high-end vacuum solutions for many years. We have a market-leading status in the ongoing innovation of gas compression techniques such as screw, claw and scroll. Our vacuum specialists are constantly improving

the performance of our products, targeting new application areas, and meeting new challenges.

The result is a wide portfolio of vacuum pumps that consistently help our customers become more efficient by lowering the cost of ownership, increasing sustainable productivity and enhancing final product quality.

Vacuum Pumps

What's your vacuum?

One of the first questions you have to consider is the type of vacuum you need. The vacuum market can be divided into two segments – fine and rough. These two areas of vacuum are very different; they utilize different technologies, products and solutions, and often serve different markets, although there are some overlaps. Pneurop, the European committee of manufacturers of compressors, vacuum pumps, pneumatic tools and allied equipment, sets the limit for rough vacuum as 1 mbar. Atlas Copco's special focus is the rough vacuum segment.

Atlas Copco has been developing state-of-the-art high-end vacuum solutions for many years. We have a market-leading status in the ongoing innovation of gas compression techniques such as screw, claw and scroll. Our vacuum specialists are constantly improving the performance of our products, targeting new application areas, and meeting new challenges.

The result is a wide portfolio of vacuum pumps that consistently help our customers become more efficient by lowering the cost of ownership, increasing sustainable productivity and enhancing final product quality.

Rough vacuum

- Pressure range: 1000 – 1 mbar (hPa).
- Also known as coarse pressure or industrial vacuum.
- Applications include medical, packaging (food/ meat and non-food), paper and printing, power, woodworking, oil and gas.

Fine vacuum

- Pressure range:
 - Medium: 1 – 10⁻⁵ mbar (hPa).
 - High: 10⁻⁵ – 10⁻⁹ mbar (hPa).
 - Ultra-high: 10⁻⁹ – 10⁻¹² mbar (hPa).
- Also known by some customers as scientific vacuum.
- Applications include semiconductor manufacturing, analytics, R&D labs, thin film coatings.



Download a QR Reader and scan the code for more information on vacuums.

www.atlascopco.com/vacuum

Oil-sealed rotary vane vacuum pumps, 20-365 m³/h, 12-215 cfm

GV 20-300

Atlas Copco's GV 20-300 range is a series of robust and reliable oil-sealed rotary vane vacuum pumps, packed with innovative features.

Oil-sealed rotary vane vacuum pumps are ideal for critical applications like packaging and material handling in the general industry. With 8 models, offering pumping speeds of between 20 and 365 m³/h, you will definitely find the right model for your specific application.

CUSTOMER BENEFITS

- **High reliability** – Thanks to a rugged design and optimal oil retention at all operating pressures. An inlet non-return valve protects the pump against counter rotation.
- **Plug and play installation** – Easy installation thanks to a compact, space-saving design.
- **Easy maintenance** – Wear is low thanks to optimally selected shaft speeds. Servicing can be done by the same engineer that services your compressed air equipment.
- **Low noise and vibration levels throughout the pressure range**



| Type | Pumping speed | | Ultimate pressure (2) | | Motor size | | Water handling capability | | Motor supply specification |
|------------------------|---------------|-------|-----------------------|------|------------|----------|---------------------------|------|--|
| Oil-sealed rotary vane | | | | | 1 ph | 3 ph | Vapor limit | | |
| | m³/h | cfm | mbar (hPa) | torr | kW | kW | mbar | kg/h | |
| GV 20 | 20 | 10.5 | 2 | 1.50 | 0.75 | Optional | 35 | 0.5 | 1 - 230V 50Hz |
| | 21 | 12.3 | 2 | 1.50 | 0.9 | Optional | 35 | 0.5 | 1 - 230V 60Hz |
| GV 25 | 25 | 14.7 | 0.5 | 0.38 | 0.75 | 0.75 | 40 | 0.7 | 1 - 230V 50Hz |
| | 29 | 17.0 | 0.5 | 0.38 | 0.9 | 0.9 | 40 | 0.7 | 1 - 230V 60Hz |
| GV 40 | 40 | 23.5 | 0.5 | 0.38 | 1.1 | 1.1 | 30 | 0.9 | 3 - 175-260/300-450V 50Hz |
| | 48 | 28.3 | 0.5 | 0.38 | 1.35 | 1.35 | 30 | 0.9 | 3 - 200-300/346-520V 60Hz |
| GV 60 | 60 | 35.3 | 0.5 | 0.38 | - | 1.5 | 40 | 1.8 | 3 - 175-260/300-450V 50Hz |
| | 75 | 44.1 | 0.5 | 0.38 | - | 1.8 | 40 | 1.8 | 3 - 200-300/346-520V 60Hz |
| GV 100 | 105 | 61.8 | 0.5 | 0.38 | - | 2.2 | 30 | 2.2 | IE2 motor 3-230/400V 50Hz (1) |
| | 125 | 73.6 | 0.5 | 0.38 | - | 3 | 30 | 2.2 | 3-IE2 motor 208-230V/265-460V 60Hz (1) |
| GV 150 | 150 | 88.3 | 0.5 | 0.38 | - | 3.3 | 25 | 2.5 | IE2 motor 3-230/400V 50Hz (1) |
| | 180 | 106.0 | 0.5 | 0.38 | - | 3.7 | 25 | 2.5 | 3-IE2 motor 208-230V/265-460V 60Hz (1) |
| GV 200 | 205 | 120.7 | 0.5 | 0.38 | - | 5.5 | 25 | 3.5 | IE2 motor 3-230/400V 50Hz (1) |
| | 245 | 144.2 | 0.5 | 0.38 | - | 6.6 | 25 | 3.5 | 3-IE2 motor 208-230V/265-460V 60Hz (1) |
| GV 300 | 305 | 179.5 | 0.5 | 0.38 | - | 7.5 | 25 | 5 | IE2 motor 3-230/400V 50Hz (1) |
| | 365 | 214.8 | 0.5 | 0.38 | - | 8.6 | 25 | 5 | 3-IE2 motor 208-230V/265-460V 60Hz (1) |

(1) Smaller non-IE2 motors are available for continuous low pressure duties.

(2) With gas ballast valve open. All units achieve better than 0.5 mbar with gas ballast closed.

Oil-sealed rotary screw vacuum pumps, 557-5734 m³/h, 328-3377 cfm GV 630-4800

Atlas Copco's oil-sealed rotary screw vacuum pumps bring reliable, efficient rough vacuum to the general industry. The GV 630-4800 combines a robust oil-sealed rotary screw technology with Atlas Copco's advanced screw element design.

Oil-sealed rotary screw vacuum pumps are particularly efficient in the operating pressure range between 1 mbar(a) to 500 mbar(a). That means the GV is ideal for applications such as printing, canning, plastics, electronics, packaging, bottling and similar industries.

Customer benefits

- **High reliability** – Oil-sealed technology offers wear-free, robust operation. Reliable, oversized motors and efficient oil-mist separation ensures durable operation.
- **Best-in-class efficiency** – With the highest performance output per kW input, the GV probably outperforms all other vacuum technologies in its pressure range. State-of-the-art coalescing filters reduce oil consumption, running temperatures and motor power consumption. Thanks to a modulating valve, the capacity of the pump can be matched exactly to the demand.
- **Plug and play installation** – A small footprint and space-saving canopy with lift-out panels offer easy installation and easy maintenance.
- **Silent operation** – The two screw elements rotate at slow speeds, so the GV runs at a sound level as low as 69 dB(A). This silent operation allows you to install the GV close to the point of use.



| Model 50 Hz version | Maximum shaft power | | | | Pumping speed | | Ultimate pressure | | Inlet connector | Dimensions (L x W x H) | Weight | |
|------------------------|---------------------|-------|--------------|-------|---------------|------|-------------------|------|-----------------|------------------------|--------|------|
| | Air-cooled | | Water-cooled | | m³/h | cfm | mbar (hPa) | torr | | mm | kg | lbs |
| | kW | hp | kW | hp | | | | | | | | |
| Model 50 Hz version | | | | | | | | | | | | |
| GV 630 | 10.1 | 13.5 | 9.8 | 13.1 | 557 | 328 | 0.7 | 0.5 | DN100 | 2040 x 1280 x 1480 | 1070 | 2355 |
| GV 1000 | 20.4 | 27.4 | 20.2 | 27.1 | 863 | 508 | 0.7 | 0.5 | DN100 | 2040 x 1280 x 1480 | 1105 | 2430 |
| GV 1200 | 30.8 | 41.3 | 30.5 | 40.9 | 1126 | 663 | 0.7 | 0.5 | DN125 | 2040 x 1280 x 1480 | 1105 | 2430 |
| GV 1600 | 41.4 | 55.5 | 39.8 | 53.4 | 1601 | 942 | 0.7 | 0.5 | DN125 | 2560 x 1710 x 1970 | 1805 | 3970 |
| GV 2500 | 58.2 | 78.1 | 56.5 | 75,8 | 2432 | 1432 | 0.7 | 0.5 | DN200 | 2560 x 1710 x 1970 | 2860 | 6290 |
| GV 4800 | 118.5 | 159.9 | 115.8 | 155.3 | 4778 | 2814 | 0.7 | 0.5 | DN200 | 2990 x 1990 x 2000 | 3680 | 8100 |
| Model 60 Hz version | | | | | | | | | | | | |
| GV 630 | 11.7 | 15.7 | 11.3 | 15.2 | 668 | 393 | 0.7 | 0.5 | DN100 | 2040 x 1280 x 1480 | 1080 | 2370 |
| GV 1000 | 22.1 | 29.6 | 21.7 | 29.1 | 1036 | 610 | 0.7 | 0.5 | DN100 | 2040 x 1280 x 1480 | 1115 | 2450 |
| GV 1200 | 37.4 | 50.1 | 36.0 | 48.3 | 1351 | 796 | 0.7 | 0.5 | DN125 | 2040 x 1280 x 1480 | 1130 | 2480 |
| GV 1600 | 49.5 | 66.4 | 48.6 | 65.2 | 1921 | 1131 | 0.7 | 0.5 | DN125 | 2560 x 1710 x 1970 | 1820 | 4000 |
| GV 2500 | 69.1 | 92.7 | 67.5 | 90.5 | 2918 | 1719 | 0.7 | 0.5 | DN200 | 2560 x 1710 x 1970 | 2885 | 6350 |
| GV 4800 | 142.6 | 191.2 | 140.3 | 188.2 | 5734 | 3377 | 0.7 | 0.5 | DN200 | 2990 x 1990 x 2000 | 3680 | 8100 |

Available accessories & options

| | | GV 630 | GV 1000 | GV 1200 | GV 1600 | GV 2500 | GV 4800 |
|-------------|--|--------|---------|---------|---------|---------|---------|
| Accessories | Liquid separators | ○ | ○ | ○ | ○ | ○ | ○ |
| | Inlet filters | ● | ● | ● | ● | ○ | ○ |
| | Vacuum tank/receivers | ○ | ○ | ○ | ○ | ○ | ○ |
| | Check valves & pump isolation valves | ○ | ○ | ○ | ○ | ○ | ○ |
| | Vacuum gauges (various types & ranges) | ○ | ○ | ○ | ○ | ○ | ○ |
| | Multiple pump controllers | ○ | ○ | ○ | ○ | ○ | ○ |
| Options | Air-cooled | ○ | ○ | ○ | ○ | ○ | ○ |
| | Water-cooled | ○ | ○ | ○ | ○ | ○ | ○ |
| | Phase sequence protection | ○ | ○ | ○ | ○ | ○ | ○ |
| | Increased water handling capability | ○ | ○ | ○ | ○ | ○ | ○ |
| | Vacuum oil PG | ● | ● | ● | ● | ● | ● |
| | Vacuum oil PG plus for extended duty | ○ | ○ | ○ | ○ | ○ | ○ |
| | Food grade oil | ○ | ○ | ○ | ○ | ○ | ○ |

● : Standard

○: Optional

CENTRIFUGAL COMPRESSORS, EXPANDERS AND PUMPS

We bring innovative drive and decades of engineering experience to the industrial equipment we produce. Our compressors, expanders and cryogenic pumps support a wide range of markets and applications across the globe.

Centrifugal Turbomachinery and Cryogenic Pumps

Atlas Copco turbocompressors, expansion turbines and cryogenic pumps are found at the heart of industries that keep the world in motion: oil and gas, industrial gases, and power generation. Our innovative compression and pump designs deliver top performance in an efficient, compact package and ensure decades of reliable use under some of the most demanding conditions.

Centrifugal Air and Gas Compressors

Atlas Copco centrifugal compressors are built using cutting-edge aerodynamic technology and proven, heavy-duty components. They deliver the high flow rates and pressure levels necessary for such important processes as plant air in petrochemical or industrial gas installations.

Utilizing multi-stage compression with as many as eight stages on a single gearbox, our centrifugal gas compressors can be configured to handle combined processes in one cycle – such as processing different gases simultaneously – and they supply the high flow and pressure levels that might otherwise require additional machinery. Our centrifugal gas compressors can handle flow volumes from 250-400 000 m³/h* and generate pressures up to 200 bar.

Exclusive impeller design and control options, such as variable inlet- and diffuser-guide vanes, ensure that pressure and flow rates remain constant even as factors such as ambient temperature or back pressure change.

Likewise, when the ability to precisely control gas volume is key – in applications such as fuel gas boosting for gas turbines – our speed controls deliver the crucial large turndown range required.

Expansion Turbines (Turboexpanders)

Whether used to liquefy natural gas for transport, create cryogenic conditions for air separation, or turn excess heat into valuable energy, the key to turboexpander performance is thermal efficiency.

Atlas Copco's proven impeller designs help generate superb cooling capacity and make these impellers the most reliable on the market. Specially-developed insulation on the expander casing and at other key areas, along with tailored shaft seals ensure that both the cold temperatures and the gases vital to your process remain within the system.

Our turboexpanders are available in compressor-loaded, integrally-g geared generator-loaded, generator-loaded or hydraulic-brake-loaded configurations. In power generation applications, they can deliver up to 25 MW per unit.

Cryogenic Pumps

Atlas Copco's full line of cryogenic pumps cover the complete liquefied natural gas (LNG) and liquefied petroleum gas (LPG) value chain from liquefaction through regasification and play crucial roles in petrochemical plants and refineries.

Backed up by more than 50 years of innovation in the field, Atlas Copco's newest line of third-generation cryogenic pumps offers distinct advantages over nearly all other competitive systems sold today.

Thanks to their cutting-edge design, Atlas Copco cryogenic pumps deliver the industry's smallest in-tank pump column size and the lowest Net Positive Suction Head (NPSH) values.

The increased usable tank storage capacity this affords, along with efficiency levels that are 5-15% greater than the industry average, translates into higher plant revenues.

Our pumps are available in flow ranges of 10 m³/h (5.89 cfm) to 3,000 m³/h (1767 cfm) and can be used in a suction pot, mounted in-tank or in a marine/fixed configuration.

**Based on flows rate in the compressor technique catalogue which is m³/min, here the rating would be 4.2 to 6666 m³/min, and for the British imperial system, it would be 147.25 - 235600 cfm*



Centrifugal compressors for gas and air applications, up to 200 bar discharge pressure, driver power up to 40 MW

Compressor GT Series

Page 171



Radial inflow expansion turbines (turboexpanders)
Expanders EC Series

Page 177



Centrifugal compressors for air and nitrogen, discharge pressures up to 30 bar

Compressor H Series

Page 172



Integrally geared expander generators for industrial applications or energy recover
Expanders EG Series

Page 178



Direct-driven Centrifugal turbocompressors polyethylene and polypropylene
Compressor T Series

Page 173



Low Pressure Vertical Turbine Pump
Type TA & TX

Page 180



Centrifugal compressors for air and gas applications, up to 70 bar

Compressor SC Series

Page 174



Process Radial Diffuser Pump – RD
Versatile Pump Handling Multiple Applications

Page 181



Integrally geared centrifugal compressor for gas and air, up to 70 bar

Compressor TP Series

Page 175



High Pressure Continuous Crossover
Type CC

Page 182



Integrally-geared turbo expanders for air applications, up to 4,000 kW / 70 bar
Expanders ET Series

Page 176


Centrifugal compressors for gas & air applications, up to 200 bar discharge pressure, driver power up to 40 MW

GT Series

Driven by Integral Gear technology, Atlas Copco's GT Series provides maximum compressor efficiency and reliability. This ensures sustainable productivity in processes across dozens of industries and applications. Our GT compressors are present from the steel mills of China to complex oil and gas operations on the world's Seven Seas – and beyond. The GT Series handles flow volumes up to 400000 m³/h (235600 cfm), in configurations up to eight stages. It handles all gases.

CUSTOMER BENEFITS

- **Customization** – From impeller design to packaging options and diffuser, GT Series compressors provide a vast range of customization options to meet your customer requirements and improve your process.
- **Regulatory compliance** – The GT Series is manufactured according to the rigorous standards of the American Petroleum Institute (API), namely API 614, Chapter 3 (gas); oil systems according to API 614.
- **Small footprint** – The compact package design reduces the compressor's footprint.
- **Maximum reliability** – This is a crucial aspect particularly in the air separation industry and oil & gas applications (marine and offshore).
- **Maximum compressor efficiency**, with one main focus being on power optimization of your process.



Centrifugal compressors for air and nitrogen, discharge pressures up to 30 bar

H Series

The H-Series centrifugal compressor marks the culmination of more than 100 years of Atlas Copco experience in air compression. Anchored in innovative engineering and manufacturing techniques, this compressor combines premier technology for the delivery of oil-free compressed air. The H-Series serves the requirements of many industries, from air separation, chemical, petrochemical, process air etc. It is widely known and accepted as an efficient, dependable and cost-effective compressor solution that comes as a standard package but also fully engineered to API specifications. The H-Series handles flow volumes up to 42500 m³/h (25032.5 cfm) in multi-stage configurations and 85000 m³/h (50065 cfm) for single-stage compressors.

CUSTOMER BENEFITS

- **Optimized performance** – Quality-engineered components optimize the performance and reliability of your process.
- **Maximum efficiency** thanks to the exclusive H-Series impeller design.
- **Customer-driven product** that fully meets your requirements in a broad range of industries and applications.
- **Energy savings** due to deployment of adjustable inlet guide vanes.
- **Localized packaging possible.**



Direct-driven Centrifugal turbocompressors polyethylene and polypropylene

T Series

Drawing from Atlas Copco's extensive experience for complex applications, the T-Series compressor is used in some of the most challenging processes. For more than two decades the T-Series compressor has been at the heart of demanding, high-profile downstream petrochemical applications worldwide, from Russia to the Middle East, and beyond. The T-Series handles discharge pressures up to 40 bar (580.2 psi) and flow volumes up to 50000 m³/h. (29450 cfm)

CUSTOMER BENEFITS

- **Maximum compressor efficiency and reliability.**
- **Superior efficiency** thanks to the unique design and position of the inlet guide vane in connection with the closed impeller.
- **Regulatory compliance** – The T-Series is manufactured according to the rigorous standards of the American Petroleum Institute (API, namely API 617, Chapter 3 (gas); oil systems according to API 614.




Centrifugal compressors for air and gas applications, up to 70 bar

SC Series

Featuring integral gear technology at the heart of the machine, the SC-Series compressor offers reliable and efficient service across dozens of applications in air separation as well as in the gas and process industries. The SC-Series is a reliable, cost-effective compressor solution and ensures that customers have sustainable productivity in their process. The SC-Series handles flow volumes up to 110000 m³/h (64790 cfm) at suction temperatures ranging from -40°C/-40°F to 200°C/392°F. It handles all gases.

CUSTOMER BENEFITS

- **Easy installation** – Compact packaging design reduces installation costs and footprint.
- **High efficiency** – Power savings in all operation modes and superior turndown rates result in maximum efficiency.
- **Regulatory compliance** – The SC-Series is manufactured according to the rigorous standards of the American Petroleum Institute (API), namely API 617, Chapter 3 (gas); oil systems according to API 614.



Integrally geared centrifugal compressor for gas and air, up to 70 bar

TP Series

Driven by integral gear technology, Atlas Copco's TP centrifugal gas compressor offers maximum reliability and efficiency for dozens of air and gas applications. It provides cost-effective, sustainable service in facilities all over the world. TP-Series compressors are known for their dependable and innovative service, as well as their adherence to API specifications. The TP-Series handles flow volumes up to 20000 m³/h (11780 cfm) at suction temperatures ranging from -40°C/-40°F to 200°C/392°F. It handles all gases.

CUSTOMER BENEFITS

- **Small footprint** – Installation costs and occupied floor space are reduced by a compact packaging design.
- **Maximum efficiency in impeller design.**
- **Customizable** – Option to use a custom combination of standardized components.
- **Flexibility** – Adjustable inlet guide vanes offer a wide operating range and excellent partial load performance.



Features of Turbocompressor Products

| Features | GT | H | T | SC | TP |
|-------------------------------------|--|------------------------------------|-----------------------------|------------------------------------|------------------------------------|
| Suction pressure (max.) | 80 bar(a) | 1.4 bar(a) (8 bar)* | 40 bar(a) | 70 bar(a) | 50 bar(a) |
| | 1160.3 psi | 20.3 psi | 580.2 psi | 797.7 psi | 797.7 psi |
| Discharge pressure (max.) | 200 bar(a) | 30 bar(a) | 40 bar(a) | 70 bar(a) | 70 bar(a) |
| | 2900.8 psi | 435.1 psi | 580.2 psi | 797.7 psi | 797.7 psi |
| Suction temperature | -200 to 200°C | -40 to 50°C | -40 to 150°C | -40 to 200°C | -40 to 200°C |
| | -328 to 392°F | -20.2 to 122°F | -40 to 302°F | -148 to 212°F | -148 to 212°F |
| Effective inlet-flow range | 250 to 400000 m³/h | 3500 to 42500 (85000**) m³/h | 15000 to 50000 m³/h | 250 to 110000 m³/h | 250 to 20000 m³/h |
| | 147.25 to 235600 cfm | 2061.5 to 25032.5 cfm | 8835 to 29450 cfm | 147.25 to 64790 cfm | 147.25 to 11780 cfm |
| Maximum No. of stages | 1 - 8 | 1 - 4 | 1 | 1 | 2 - 5 |
| Gases handled | All gases | Air, nitrogen | Polyethylene, polypropylene | All gases | All gases |
| Impeller types | Open / closed | Open | Open | Open | Open |
| Shaft / impeller connection | Hirth serration | Microspline | Hirth serration | Microspline | Microspline |
| Seals | | | | | |
| Labyrinth | ● | ● | | ● | ● |
| Carbon ring | ● | ● | | ● | ● |
| Dry-gas seal | ● | | ● | ● | ● |
| Capacity / pressure control | | | | | |
| Variable inlet-guide vanes (IGV) | ● | ● | ● | ● | ● |
| Variable diffuser-guide vanes (DGV) | ● | ● | | ● | |
| Variable speed | ● | | ● | ● | ● |
| Inlet throttle | ● | ● | | ● | ● |
| API | 672 / 617 | 672 | 617 | 672 / 617 | 672 / 617 |
| Axial thrust compensation | High-speed axial bearings or thrust collar | High-speed axial bearings | High-speed axial bearings | High-speed axial bearings | High-speed axial bearings |
| Oil system | Manufacturer's standard or API 614 | Manufacturer's standard or API 614 | API 614 | Manufacturer's standard or API 614 | Manufacturer's standard or API 614 |
| Coupling | Dry | Dry | Dry | Dry | Dry |
| Test code | VDI2045 / ASME PTC10 | VDI2045 / ASME PTC10 | VDI2045 / ASME PTC10 | VDI2045 / ASME PTC10 | VDI2045 / ASME PTC10 |

* H-booster on request

** single stage compressors

Integrally-g geared turbo expanders for air applications, up to 4,000 kW / 70 bar

ETB, ETG, ETF Series

Atlas Copco's turbo expander solutions for the air separation market ensure smooth process operations in applications such as cryogenic expansion, steel and electronics. They maximize cold power in plants, while at the same time providing simple installation, operation and maintenance. Atlas Copco also provides compressors for air separation plants, to give you a complete portfolio of solutions in this market.

CUSTOMER BENEFITS

- Customized solutions
- Maximum efficiency
- Minimized energy consumption
- Superior cooling capacity in cryogenic processes
- Robust construction
- Proven impeller design to precisely meet customer needs
- Wide operational range
- Maximum reliability in turboexpander performance



| Features | ETB, ETG, ETF Series | |
|-------------------------|---|---|
| Suction pressure (max.) | 160 bar(a) | 2320.6 psi |
| Suction temperature | -220 to 510 °C | -364 to 950 °F |
| Maximum No. of stages | 1 - 4 | 1 - 4 |
| Gases handled | All industrial gases and hydrocarbon gas mixtures, including condensing streams | All industrial gases and hydrocarbon gas mixtures, including condensing streams |

Radial inflow expansion turbines (turbo expanders)

EC, ECM, ECMi

Atlas Copco's turboexpanders convert the internal energy available in a gas stream into useful work by lowering its pressure, thereby producing cooling and shaft power. Turbo expanders are used to produce refrigeration or recover power for petrochemical hydrocarbon processing plants. They typically drive a single-stage, centrifugal compressor, with both the expander and compressor optimized for the process duty. These custom engineered expander compressors are designed and manufactured to ensure the highest reliability and quality to meet your specific specifications. Incorporating the latest technology, their aerodynamic designs maximize machinery performance without sacrificing dependability. Hydrocarbon applications include LPG, NGL, DPC, LNG and nitrogen rejection. Chemical/petrochemical applications include ethylene olefin recovery, ammonia purification, carbon monoxide purification, propane dehydrogenation, and hydrogen recovery.

CUSTOMER BENEFITS

- **Custom engineered solutions** – Expander compressors are designed specifically to customer specifications and unique process requirements.
- **Ultra-high efficiency** – Turbo expanders provide high efficiency refrigeration or power recovery.
- **Robust construction** – Expander compressors are designed for offshore/onshore, outdoor unprotected and attended or unattended sites. They are custom designed for desert, tropical and ambient temperatures as well as hazardous areas (Division 1/Zone 1, Division 2/Zone 2).
- **Highest quality design and production systems** – ISO 19001, 14001 and 18001 quality certification, all machines meet or exceed industry (API 617, API 614, API 670 and ANSI B31.3) and international standards (IEC, NEC, ASME, BS5500).
- **Long-lasting reliable performance** – Many of our expander compressors are in service for 20 years without a shutdown.



| Features | EC, ECM, ECMi | |
|-------------------------|---|---|
| Suction pressure (max.) | 200 bar(a) | 2900.8 psi |
| Suction temperature | -220 to 200°C | -364 to 392°F |
| Maximum No. of stages | 1 | 1 |
| Gases handled | All industrial gases and hydrocarbon gas mixtures, including condensing streams | All industrial gases and hydrocarbon gas mixtures, including condensing streams |

Integrally geared expander generators for industrial applications or energy recovery

EG, EGi

Whether you want to produce electricity as a by-product of an industrial process, from a geothermal resource, from waste heat, or recover power in a pressure letdown application, Atlas Copco's expander generators are a reliable solution for energy recovery and electrical power production. Utilizing the Organic Rankine Cycle (ORC), typical energy recovery applications include geothermal, waste heat recovery, pressure letdown and cold energy recovery. The speed reduction gearbox features a parallel shaft and integral gearbox. Driven by our integral gear expertise, the expander generators can be configured with one to four stages on a single gearbox to achieve the lowest cost per kilowatt power-train solution. Atlas Copco provides partial or complete solutions, from the core expander to the complete system.

CUSTOMER BENEFITS

- **Built to last** – Their robust construction can withstand rough treatment over a long lifetime of operation in the harshest of work environments.
- **Reliability Centered Maintenance (RCM)** – Maintenance system based on statistical data and experience.
- **Power** – Power generating ranges up to 25 MW per expander stages.
- **Unique design** – Single or multi-stage turbine design mounted on the same integral gearbox.
- **High efficiency** – Maximum energy recovery efficiency and plant availability.
- **Complete solution** – Partnerships with expert companies for complete cycle design/complete recover solutions.
- **Highest quality design and production systems** – ISO 19001, 14001 and 18001 quality certification, all machines meet or exceed industry (API 617, API 614, API 670 and ANSI B31.3) and international standards (IEC, NEC, ASME, BS5500).



| Features | EG, EGi | |
|-------------------------|---|---|
| Suction pressure (max.) | 200 bar(a) | 2900.8 psi |
| Suction temperature | -220 to 300°C | -364 to 572°F |
| Maximum No. of stages | 1 - 4 | 1 - 4 |
| Gases handled | All industrial gases and hydrocarbon gas mixtures, including condensing streams | All industrial gases and hydrocarbon gas mixtures, including condensing streams |

Low Pressure Vertical Turbine Pump

Type TA & TX

Atlas Copco Gas and Process Type TA and TX Vertical Turbine Pumps are equipped with Atlas Copco's patented HyPerInducer®, which offers the lowest Net Positive Suction Head (NPSH) in the industry. This alone increases the active volume of the storage tanks, creating more accessible inventory. The use of the vertical turbine bowl diffusers completely eliminates rotating stalls and improves pump efficiency by up to 86%. Multi-stage designs are created by adding a greater amount of control to each set speed. This allows for lower tip speeds and less rotating mass. The Type TA and TX Turbine flow handles up to 3000 m³/hr and handles fluid temperatures ranging from -196 °C/-320 °F to 45 °C/ 113 °F.

CUSTOMER BENEFITS

- **Upto 86% efficiency.**
- **Hydraulic designs with higher specific speeds, resulting in higher efficiency.**
- **Easy maintenance.**
- **An active thrust balance system for increased bearing life.**



| Features | Type TA & TX | |
|---------------|---|---|
| Flow | Up to 3000 m³/hr | 1765 cfm |
| Head | Up to 350 m | Up to 350 m |
| Fluid Temp. | -196 °C to 45 °C | -320 to 113° F |
| Motor | Submersible, 50 & 60 Hz designs, variable frequency drive (VFD), up to 6600 volts | Submersible, 50 & 60 Hz designs, variable frequency drive (VFD), up to 6600 volts |
| Gases handled | all gases | all gases |

Process Radial Diffuser Pump – RD

Versatile Pump Handling Multiple Applications

Atlas Copco Gas and Process offers a full range of process pumps able to handle a multitude of different applications, including the transfer of hydrocarbon liquids. The versatility of these pumps is exhibited by their use in liquefaction plants, petrochemical plants, refineries, and terminals. They can be configured in a multitude of ways, including pot-mounted, in-tank, and fixed configuration. When combined with close-coupled stage/designs, the large diameter of the pump shaft ensures dimensional stability and, ultimately, peace of mind. The pump's robust rotor shaft allows for easy maintenance and is equipped with multi-stage vane island diffusers providing constant head rise to shut-off and significantly increased MTBO. The radial diffuser pump's handles up to 250 m³/hr and fluid temperatures ranging from -196 °C/-320 °F to 45 °C/113 °F.

CUSTOMER BENEFITS

- **High versatility** – can be used in a number of different plants and terminals.
- **Easy maintenance.**
- **Ability to handle high vapor fractions with Atlas Copco's patented HyPerInducer®.**
- **Dependable** – can be paired with close coupled stage/designs.



| Features | Versatile Pump Handling Multiple Applications | |
|-------------|---|---|
| Size | Up to 200 kW | Up to 200 kW |
| Capacity | Up to 250 m ³ /hr | 117.7 cfm |
| Head | Up to 1000 m | Up to 1000 m |
| Fluid Temp. | -196 °C to 45 °C | -320 to 113 ° F |
| Motor | Low voltage, 50 & 60 Hz or variable speed | Low voltage, 50 & 60 Hz or variable speed |

High Pressure Continuous Crossover Type CC

With up to 86% efficiency, the Atlas Copco Gas and Process' High-Pressure Type CC pump is among the most efficient on the market. Because these pumps can represent a large percentage of an LNG terminal's electric power usage, increased efficiency significantly cuts costs. Equipped with multi-stage continuous crossover diffusers, the Type CC pump features constant head rise to shut-off.

Reliability represents an additional hallmark of Type CC pumps. The active thrust balance system increases bearing life, and a robust rotor shaft allows for easy maintenance. The Type CC pump handles up to 600 m³/hr and fluid temperatures ranging from -196 °C/-320 °F to 45 °C/113 °F.

CUSTOMER BENEFITS

- **High efficiency** – higher specific speed hydraulic design.
- **Easy maintenance.**
- **Ability to handle high vapour fractions with Atlas Copco's patented HyPerInducer®**
- **Constant diameter pump shaft** – ensures dimensional stability when combined with close coupled stage/designs.



| Features | Versatile Pump Handling Multiple Applications | |
|-------------|---|---|
| Size | Up to 3000 kW | Up to 3000 kW |
| Capacity | Up to 600 m ³ /hr | 353.1 cfm |
| Head | Up to 2500 m | Up to 2500 m |
| Fluid Temp. | -196 °C to 45 °C | -320 to 113 °F |
| Pump Ns | 1250, 1600 | 1250, 1600 |
| Motor | 50 & 60 Hz designs, variable speed, up to 6600 volts variable frequency drive (VFD) | 50 & 60 Hz designs, variable speed, up to 6600 volts variable frequency drive (VFD) |

TOTAL CUSTOMER CARE

Our organization and people are committed to the maximum operational availability and efficiency of your compressed air network.

Total customer care

Your bottom line, maximum availability of our equipment at minimum total operating cost, is the top priority for all of us at Atlas Copco. Our way of achieving that builds on interaction, on long-term relationships and involvement in your processes, needs and objectives.

Total customer care is our goal at any level of service interaction with you; from standardized genuine parts over tailor-made service plans to remote monitoring and optimization.

We want you to see Atlas Copco as a real performance partner that can contribute to the productivity of your processes. The best way of taking care of your interest is by taking the best care of your equipment.



SAVE ENERGY

Page 161 - 163



MONITOR YOUR PRODUCTS

Page 164



CUSTOMER SUPPORT PLANS

Page 165 - 168



UPGRADE YOUR PRODUCT

Page 169 - 170



GENUINE PARTS

Page 171 - 179



AIR DISTRIBUTION

Page 180

Download a QR Reader and scan the code for:
"Atlas Copco Service solutions to optimize the Compressor room"



Save energy

Compressed air is one of the most important utilities in the industry. It is also one of the largest consumers of energy.

With their detailed and extensive knowledge of compressed air, our energy and air consultant engineers will be able to determine an acceptable operating balance, that is both within the capabilities of your compressors and also adequate to satisfy your production with minimized operational running costs.

Maximize the performance of your compressor

Based on an audit of your production processes Atlas Copco consultants can suggest a more performing set-up for your compressed air installation, with an eye on maximum availability at lowest possible cost.

Atlas Copco logical sequence towards sustainable energy savings:

1. Pre-assessment

to estimate savings potentials

2. AIRScan energy assessments/audits

to identify savings potentials through measurement and simulations

3. Recommendations

to prepare your system for the optimization by exchanging the latest, most efficient components

4. Optimize


to achieve the savings by implementation of energy saving accessories and solutions

5. Online monitoring

to ensure the solution implemented is delivering the savings as prescribed

6. Regular AIRScan energy assessments/audits

to validate after the improvements and find further saving potentials



AIRScan

Tangible information for real solutions

A clear understanding of the changing demands over time is a corner stone in any process of system optimization. Defining the limitations of your current compressed air system is the key to finding the best solution to achieving energy efficiency for your business.

Understanding your Compressed Air Systems

A thorough survey of the compressed air system dynamics, including logging and analysing all the air net key parameters allows you to determine the right operating balance and to identify the energy savings potentials.

Using the logged information, our compressed air experts will provide a comprehensive and fully detailed report, including cost analysis, graphs and the starting points towards improving the compressed air system. At the end of the survey you will have a valuable document stating the “real status” of your system’s performance, including recommendations to finally achieve sustainable energy savings.




Air optimization

Reduce your energy consumption

Efficient compressor management is the fastest way to achieve energy savings. Each 1 bar (14.5 psi) reduction in working pressure results in 7% direct energy savings and further 3% is saved through leak reduction. Our range of ES Central Controllers will enable you to link all compressors and dryers, lower your overall pressure band, eliminate the need for higher working pressure and optimize the compressor mix at all times.

Using advanced control systems, you can maximize energy savings by:

- Regulating the system pressure within a pre defined and narrow pressure band.
- Scheduling shutdown to avoid costs during non production hours.
- Equalizing workload to avoid overloads on individual machines.
- Reducing maintenance costs thanks to comprehensive, flexible machine sequence control.
- The result is a properly managed compressed air system that can save energy, reduce maintenance cost and increase uptime.






Heat recovery system

By recovering rejected heat and reusing it in your production cycle, allows you to further improve the overall efficiency of any compressed air system and to reduce your plant's total energy consumption.

Through the compression process, part of the energy is lost as radiation. Atlas Copco's Energy Recovery unit is able to extract an amount of energy from compressed air that is equivalent to the amount of energy that the electric motor uses.

The most common uses for the recovered energy include process heating, space heating and water heating.



Monitor your products

Keeping an eye on your equipment at all times is the best way for Atlas Copco to prevent production loss due to a breakdown. This inside view on your operation allows us to plan for maintenance pro-actively.

Compressed air plays a vital part in almost all modern manufacturing processes. In today's competitive production environments, being able to reduce costs, increase efficiency and guarantee maximum uptime is high on everyone's priority list.

SMARTLINK

SMARTLINK is an easy to install, efficient to monitor, easy tailored compressor monitoring program. It offers your company a complete insight of your compressed air production. It helps to predict potential problems (and thus anticipate them); it shows how and where the production can be optimized and energy can be saved.

SMARTLINK is as flexible and informative as you want it to be. Choose from the 3 levels which solution best fits your company.



SMARTLINK Service: Rule out all uncertainties. With SMARTLINK Service installed on your compressors, scheduling maintenance visits becomes as simple and easy as it should be; your service log book is always just one click away and your online link with Atlas Copco allows you to request and receive quotes for spare parts or additional services very fast.



SMARTLINK Uptime: Keep your compressors up and running. By e-mail and/or text, you receive all relevant machine indications (warnings and shutdowns) in advance. Based on this information, you can then take all necessary actions and measures to avoid the risk of a breakdown.



SMARTLINK Energy: Safeguard the performance of your equipment. With SMARTLINK Energy, Atlas Copco enables you to continuously monitor and analyze the energy efficiency of your compressor room. You decide on the performance indicators, you define the benchmarks. SMARTLINK analyzes and reports. You can make accurate and immediate improvements when needed. The results can be used for energy monitoring according to ISO50001



VISUALIZATION

Knowing exactly how your system is running makes identifying ways for improvement much easier. The Atlas Copco monitoring products provide you with the transparency you need to assess system performance. Based on this analysis you can then easily determine a course of action to improve system usage and limit energy consumption costs.




FEATURES & BENEFITS

- **Increased transparency through consolidation of all data.**
- **Logging & trending to establish the exact performance of your system.**
- **Real-time display of machine values and statuses directly on your screen.**

Gateways

Monitor and control through Field Bus Connections. Atlas Copco Elektronikon compressor controllers and ES central controllers can be integrated into your existing plant monitoring and control systems, based on the most popular field bus connections Modbus and Profibus.



SUPERVISION

Having the same interests at heart, Atlas Copco's ultimate goal is to provide you with the hassle-free compressed air to run your business.

FEATURES & BENEFITS

- **No need for frequent machine checks, saving you time and money.**
- **Realize maximum uptime and reliability, supported by the Atlas Copco service organization.**
- **A perfect complement to the Atlas Copco Service Plan, reducing your total cost of ownership.**

With maximum uptime and reliability being highly important elements in your everyday production workflow, continuous surveillance is a top priority. With Supervision, Atlas Copco handles the event notifications and provides the immediate response necessary, supported by a response time guarantee.



Customer support plans

What you need is a solution to keep your production optimal at all time and preferably at the lowest operating cost. Our specialized advisors will visit your production facilities and assess your specific needs. This allows us to propose the most cost effective Customer Support Plan for your maintenance needs.

Ways to ease your mind:

- **We leave it in your hands**

We deliver the necessary spare parts and leave the actual maintenance up to you. We check your compressed air system regularly and identify the necessary actions. The output of each inspection is a complete diagnostic report.

- **We give you a hand:**

We service your compressed air system at predetermined intervals to lower the risk of unexpected problems and keep your production process optimal at all times. The routine maintenance costs are fixed, which allows you to easily forecast them.

- **You hand it to us:**

We service your compressed air installation following a complete maintenance system that covers all breakdowns. Your equipment will be kept in prime condition at any time and the annual costs for the agreed



period are fixed. This includes all the required parts, labour and travel expenses. There are no hidden surprises. You have total peace of mind.

We leave it in your hands Parts-Only Preventive Maintenance Plan

This Plan covers all parts required to service your Atlas Copco machine as per the recommendations found in the instruction manual. Parts are delivered to you at the correct intervals and in a pro-active manner.

FEATURES & BENEFITS

- Improved equipment reliability thanks to the genuine Atlas Copco parts and lubricants
- Timely delivery of all required service kits reducing your administration
- Guaranteed parts availability allowing you to eliminate expensive stock



We give you a hand

Service at predetermined intervals

Preventative Maintenance Plan

This Plan covers all regular maintenance for your compressed air equipment in a proactive manner. Certified and trained Atlas Copco service technicians use genuine parts and lubricants to maintain your installation as it should be. This is the best way to lower the risk of unexpected problems allowing you to optimize your production process. The plan can be customized and adjusted at any time



FEATURES & BENEFITS

- Improved equipment reliability thanks to genuine parts and expert technicians
- Stable costs up front helping you balance your maintenance budget
- Eliminate stock and administration by letting the experts take care of it

Inspection Plan

A compressed air system can only be managed efficiently if the right data is available. Atlas Copco's Inspection Plan consists of regular inspection visits to identify any actions required to keep your compressed air system in prime operating condition. The output of the Inspection Plan is a complete diagnostic report, from which any work related to subsequent improvements can be quoted separately, allowing you to follow separate approval flows.



FEATURES & BENEFITS

- No surprises, fixed yearly fee to perform the inspections including all labour and travel costs
- Improved equipment reliability thanks to regular follow-ups by the experts
- Comprehensive diagnostic report after each inspection visit

Fixed Price Services for Regular Maintenance

From machine inspections to labour intensive recommended visits, Fixed Price Services offer you a clear path to maintaining your compressed air installation. Atlas Copco's trained technicians arrive at your door with all required parts to get the job done. They ensure that your machine runs in it's most efficient way, with lower energy consumption and less risk of unexpected costs due to failures.



FEATURES & BENEFITS

- No surprises, one fixed price to perform the work including all travel, material and labour costs
- All manufacturer recommended service activity list done and comprehensive diagnostics report after each visit
- Reduce administration and inventory by letting Atlas Copco take care of it

Fixed Price Services for Overhaul

As the owner of Atlas Copco equipment, you are already familiar with its unique design features that help to achieve high reliability and the lowest total cost of ownership. Overhaul performed after years of equipment operation helps to keep initial reliability and efficiency. Atlas Copco's trained technicians arrive at your door with all required parts to get the job done, and leave you knowing that your machine is in nearly brand new condition.



FEATURES & BENEFITS

- All manufacturer recommended service activity list to keep reliability and efficiency as from day one
- Competent Atlas Copco technicians to perform such a crucial work
- No surprises, one fixed price to perform the overhaul to avoid subsequent downtime and production lost

You hand it to us

Complete maintenance system

Total Responsibility Plan

This Plan lives up to its name – total peace-of-mind with full coverage of the unit including: air ends, motor, electrical and electronic systems, coolers. The program consists of certified Atlas Copco technicians providing you with all regular maintenance, engineering improvements, breakdown repairs and machine overhauls . It is a complete maintenance system with fixed annual costs for the agreed period.



FEATURES & BENEFITS

- Use of genuine parts and expert technicians for complete coverage including overhauls and unfortunate breakdowns
- Stable costs removing all surprises as you balance your maintenance budget
- Eliminate stock and administration by letting the experts take care of it

AIRXtend

Atlas Copco's AIRXtend program is a five (5) year protection plan to maintain your system with fixed annual costs. This warranty extension is supported by the use of certified Atlas Copco technicians to perform all preventative maintenance for your system at the correct interval and in a proactive manner. Relax knowing that only the highest quality spare parts and consumables are used, originating from the same factories as your equipment.



FEATURES & BENEFITS

- Use of genuine parts and expert technicians extending your warranty to five years
- Stable costs up front helping you balance your maintenance budget
- Eliminate stock and administration by letting the experts take care of it

Upgrade your product

Our upgrade kits are the result of continuous engineering work to make the latest technology available for your existing equipment range. This will inevitably improve the key performance features such as energy consumption and reliability. Intelligent use and the sustained health of core parts are the basic requirements for the lifelong optimum availability of your equipment.

These upgrades increase the reliability and availability of your equipment. Furthermore, upgrading your compressor system will result in substantial energy savings, while the cost will in most cases be equivalent to or even less than a replacement of older control systems.

FEATURES & BENEFITS

- **Optimized performance**

With the portfolio of upgrades your machines will be equipped with the latest available options, allowing you to make substantial energy savings.

- **Enhanced reliability**

Upgrade kits focus on reliable performance of critical components and increased reliability will allow your equipment to reach a longer lifetime.

- **Increased availability**

With upgrades, availability is increased thanks to automated control and preventive replacement of all essential components. This means that the continuity of your process is not jeopardized by unnecessary downtime.

Upgrade programs

Make use of the latest technology

Upgrades take advantage of the most recent computer technology and of the progress in sophisticated compressor control software.



Elektronikon controller

The Elektronikon® controller is at the height of technology in sophisticated compressor control software. An upgrade will improve the overall reliability and uptime of your equipment, and extend connectivity to modern plant control systems.

Xchange programs

Replace major components with new more efficient components

The Xchange Program offers you the possibility to replace major components of your compressor with new more efficient components.

Motor xchange program

Energy consumption is the major cost in the total life cycle cost of any compressor. Under the Xchange Motor Program, the latest high efficiency motors are used to replace old less efficient motors or failed motors that require rewinding.

These new motors come complete with adaptation components making the exchange a quick exercise. The energy savings with the new motors are guaranteed.



Element xchange program

The overhaul is arranged in advance based on the expected life of the compressor element and condition monitoring. This proactive planning ensures that there is a reduced risk of failure and prevents production loss. The combination of Atlas Copco genuine parts and skilled expertise by Atlas Copco engineers ensures that overhauled elements are restored to their original highly performance levels, increasing your profitability.



Converter xchange program

The Xchange Converter program is a one step replacement solution to upgrade Atlas Copco VSD compressors with new variable speed drives. The lifecycle of a variable speed drive progresses from active phase to the obsolete phase in just a few years. Towards the obsolete phase the converters become difficult and expensive to repair.

The Converter Xchange program easily overcomes this difficulty and ensures that the customer's equipment is back in operation after a minimal intervention period.



Genuine parts

Because Atlas Copco genuine parts are built according to the same quality standards as your compressor, you are guaranteed that your production, even after servicing your compressor, will remain at the same high level.

The advantages of using Atlas Copco's genuine parts:

- **Longer life expectancy**

Regularly servicing your equipment using genuine spare parts ensures that your installation **will last longer**. We guarantee that each new component performs equally well as the part it replaces.

- **Superior quality**

Our genuine parts are manufactured to the same exacting standards as your installed compressor. They have passed the same endurance tests and proven to be the best protection for your investment.

- **Reliability and productivity**

Using genuine parts substantially lowers the risk of a production breakdown, which would not only be very costly, but could also endanger your product quality, deadlines and profit margins. In short, genuine parts offer optimal performance of your compressed air installation.

- **Energy savings and cost effectiveness**

Regular replacement of parts combined with the use of genuine Atlas Copco parts make your compressed air installation last longer and cause a minimal average pressure drop, which leads to energy savings and cost effectiveness and maximum air delivery at the lowest cost of ownership.

- **World class logistics**

The continuity of your production process can only be guaranteed when the quality spare parts arrive at the right place and the right time. With our genuine parts distribution system, operating 24/7, you can rest assured your production continuity is in safe hands.



Lubricants



Greases



Maintenance kits




Filters



Line Filters

Lubricants

Engineered to protect



Atlas Copco lubricants are engineered with the exact right selection of additives that interact in just the right proportion to obtain optimal performance. The additives not only support the base lubrication requirements, they also interact in multi processes in the compressor.

The properties of quality

All our efforts are aimed at optimizing the performance of your Atlas Copco compressor for the longest lifetime at the **lowest operating cost**.

The experts in our laboratories are uniquely skilled in specifying lubricant properties for Atlas Copco compressors to operate optimally in a wide range of settings and conditions, during several thousands of hours.

Atlas Copco lubricants are a unique blend of chemical properties, engineered for **optimal performance** in their dedicated functions.

Atlas Copco Fluids for screw compressors

Roto-Inject Fluid

Atlas Copco Roto-Inject Fluid is specially formulated to protect your GA-GX rotary screw compressors and neutralize pollution. It guarantees the longest lifetime, trouble free, with constant performance, at the best operating cost.

Years of experience on thousands of types of Atlas Copco equipment have proven Roto-Inject Fluid to match all lubrication demands in varied conditions. It boasts an extended service interval of up to 4 000 hours for operation in a mild environment. This is critical to achieve the best reliability and reduce the service lifetime cost.



Roto-Xtend Duty Fluid

When your air compressors need to perform at top capacity, only the Atlas Copco lubricant is good enough. That's why it pays to use Roto-Xtend Duty Fluid. Atlas Copco superior performance long life PAO oil, specifically developed for use in Atlas Copco oil injected screw compressors.

Based on synthetic hydrocarbons and special additives, our engineered 8 000 h lubricant has proven its ability to meet all lubrication demands under widely varying conditions. Roto-Xtend Duty Fluid increases compressor reliability, reduces lifetime operating costs and makes your equipment last longer.



Roto-Food Grade Fluid

Roto-Foodgrade Fluid is a high performance fluid specifically designed for use in oil injected screw compressors operating in the food and beverage and packing industry. National and international regulations specify strict manufacturing standards regarding contamination risk management in this industry.

Our Roto foodgrade is based on a careful blend of synthetic fluids and additives that meet these stringent requirements, allowing for active Critical Control Points management (in an HACCP system) and providing increased customer confidence in the food products' safety.



Atlas Copco Fluids for piston compressors

Piston Fluid

Piston compressors pose extreme demands to lubricants: the high compression temperature - possibly exceeding 150°C (300°F) - pressures up to 20 bar, condensation - typically during low cycle load - and dust contamination in installations that are not optimally maintained.

Traditional lubricants cannot cope with these extreme conditions, resulting in fast oil degradation, overheating and potentially irreversible damage and high repair costs. Therefore, high performing lubricants increase the equipment lifetime. The Atlas Copco Piston Fluid has been developed as a high resistance lubricant, withstanding severe conditions, with a long service interval and superior performance.

Considering the low oil content in piston compressors, often less than 2 liters, the economy of lesser quality oils simply is not worth the risk.



HiPER Fluid

HiPER Fluid is a premium quality reciprocating compressor lubricant, which has been developed for and tested in Atlas Copco's high pressure reciprocating compressors (product lines Intermech and GreenField)

Applications:

Compressed Natural Gas Compressors
Industrial Gas Compressors

HiPER Fluid meets the most stringent qualification in order to increase the performance and life time of your investment. The oil is specifically blended to handle local variations in gas composition.



Automan Fluid

Automan piston compressors pose extreme demands to lubricants: the high compression temperature, possibly exceeding 150°C (300°F), pressures up to 20 bar, condensation - typically during low cycle load - and dust contamination in installations that are not optimally maintained.

Traditional lubricants cannot cope with these extreme conditions, resulting in fast oil degradation, overheating and potentially irreversible damage and high repair costs. Therefore, high performing lubricants increase the equipment lifetime. The Atlas Copco Automan Fluid has been developed as a high resistance lubricant, withstanding severe conditions, with a long service interval and superior performance.

Considering the low oil content in piston compressors, often less than 2 liters, the economy of lesser quality oils is simply not worth the risk.



Atlas Copco Lubricants

Roto-Z

Roto-Z is a high quality lubricant, uniquely tailored to the specific requirements of the Atlas Copco Z-compressors. Its special formulation yields top performance and maximum lifetime of all moving parts. Reliability is safeguarded and equipment availability is maximal.

Roto-Z is cost-effective too: drain intervals are doubled in comparison to conventional lubricants. Roto-Z incorporates the functional benefits of a preservative mineral oil, which allows for an extended on-site storage of several months.



Roto-H Plus

Roto-H Plus is a unique lubricant, especially created for Atlas Copco oil-free centrifugal ZH compressors. The heavy-duty blend provides optimum lubrication of the compressor sleeve bearings. In addition, Roto-H Plus guarantees top performance and maximum durability of all other moving parts. This improved reliability translates into maximum equipment uptime.

It is a highly cost-effective lubricant: drain intervals can extend up to 24 000 hours* with only a 6-monthly oil analysis in between.

** Subject to normal operating conditions.*



Roto-M

Roto-M is your best safeguard for good hypoid gear lubrication. It is a heavy-duty, high-viscosity blend, formulated specifically for the gear boxes on Atlas Copco MD absorption air dryers.

Roto-M provides the high film strength required in hypoid gear applications. It minimizes wear and tear and guarantees optimum lubrication of the MD worm gear drive, under all operating conditions. Its superior reliability translates into maximum equipment uptime.



Recip Oil

Recip Oil is a unique lubricant, especially created for Atlas Copco oil-free reciprocating compressors and boosters. The special blend provides optimum lubrication for high pressure applications and guarantees top performance and maximum durability of all moving parts. This improved reliability translates into maximum equipment uptime.



Greases Engineered to protect

To help your compressor perform to its optimal design standards, you need a grease that stays in place and provides effective protection and lubrication under challenging conditions. The longer the grease lasts, the longer the motor lasts, and the less lubrication maintenance for your compressor. With a full product range of Roto-Glide greases, you can select the grease to meet your specific requirements.

Roto-Glide:

Roto-Glide sets a new, high standard in motor bearing lubrication. Its special heavy-duty formulation provides improved bearing protection at higher operating temperatures. Because of its greater stability, Roto-Glide permits extended motor greasing intervals of up to 4 000 hours depending on the type and use of the motor.

Roto-Glide guarantees optimum lubrication of the electric motors used in Atlas Copco Z- and G-series air compressors. Improved reliability translated into maximum equipment uptime.



Maintenance kits

The parts you need, when you need them

Save time getting the right parts

The Service kits supplied by Atlas Copco contain every item down to the last gasket. Just think of the time saved; time that without a service kit would be wasted checking different sources to get a complete set of the parts you need.

Covers your complete maintenance needs

Service kits contain all the parts needed as part of a scheduled maintenance program. So from now on you can rely on one single source for all your spare parts. When installed by an Atlas Copco technician, his experience and training will keep downtime to the minimum and ensures your equipment will be kept in top condition throughout its operating life.



Advanced technology for clean condensate

For assured performance and maximum maintenance intervals, the specially designed OSC service kits are highly recommended. Each kit is designed to make life as easy and simple as possible, providing all the equipment needed for a fast, clean and trouble free element changeover.



Line Filters

Compressed Air Filters

Product description

Building on many years of experience in compressed air solutions and through continuous in-depth research and testing, Atlas Copco has developed a complete range of top-of-the-bill DD, DDp, PD, PDp and QD filters according to the latest international standards which efficiently reduce all types of contamination with minimal pressure drop.



Filters

Protect your investment

Compressor oil filtration

Dust and dirt contaminating the compressor oil can lead to damage to or performance losses for rotors and their housings. Since the same oil lubricates the compressor element bearings, damage to these vital components could potentially lead to rotor contact and service failure.

Genuine Atlas Copco compressor oil filters have high performance and are composed of specific filter elements. Features include high-grade filtration efficiency, temperature resistance, and resistance to synthetic oils. Built to withstand high operating pressures, Atlas Copco filters have superior service life, thanks to their high dirt holding capacity.



Compressor air filtration

Compressor rotors operate with minimal clearances, guaranteeing high performance. However, dirt particles can cause damage, reducing performance and potentially increasing operating costs. To safeguard the high-tech screw element at the heart of your investment, Atlas Copco focused on the intake air filtration system.

Atlas Copco uses special filtration elements to prevent contaminants from passing into the compressor. Yet, we designed them to allow the volume of air to freely flow into the machine. Parts from other manufacturers can never match the performance of these genuine Atlas Copco parts.



Compressor oil separation

Only genuine Atlas Copco replacement oil separator elements can offer extremely low oil carryover combined with low pressure differentials. This means better quality air and minimal operating costs through lower oil consumption and longer service life of fine filters installed downstream.



AIRnet

Compressed air piping system

AIRnet is a compressed air piping system that delivers quality air exactly where you need it, from compressor to the point of use. The unique benefits of AIRnet effectively reduce the cost of ownership of your piping system. Discover AIRnet at www.airnet-system.com

CUSTOMER BENEFITS

- AIRnet provides optimum air quality at the point of use
- **FAST** - AIRnet saves you 70 % on installation time vs. traditional piping systems.
aa
- **EASY** - 3 simple steps: CUT to length and deburr. INSERT in the fitting on the marked depth. SECURE and tighten correctly.
- **RELIABLE** - All AIRnet products come with a 10-year warranty on all fittings and pipes, against any damages resulting from material defect.

www.airnet-system.com



Serving the oil and gas industry with energy efficient solutions





Discover the new Atlas Copco Kiosk app

You can download this app via the App store (search for "Atlas Copco Kiosk").

Once installed, you will see all the leaflets lined up on a bookshelf. You can choose which leaflets you download and push notifications keep you up to date of the latest versions. Choose your language in the main screen to find translations. Once downloaded, an iLeaflet remains available offline.



www.appstore.com/AtlasCopcoKiosk

Please note the AppStore will only work on iPad.